

KAS1201PC

Part number: KAS1201PC

Mini switching power supply 12Vdc 1A with cable included



APPLICATION FIELDS



RESIDENTIAL



COMMERCIAL



MEDICAL



PUBLIC SERVICE



PUBLIC ENTERTAINMENT

Installation	Surface
Format	home
Technology	Switching
Phase	Single
Input voltage (Vac)	100 - 240 Vac
Input current Iout (A)	0,2 (115Vac) / 0,12 (230Vac)
Inrush current (A)	20
Input frequency (Hz)	50 - 60
Power Dissipation at 230Vac (W)	3
Efficiency (%)	>80

Power (W)	12
Output voltage	12 Vdc
Adjustable Output (Vdc)	11 - 14
Output current (A)	1
Working temperature (°C)	-20 +60
Cooling	Natural
Derating	-
IP rating	IP20
Parallel connection	No
Available contact	-
Communication	-
Signalling	Output present
Protections	Overload, Short circuit
Connection	Screw
Material	Plastic fire-retardant UL-94V-0
Standards	EN 61000-3-3, EN 61000-6-1, EN 61000-6-3, EN 62368-1
Classification Pelv / Selv	pelv / selv
Warranty	2 Year
Package quantity (pieces)	1
Height (mm)	33
Width (mm)	56
Depth (mm)	56
Weight (Kg)	0,06