

CM42-S Mini Split Camera

5MP Image Quality in a Compact, Split-Design Camera for Optimal Monitoring in Tight Spaces



Overview

The CM42-S indoor mini split camera is a discreet camera, engineered to blend into a variety of environments. The compact CM42-S is comprised of a sensor unit, main unit, and 2-meter / 6-foot USB-C connecting cable, making it an ideal choice for installations in ATMs, retail settings, and other confined spaces.

Despite the sensor's small size (H: 47.4mm / 1.9in, W: 36.4mm / 1.4in, L: 40.2mm / 1.6in), the CM42-S features 5MP resolution and an Ambarella CV25 processor, making it ideal for a variety of deployments. An audio port allows for an external microphone, enabling customers to complement video monitoring with audio recording. Its 2-meter / 6-foot USB-C connecting cable offers flexible and customizable installation, and its HDMI output promotes streaming locally to a display, like a public viewing monitor, which are often found in retail environments. The CM42-S is engineered to capture video even in low-light conditions, making it suitable for round-the-clock monitoring.

Key features

Discreet design

The separate sensor unit and main unit make the CM42-S ideal for deployments in ATMs, retail environments, and other locations that require small form factors.

Auxiliary audio and video support

Connect to an external microphone or public viewing monitor for comprehensive coverage and security.

Versatile installation

2-meter / 6-foot USB-C connecting cable between the sensor unit and main unit accommodates diverse installation scenarios.

Excellent image quality at day or night

5MP resolution and 15 meter / 49 feet IR range ensures clear video capture in many conditions.



CM42-S Mini Split Tech Specs

Camera features

Image Sensor	1 / 2.8" Progressive CMOS	Shutter Speed	1 / 30 sec. to 1 / 10,000 sec.
Sensor Resolution¹	5MP (2592 x 1944)	Day/Night	IR-cut filter for day and night function
Lens Type	Fixed	IR Cut Filter	Yes
Focal Length	3.2mm	IR Range	15m / 49ft
Aperture	F1.6	Minimum Illumination	0.009 lux @ F1.9 (Color) 0 lux with IR Illuminators on
Iris	Fixed	Onboard Storage	Capacity: From 256GB, 768GB Card: MicroSD, SDXC
Field of View (after LDC²)	Horizontal: 99° (80°) Vertical: 71° (63°) Diagonal: 107° (92°)	CPU	Ambarella CV25S88
Inputs/Outputs	3.5mm audio input, micro-HDMI output, +/- AUX ⁴ with 12V / 4W power output, USB-C sensor input ³		

Standard video settings

Compression	H.265, H.264	Historical Video Settings	Adaptive quality ¹
Frame Rate⁵	24fps	Live Streaming Settings	High quality (HQ): Up to 3,000 Kbps (default) Standard quality (SQ): Up to 600 Kbps
WDR Technology	104 dB dynamic range, true WDR, dual exposure		

Standard audio settings

Audio	Supported	Interface	3.5mm audio input
Audio Capacity	One-way audio		

Power and network

Power Input⁶	With IR: IEEE 802.3af Type 1 PoE Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: N/A	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 / 1000 Mbps
Power Consumption⁶	With IR: 37 - 57V, 0.12 - 0.19A, 7.25W Without IR: 37 - 57V, 0.08 - 0.12A, 4.3W Extended temperature range: N/A	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: Yes

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Should the customer choose to use their own USB-C cable, it must be USB-C 3.1 (or higher) speed rated.

4. +/- Aux not currently supported. Support is forthcoming.

5. Frame rate can be adjusted by support.

6. Extended temperature range includes operating temperatures below -8.5°C / 16.7°F and assumes IR will be enabled.



CM42-S Mini Split

Tech Specs


General

Operating Temperature	-10°C to 50°C / 14°F to 122°F	LED Indicator	System power and status indicator
Humidity	0 to 90%	Warranty	10 Years
Included Accessories	T10 security torx screwdriver, 1x 1/4"-20 screw, 4x wall screws, 4x wall anchors, 1x 2m USB-C cable, double-sided tape for wall mounting main unit and sensor unit mount bracket	Certifications	FCC, IC

Mechanical

Weight	Camera Main Unit: 242.8g / 8.6oz Camera Sensor Unit: 110.2g / 3.9oz USB-C Cable: 79.9g / 2.8oz	Body	Aluminum, plastic
Dimensions ⁷	Camera Sensor Unit: H: 47.4mm / 1.9in, W: 36.4mm / 1.4in, L: 40.2mm / 1.6in Camera Main Unit: H: 25.5mm / 1.0in, W: 89.0mm / 3.5in, L: 152.0mm / 6.0in		

Dimensions



Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, Person of Interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and Storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People Analytics	People search, attribute search, face search, Occupancy Trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and Privacy	Live links, live face blur, privacy regions, audit log
Vehicle Analytics	Vehicle search, attribute search, motion search, trajectory analysis, Occupancy Trends, AI-powered search		

7. Mechanical dimensions listed here represent the sensor unit without the bracket attached.



Ordering Information

CM42-S Mini Split pricing

Model Number	MP ¹	WDR	Lens	IR Range	Onboard Storage	Maximum SQ Onboard Retention ¹	People/Vehicle Analytics	Cost (MSRP) ^{USD}
CM42-256S-HW	5.0MP	✓	Fixed	15m / 49ft	256GB	30 Days	✓	\$999
CM42-768S-HW	5.0MP	✓	Fixed	15m / 49ft	768GB	90 Days	✓	\$1799

Video Security Cloud License pricing

Model Number	Description	Cost (MSRP) ^{USD}
LIC-CAM-1Y	1-Year Camera License	\$199
LIC-CAM-3Y	3-Year Camera License	\$549
LIC-CAM-5Y	5-Year Camera License	\$899
LIC-CAM-10Y	10-Year Camera License	\$1,799

Viewing Station pricing

VX52-HW	VX52 Viewing Station	\$499
LIC-VX-1Y	1-Year Viewing Station License	\$499
LIC-VX-3Y	3-Year Viewing Station License	\$1,299
LIC-VX-5Y	5-Year Viewing Station License	\$1,999
LIC-VX-10Y	10-Year Viewing Station License	\$3,999

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>