

CS39-K			
Product image		Features	
		★ F2.0 large aperture, more light intake, clearer night vision	
		★ Infrared night vision, indoor night vision distance 8-10 meters	
		★ WiFi connection, remote access	
		★ ISP image processing technology, preserving true colors	
		★ Human detection, real time alerts	
No.	Sorts	Type	Parameters
1	System	Operating system	Linux
		Online visitor	Supports 4 visitors at the same time
		APP	O-KAM Pro
2	Collection	CPU	Ingenic
		Memory	512Mb
		Lens	4mm
		Image sensor	1/3.27 2MP progressive scanning CMOS sensor
		Minimum illumination	0.5Lux (color mode), 0.1Lux (b&w mode)
		Sensor performance	Support automatic white balance, automatic gain control and automatic backlight compensation
		Night vision	Black and white night vision
3	Video	Viewing angle	Diagonal 81°
		Resolution	1080P 1920x1080/15FPS/2MP ; 1296P 2304x1296/15FPS/3MP (Interpolation)
		Night vision	Black and white night vision
		Compression standard	H.264 main profile/Motion-JPEG/JPEG
		IR control	IR-CUT, soft photosensitive control
4	Audio	Bit rate	128 ~ 4096kbps
		Image adjustment	Brightness, contrast, OSD display
		Input	Built-in -38dB microphone
		Output	Built-in 8Ω1W speaker
5	Pan/Tilt	Sampling frequency/bit width	8KHz/16bit
		Compression standard/Bit	G711A
		Rotation angle	Pan: 355° Tilt: 135°
		Network interface	N/A
6	Network	Network protocol	TCP/IP,HTTP,TCP,UDP,DHCP,DNS,NTP,RTSP,P2P
		Wireless network	IEEE802.11b/g/n
		Wireless frequency	2.4G
		Wireless security encryption	64/128-bit WEP/WPA-PSK/WPA2-PSK
7	Storage	External TF card	Supports T-Flash cards (up to 256GB)
		Cloud storage	Support cloud storage, users can purchase according to their needs.
8	Calling Function	Touch Call	Touch the call button on the camera. When the App receives a call alert, the user can press the answer icon in the App to start a two-way intercom.
9	Alarm	Alarm detection	Motion detection, human detection, human framing, human tracking and area detection
10	Physical Indicators	Rated voltage	DC5V±5%
		Power consumption	Rated: 2.9W (0.58A); Full function on: 6W (1.2A)
		Operating condition	Working temperature: -10 ~ 45°C, working humidity <90%
		Weight	Net weight: 235g Gross weight: 435g
		Camera size	82x82x125mm
		Packaging box size	90x90x185mm
		Carton size	470x470x395mm, 50PCS/carton