

## Low Profile Ducted, 14kW

Ducted

White



Low Profile Ducted systems offer total heating and cooling to multiple rooms, with a slim indoor unit hidden in the ceiling and discreet vents.

- Precise temperature control, with an operational range from -20°C to 50°C
- Slim design for installation in shallow ceiling cavities, such as in multistorey buildings
- Remote control using the SmartHQ™ app when the optional Wi-Fi accessory is installed
- Blue Fin coating on the outdoor condenser helps to prevent environmental corrosion

### FEATURES & BENEFITS

#### Comfort in all conditions

Control the humidity level inside using the Dry function. By removing excess moisture in the air, you can create a comfortable and healthy environment that feels cooler – all while using less energy than Cool mode.

#### Control from anywhere

Installing the optional Wi-Fi accessory lets you control your air conditioning from your phone with the SmartHQ™ app, or use voice control with a smart home device.

#### Efficient and effective

The DC fan motor is more energy efficient than a standard AC motor and it is also highly adjustable. This means you can adjust the static pressure and airflow for optimal performance to suit your layout.

#### Flexible installation

The low-profile design of this unit is ideal for installation in shallow ceiling cavities, such as between floors in multistorey buildings. The panel system also allows for easy conversion between rear or bottom return air installation.

#### Peace of mind

Moisture from the air is collected during normal operation. The Low Profile Ducted indoor unit has a condensate pump with built-in fail-safe switch for reliable moisture draining in confined spaces.

#### Central controller

With an optional central controller, you can control individual or connected units from a simple-to-use display. Schedule your air conditioning to turn on to create the perfect environment just before you wake up, or switch off at the end of the workday.

### SPECIFICATIONS

#### Capacity

Cooling capacity (kW)	13.0kW
Heating capacity (kW)	15.0kW

#### Consumption

COP	3.5
EER	3.16
HSPF-RES (Hot/Average/Cold)	3.646 / 3.351 / 2.978
HSPFCOM (Hot/Average/Cold)	3.634 / 3.455 / 3.060
TCSPF-COM (Hot/Average/Cold)	4.410 / 4.465 / 4.749
TCSPF-RES (Hot/Average/Cold)	4.134 / 3.858 / 3.977

#### Features

24 Hour timer	•
Auto restart	•
Blue fin coils	•
Condensate pump	•
DC inverter	•
DRED (Demand Response) ready	•
Dry mode	•
MEPS approved	•
Refrigerant factory charge	2.9
Self diagnostics	•
SmartAir2 WiFi adaptor	Optional
SmartHQ WiFi control	Optional
Standard controller	Optional
Voice control via Google Home or	•

#### Installation

Indoor unit model	AD140S2SM7FA
Indoor unit weight	52kg
Liquid line	Pipe size 9.52
Maximum pipe run	75

Outdoor unit model	<b>1U140S2SP5FA</b>
Outdoor unit weight	<b>105kg</b>
Suction line	<b>Pipe size 19.05</b>

### Performance

Airflow	<b>694L/S</b>
DC inverter	<b>•</b>
R32 Refrigerant	<b>•</b>
Sound power SWL (outdoor)	<b>70dBA</b>
Sound pressure SPL (indoor)	<b>46 / 43 / 38dBA</b>
Sound pressure SPL (outdoor)	<b>53dBA</b>

### Power Requirements

Power phase	<b>1.0</b>
Supply frequency	<b>50Hz</b>
Supply voltage	<b>230V</b>

### Product dimensions

Indoor unit depth	<b>700 mm</b>
Indoor unit height	<b>248 mm</b>
Indoor unit width	<b>1500 mm</b>
Outdoor unit depth	<b>370 mm</b>
Outdoor unit height	<b>1350 mm</b>
Outdoor unit width	<b>950 mm</b>








### Warranty

Parts and labour	<b>5 years</b>
------------------	----------------

SKU	<b>51585</b>
-----	--------------

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? 2020 Haier Inc. All rights reserved.

### Other product downloads available at haier.com

	User Guide - Wired Controller YR-E17A
	User Guide - Wired Controller YR-E16B
	User Guide - Smartzone Controller
	Product Brochure
	Service & Warranty
	Installation Guide - Duct Type Air Conditioner
	Installation Guide - Split System Air Conditioner

### A PEACE OF MIND SALE

**24 Hours 7 Days a Week Customer Support**

**T** 1300 729 948 **W** www.haier.com