QUICK REFERENCE GUIDE > OR90SDG6X1 Date: 15.09.2025 > 1

90cm Series 9 Contemporary 5 Burner Dual Fuel Pyrolytic Freestanding Cooker

Series 9 | Contemporary




Get the best of both worlds with dual fuel. A gas hob with wok burner is paired with a convection oven with 9 functions.

- Five burner cooktop with with dual wok burner and two powerful triple ring burners
- Convection oven with 140L total capacity and nine oven functions plus rotisserie, including Pastry Bake™ with pizza mode
- · Non-tip full-extension shelves for safe removal of hot dishes

Pyrolytic self-clean that breaks down food residue for an easy clean

DIMENSIONS

Height	898 - 946 mm
Width	897 mm
Depth	600 mm



FEATURES & BENEFITS

Multi-Shelf Cooking

Our AeroTech $^{\text{m}}$ system circulates air evenly throughout the entire oven so dishes on the top shelf turn out just as perfect as food cooking on the bottom shelf.

Quality And Durability

Every detail has been carefully crafted. The solid, perfectly balanced soft-close door, precise electric temperature control and chromed cast zinc dials all add up to an exceptional, premium range.

Burner Power & Control

Instant and immediate control from the highest to the gentlest heat. The finely tuned hob controls let you sear, stir fry or simmer a delicate sauce to perfection.

Easy To Clean

Cleaning up spills is effortless. Your hob simply needs a quick wipe to keep it looking good as new. The pyrolytic self-clean oven cycle breaks down food residue at a very high temperature, leaving a light ash that's easily removed with a damp cloth.

Even Heat

Accurate, electronically-controlled oven heat ensures a great result every time.

Large Capacity Oven

The generous 140L total capacity oven gives you plenty of space to cook multiple dishes at once.

SPECIFICATIONS

Accessories (included)

Flat wire shelf	1
Full extension sliding shelves	2 sets (part 578744)
Full extension telescopic shelves	2 sets (part 578744)
Grill rack	TRUE
Roasting dish	1
Rotisserie set	1 set

QUICK REFERENCE GUIDE > OR90SDG6X1 Date: 15.09.2025 > 2

Accessories (sold separately) Kick strip, stainless steel (optional)	cast) • KICKOR90X1	Consumption Energy usage	1.6.2l/W/b/ovele	Electronic oven control Full extension telescopic sliding shelves Soft open/close door True convection	•
Accessories (sold separately)	KICKOR90X1	Energy usage	1.6.2l/W/b/ovelo	Soft open/close door	•
	KICKOR90X1	Energy usage	1.6.2kWh/ayala		•
	KICKOR90X1	Energy usage	1.62kWh/ayala	True convection	•
	KICKOR90X1		1.62kWh/ayala		-
Kick strip, stainless steel (optional)	KICKOR90X1		1.62kWh/cycle	Twin cavity fans	•
		In-use energy carbon emissions estimate	0.5kgCO2e/cycle	Warming drawer	•
Burner ratings		Combania		Out on formation a	
Dual wok burner inner/outer (LPG)	0.3 - 4.5kW	Controls		Oven functions	
		Audio feedback	•	Bake	•
	0.4 - 4.5kW	Automatic cooking/minute timer	•	Energy slow cook	•
Maximum burner power	4.5kW	Automatic pre-set temperatures	•	Fan bake	•
Semi-rapid burner (LPG)	1.2kW	Celsius/Fahrenheit temperature	•	Fan forced	•
Semi-rapid burner (natural gas)	1.2kW	Electronic clock	•	fanGrill	•
Total cooktop power	14.9kW	High resolution display	•	Grill	•
Triple ring wok burner (LPG) x2	4.0kW	Laser etched graphics	•	Number of functions	9
Triple ring wok burner (natural gas) x2	4.0kW	Precise electronic temperature control	•	Pastry Bake with Pizza mode	•
		Sabbath mode	•	Roast	•
Capacity		Turned stainless steel clock buttons	•	Rotisserie	•
Capacity		Turned stainless steel clock crown (dial)	•	True convection	•
Shelf positions (main oven)	6	Turned stainless steel dials with illuminated	•		
Total capacity	140 L	halos			
Usable capacity (main oven)	120 L			Oven performance	
		Installation Dimensions		CoolTouch door	Quadruple glazed
Cleaning		Installation cutout dimensions (Depth)	600 mm	Warming drawer power	202 W
Acid resistant graphite enamel	•	Installation cutout dimensions (Width)	900 mm		
Drop down grill element	•			Power requirements	
Pyrolytic proof shelf runners	•		<u></u>	Amperage	23 A
Pyrolytic self-clean	•	Oven features		Supply frequency	50 Hz
Removable oven door	•	AeroTech™ technology	•	Supply frequency	30 HZ

QUICK REFERENCE GUIDE > OR90SDG6X1

Product details

Self Cleaning Sf Yes

Product dimensions

 Depth
 600 mm

 Height
 898 - 946 mm

 Width
 897 mm

Rangetop features

Brass burner spreader (power burner)

Embossed brass burner cap (power burner)

Hob rear trim

60 mm

LPG / Natural Gas compatible

Sealed range top

Safety

Advanced cooling system	
Anti-tilt bracket	
Balanced oven door	
Catalytic venting system	
CoolTouch door	
Flame failure system	
Full extension telescopic sliding shelves	
Non-tip shelves	
Spill containment	26

SKU 81698

The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. © Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

Declaration of Conformity

Energy Rating

Installation Guide

Installation Guide - Kick Strip

Product Information Sheet

Product Fiche

Revit Dual Fuel Cooker

Rhino Dual Fuel Cooker

Sketchup Dual Fuel Cooker

↓ User Guide Dual Fuel Cooker

Where applicable:

All appliances use energy, and energy usage typically generates carbon emissions. Fisher & Paykel Appliances' In-use Energy Carbon Emissions Estimate indicates carbon emissions from a product's in-use energy. This is calculated either annually or per cycle, using the product's market-specific energy label energy consumption data multiplied by the carbon emissions factor for energy in your country or region.

Our In-use Energy Carbon Emissions Estimate is designed to assist customers in making informed purchasing decisions when comparing different Fisher & Paykel products. For example, a heat pump dryer typically has a lower In-use Energy Carbon Emissions Estimate than a vented dryer.



