

# Fremco Hydraulic Multipower Pack

Product Images

Product Code: MULTIPOWER



## Short Description

---

The Hydraulic Multipower Pack is the required hydraulic power source for the MiniFlow, MultiFlow and PowerFlow machines.

- Oil flow 18 l.p.m at 3300 r.p.m.
- Working pressure nominal 100 bar.
- Pressure relief valve set at 110 bar.
- Pump gear pump.
- Oil temperature Max. 70°C.
- Hydraulic oil tank capacity min. 5 litres/max. 7 litres
- Petrol tank capacity 3.1 litres
- Hydraulic system - Max. 8 litres
- Filter system (filter element) 25 Micron with by-pass
- Engine Honda gX200QX7 6.5 hP (gross power) 4-stroke petrol with oil alert system.
- Petrol - normal or unleaded.
- Engine oil 1.1 litres.
- Guaranteed sound power level  $L_{wA}$  100 dB
- Sound pressure level 1 m  $L_{pA}$  88 dB
- Dimensions (l x w x h) 630x530x510 mm
- Weight, without hydraulic oil 54 kg.

## Description

---

The Hydraulic Multipower Pack is the required hydraulic power source for the MiniFlow, MultiFlow and PowerFlow machines.

- Oil flow 18 l.p.m at 3300 r.p.m.
- Working pressure nominal 100 bar.
- Pressure relief valve set at 110 bar.
- Pump gear pump.
- Oil temperature Max. 70°C.
- Hydraulic oil tank capacity min. 5 litres/max. 7 litres
- Petrol tank capacity 3.1 litres
- Hydraulic system - Max. 8 litres
- Filter system (filter element) 25 Micron with by-pass

- Engine Honda gX200QX7 6.5 hP (gross power) 4-stroke petrol with oil alert system.
- Petrol - normal or unleaded.
- Engine oil 1.1 litres.
- Guaranteed sound power level  $L_{wA}$  100 dB
- Sound pressure level 1 m  $L_{pA}$  88 dB
- Dimensions (l x w x h) 630x530x510 mm
- Weight, without hydraulic oil 54 kg.