


5TH GENERATION ADVANTAGE SERIES

DUCTLESS MINI-SPLIT HEAT PUMP

Eligible for
MRCOOL[®]
CARE[✓]
PROGRAM



CHARGED WITH
R-454B
REFRIGERANT



 JUST ASK
amazon alexa

 works with the
Google Assistant



**SMART HVAC
CONTROLLER[®]**

- ✓ Affordable
- ✓ Highly Efficient
- ✓ Low Ambient Cooling
- ✓ 16 Ft Install Kit Included**

***Must be installed by HVAC technician*

SCAN HERE >
for the most up-to-date
version of this brochure.



*Pat: <https://www.mrcool.com/mrcool-patents/>

Version Date: 07-08-2025



FEATURES



Timer



Smartphone App



Leakage Detection

LOW 5°F

Low Ambient Cooling



Follow me®



Quiet Running



Gold Fin® Condenser



DC Inverter

MODEL NO.		Indoor Unit	A-09-HP-WMAH-115D-O	A-12-HP-WMAH-115D-O	A-09-HP-WMAH-230D-O
		Outdoor Unit	A-09-HP-C-115D-O	A-12-HP-C-115D-O	A-09-HP-C-230D-O
CAPACITY & PERFORMANCE					
Cooling Capacity		Btu/h	9000	12000	9000
	SEER2	Btu/w	21.5	21.2	21.2
	EER2	Btu/w	12.5	10.1	12.6
Heating Capacity		Btu/h	10000	12000	10000
	HSPF2-4	Btu/w	9.0	8.7	9.1
	HSPF2-5	Btu/w	7.0	6.7	7.0
Max Coverage Area*		sq. ft.	Up to 400	Up to 550	Up to 400
Outdoor noise level (Hi)		dB(A)	52.5	54.0	53.5
*Max Coverage Area is determined using ideal installation conditions.					
ELECTRICAL PARTS					
Power Supply		V - Hz.Ph	115V - 60Hz, 1Ph	115V - 60Hz, 1Ph	208-230V - 60Hz, 1Ph
Minimum Circuit (Disconnect)					
	Indoor	A	3.0	3.0	3.0
	Outdoor	A	18.0	19.0	12.0
Maximum Fuse (Breaker)					
	Indoor	A	15.0	15.0	15.0
	Outdoor	A	20.0	20.0	15.0
DIMENSIONS & WEIGHT					
Net Dimension (WxDxH)					
	Indoor	inch	28.43 x 7.36 x 11.42	31.57 x 7.44 x 11.69	28.43 x 7.36 x 11.42
	Outdoor	inch	30.12 x 11.93 x 21.85	30.12 x 11.93 x 21.85	30.12 x 11.93 x 21.85
Packing Dimension (WxDxH)					
	Indoor	inch	31.10 x 10.63 x 14.76	34.45 x 11.22 x 14.96	31.10 x 10.63 x 14.76
	Outdoor	inch	34.92 x 13.27 x 24.02	34.92 x 13.27 x 24.02	34.92 x 13.27 x 24.02
Net/Gross Weight					
	Indoor	lbs	17.42/22.93	19.40/25.13	16.98/22.27
	Outdoor	lbs	56.66/62.17	61.29/67.02	54.23/59.74
REBATE SUMMARY					
Energy Star V6.1			✓		✓
Energy Star V6.1 Cold Climate					✓
Federal Tax Credits			✓		✓
NEEP			✓	✓	✓
GHG			✓		✓
CEE Tier 1 - North			✓	✓	✓
CEE Tier 2 - North					
CEE Tier 1 - South			✓		✓
CEE Tier 2 - South			✓		✓
MASS Save					✓



*Data provided by AHRI

All specifications are preliminary and are subject to change during mass production.



MODEL NO.	Indoor Unit		A-12-HP-WMAH-230D-O	A-18-HP-WMAH-230D-O	A-24-HP-WMAH-230D-O	A-36-HP-WMAH-230D-O
	Outdoor Unit		A-12-HP-C-230D-O	A-18-HP-C-230D-O	A-24-HP-C-230D-O	A-36-HP-C-230D-O

CAPACITY & PERFORMANCE

Cooling Capacity		Btu/h	12000	18000	24000	36000
	SEER2	Btu/w	21.3	19.2	18.7	18.0
	EER2	Btu/w	10.8	10.8	10.0	9.0
Heating Capacity		Btu/h	12000	18800	24000	36000
	HSPF2-4	Btu/w	9.1	9.6	9.3	8.5
	HSPF2-5	Btu/w	7.0	7.5	7.3	6.8
Max Coverage Area*		sq. ft.	Up to 550	Up to 800	Up to 1050	Up to 1550
Outdoor noise level (Hi)		dB(A)	54.0	56.0	59.5	60.5

*Max Coverage Area is determined using ideal installation conditions.

ELECTRICAL PARTS

Power Supply		V - Hz.Ph	208-230V- 60Hz, 1P	208-230V- 60Hz, 1P	208-230V- 60Hz, 1P	208-230V- 60Hz, 1P
Minimum Circuit (Disconnect)						
	Indoor	A	3.0	3.0	3.0	3.0
	Outdoor	A	13.0	15.0	19.0	33.0
Maximum Fuse (Breaker)						
	Indoor	A	15.0	15.0	15.0	15.0
	Outdoor	A	15.0	20.0	20.0	35.0

DIMENSIONS & WEIGHT

Net Dimension (WxDxH)						
	Indoor	inch	31.57 x 7.44 x 11.69	37.99 x 8.46 x 12.56	42.52 x 8.90 x 13.19	49.57 x 11.10 x 14.25
	Outdoor	inch	30.12 x 11.93 x 21.85	31.69 x 12.99 x 21.81	35.04 x 13.46 x 26.50	37.24 x 16.14 x 31.89
Packing Dimension (WxDxH)						
	Indoor	inch	34.45 x 11.22 x 14.96	41.14 x 12.01 x 16.14	45.47 x 16.34 x 12.60	52.76 x 17.72 x 15.16
	Outdoor	inch	34.92 x 13.27 x 24.02	36.02 x 14.57 x 24.21	39.17 x 15.67 x 29.13	42.91 x 19.68 x 34.84
Net/Gross Weight						
	Indoor	lbs	19.40/25.13	24.47/32.63	30.64/39.46	40.34/54.01
	Outdoor	lbs	59.08/64.37	72.31/78.48	94.58/102.29	150.35/160.27

REBATE SUMMARY

Energy Star V6.1				
Energy Star V6.1 Cold Climate			✓	
Federal Tax Credits				
NEEP	✓	✓	✓	✓
GHG			✓	
CEE Tier 1 - North	✓	✓	✓	✓
CEE Tier 2 - North		✓		
CEE Tier 1 - South				
CEE Tier 2 - South				
MASS Save			✓	

*Data provided by AHRI

All specifications are preliminary and are subject to change during mass production.



ALL MRCOOL® Ductless Mini splits HEAT and COOL Efficiently
And Can Be Programmed And Controlled Remotely With
Our Smartphone APP, Optional HVAC Ductless Mini-Stat, Or
Included Hand-held Remote Control.

www.mrcool.com

48 Remington Way | Hickory, KY 42051 | 270.366.0457

*The original, registered owner must be enrolled in the MRCOOL® Care Program every year in order to qualify for the 2 year full unit replacement for compressor failure and lifetime compressor replacement.