


# 4" X 3" FLOOD **DRIVING LIGHT SET** & HARNESS KIT

WP ITM. LM534391H Care & Use Instructions



## Important, retain for future reference: Read carefully

\*Check state and local laws before use. Items are DOT/SAE compliant when used in cordance to this manual. The manufacturer, distributor, and seller shall not be liable for any injury, loss or damage, incidental or consequential, arising out of the use or intended use of the product.

## WARNINGS

## IMPORTANT SAFETY INSTRUCTIONS

- 1. SAVE THESE INSTRUCTIONS This manual contains important safety and operating instructions.
- 2. Before using this product, read all instructions and cautionary markings
- 3. Do not expose the bare wires to rain, moisture, or snow.
- 4. Use of an attachment not recommended or sold by the manufacturer may result in a risk of fire, electric shock, or injury to
- 5. Do not operate with damaged Driving Light Set replace it immediately.
- 6. Do not operate the Driving Light Set if it has received a sharp blow, been dropped, or otherwise damaged in any way; take it to a qualified servicepersor
- 7. Do not disassemble the Driving Light Set; take it to a qualified serviceperson when service or repair is required. Incorrect reassembly may result in a risk of electric shock or fire.
- 3. To reduce risk of electric shock, disconnect the Driving Light Set before attempting any maintenance or cleaning. Turning off controls will not reduce this risk.

## **CAUTIONS**

- 1. Do not install or use product if it, in any way, impairs the safe operation of your vehicle.
- 2. Follow manufacturer's instructions to ensure the product is properly and safely installed.
- 3. Check your state or provincial laws before installing. Vehicle owner must comply with all applicable laws.
- 4. This product is intended for off-road purposes. Manufacturer and Seller assume no liability for installation or use, which are solely the responsibility of the purchaser.

5. The Manufacturer and Seller are not responsible or liable for consequential, incidental, or indirect damages, whether to person or property, resulting from the installation or improper use of this

**⚠ WARNING:** This product can expose you to chemicals including Di(2-ethylhexyl)phthalate (DEHP) and Diisononyl Phthalate (DINP), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

## **SPECIFICATIONS**


Beam Pattern: 1200LM Each Raw Lumens: 8 Each No. of LED Chips:

50,000 Hours LED Lifespan: 6500K Daylight White Color Temperature: 0.85A Each Amps:

10W Each Watts: 12V-24V DC IP67 Dust & Waterproof IP Rating:

Wire Gauge: 20AWG Yes DOT Compliant:

## PACKAGE INCLUDES



2 x 4" x 3" Flood Driving Lights

## Wiring Kit:



1 x Wiring Harness (In-line Relay and 15A Fuse)

4 x Spade Terminals

(Connectors and Sleeves)

## **Installation Kit:**



2 x M8 Nuts

2 x M8 Hex Head Screws (L25) 2 x M8 Washers 2 x M8 Spring Washers

\*The Flood Driving Lights come with the hex head screws, washers, spring washers, and nuts pre-installed. Please remove these components before continuing with the installation.

## **RECOMMENDED TOOLS & MATERIALS (NOT INCLUDED)**

- 3/8" Drill bit
- Wire strippers / cutters
- Ratchet & sockets / wrenches
- Wire extension (see AWG in Specifications)
- Connectors (crimp, heat shrink, quick splice)
- Non-conductive electrical tape
- Power Hub (LM534403, sold separately)




1 x Allen Kev

- Cable ties
- Wire loom
- Grommets

## **BEFORE INSTALLATION**

- 1. Electrical Ratings
  - Determine amperage requirements for the lights (Amps = Watts/Volts).
  - Use the correct fuse. The fuse rating should be higher than the total current draw of the lights to protect against surges or shots.
- Relay Requirements
- Use a relay for high amperage. If the lights draw more than 10 amps, use a relay to safely switch the higher current. The relay acts as a switch, allowing a low-current circuit to control a high-current circuit without running high current through the switch itself
- 3. Battery & Alternator Capacity
- Ensure your vehicle's battery and alternator can handle the additional load from the lights without draining the battery or overloading the alternator. Consider upgrading if your electrical system is already heavily loaded.

## **DIMENSIONS & MOUNTING**






1.73" / 43.92mm

106.7mm

# Screw (L25 M8 Washer M8 Spring Washer M8 Nut

**CAUTION:** When used as parking lights, the lights must be mounted at a height of not less than 15" nor more than 72" above the road surface. Alternatively, when used as auxiliary lights, they are intended to supplement, not replace, the vehicle's high-beam headlights.


## RECOMMENDED MOUNTING LOCATIONS



# **MOUNTING OPTIONS**

(Not Included)

- Ensure clamp-on mounts are appropriate for your light size.



Black Wire: Connect to ground (-) Red Wire: Off road light, connect

Blue Wire: Auxiliary light, connect to 12V power source (+)


White Wire: Parking light, connect to 12V power source (+)

## Option A - Wiring Harness

- Draw a diagram of where you want to install the lights, where the wires will run, where the relay and switch will be installed
- This will help you determine the amount of wiring you will need. Measure
- It will also help you determine where to permanently mount relay, switch, With the engine cool, test fit the wiring harness to ensure proper lengths for
- . Insert the RED (+) wire from the light into the RED (+) spade terminal on the wiring harness, and the adjacent BLACK (-) wire from the light into the BLACK (-) spade terminal. Use a crimp tool to secure both wires.
- . Repeat step 3 to connect a second light.
- 5. Once all lights are connected to the wiring harness, test light functionality.

**NOTE:** Use the provided connectors and sleeves for lighting connection if

- 6. If lights are functioning properly, it is now time to ensure the switch and relay are routed appropriately. NOTE: The in-line switch and relay will likely need to be secured and
- installed beyond the firewall inside the vehicle's interior. Look for a grommet on the firewall or in the upper part of the driver and passenger footwells Reference your vehicle's manual or other resources to determine how to best gain access through the firewall.
- Mount the switch.
- 8. Power on your vehicle and test the lights.
- 9. If everything is working properly, turn off your vehicle and secure any loose
- NOTE: Cable ties and wire loom are recommended for cable management and protection. Cable ties and wire loom are not included.



### Option B - Direct To Battery


- See Specifications for this light's AWG.
- for manual light control
- Recommendation: TYPE S 12V 40A Relay (included)

## Option C - Power Hub (LM534403, Sold Separately)


- utilizing DOT/SAE light mode functions. See the TYPE S LYNX 6, a 6-Switch Control Panel & Power Hub

40A Relay

- Test lights before finalizing installation.
- Use cable ties to secure loose wiring. Stay away from sources of heat and moving parts.



- This will require appropriate positive and negative extension wire gauge.
- Additional part requirements: In-line fuse holder, ring terminals, and switch
- This option is ideal for powering and controlling more than 2 lights and for



\\_\_\_\_\_/


Lighting Connection

6-Switch Control Panel & Power Hub (LM534403, sold separately)

Apple CarPlay

**OPTIONAL ACCESSORIES** 

Android Auto



LYNX 6

Visit www.typesauto.com for more information on where you can purchase additional accessories.

## WARRANTY

## LIMITED WARRANTY

TYPE S warrants, to the original purchaser, that its products are free from defects in material and workmanship for 2 years from the date of original purchase. Where permitted by law, TYPÉ S's liability shall be limited to that set forth in this limited express warranty. This limited express warranty shall be the exclusive remedy of the purchaser and TYPE S makes no other warranty of any kind aside from the limited

NOTE: Warranty only applies for North American customers of

## CONDITIONS OF WARRANTY

express warranty stated above.

If during the 2-year warranty period your new product is found to be defective, TYPE S will repair such defect, or replace the product, without charge for parts or labor subject to the following conditions:

- 1. All repairs must be performed by TYPE S.
- 2. All warranty claims must be accompanied by a copy of the sales receipt or bill of sale.
- 3. The equipment must not have been altered or damaged through negligence, accident, improper operation, or failure to follow the product instructions for installation, use, or care
- 4. The replacement of parts is excluded from the warranty when replacement is necessary due to normal wear and tear.
- 6. This is a "repair or replace" warranty only, and does not cover the costs incurred for the installation, removal or reinstallation of the product, or damage to any mobile phone device or vehicle.

5. Repair or replacement parts supplied by TYPE S under this warranty

are protected only for the unexpired portion of the original warranty.

## OWNER'S RESPONSIBILITIES:

TYPE S will make every effort to provide warranty service within a nable period of time. SHOULD YOU HAVE ANY QUESTIONS ABOUT SERVICE RECEIVED OR IF YOU WOULD LIKE ASSISTANCE IN OBTAINING SERVICE, PLEASE CALL TOLL FREE 1.866.294.9244 DURING REGULAR BUSINESS HOURS MONDAY THROUGH FRIDAY 8:00 AM TO 5:00PM

NOTE: Toll Free # is for North America Customers ONLY. See Customer service section for customer contact numbers for other

For customer service and technical support, please call us at 1.866.294.9244. If at that time it is determined that a replacement unit is needed, the support representative will issue a Return Authorization and instruct on how to get a new unit. TYPE S makes no other warranty of any kind aside from the limited express warranty stated herein.

DISCLAIMER OF WARRANTIES, INCLUDING WARRANTY OF MERCHANITARII ITY AND WARRANTY OF FITNESS FOR PARTICULAR PURPOSE: EXCEPT AS SPECIFICALLY SET FORTH HEREIN, NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIES, IS MADE AS TO THE DRIVING LIGHT SET. EXCEPT AS EXPRESSLY SET FORTH HEREIN, TYPE S AND/OR ITS AFFILIATES EXPRESSLY DISCLAIMS, WITHOUT LIMITATION, ANY STATUTORY WARRANTIES AND ALL IMPLIED WARRANTIES INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

TYPE S and/or its affiliates are not responsible for a user's intended or actual use of the Driving Light Set. In no event shall TYPE S and/or its affiliates have any liability for any losses (whether direct or indirect, in contract, tort or otherwise) incurred in connection with the Driving Light Set, including but not limited to damaged property, personal injury and/or loss of life. Neither shall TYPE S and/or its affiliates have any liability for any decision, action taken based on relying on the stability or performance of the Driving Light Set. TYPE S and/or its affiliates, the manufacturer, distributor and seller shall not be liable for any injury, loss or damage, incidental or consequential, arising out of the use or intended use of the product.

Apple CarPlay is trademark of Apple Inc. Android Auto is trademark of Google LLC

4" x 3" Flood Driving Light Set LM534391H Responsible Party: 2975 Red Hill Ave., Ste. 100. Costa Mesa, CA 92626, U.S.A

Tel: 1.866.294.9244

## TYPES

2975 Red Hill Ave., Ste. 100 Costa Mesa, CA 92626, U.S.A 1.866.294.9244 | info@typesauto ©2024 TYPE S. All rights reserved.


Made in Cambodia

- This method will require drilling directly into your vehicle. Select

Option B - Third-Party Universal / Custom Mounting Brackets

- Ensure mounting brackets are appropriate for your light size.

## **WIRING**



to 12V power source (+)

ML-534391H\_V1

A Horizon Brands Company

Option A - Direct To Vehicle

a sturdy, secure location. See drill bit requirements in Specifications.

Option C - Third-Party Universal Clamp-On Light Mounts

