UTVS-RNG-2BATT-KIT





PERFORMANCE AUDIO

WARRANTY

Should your product require service, please consult with the dealer from which it was purchased or contact a local UTV STEREO dealer directly. Units received without an accompanying return authorization number will not be processed. Please contact your UTV Stereo dealer or contact UTV Stereo directly to obtain a return authorization number. Additionally, you must include a copy of your purchase receipt from an authorized UTV Stereo dealer for consideration of an in-warranty service. Units received without a receipt will be held for 30 days. Allowing us time to contact you and obtain a copy of the receipt. After 30 days, all units will be returned. For more information please visit our website.



DO NOT SUBMERGE THIS PRODUCT.
THIS WILL VOID YOUR WARRANTY.



FAILURE TO FOLLOW INSTALLATION INSTRUCTIONS COULD VOID YOUR WARRANTY.

UTV STEREO and the UTV STEREO logo are registered trademarks. All other brand names are trademarks or registered trademarks of their respective owners. These trademark holders are not affiliated with UTV Stereo. All rights reserved. Designed in USA.

Copyright[©] 2025 UTV STEREO

Tel. 480-616-2299 Address: 7561 East Baseline Road Mesa, AZ 85209

DESIGNED FOR UTV - POWERSPORTS - MARINE

480.616.2299 / UTVSTEREO.COM



CONTENTS:

- Parts List
- Wire Diagram
- Installation Instructions

OWNERS MANUAL

FOR MODEL: UTVS-RNG-2BATT-KIT


POLARIS RANGER 2ND BATTERY KIT

PART #: UTVS-RNG-2BATT-KIT

PARTS LIST:	
TANTO LIST.	
UTVS 1200 Battery	x1
80A Isolator	x1
Battery Mount	x1
Top Bracket	x1
4 AWG Blue Power Wire	x2
4 AWG Black Ground Wire	x1
12 AWG Braided Harness	x1
L-Bracket	x1
Mounting Hardware:	
Thread Cutting Bolt	x1
Self Tapping Screws	x2
Split Washers	x5
Flat Washers	x2

WIRE DIAGRAM:

Bolts





access the battery compartment











Remove the 3 bolts shown here

Remove the 2 hex bolts on side step

Remove single hex bolt shown here

passenger floor













Remove 4 hex bolts located under the vehicle shown here

Remove the plastic panel

Prepare 2nd battery kit parts

Remove the hardware from the

smaller posts of isolator

Remove hardware from main posts of isolator

Connect Blue 4AWG wires to the larger posts of isolator













Secure Blue 4 AWG wires tightly

х5

Attach the isolator to the battery plate using the included hardware

Remove the 2 plastic clips shown here

Remove the bolt shown here

Attach the 4AWG Ground wire to the vehicle

Re-tighten the bolt















the L-Bracket

Place the thread cutting bolt through

Attach securely to vehicle

Place the battery plate into the vehicle Line up the 2 holes shown on plate

Use the hardware shown to secure with 2 holes in vehicle battery plate to L-Bracket


















Use included self tapping screws to secure the battery plate to the frame

Place the UTVS 1200 Battery onto the battery plate


Place the battery bracket over the battery and secure using the hardware shown

Remove the cover to the Pulse Bar located on the rear passenger side roof liner



Run the harness through the













roof liner as shown

Remove the plastic piece shown

Remove the 4 holts shown here

Run the harness down through the plastic down to the 2nd battery

from harness to isolator

Secure tightly



and negative terminals of UTVS 1200 battery vehicle battery compartment





Tighten securely

