



Split System Heat Pumps Single Phase – 1½-5 Tons



Gold SI (4A6H3-B)

Table SH-3-A— Gold SI Heat Pump (Previously Heritage 13)


Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size	
			H	W	D					OD Gas	OD Liq.
4A6H3018C1000A	208/230/1/60	19,000	29	33	30	189	76	9	15	5/8	3/8
4A6H3024C1000A	208/230/1/60	24,000	29	33	30	191	75	12	20	5/8	3/8
4A6H3030B1000A	200/230/1/60	29,400	33	33	30	221	76	15	25	3/4	3/8
4A6H3036B1000A	208/230/1/60	34,800	33	37	34	261	75	18	30	3/4	3/8
4A6H3042B1000A	208/230/1/60	41,500	33	37	34	253	75	26	45	3/4	3/8
4A6H3048B1000A	208/230/1/60	47,000	37	37	34	269	75	28	50	7/8	3/8
4A6H3060B1000A	208/230/1/60	57,500	41	37	34	284	75	34	60	7/8	3/8



Silver XI (4A6B4)

Table SH-3-B— Silver XI Heat Pump (Previously American Standard 14)

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size	
			H	W	D					OD Gas	OD Liq.
4A6B4018G1000A	208/230/1/60	18,000	29	33	30	204	76	9	15	5/8	3/8
4A6B4024G1000A	208/230/1/60	24,000	33	33	30	236	76	11	15	5/8	3/8
4A6B4030G1000A	208/230/1/60	30,000	33	37	34	273	78	15	25	3/4	3/8
4A6B4036G1000A	208/230/1/60	36,000	33	37	34	261	76	18	30	3/4	3/8
4A6B4042E1000A	208/230/1/60	42,000	41	37	34	313	78	27	45	3/4	3/8
4A6B4048E1000A	208/230/1/60	48,000	45	37	34	331	78	29	50	7/8	3/8
4A6B4049E1000B	208/230/1/60	48,000	45	37	34	331	76	28	50	7/8	3/8
4A6B4060E1000A	208/230/1/60	60,000	45	37	34	332	78	35	60	7/8	3/8
4A6B4061E1000A	208/230/1/60	60,000	45	37	34	332	76	36	60	1 1/8	3/8




Silver SI (4A6B3)

Table SH-3-C— Silver SI Heat Pump (Previously American Standard 13)

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size	
			H	W	D					OD Gas	OD Liq.
4A6B3018B1000A	208/230/1/60	17,000	29	33	30	201	79	9	15	5/8	3/8
4A6B3024B1000A	208/230/1/60	23,000	29	33	30	204	81	12	20	5/8	3/8
4A6B3030B1000A	208/230/1/60	28,500	33	33	30	221	80	15	25	3/4	3/8
4A6B3036B1000A	208/230/1/60	34,500	33	37	34	261	79	18	30	3/4	3/8
4A6B3042B1000A	208/230/1/60	40,500	33	37	34	253	80	26	45	3/4	3/8
4A6B3048B1000A	208/230/1/60	46,500	37	37	34	269	78	28	50	7/8	3/8
4A6B3060B1000A	208/230/1/60	58,500	41	37	34	284	78	34	60	7/8	3/8

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.



Silver SI (4TWB3)

Table SH-3-D — Silver SI Heat Pump (Previously American Standard 13)

Model Number	Power Supply	Nom. Cap. Cooling (BTUH)	Uncrated Dimensions(in.)			Shipping Weight (lbs.)	Sound** Rating	MCA*	Max. Fuse*	Line Size (in)	
			H	W	D					OD Gas	OD Liq.
4TWB3018C1000A	208/230/1/60	17,000	29	33	30	189	79	9	15	5/8	3/8
4TWB3024C1000A	208/230/1/60	23,000	29	33	30	191	81	12	20	5/8	3/8
4TWB3030B1000B	208/230/1/60	28,500	33	33	30	221	80	15	25	3/4	3/8
4TWB3036B1000B	208/230/1/60	34,500	33	37	34	261	79	18	30	3/4	3/8
4TWB3042B1000B	208/230/1/60	40,500	33	37	34	253	80	26	45	3/4	3/8
4TWB3048B1000B	208/230/1/60	46,500	37	37	34	269	78	28	50	7/8	3/8
4TWB3060B1000B	208/230/1/60	58,500	41	37	34	284	78	34	60	7/8	3/8

* Information subject to change. Please confirm with current Product Data/Service Facts for current factory production.

** Rated in accordance with AHRI Standard 270-2008.

Split System Heat Pumps Single Phase – 1½-5 Tons

Table SH-4-A — Features

	(4A6H3-B)	(4A6B4)	(4A6B3)	(4TWB3)
• SEER up to	14.50	16.00	14.00	14.00
• HSPF up to	9.00	9.00	8.50	8.50
• Duration™ compressor	✓	✓	✓	✓
• Comfort-R™ mode approved	✓	✓	✓	✓
• DuraBase™ base, fast complete drain, weatherproof	✓	✓	✓	✓
• Easy-Sess™ cabinet, service access & refrigerant connections with full coil protection	✓	✓	✓	✓
• Spine Fin™ coil	✓	✓	✓	✓
• Compressor sump heat - factory installed	—	✓	✓	—
• Demand Defrost Control w/ Lite Port™ /Stored Diagnostics	✓	✓	✓	✓
• Quick start kit-factory installed	1½-3,5	1½-3,5	1½-3	1½-3
• Low Pressure Switch	3.5-5	3.5-5	3.5-5	3.5-5
• Factory supplied charge	R-410A	R-410A	R-410A	R-410A
• Glossy corrosion resistant finish	✓	✓	✓	✓
• High pressure switch	✓	✓	✓	✓
• Internal high / low pressure & temperature protection	✓	✓	✓	✓
• Liquid line filter drier - factory installed	✓	✓	✓	✓
• Polyslate gray cabinet	—	✓	✓	✓
• Spinnaker gray cabinet	✓	—	✓	—
• 10-year registered limited warranty on compressor, outdoor coil & all other functional parts (Residential Use)®	✓	✓	✓	✓
• Extended warranties available	✓	✓	✓	✓

Table SH-4-B — Optional Accessories

Model Number	Description	Shipping Weight				
AY28X084.....	Evaporator Defrost Control	1	✓	✓	✓	✓
BAYCCHT300	Crankcase Heater Kit (Reciprocating)	1	1½-3	1½-3	1½-3	1½-3
BAYCCHT301	Crankcase Heater Kit (Scroll)	1	3½-5	3½-5	3½-5	3½-5
BAYECMT023	Extreme Conditions Mounting Kit (Base 2/3).....	2	1½-2½	1½-2½	1½-2½	1½-2½
BAYECMT004	Extreme Conditions Mounting Kit (Base 4).....	2	3-5	3-5	3-5	3-5
BAYINS001.....	Insulation Kit.....	1	✓	✓	✓	✓
BAYISLT101	Rubber Isolators.....	1	✓	✓	✓	✓
BAYKSKT260	Start kit (Scroll).....	1	3½-4	3½-5	3½-5	3½-5
BAYLEGS002A	Snow Legs Base and Cap 6" High (Black)	1	✓	✓	✓	✓
BAYLEGS003A	4" Extension (Black)	1	✓	✓	✓	✓
BAYLOAM103	Low Ambient Kit	1	✓	✓ ^④	✓	✓
BAYSEAC001	Seacoast Kit.....	1	✓	✓	✓	✓
TAYASCT501A ^{①②}	Anti-Short Cycle Timer	2	✓	✓	✓	✓
TAYPLUS103A	Heat Pump Control Kit	3	✓	✓	✓	✓
PAI00309 ^⑤	Heresite Spraypaint.....	1	✓	✓	✓	✓

Comfort Controls — See Comfort Controls/Zone Sensors Section

① Not for use with programmable thermostats.

② Activated on Power Off.

③ Registered Limited Warranty terms are available when you register within 60 days of installation. You can register online at americanstandardair.com or by phone at 800-554-8005; otherwise American Standard Heating & Air Conditioning's Base Limited Warranty terms will apply. Base Limited Warranty information on specific products can be found on ASDealerNet.com.

④ For operation to 20°F outdoor ambient.

⑤ Used for additional seacoast corrosion protection. Refer to bulletin number UN-SVB11A-EN for application information.