

Hisense

50
Pints/24hr

Dehumidifier

Model AHD5024KP1G



- Bucket full indicator avoids overflows
- 3 Modes – Auto, Continuous, Manual
- 3 Fan Speeds (High, Low, Auto)
- Low-temperature Operation (38°F)



Built-in Pump for Easy Draining

Built-in pump and Quick-connect water hose included to discharge the water into a sink or basement window.



Energy Efficient

Energy Star means it's more energy efficient and helps reduce your utility bill.



Filter Indicator

Washable filter helps to reduce bacteria, odors and particles.



Warranty

2 Years Parts & Labor.

Control Humidity – Helps keep your home conveniently dry, fresh, and quiet, with the added convenience of a built-in pump

The Hisense AHD5024KP1G Energy Star 50 Pint 2-Speed Dehumidifier has a built-in pump that can quickly discharge water out a basement window or into a sink using the included quick-connect hose. Reliable and eco-friendly this dehumidifier can operate at temperature as low as 38°F. Three operating modes (manual set, continuous and auto-dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

TECHNICAL SPECIFICATIONS

Performance	Performance
Dehumidification (Pints/24 hours)	50
Coverage	Up to 4500 sq ft
Refrigerant	R-32
Noise Level in dB(A)	45-48 dB(A)
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	Dimmable LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% ~ 80%
Timer	Yes, 30 minutes to 24 hours
Fan Speeds	3 Speeds (High, Low, Auto)
Auto Bucket Shutoff	Yes
Garden Hose Connection	Yes, garden hose not included
Washable Filter	Yes

Electrical	
Voltage / Freq / Amps	115V / 60Hz, 7.2A* / 4.9A
Power Cord Length	6 feet
Accessories	
Quick Connect Hose	Yes, included (9mm diameter)
Length of Included Pump Hose	16 feet
Max Pump Discharge Height	16 vertical feet
Approvals	
Safety	UL
Energy	Energy Star
Shipping	
Unit Dimension WxHxD (mm)	384 x 629 x 272
Net Weight (kg)	18.3
Unit Dimension WxHxD (inch)	15.1 x 24.8 x 10.7
Net Weight (lbs)	40.3
Warranty/UPC	
Parts & Labor	2 Years
UPC	810088366413

Note:

*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Control Panel



3 Draining Options

Bucket conveniently located on front with handle for easy emptying



Built-in pump pushes water up to 16 vertical feet using included hose, allowing for drainage into a sink or out a window



Use a garden hose (not included) for continuous draining to avoid emptying the bucket.

