



VF418PF



**Small distributor,golf,flush,4row,IP40,72M,MS-terminal,PE,white door**

#### Technical characteristics

##### Voltage

|                 |             |
|-----------------|-------------|
| Nominal voltage | 400 - 400 V |
|-----------------|-------------|

##### Installation, mounting

|                            |                |
|----------------------------|----------------|
| Suitable for outdoor usage | No             |
| Mounting on                | Flush mounting |

##### Electric current

|               |      |
|---------------|------|
| Rated current | 63 A |
|---------------|------|

##### Equipment

|                             |     |
|-----------------------------|-----|
| Number of rails             | 4   |
| Number of rows              | 4   |
| Number of section in width  | 1   |
| With lock                   | No  |
| Has neutral terminal block  | No  |
| Has earthing terminal block | Yes |
| Has mounting plate          | No  |

##### Capacity

|                   |    |
|-------------------|----|
| Number of modules | 72 |
|-------------------|----|

##### Functions

|                     |     |
|---------------------|-----|
| With conduit inlets | Yes |
|---------------------|-----|

##### Dimensions

|                       |          |
|-----------------------|----------|
| Height                | 688 mm   |
| Width                 | 460 mm   |
| Depth                 | 97.50 mm |
| Built-in height       | 652 mm   |
| Built-in width        | 426 mm   |
| Built-in depth        | 72 mm    |
| Number of width units | 18       |

##### Cover, door

|                           |    |
|---------------------------|----|
| Number of cabinet doors   | 1  |
| Number of locks           | 0  |
| Door/cover is transparent | No |

##### Materials

|          |         |
|----------|---------|
| Material | Plastic |
|----------|---------|

Subject to technical modifications

|                       |            |
|-----------------------|------------|
| RAL code              | 9010       |
| Colour                | Pure white |
| Ultraviolet-resistant | No         |

#### Safety

|                               |                            |
|-------------------------------|----------------------------|
| Protection class              | Isolation class II         |
| Impact resistance IK          | IK07                       |
| Ingress Protection (IP) class | IP40                       |
| Locking type                  | Snap on lock, Without lock |
| Glow wire test                | 650 °C                     |