

STOP OVERCOOLING. START DRYING.

Industry experts agree energy efficient building techniques have reduced air conditioning runtime, resulting in the need for dedicated dehumidification in homes. Overcooling to control relative humidity isn't effective, or economical, and can lead to comfort and health issues.

Dedicated to better IAQ, Santa Fe Ultra Series dehumidifiers help to efficiently, and effectively, protect the home and aids in creating a living space that is both healthier and more comfortable.

Santa Fe Ultra Series dehumidifiers integrate directly with the HVAC system to provide:

- Dedicated dehumidification for the entire home, regardless of AC runtime
- Fresh air intake / outdoor air ventilation capable
- Superior MERV-13 filtration
- The industry's best warranty! 6-Year Total Peace of Mind Warranty that includes 5-year full replacement, plus 1-year parts.



Santa Fe Stand-Alone Dehumidifiers



Compact70



Oasis™ 105



Classic



Impact155

Santa Fe Air Purifiers



Portable HEPA + UV



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

Contact us: Santa-Fe-Products.com or 800-533-7533



SANTA-FE™
6-YEAR TOTAL PEACE OF MIND WARRANTY
5-YEAR FULL REPLACEMENT + 1-YEAR PARTS



ENGINEERED
MADISON, WI



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

**DEDICATED
DEHUMIDIFICATION**

+

**FRESH AIR
VENTILATION**

+

**SUPERIOR
FILTRATION**

SANTA-FE-PRODUCTS.COM | 800-533-7533

TS-2076 11/24 Rev C



SANTA-FE™
INDOOR AIR QUALITY SOLUTIONS

PRODUCT LINE UP



Ultra70
4044100



Ultra98
4044300



Ultra120
4044400



Ultra155
4031070



Ultra205
4031560

TEST CONDITIONS	PERFORMANCE DATA				
#1 - AHAM 80°F/60% @ 0" WC	70 PINTS / DAY 3,215 LATENT CAP. / HR	100 PINTS / DAY 4,593 LATENT CAP. / HR	118 PINTS / DAY 5,145 LATENT CAP. / HR	155 PINTS / DAY 6,807 LATENT CAP. / HR	205 PINTS / DAY 9,003 LATENT CAP. / HR
#2 - DOE 73°F/60% @ 0.2" WC	52.5 PINTS / DAY 2,412 LATENT CAP. / HR	71.4 PINTS / DAY 3,280 LATENT CAP. / HR	88 PINTS / DAY 4,042 LATENT CAP. / HR	130 PINTS / DAY 5,709 LATENT CAP. / HR	165 PINTS / DAY 7,246 LATENT CAP. / HR
#3 - MANUAL S 75°F/55% @ 0.2 WC	55 PINTS / DAY 2,526 LATENT CAP. / HR	68 PINTS / DAY 3,123 LATENT CAP. / HR	91 PINTS / DAY 4,180 LATENT CAP. / HR	118 PINTS / DAY 5,182 LATENT CAP. / HR	156 PINTS / DAY 6,851 LATENT CAP. / HR
#4 - MANUAL J 75°F/50% @ 0.2" WC	44 PINTS / DAY 2,050 LATENT CAP. / HR	63 PINTS / DAY 2,930 LATENT CAP. / HR	79 PINTS / DAY 3,670 LATENT CAP. / HR	109 PINTS / DAY 4,765 LATENT CAP. / HR	129 PINTS / DAY 5,665 LATENT CAP. / HR
MAXIMUM RECOMMENDED VENTILATION AIR	50 CFM	106 CFM	116 CFM	129 CFM	174 CFM
CURRENT DRAW @ Test Condition #1	5.1 AMPS	5.9 AMPS	7.3 AMPS	8.0 AMPS	13.2 AMPS
EFFICIENCY @ Test Condition #1	5.5 PINTS/KWH	6.12 PINTS/KWH	5.44 PINTS/KWH	7.3 PINTS/KWH	5.7 PINTS/KWH
BLOWER	150 CFM @ 0.0" WC 140 CFM @ 0.2" WC 130 CFM @ 0.4" WC	320 CFM @ 0.0" WC 297 CFM @ 0.2" WC 215 CFM @ 0.4" WC	350 CFM @ 0.0" WC 285 CFM @ 0.2" WC 210 CFM @ 0.4" WC	391 CFM @ 0.0" WC 363 CFM @ 0.2" WC 337 CFM @ 0.4" WC	526 CFM @ 0.0" WC 495 CFM @ 0.2" WC 458 CFM @ 0.4" WC
REFRIGERANT	R454B	R454B	R454B	R410A	R410A
AIR FILTER	MERV-13	MERV-13	MERV-13	MERV-13	MERV-13
DIMENSIONS	12"Wx12"Hx28"D	14.50"Wx19.50"Hx32.38"D	14.38"Wx21"Hx32.19"D	20.25"Wx21.75"Hx41.50"D	20.25"Wx21.75"Hx41.50"D
WEIGHT	55 LBS.	81 LBS.	91 LBS.	140 LBS.	140 LBS.
WARRANTY	6 YEARS	6 YEARS	6 YEARS	6 YEARS	6 YEARS



Santa Fe Ultra Series dehumidifiers can be controlled comfortably from the living space using the **UltraDEH 3000 Digital Control**. Remote sensing option also available with the **UltraDEH 3000R**.

UltraMD33
4044610



TEST CONDITIONS	TEST CONDITIONS	CURRENT DRAW	EFFICIENCY	BLOWER	REFRIGERANT	AIR FILTER	DIMENSIONS	WEIGHT	WARRANTY
#1 - AHAM @ 80°F/60%RH	#2 - DOE @ 65°F/60%RH								
37 PINTS / DAY 1,700 LATENT CAP. / HR	22 PINTS / DAY/ 1,011 LATENT CAP. / HR	2.2 AMPS @ DOE	3.46 PINTS/KWH @ DOE	155 CFM @ 0.0" WC	R454B	WASHABLE	14.1875"W x 30"H x 5.75"D	39 LBS.	6 YEARS

The UltraMD33 is not ductable.