




INSTRUCTION MANUAL



CAR FRIDGE Brand:BODEGA Model:D31A

DC12V/24V AC100-240V





CAR FRIDGE



CONTENTS

ATTENTIONS	Page 1
CAR REFRIGERATOR OPERATION	Page 2
COMPONENT DIAGRAM	Page 2
OPERATION METHOD	Page 3
INSTALLATION	Page 4
USE APP	Page 5
TROUBLESHOOTING	Page 7
FAILURES AND SOLUTIONS	Page 8
APPLICATIONS	Page 8
SAFETY ATTENTION ————————————————————————————————————	Page 9
WARRANTY	Page 10



▶ ATTENTIONS

Before using the refrigerator, please read this manual carefully and keep it properly

- Before the first use of refrigerator, you should clean it inside and outside with a damp cloth.
- Do not fill the refrigerator with corrosive liquids. Do not directly pour liquids into the refrigerator.
- When the refrigerator is not used for a long time, please disconnect the power supply and keep it dry.
- Please clean the inner chamber regularly to prevent odor bacteria and ensure food safety.
- Shut down the refrigerator and battery before pulling by the trolley (If with battery).

Connect the power supply

- Find the DC power cord in the kit. Connect DC plug to the power outlet of the car refrigerator.
- Well place the refrigerators in the car (back-up, seats....)
- Lay out power cords as per the interior space of your car. Insert the cigarette lighter plug (one side of the power cord) into the car cigarette lighter hole.



Connect the car refrigerator

- Connect the car cigarette lighter / DC Power Cord / Connect the car refrigerator (Standard mode) / Connect the car refrigerator (Built-in Mode)
- The refrigerator can be connected to more than one source of energy.
- The refrigerator can be directly connected to the 12V/24V DC power supply.
- If the refrigerator is used in 100-240V power supply, an AC adapter should be adopted.



▶ CAR REFRIGERATOR OPERATION

Car Battery Protection Voltage Reference


Built-in ECO electronic control module can automatically monitor car battery voltage.
 Refrigerator will be automatically cut off when the power is excessively consumed,
 So that protecting the battery consumption from too low to affect auto ignition.

Voltago	High Level set to be factory default (Voltage Protection)		
Voltage	H (High) level	N (Medium) level	L (Low) level
12V	11.3V OFF, 12.5V ON	10.1V OFF, 11.4V ON	8.5V OFF, 9.6V ON
24V	24.6V OFF, 26V ON	22.3V OFF, 23.7V ON	21.3V OFF, 22.7V ON

• Note: when the refrigerator is on work, "OFF" or "ON" is the stop or start of the compressor

► COMPONENT DIAGRAM


- ① Cabinet
- 2 Display
- ③ Drawer
- Wire baffle board
- (5) Drawer handle
- ® Drawer face
- 7 Drawer slider
- ® Position bracket





▶ OPERATION METHOD

- **WARNING!** Condensation or ice may appear around door gasket and front of cabinet if the fridge runs for long time. It's normal. Please clean the condensation or ice with dry towel.
- **WARNING!** The fridge is designed for outdoor camping, not suitable for long term freezing food.
- **WARNING!** To save energy and avoid condensation or ice issue, please not run the fridge with setting lower than 0°C/32°F for long term.
- **WARNING!** Defrost water may leak from inner compartment of cabinet if the fridge is powered off or standy by for long time. It's normal. Please clean the inner side by dry towel if you plan to depose the fridge.



Turn On/Off

• Press " \circlearrowleft " key to turn on/standby the refrigerator.

Temperature Setting

- Press " + " or " " key to adjust the temperature.
 Long press " + " or " " key, temperature will be linearly adjusted by 2 per second.
- If no operations were detected, temperature display will flash for 3s, then exit and save the current temperature.
- Meanwhile, it shows the actual temperature inside the box.
- The default temperature for initial startup is 0°C/32°F
- When the running indicator is lighting, it means the compressor of fridge is running.

Celsius (°C) / Fahrenheit (°F)Conversion

• Concurrently Press " + " & " - " keys for 3s to switch Celsius (°C) and Fahrenheit (°F).



MAX / ECO Mode Conversion

Battery Protection Setting (The factory default voltage is H1)

- Battery Protection Levels: H1 (High) → N2 (Medium) → L3 (Low)
- Press " �� " key for 3s to enter the battery protection setting. Press " �� " key again to switch H1→N2→L3 levels in turns.
- If no operations were detected, the set level will flash for 3s, then exit and save the current setting.

Power-off Memory Function

- There is a power-off memory function for the car refrigerators. When the power is lose, working state (On/Off status, working mode etc.) which before power-off can be automatically recovered at the next startup, no need to set it again.
- ECO: Energy-saving cooling MAX: Powerful cooling

▶ INSTALLATION

Position and installation

Installation kits



M6 Nut x 4




M6 Bolt x 12




Bracket x 4

Installation process

 Mount two brackets on each side of fridge by Bolts and Nuts. Keep same position even the compressor unit is located at side.











• Then fix the fridge on installation flat by brackets, bolts and nuts.




• Installation dimension, please pay attention to below drawing.

Please keep at least 5~10cm space for compressor unit to ensure cooling performance.



Compressor unit locates two sides



Compressor unit locates rear

▶ USE APP

We recommend to download the APP by scanning the QR code, it is fast and accurate.

Android System: Scan icon QR code iOS system: Search for "Car Refrigerator" in the App store

IOS APP download code

Adroid APP download code



Car Refrigerator



If you download the APP from app shop, please search "car refrigerator".

- -This method is only available for Apple system users;
- -You must select the app with all lowercase name to download, please select the correct app to download according to the icon.

Operation Steps



1. Click to turn on Bluetooth & GPS(Make sure it is turned on) .



3. Connect the device. After search for the device, Press '\$\text{\text{\text{\$}}}\text{"button} in the fridge control panel



2. Click to search for devices when Bluetooth & GPS is turned on.



4. Enter the main control

Setting





▶ TROUBLESHOOTING

 Advice: If there is any abnormal situations that cannot be resolved through simple fault analysis, please contact professional customer service for assistance.

Car Refrigerator Does Not Work

- Check if the power is connected properly.(check If the plug is loosened or positive and negative poles are reversed).
- Check if the power switch on the operation panel is turned on.
- Check if the cooling ventilation is normal.
- Check if the fuse is blown.

Poor Cooling Performance

- Check if the lid is closed properly
- · Check if the door seal is damaged or deformed.
- Check if there is poor ventilation around the fridges.
- Check if the temperature is set properly.

Abnormal Noise

- Refrigerator is not put on a flat level surface
- Check for vibrations in surrounding objects
- Parts in the refrigerator get loose or fall off.

Refrigerator Condensation

• It is normal that there slightly will be some condensation on the refrigerator surface when air humidity is more than 75%.

Definition Of Error Codes On The Display

Error Code	Error Type
E1	Low Input Voltage
E2	Fan Fault
E3	Input Voltage Fault due to compressor starts frequently
E4	Low Rotational Speed of Compressor
E5	Overheating of Controller Chip
E6	Open or Short Circuit of NTC

7



► FAILURES AND SOLUTIONS

E1: Low Input Voltage

- Failure 1: Insert refrigerator power cord into cigarette lighter before the car starts. Solution 1: Wait for a while to connect the car after it started.
- Failure 2: Input voltage of the adapter is too low.
- Solution 2: Adjust the battery protection level to middle-voltage or low-voltage. If it doesn't work, please replace a new adapter.

E2: Fan Fault

• Please replace a new fan when identify there is a fan malfunction.

E3: Input Voltage Fault due to compressor frequently start

When the refrigerator is used in car and E3 appearing

- Please shut down for 5 minutes and restart it.
- If it doesn't work, that can be identified to be E1 fault, please solve it according to the solution of E1.

When the refrigerator is connecting with adapter and E3 appearing

- Please adjust battery protection level to the middle level or low level.
- If it doesn't work, please replace a new adapter.

E4: Low Rotational Speed of Compressor

• Please adjust input voltage and repower it.

E5: Overheating of Controller Chip

 Please power off for 5 minutes and check if the overheating is caused by the bad ventilation around compressor.

▶ APPLICATIONS



With an additional battery, you can hold any temperature you set in any situations without worries.





When storing ice cream in refrigerator, please set to the lowest temperature and keep power on constantly.



Prevent healthy problems from bottled water deterioration caused by the high temperature.



Keep fresh for the frozen food and luxurious seafood during the long travelling.



Freshness of tealeaves is effectively preserved by car refrigerator, you can enjoy the fresh and delicious tea any time during the self-driving travelling.



Coating of sunglasses will drop off at the high temperature, car refrigerator is the best ideal place to put away.



Cosmetic is easy to go bad at high temperature, so the best choice to store outside is with a car refrigerator.



Ideal storage temperature for red wine is 10°C-15°C, the precise temperature control of car refrigerator guarantees the storage temperature for it.



Fruits cannot be kept in hot car for more than 2 hours, even it is in the air conditioning. But car refrigerator is able to effectively keep the fruit fresh for a long time.

► SAFETY ATTENTION

- Ensure proper connecting of voltage for the refrigerator at any time. (Parameter label shows the approved voltage for car refrigerator).
- Do not directly pour any liquid into the car refrigerator.
- It is forbidden to modify the refrigerators privately, in case of dangers.
- Refrigerators should not be exposed to the rain.

Manufacturer: Guangdong Minghua Auto Equipment Technology Co., Ltd

Address: 9# East of Changxing Road, Jun'an Town, Shunde District, Foshan City, Guangdong

Province, China

Contact: Mickey Tel: +1 (313) 913-7585 E-Mail: info@bodegacooler.com



Brand:BODEGA

Thank you for purchasing BODEGA product. We sincerely hope that you are satisfied with the product.

We'd like to offer you 12-month warranty for free.

Once activated the warranty, you will be ensured that if anything goes wrong with your product. Replacement unit/parts will be warranted during the warranty period.

- What you need to do -

Any help or questions during use, please contact us via website

www.bodegacooler.com, send amail to info@bodegacooler.com,

we will service you within 24 hours.

When contacting us, we suggest to send Order ID,

problem and a photo or a video for helping us much

more clearer about the problem and offer you the best solution.

info@bodegacooler.com https://www.bodegacooler.com/ <u>a</u>)