

V-TAC

Meaningful Innovation.



Smart Cameras

V-TAC introduces its all-new extensive range of smart cameras – fully compatible with any smart device (mobile phones, tablets, or PCs) through Wi-Fi integration. These cameras offer detection alerts via email — all available in standard UK & EU plugs for compatibility.

Key Features

- Standard wireless frequencies for Wi-Fi transmission
- High definition, high resolution videos at standard frames per second
- Supports iOS & Android devices
- Real-time alerts sent straight to your mobile for motion detected
- Night Vision
- Two-Way Audio
- Video storage: Micro SD storage or cloud transmission

Security System



NEW SMART 4G HD SOLAR ENERGY
PTZ CAMERA

SKU	Model	Box Qty
11615	VT-11024-4G-B	6

- 8W Solar Panel
- 18650 2600mAh Battery
- PTZ Camera 4G with Monocrystalline Silicon Solar Panel
- 360° VR with PIR Detection with a lens angle of 95°
- Voice monitor and full color night vision
- Resolution: 2MP (1920x1080)
- Alarm Mode: Realtime calling or push message
- PTZ Angle: Horizontal 355°, Vertical 100°
- Voice Monitoring distance 20 Meters
- Local Storage TF Card Max 128GB(Not Included)
- PIR Sensor with Detection Distance 0-12 Meters
- 3.6mm Lens

360°
VRBUILT-IN
BATTERYPIR
DETECTIONVOICE
MONITORFULL COLOR
NIGHT VISIONIP65
RATING**NEW** SMART 4G HD SOLAR ENERGY
PTZ CAMERA

SKU	Model	Box Qty
11616	VT-11024-4G-W	6

- 8W Solar Panel
- 18650 2600mAh Battery
- PTZ Camera 4G with Monocrystalline Silicon Solar Panel
- 360° VR with PIR Detection with a lens angle of 95°
- Voice monitor and full color night vision
- Resolution: 2MP (1920x1080)
- Alarm Mode: Realtime calling or push message
- PTZ Angle: Horizontal 355°, Vertical 100°
- Voice Monitoring distance 20 Meters
- Local Storage TF Card Max 128GB(Not Included)
- PIR Sensor with Detection Distance 0-12 Meters
- 3.6mm Lens

360°
VRBUILT-IN
BATTERYPIR
DETECTIONVOICE
MONITORFULL COLOR
NIGHT VISIONIP65
RATING

NEW **SMART WIFI HD SOLAR ENERGY PTZ CAMERA**



SKU	Model	Box Qty
11617	VT-11024-B	6

- 8W Solar Panel
- 18650 2600mAh Battery
- PTZ Camera WiFi with Monocrystalline Silicon Solar Panel
- 360° VR with PIR Detection with a lens angle of 95°
- Voice monitor and full color night vision
- Resolution: 2MP (1920x1080)
- Alarm Mode: Realtime calling or push message
- PTZ Angle: Horizontal 355°, Vertical 100°
- Voice Monitoring distance 20 Meters
- Local Storage TF Card Max 128GB(Not Included)
- PIR Sensor with Detection Distance 0-12 Meters
- 3.6mm Lens



360°
VR



BUILT-IN
BATTERY



PIR
DETECTION



VOICE
MONITOR



FULL COLOR
NIGHT VISION



IP65
RATING

NEW **SMART WIFI HD SOLAR ENERGY PTZ CAMERA**



SKU	Model	Box Qty
11618	VT-11024-W	6

- 8W Solar Panel
- 18650 2600mAh Battery
- PTZ Camera WiFi with Monocrystalline Silicon Solar Panel
- 360° VR with PIR Detection with a lens angle of 95°
- Voice monitor and full color night vision
- Resolution: 2MP (1920x1080)
- Alarm Mode: Realtime calling or push message
- PTZ Angle: Horizontal 355°, Vertical 100°
- Voice Monitoring distance 20 Meters
- Local Storage TF Card Max 128GB(Not Included)
- PIR Sensor with Detection Distance 0-12 Meters
- 3.6mm Lens



360°
VR



BUILT-IN
BATTERY



PIR
DETECTION



VOICE
MONITOR



FULL COLOR
NIGHT VISION



IP65
RATING

CAMERA WITH LED LIGHTS IP65



SKU	Model	Box Qty
8988	VT-5158	20

- Input Power - DC:12V±5%
- Auto tracking
- Motion & Sound Detection
- 2.4~2.4835 Ghz Wireless Frequency
- 220°/ 90° Pan/Tilt
- 2304x1296P Resolution
- 3.0M pixel HD CMOS Image Sensor
- 3.6mm Lens
- H.265/Mjpeg Video Compression
- Protocol: TCP, UDP, DHCP, DNS, RTSP, P2P
- 10 meters Night Vision
- 25—30fps Frame Rate
- Two way Audio
- Wireless Security: WEP/WPA-PSK/WPA2- PSK data encryption
- Micro SD up to 128gb Storage
- Lan port RJ-45
- Supports Android & IOS devices
- IEEE802.11b/g/n Wireless LAN
- IP Rating: IP65

SECURITY CAMERA



SKU	Model	Box Qty
8478	VT-5135	50

- Input Power - DC:12V±10%
- Resolution - 1920x1080
- Image Sensor - 1/2.8" Low illumination CMOS Sensor
- Lens - 3.6mm@F1.8
- Minimum illumination - Color-0.01Lux @(F1.2, AGC ON); 0 Lux with IR
- Black and White - 0.001 Lux @ (F1.2, AGC ON), 0 Lux with IR
- Shutter - 1/50 (1/60) seconds to 1/10,000 seconds
- Designed with Lens Type M12
- Day and night conversion mode - Supports IR-CUT
- Frame rate 1080P@20fps
- Supports Protocols - TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP
- Communication interface - 1 10/100Mbps adaptive Ethernet port, RJ45 interface
- Infrared distance of 20-30 meters
- Audio - No
- IP Rating - IP65

SECURITY CAMERA



SKU	Model	Box Qty
8479	VT-5136	20

- Input Power - DC:12V
- Resolution - 1920x1080
- Image Sensor - 1/2.7" CMOS 0.001LUX/F1.2(Colorful)
- Video Compression - 32kbps-8mbps
- 2.0 Mega pixel
- Electronic Shutter - 1/25---1/10000 Second
- Day and night conversion mode - Full Color
- 3D DNR (Digital noise reduction)
- H.265 encoding type - Profile_Baseline
- Intelligent Alarm - Motion detection, occlusion alarm, video loss, network cable disconnection, IP address conflict
- Support Protocols - TCP/IP, DHCP, HTTP, DNS, RTP RTSP
- Docking Protocols - ONVIF, Hikvision, Dahua
- Universal feature - One-click recovery, dual stream, heartbeat, mirroring, video masking, anonymous access
- Communication interface - 1 RJ45 10M / 100M adaptive Ethernet port