



# Smartbright Waterproof G3 WT068C

WT068C CW LED18 L600 PSU

-

Philips Smartbright Waterproof G3 batten offers exceptional value. It is Perfect for everyday lighting installations. Available in 3 standard sizes, it has option of Standard and through wiring version.

## Product data

General information	
Light source color	865 cool daylight
Optical cover/lens type	-
Control interface	-
Protection class IEC	Safety class II
CE mark	CE mark
Number of products on MCB of 16 A type B 1	
Light source engine type	LED
Operating and electrical	
Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Power Factor (Min)	0.9

Controls and dimming	
Dimmable	No
Mechanical and housing	
Housing Material	Polycarbonate
Optical cover/lens material	Polycarbonate
Optical cover/lens finish	Opal
Overall length	598 mm
Overall width	69 mm
Overall height	74 mm
Color	White and gray
Dimensions (Height x Width x Depth)	74 x 69 x 598 mm
Approval and application	
Ingress protection code	IP66 [ Dust penetration-protected, jet-proof]

## Smartbright Waterproof G3 WT068C


Mech. impact protection code	IK06 [1 J]
<b>Initial performance (IEC compliant)</b>	
Initial luminous flux (system flux)	1800 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	110 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial input power	16.5 W
Power consumption tolerance	+/-10%
<b>Application conditions</b>	
Ambient temperature range	-20 to +45 °C

<b>Product data</b>	
Full product code	871016336059199
Order product name	WT068C CW LED18 L600 PSU
EAN/UPC - Product	8710163360591
Order code	911401881380
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881380
Net Weight (Piece)	0.270 kg



### Dimensional drawing

WT068C-2ft



WT068C CW LED18 L600 PSU

