




ELITE

ZERO DROP TECHNOLOGY




SB ELITE TivoTape™



Project: _____ TYPE: _____

- Low bin tolerance with a 1.5 Step McAdam Ellipse standard
- Factory produced with Tivoli's eXo Shield coating
- High CRI value
- Factory soldered lead wire
- IP67 Wet location available
- Multiple mounting channel options
- Large range of available Kelvin temperatures
- Low lead times
- 4oz. Copper Trace
- 5 Year warranty

Dimensions



Order Guide

PRODUCT CODE	INTENSITY	INSTALL	LED COLOR	LENGTH	VOLTAGE
TPLE	SB	I			24
TPLE = TivoTape ELITE	SB = Standard Brightness	I = Indoor	22 = 2200K 40 = 4000K 50 = 5000K	R = * Full Roll (164 ft) MR = Maximum Run (29')	24 = 24V DC

*Leave blank if specifying run lengths. A layout/drawing must accompany each order showing run length and location

Note: A layout/drawing must accompany each order showing run length and location


Note: Runs with LEAD-C are rounded **up** to next cut interval (unless otherwise specified)

Note: Runs with LEAD-D are rounded **down** to next cut interval (unless otherwise specified)


Specification

Output (based on 3000K)			
Kelvin Temperature	2200K	4000K	5000K
Lumens/ft	317	378	381
Efficacy (Lm/W)	100	117	119
Color Rendering Index (CRI)	90+		
Electrical			
Input Voltage	24V		
Power Supply	Class 2		
Power Consumption W/ft	3.2 W/ft.		
Maximum Run Length	29'		
Maximum Run Length (JA8)	24'		
Wire Size (End Prep)	18 AWG, 2 wire		
Dimming	MLV/ELV/0-10V/DMX		
Physical			
LED Package	2835		
LEDs/ft	73		
Adhesive	3M VHB Tape		
Copper Trace	4 Ounce		
Dimensions	15/32" (12mm)		
Cut Increments	1 5/16"		
Operating Temperature	-40°F (-40°C) ~ +140°F (+60°C)		
Certification and Testing			
Certification	UL Listed		
Lumen Maintenance (L70) Hours	60,000		
Binning Tolerance	1.5 Step MacAdam Elipse		
Environment	IP54 Damp Location, Conformal eXo Shield Coated		
Warranty	5 years		

Photometrics Based on 3000K



Maximum Candela = 118.58
 Located At Horizontal Angle = 0
 Vertical Angle = 0
 #1 Vertical Plane Through Horizontal Angles (0-180) (Through Max. Cd.)
 #2 Vertical Cone Through Vertical Angle (0) (Through Max. Cd.)




Power Leads and Jumpers (Installed by Tivoli's certified solderers)



TPL-I-LEAD-2-C

LEAD/END


24" standard 2 conductor
18AWG lead wire factory
attached to one end of tape



TPL-I-LEAD-2-D

LEAD/LEAD


24" standard 2 conductor
18AWG lead wire factory
attached to both ends of tape



TPL-I-XEP-2

EXTRA LEAD WIRE

Additional factory attached
18AWG lead 2 wire to extend
lengths of LEAD-C and LEAD-D
up to 20 ft. max
Sold per foot



TPL-I-CONN

18-22AWG BUTT CONNECTORS
Used to interconnect factory
attached lead wires.
Sold individually.

Snap Power Lead and Jumpers (For in-field connection)



TPL-I-12-SNP-LEAD-XX

XX = 12 (12"), 60 (60")

2 conductor 20AWG lead wire
field attached
Sold 10pcs




TPL-I-12-SNP-JUMPER-6

6" 2 conductor 20AWG jumper
wire field attached
Sold 10pcs




TPL-I-12-SNP-JOINER

2 conductor joiner field
attached
Sold 10pcs




Compatible Extrusions


Fits 12mm Snap Connector

**MCHAN-8-LP**


Low profile NO LENS OPTION
clear polycarbonate, length 8'

**TPL-I-45-MCH-8-S**


White PVC, 45° NO LENS
length 8'

**DWAR-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**EDGE-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**MINI-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**MOFT-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**DYER-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**WRNR-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**NOYS-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**VALN-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**DOME-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**ALTN-CHAN-SLV-6.5**


Anodized Aluminum Extrusion,
available in 6.5' lengths

**MRSL-CHAN-SLV-6.5**


Anodized aluminum extrusion
available in 6.5' length

**HRIZ-CHAN-SLV-6.5**

Anodized aluminum extrusion
available in 6.5' length

**ASTR-CHAN-SLV-6.5**


Anodized aluminum extrusion
available in 6.5' length

**INF-X-CHAN-8**


X = C (clear), F (frosted)
PC extrusion,
available in 8' lengths

Compatible Extrusions


■ Fits 12mm Snap Connector




COTA-CHAN-SLV-6.5
Anodized Aluminum Extrusion,
available in 6.5' lengths




CARU-CHAN-SLV-6.5
Anodized aluminum extrusion,
available in 6.5' lengths



HAYS-CHAN-SLV-6.5
Anodized Aluminum Extrusion,
available in 6.5' lengths




DUET-04-CHAN-XXX-6.5
XXX = SLV (silver), **WHT** (white),
GLD (gold), **BLK** (black)
Aluminum extrusion




DUET-04-CHAN-M-6.5
Mud-In PC fire-proof extrusion
6.5' Length

Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-CHAN-M-6.5** are required for mud-in application




DUET-04-CHAN-SLV-6.5
Anodized aluminum extrusion
available in 6.5' length


Note: **DUET-04-CHAN-SLV-6.5** and **DUET-04-LNS-R-XXX-6.5** are required for recessed application




FRE-CHAN-SLV-6.5
Anodized Aluminum Extrusion,
available in 6.5' lengths



RIDG-CHAN-SLV-8
Anodized Aluminum Extrusion
length 8'



TPL-I-45-MCH-8
White PVC 45° extrusion
INF-X-LNS-8
X = C (clear), **F** (frosted)
Polycarbonate lense
available in 8' length



ANZI-CHAN-XXX-6.5
XXX=SLV (Silver), **BLK** (Black),
WHT (White)
Anodized Aluminum Extrusion,
available in 6.5' lengths



Note: For complete information on DUET 04 profile, refer to specification

In-Wall Controls



TVOQ-1-WH
White



TVOQ-10-XX-7
XX = BK (Black), **WH** (White)



TVOQ-2-BK
Black

Power Supplies

INFINITY - MLV / ELV / 0-10V / PWM / TRIAC

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	MIN LOAD	CIRCUIT CAPACITY
Infinity Series Class 2 Transformer	INF-J-30-1-1.3-24	Indoor / Outdoor	100 - 277V AC	24V DC	1	30W	3W	1.3A
	INF-J-60-1-2.5-24				1	60W	6W	2.5A
	INF-J-96-1-4-24				1	96W	9W	4A
	INF-J-192-2-4-24				2	2x96W	2x9W	2x4A
	INF-J-288-3-4-24				3	3x96W	3X9W	3x4A

ER

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ER Series Class 2	ER-80-1.3.3-24-D	Indoor / Outdoor	100-277V AC 50/60 Hz	24V DC	1	80W	3.3A
ER Series Class 2 0-10V Dimming	ERG-80-24-DIM1-10						

ADUL/ADNM - NON DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-D	Indoor/Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-D	Indoor			1	96W	4A
	ADUL-240-2-4-24-D	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-D	Indoor			3	3x96W	3x4A

ADUL/ADNM - 0-10V DIMMING

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DOT	Indoor/Outdoor	100-277V AC 50/60 HZ	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-DOT	Indoor			1	96W	4A
	ADUL-240-2-4-24-DOT	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-DOT	Indoor			3	3x96W	3x4A

ADUL/ADNM - DMX SINGLE ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL/ADNM Series Class 2 Transformer	ADNM-90-1-4-24-DIN	Indoor/Outdoor	100-277V AC 50/60 Hz	24V DC	1	90W	3.75A
	ADUL-120-1-4-24-DIN	Indoor			1	96W	4A
	ADUL-240-2-4-24-DIN	Indoor			2	2x96W	2x4A
	ADUL-320-3-4-24-DIN	Indoor			3	3x96W	3x4A

Power Supplies

ADUL - DMX MULTI ADDRESS

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADUL Series Class 2 Transformer	ADUL-240-2-4-24-DIN-2	Indoor	100-277V AC 50/60 Hz	24V DC	2	2x96W	2x4A
	ADUL-320-3-4-24-DIN-3				3	3x96W	3x4A

ADNM - DMX/DALI FLICKER-FREE FOR TV STUDIO

DESCRIPTION	CAT NO	APPLICATION	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CIRCUIT BREAKERS	MAX LOAD	CIRCUIT CAPACITY
ADNM Series Class 2 Transformer	ADNM-120-1-4-24-DTV	Indoor / Outdoor	100-277V AC 50/60 HZ	24V DC	1	1x96W	1x4A
	ADNM-240-2-4-24-DTV				2	2x96W	2x4A
	ADNM-320-3-4-24-DTV				3	3x96W	3x4A

Dimmers

DIMMING - 0-10V

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
0-10V Dimmer	DIM-LD-010	Indoor	12V/24V DC	12V/24V DC	30 mA max. output (sink only)

DIMMING -MLV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
MLV Dimmer	N-600	Indoor	120V AC	120V AC	450W
	N-1000				800W
	N-1500				1200W
	D-600				450W
	M-600				450W
	M-1000				800W

DIMMING - ELV

DESCRIPTION	CAT NO	APPLICATION	INPUT VOLTAGE	OUTPUT VOLTAGE	MAX LOAD
ELV Dimmer	ME-600	Indoor	120V AC	120V AC	450W
	DE-300				300W