

KMS-1122MLJ 07/02/24 Item # 13253

WxDxH 22" x 181/8" x 311/4"

Shipping Dimensions 30^{1/2}" x 30" x 37"

Installation Dimension* SRK-12J / SRK-12J3 523/8" x 191/2" x 43"

Actual Dimension **SRK-12J / SRK-12J3** 50^{1/4}" x 17" x 28"



KMS-1122MLJ Remote Air-Cooled Shown on optional Lancer 30" Dispenser





Features

- Individual crescent cube
- Stainless steel evaporator
- ► CycleSaver™ design CycleSave



- Up to 1151 lbs. of ice production per 24 hours
- · Durable stainless steel exterior
- EverCheck[™] alert system
- No heat, less noise
- · CFC / HFC Free Foam
- · R-404A Refrigerant
- Not recommmended for side-by-side application















Warranty:

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil.


Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries

			ICE PRODUCTION		WATER USAGE		ELECTRICAL				
Condenser		Model	Air / Water Temp Lbs. per 24 hours 70°/ 50°F 90°/ 70°F		Potable Condenser Gal. per 100 lbs. 90°/ 70°F Gal. per 100 lbs. 90°/ 70°F		kWh Used per 100 lbs. Voltage 90°/ 70°F		Circuit Wires (including ground)	Refrigerant Charge Amount	Net / Ship Weight (lbs.)
	Remote	KMS-1122MLJ with SRK-12J	1151	1075	16.0	N/A	4.2	115V/60/1*	4 [‡]	7.1 oz.	122 /152
	Remote	KMS-1122MLJ with SRK-12J3	1151	1100	16.0	N/A	4.05	115V/60/3*	4	7.1 oz.	122 /152
* Voltage supply for KMS Ice Maker										MS Ice Maker is	

		LINE SETS - Brazing Required			TEMP RANGE	ELECTRICAL					Supplied from the SNK hemote condenser			
Condenser	Model	25' Length	35' Length	55' Length	Ambient (Outdoor Use)	Voltage Range	Min. Circuit/ Max. Fuse Size	Amperage	Voltage	Circuit Wires (including ground)	Heat Rejection BTU/hr.	Refrigerant Charge Amount	Net / Ship Weight (lbs.)	
Remote	SRK-12J	HS-0250 [†]	HS-0251 ⁺	HS-0252 [†]	-20 - 122°	187-253VAC	20A	11.6A	208-230V/60/1	4 [‡]	16,500	15 lb. 14 oz.	230 /275	
Remote	SRK-12J3	HS-0250 [†]	HS-0251 [†]	HS-0252 [†]	-20 - 122°	187-253VAC	20A	10.5A	208-230V/60/3	4	17,300	15 lb. 14 oz.	230 /275	

Line sets require refrigerant. If neutral is not available transformer kit (HS-5030) is required. Refer to instruction manual for installation and electrical requirements. See instruction manual for wiring diagram. Power cord not included. Must be hard-wired at site.

KM*Edae*™ Cube Dimensions*



§ approximate size in inches, image not to scale

Operating Limits- KMS-1122MLJ

· Ambient Temp Range 45 - 100°F Water Temp Range 45 - 90°F

10 - 113 PSIG Water Pressure

· Voltage Range 187-253V‡

• If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

[‡] Voltage supply for KMS Ice Maker is supplied from the SRK Remote Condensel

Service- KMS-1122MLJ

- . Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance and/or service should they be required.
- · Panels easily removed and all components accessible for service.

Plumbing- kms-1122MLJ


- Icemaker Water Supply Line: Minimum 3/8" Nominal ID Copper Water Tubing or Equivalent
- · Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent

Service- SRK-12J(3)

- Allow 24" (61 cm) clearance in both front and rear for proper air circulation and ease of maintenance/service.
- For best performance the Remote Condenser should not be more than 33 feet above the icemaker or no more than 10 feet below it. These distances are measure from fitting to fitting.


Hoshizaki reserves the right to change specifications without notice






mm [inches]

REMOTE AIR-COOLED



SRK-12J(3) REMOTE CONDENSER




THE MANAGE CONNECTION


AND THE CONNECTION

AND

OP VIEW



REMOTE AIR-COOLED



SRK-12J(3) REMOTE CONDENSER

