



Wall-hung electric storage water heater
can be installed over or under the sink



ENAMELLED
STEEL TANK



POLYURETHANE
INSULATION



TEMPERATURE
REGULATION



ANTI-FREEZE

- GLASSLINED INNER TANK
- OVERSIZED MAGNESIUM ANODE
- EXTERNAL TEMPERATURE CONTROL
- HIGH SENSITIVITY THERMOSTAT
- PRESSURE SAFETY VALVE TESTED AT 8 BARS
- ECOLOGICAL THICK POLYURATHANE INSULATION

customizable
comfort



Technical data - Overall dimensions

		BLU R					BLU R		
		10 OR	10 UR	15 OR	15 UR	30	10	15	30
Capacity	l	10	10	15	15	30	a mm	360	446
power	W	1200	1200	1200	1200	1500	b mm	254	360
voltage	V	230	230	230	230	230	c mm	360	446
heating time (delta T=45°C)	h _{min}	0,29	0,29	0,44	0,44	1,10	d mm	92	115
max heating temperature	°C	80	80	80	80	80	e mm	144	165
Heat dispersion	kWh/24h	0,43	0,55	0,53	0,65	0,61			
max working pressure	bar	8	8	8	8	8			
weight	kg	6,4	6,4	7,1	7,2	12			
protection	IP	X1	X1	X1	X1	X1			

OR= oversink
UR= undersink

BLU R 10 OR

3605462

BLU R 10 UR

3605463

BLU R 15 OR


3605464

BLU R 15 UR

3605465

BLU R 30

3605466



LEGEND

E cold water inlet G 1/2"

U hot water outlet G 1/2"