



VIEWBOARD

# ViewBoard IFP9850-4


## Key Features

- Natural pen-on-paper writing experience with Ultra Fine Touch technology
- Seamless plug-and-present connectivity via USB-C
- Native whiteboarding software for seamless annotation and collaboration
- Wireless content sharing and 4-way split screen for multiple contributors
- myViewBoard Manager for simplified and centralised display management



## Product Description

The ViewBoard® 50-4 is a sleek 98" 4K interactive display purpose-built for seamless presentation in corporate and educational spaces. Simply connect your laptop or tablet via a single USB-C cable for instant and effortless presentation functionality. Annotate and collaborate in real-time using integrated myViewBoard® digital whiteboarding software and enjoy a naturally smooth writing experience supported by Ultra Fine Touch technology and dual fine-tipped pens for digital accuracy. And to allow multiple contributors within a single presentation, ViewBoard® Cast offers single sign-on wireless content sharing with up to a 4-way split screen. Encased in a stylishly slim bezel, the ViewBoard® 50-4 not only elevates any room, but also empowers IT teams with myViewBoard® Manager, a web-based remote management system, for simplified and centralized display management from anywhere, anytime.



DISPLAY	
Panel Size:	98"
Panel Type:	TFT LCD Module with DLED Backlight
Display Area (mm):	2171.85(H) x 1232.35(V) (97.52"diagonal)
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160(Pixels)
Colors:	1.07B colors (10bit)
Brightness:	450 nits
Backlight Life:	50,000 Hours (Min.)
Contrast Ratio:	DCR: 3000:1
Response Time:	8ms(TYP.)
Viewing Angles:	H = 178, V = 178typ.
Backlight Life:	30,000 Hours (Min)
Surface Treatment:	Anti-glare
Disclaimer:	50,000 hours backlight life at 8 hours of use per day

PLATFORM	
Processor:	ARM Cortex A73*4
RAM:	4GB DDR4
Storage:	32GB
TOUCH	
Type/ Tech:	Ultra fine touch technology
Touch Resolution:	32768 ×32768
Touch Point:	20 points touch, 10 points writing

INPUT	
HDMI:	HDMI 2.0 x3 (3840x2160 @60Hz)
RGB / VGA:	x 1
Audio:	x 1
RS232:	x 1
OPS:	X1 PC Slot
WiFi:	x 1 WiFi Slot

OUTPUT	
HDMI:	HDMI out 2.0 x1 (3840x2160 @60Hz)
Audio:	3.5mm * 1
SPDIF:	x1

LAN	
RJ45:	x2

USB	
Type A:	USB2.0 x 1USB3.0 x 4
Type B:	x2, for touch
Type C:	x1

SPEAKERS	
16Wx2	

TOP CAMERA PLATE	
YES	

COMPATIBILITY	
RGB PC/HDMI PC:	1920x1080
HDMI:	4K 60Hz/30Hz/1080p

EMBEDDED OS	
Android 9	

BUNDLE SOFTWARE	
Basic Annotation Software:	myViewBoard for android
Pro Annotation Software:	myViewBoard for windows (Embedded in Windows Slot-in PC)
Wireless Presentation:	Viewboard Cast

SPECIAL FEATURES	
All-in-one USB port:	Front "SmartPort USB" to all channels.
Simple LAN sharing between IFP and slot-in device:	Yes
Light Sensor:	Yes

POWER	
Voltage:	100-240VAC +/- 10% Wide Range
Consumption:	On mode: 192.5W, Off mode< 0.5W

ERGONOMICS	
Wall Mount (VESA® ):	800*600

OPERATING CONDITIONS	
Temperature (° C):	0°C to 40°C
Humidity:	10% ~ 90% RH non-condensing

DIMENSIONS (W X H X D)	
Physical (inch / mm):	88.4 x 52.1 x 3.6 in /2245 x 1323 x 91 mm
Packaging (inch / mm):	95.9 x 58.8 x 13.6 in / 2435 x 1483 x 346 mm

WEIGHT	
Net (lb / kg):	228.4lb / 103.6kg
Gross (lb / kg):	293.7lb / 133.2kg

REGULATIONS	
FCC, cTUVus, EPEAT, ES8, LBL, CE, CB, RCM	

PACKAGE CONTENTS	
1. Power cord 2. Remote control with AAA battery 3. USB cable for touch 4. Touch pen x 2 5. Quick Start Guide 6. RS232 adapter 7. Clamp x 5 8. Camera plate 9. Screw x 8 10. HDMI cable 11. USB Typc-C cable	

COMPATIBLE SLOT-IN PC	
VPC12-WPO series/VPC25-O series/VPC27-O series	