

Operating Instructions

ELITE

VSX-21

FEDERAL COMMUNICATIONS COMMISSION DECLARATION OF CONFORMITY

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Product Name: AUDIO/VIDEO MULTI-CHANNEL RECEIVER

Model Number: VSX-23TXH, VSX-21TXH

Responsible Party Name: PIONEER ELECTRONICS SERVICE, INC.

Address: 1925 E. DOMINGUEZ ST. LONG BEACH, CA 90801-1760, U.S.A.

Phone: 1-800-421-1404

IMPORTANT NOTICE

THE SERIAL NUMBER FOR THIS EQUIPMENT IS LOCATED IN THE REAR.

PLEASE WRITE THIS SERIAL NUMBER ON YOUR ENCLOSED WARRANTY CARD AND KEEP IN A SECURE AREA. THIS IS FOR YOUR SECURITY.

D1-4-2-6-1*_A1_En

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

D8-10-1-2_A1_En

This Class B digital apparatus complies with Canadian ICES-003.

D8-10-1-3_A1_En

Information to User

Alterations or modifications carried out without appropriate authorization may invalidate the user's right to operate the equipment.

D8-10-2_A1_En

CAUTION

This product satisfies FCC regulations when shielded cables and connectors are used to connect the unit to other equipment. To prevent electromagnetic interference with electric appliances such as radios and televisions, use shielded cables and connectors for connections.

D8-10-3a_A1_En

This product is for general household purposes. Any failure due to use for other than household purposes (such as long-term use for business purposes in a restaurant or use in a car or ship) and which requires repair will be charged for even during the warranty period.

K041 En

WARNING

This equipment is not waterproof. To prevent a fire or shock hazard, do not place any container filled with liquid near this equipment (such as a vase or flower pot) or expose it to dripping, splashing, rain or moisture.

D3-4-2-1-3 B En

WARNING

Before plugging in for the first time, read the following section carefully.

The voltage of the available power supply differs according to country or region. Be sure that the power supply voltage of the area where this unit will be used meets the required voltage (e.g., 230 V or 120 V) written on the rear panel.

D3-4-2-1-4_A_En

CAUTION

To prevent fire hazard, the Class 2 Wiring Cable should be used for connection with speaker, and should be routed away from hazards to avoid damage to the insulation of the cable.

IMPORTANT



The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electric shock to persons.

CAUTION RISK OF ELECTRIC SHOCK DO NOT OPEN

CAUTION:

TO PREVENT THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE COVER (OR BACK). NO USER-SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

D3-4-2-1-1_A1_En

IMPORTANT SAFETY INSTRUCTIONS

- 1) Read these instructions.
- 2) Keep these instructions.
- 3) Heed all warnings.
- Follow all instructions.
- 5) Do not use this apparatus near water.
- 6) Clean only with dry cloth.
- 7) Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.
- 8) Do not install near any heat sources such as radiators, heat registers, stoves, or other apparatus (including amplifiers) that produce heat.
- 9) Do not defeat the safety purpose of the polarized or grounding-type plug. A polarized plug has two blades with one wider than the other. A grounding type plug has two blades and a third grounding prong. The wide blade or the third prong are provided for your safety. If the provided plug does not fit into your outlet, consult an electrician for replacement of the obsolete outlet.
- 10) Protect the power cord from being walked on or pinched particularly at plugs, convenience receptacles, and the point where they exit from the apparatus.

- 11) Only use attachments/accessories specified by the manufacturer.
- 12) Use only with the cart, stand, tripod, bracket, or table specified by the manufacturer, or sold with the apparatus. When a cart is used, use caution when moving the cart/apparatus combination to avoid injury from tip-over.



- 13) Unplug this apparatus during lightning storms or when unused for long periods of time.
- 14) Refer all servicing to qualified service personnel. Servicing is required when the apparatus has been damaged in any way, such as power-supply cord or plug is damaged, liquid has been spilled or objects have fallen into the apparatus, the apparatus has been exposed to rain or moisture, does not operate normally, or has been dropped.

 P1-4-2-2-En

WARNING

To prevent a fire hazard, do not place any naked flame sources (such as a lighted candle) on the equipment.

D3-4-2-1-7a_A_En

Operating Environment

Operating environment temperature and humidity: +5 °C to +35 °C (+41 °F to +95 °F); less than 85 %RH (cooling vents not blocked)

Do not install this unit in a poorly ventilated area, or in locations exposed to high humidity or direct sunlight (or strong artificial light)

D3-4-2-1-7c* A1 En


VENTILATION CAUTION

When installing this unit, make sure to leave space around the unit for ventilation to improve heat radiation (at least 60 cm at top, 10 cm at rear, and 30 cm at each side).

WARNING

Slots and openings in the cabinet are provided for ventilation to ensure reliable operation of the product, and to protect it from overheating. To prevent fire hazard, the openings should never be blocked or covered with items (such as newspapers, table-cloths, curtains) or by operating the equipment on thick carpet or a bed.

D3-4-2-1-7b_A_En



If the AC plug of this unit does not match the AC outlet you want to use, the plug must be removed and appropriate one fitted. Replacement and mounting of an AC plug on the power supply cord of this unit should be performed only by qualified service personnel. If connected to an AC outlet, the cut-off plug can cause severe electrical shock. Make sure it is properly disposed of after removal. The equipment should be disconnected by removing the mains plug from the wall socket when left unused for a long period of time (for example, when on vacation).

D3-4-2-2-1a A1 En

CAUTION

The **OSTANDBY/ON** switch on this unit will not completely shut off all power from the AC outlet. Since the power cord serves as the main disconnect device for the unit, you will need to unplug it from the AC outlet to shut down all power. Therefore, make sure the unit has been installed so that the power cord can be easily unplugged from the AC outlet in case of an accident. To avoid fire hazard, the power cord should also be unplugged from the AC outlet when left unused for a long period of time (for example, when on vacation).

D3-4-2-2-2a A En

WARNING: Handling the cord on this product or cords associated with accessories sold with the product will expose you to chemicals listed on proposition 65 known to the State of California and other governmental entities to cause cancer and birth defect or other reproductive harm.

D36-P4_A_En



Contents

Flow of settings on the receiver7	Switching components on and off using the 12 volt trigger
01 Before you start	Connecting a PC for Advanced MCACC output 36 Connecting an HDMI-equipped component to
Features	the front panel input
Checking what's in the box	Connecting a component to the front panel inputs 38
	Connecting on iDad
Loading the batteries	Connecting a LISP daying
Operating range of remote control unit 9	Plugging in the receiver
02 Controls and displays	04 Basic Setup
Remote control	Cuitabing the anadyar impadance
Front panel	Changing the OSD display language
Display	(OSD Language)
	Automatically setting up for surround sound
03 Connecting your equipment	(Auto MCACC)
Rear panel	Problems when using the Auto MCACC Setup 43
Determining the speakers' application 17	The Input Setup menu4
Other speaker connection	Input function default and possible settings
Placing the speakers	h
THX speaker system setup	
Some tips for improving sound quality 18	Dlaving a source
Connecting the speakers	Disting a service with LIDMI connection
Installing your speaker system 20	Selecting the multichannel analog inputs 46
Standard 5.1/6.1/7.1-channel surround	Diaving on iDod
connections	Playing back audio files stored on an iPod 46
Bi-amping your speakers	Playing a USB device
Bi-wiring your speakers	Dlaying back audio files stored
Selecting the Surr Back system 22	on a LISP moment device
ZONE 2 setup 22	Playing back photo files stored
Speaker B setup	on a LISB momony device
Bi-Amping setup	Also at a love ble file forments
About the audio connection	Listoping to the radio
About the video converter	Improving EM cound
Connecting your TV and playback components 24	Lloing Noural THY
Connecting using HDMI	Tuning directly to a station
Connecting your DVD player with no HDMI output 25	Coving station property
Connecting your TV with no HDMI input	Naming station presets
Connecting an HDD/DVD recorder, VCR and	Listaning to station projects
other video sources	Listening to Satellite Radio
Connecting a satellite/cable receiver or other set-top box	Listening to XM Radio
Connecting the multichannel analog inputs 29	Using XM HD Surround53
	Saving channel presets53
Connecting other audio components	
Connecting additional amplifiers	Lictoring to SIPILIS Padio
Connecting AM/FM antennas	Saving channel presets55
Connecting external antennas	Using the SIRIUS Menu
Connecting an XM Radio tuner	
Connecting a Sirius Connect™ tuner	
MULTI-ZONE setup	
Making MULTI-ZONE connections	
Connecting an IR receiver	
Operating other Pioneer components with	Using the Home THX modes
this unit's sensor	

Listening in stereo	Data Management
Using Front Stage Surround Advance58	Renaming MCACC presets89
Using Stream Direct	Copying MCACC preset data89
Using surround back channel processing59	Clearing MCACC presets
Using the Virtual Surround Back mode60	
Setting the Up Mix function	11 The system and the other setup
Selecting MCACC presets	Making receiver settings from the System Setup
Choosing the input signal	menu
Better sound using Phase Control61	Manual speaker setup90
	Surround back speaker setting91
07 KURO LINK	Speaker Setting
Making the KURO LINK connections	Channel Level
Cautions on the KURO LINK function63	Speaker Distance93
About connections with a product of a different	X-Curve
brand that supports the KURO LINK function 64	THX Audio Setting
KURO LINK Setup	The Other Setup menu
Setting the PQLS function	Multi Channel Input Setup94
Before using synchronization	ZONE Audio Setup
	Power ON Level Setup
Synchronized amp mode operations	Volume Limit Setup
Cancening Synchronized amp mode	Flicker Reduction Setup
00 Hainer ather from tions	Tilcher Neddetion Setup
08 Using other functions	12 Additional information
Setting the Audio options	Speaker Setting Guide
Setting the Video options	Positional relationship between speakers and
Using the MULTI-ZONE controls	monitor
Making an audio or a video recording	Troubleshooting
Reducing the level of an analog signal	Power
Using the sleep timer	No sound
Dimming the display	Other audio problems
Switching the HDMI output	Video
Checking your system settings	Settings
Resetting the system	Professional Calibration EQ graphical output 102
Default system settings	Display102
,	Remote control
09 Controlling the rest of your system	HDMI 103
Operating multiple receivers	Important information regarding the HDMI
Setting the remote to control other components 73	connection104
Selecting preset codes directly	USB interface
Resetting the remote control presets	XM radio messages
Default preset codes	SIRIUS radio messages
Controls the components	Surround sound formats
	Dolby
10 The Advanced MCACC menu	DTS
Making receiver settings from the Advanced	Windows Media Audio 9 Professional
MCACC menu	About iPod
Automatic MCACC (Expert)	About Neural – THX Surround
Manual MCACC setup80	About SIRIUS and XM
Fine Channel Level81	Auto Surround, ALC and Stream Direct with
Fine Speaker Distance	different input signal formats112
Standing Wave82	Preset code list
Acoustic Calibration EQ Adjust83	Specifications
Acoustic Calibration EQ Professional83	Cleaning the unit
Checking MCACC Data86	Our philosophy
Speaker Setting	Index
Channel Level87	
Speaker Distance	
Standing Wave87	
Acoustic Cal EQ	
Output PC	

Flow of settings on the receiver

The unit is a full-fledged AV receiver equipped with an abundance of functions and terminals. It can be used easily after following the procedure below to make the connections and settings.

The colors of the steps indicate the following:

Required setting item

Setting to be made as necessary

1 Before you start

- Checking what's in the box (page 9)
- Loading the batteries (page 9)



2 Determining the speakers' application (page 17)

- 7.1ch surround connection
- 5.1ch surround & Front Bi-amping connection
- 5.1ch surround & ZONE 2 connection
- 5.1ch surround & Speaker B connection



3 Connecting the speakers

- Placing the speakers (page 18)
- Connecting the speakers (page 19)
- Standard 5.1/6.1/7.1-channel surround connections (page 20)
- Bi-amping your speakers (page 21)



4 Connecting the components

- About the audio connection (page 22)
- About the video converter (page 23)
- Connecting your TV and playback components (page 24)
- Connecting AM/FM antennas (page 31)
- Plugging in the receiver (page 39)



5 Switching the speaker impedance (page 40)

(Only if the impedance of the connected speakers is 6 Ω to 8 Ω)



6 Power On



7 Changing the OSD display language (OSD Language) (page 40)



Surround back speaker setting (page 91)



MCACC speaker settings

 Automatically setting up for surround sound (Auto MCACC) (page 41)



10 The Input Setup menu (page 43)

(When using connections other than the recommended connections)



11 Switching the HDMI output (page 71)

(VSX-23TXH model only)



12 Basic playback (page 45)



13 Adjusting the sound and picture quality as desired

- Using the various listening modes
- Using surround back channel processing (page 59)
- Better sound using Phase Control (page 61)
- Measure the all EQ type (SYMMETRY/ALL CH ADJ/ FRONT ALIGN) (page 78)
- Change the channel level while listening (*Tip* on page 92)
- Switches on/off the Acoustic Calibration EQ, Sound retriever or Dialog Enhancement (page 66)
- Setting the PQLS function (page 65)
- Setting the Audio options (Tone, Loudness or Sound delay, etc.) (page 66)
- Setting the Video options (page 68)



14 Other optional adjustments and settings

- KURO LINK Setup (page 64)
- The Advanced MCACC menu (page 77)
- The system and the other setup (page 90)



15 Making maximum use of the remote control

- Operating multiple receivers (page 73)
- Setting the remote to control other components (page 73)

Chapter 1: Before you start

Features

Advanced Direct Energy design

This receiver offers a new advancement in discrete design unique to Pioneer for high-power drivability, low distortion and stable imaging. Through a circuit design that minimizes the energy loss of the amplifier for each of the channels, this receiver generates equal amplifier power to all channels, eliminating the possibility of one channel dominating a particular sound field.

Easy setup using Advanced MCACC

The Auto MCACC Setup provides a quick but accurate surround sound setup, which includes the advanced features of Professional Acoustic Calibration EQ. This innovative technology measures the reverb characteristics of your listening area, allowing you to customize your system calibration with the help of a graphical output that can be displayed on-screen or using computer. With the additional benefits of numerous MCACC preset memories, standing wave control and microphone measurements from a series of reference points, your home theater experience can be truly customized for optimal surround sound.

THX Select2 Plus certified design

This receiver bears the THX Select2 Plus logo, which means it has passed a rigorous series of quality and performance tests covering every aspect of the product. This includes testing of pre-amplifier and power amplifier performance and operation, and hundreds of other parameters in both the digital and analog domain, making your home theater experience as faithful as possible to what the director intended.

Dolby Digital and DTS decoding, including Dolby Digital EX, Dolby Pro Logic IIx, DTS 96/24, DTS-ES, Dolby Digital Plus, Dolby TrueHD, DTS-EXPRESS and DTS-HD **Master Audio**

Dolby Digital and DTS decoding brings theater sound right into your home with up to six channels of surround sound, including a special LFE (Low Frequency Effects) channel for deep, realistic sound effects.

The built-in Dolby Pro Logic IIx and DTS Neo:6 decoders not only provide full surround sound decoding for Dolby Surround sources, but will also generate convincing surround sound for any stereo source.

Also, with the addition of a surround back speaker, you can take advantage of the built-in Dolby Digital EX and DTS-ES decoders for six-channel surround sound.

Furthermore, Dolby Digital Plus and Dolby TrueHD, which are designed for the next-generation highdefinition media such as Blu-ray Disc and HD DVD. support up to 7.1 channels and 8 channels respectively.

DTS-EXPRESS is a low-bitrate encoding technology supporting up to 5.1 channels, with fixed data transfer rates ranging from 24 kbps to 256 kbps (this encoding is available only when signals are delivered to this receiver as primary audio).

DTS-HD Master Audio delivers audio signals to listeners without any loss of data with its high transfer rates.

Phase Control

The Phase Control technology incorporated into this receiver's design provides coherent sound reproduction through the use of phase matching for an optimal sound image at your listening position.

Sound Retriever

The Sound Retriever feature employs DSP technology to restore sound pressure and smooth jagged artifacts left over after compression. This helps bring CD quality sound back to WMA and MP3 audio files and achieves a richer sense of presence when playing Dolby Digital, DTS or WMA 9 Pro audio formats recorded in multiple channels on DVDs and other discs.

Front Stage Surround Advance

With the Front Stage Surround Advance feature, you can enjoy seamless, natural surround sound effects using only the front speakers, without deteriorating the quality of the original sound.

Auto Level Control

When the source is played in Auto level control mode (ALC), this receiver automatically equalizes the playback sound level according to the variation in recording levels.

HDMI and digital video conversion

This receiver is compatible with the HDMI digital video format, providing you with high-definition digital video/ audio via a single cable.

High-quality sound formats such as DTS-HD and Dolby TrueHD are supported while this receiver is also compatible with the Deep Color feature. You can operate this receiver in synchronization with your Pioneer component that supports the KURO LINK function by connecting your component to this receiver via HDMI. Also, the built-in digital video converter of this receiver makes both de-interlacing and up-scaling possible, and analog video signals being input are converted and output as digital video signals at the HDMI terminal.

Before you start

XM and SIRIUS Ready

With the XM and SIRIUS Radio terminals, you'll be up and running in no time. This receiver's enhanced compatibility makes XM HD Surround playback as well as on-screen control of your XM and SIRIUS Radio an added possibility.

iPod/iPhone and USB Ready

This receiver has the terminals for connecting an iPod/ iPhone unit and a USB mass storage device.

The iPod terminal is ready for handling digital audio and video, and this receiver's enhanced compatibility makes on-screen control of your iPod an added possibility.

The USB terminal allows you to listen to two-channel audio from a USB mass storage device connected to this receiver.

Checking what's in the box

Please check that you've received the following supplied accessories:

- Setup microphone (cable: 5 m (16.4 ft.))
- · Remote control unit
- AA size IEC R6 dry cell batteries (to confirm system operation) x2
- AM loop antenna
- · FM wire antenna
- · iPod cable
- · Power cord
- · Warranty card
- These operating instructions


Installing the receiver

• When installing this unit, make sure to put it on a level and stable surface.

Don't install it on the following places:

- on a color TV (the screen may distort)
- near a cassette deck (or close to a device that gives off a magnetic field). This may interfere with the sound.
- in direct sunlight
- in damp or wet areas
- in extremely hot or cold areas
- in places where there is vibration or other movement
- in places that are very dusty
- in places that have hot fumes or oils (such as a kitchen)
 - Do not touch this receiver's bottom panel while the power is turned on. The bottom panel gets hot when the power is on, and touching it could cause burns.

Loading the batteries



CAUTION

Incorrect use of batteries may result in such hazards as leakage and bursting. Observe the following precautions:

- · Never use new and old batteries together.
- Insert the plus and minus sides of the batteries properly according to the marks in the battery case.
- Batteries with the same shape may have different voltages. Do not use different batteries together.
- When disposing of used batteries, please comply with governmental regulations or environmental public instruction's rules that apply in your country or area.


WARNING

Do not use or store batteries in direct sunlight or other excessively hot place, such as inside a car or near a heater. This can cause batteries to leak, overheat, explode or catch fire. It can also reduce the life or performance of batteries.

Operating range of remote control unit

The remote control may not work properly if:


- There are obstacles between the remote control and the receiver's remote sensor.
- Direct sunlight or fluorescent light is shining onto the remote sensor.
- The receiver is located near a device that is emitting infrared rays.
- The receiver is operated simultaneously with another infrared remote control unit.



Chapter 2:

Controls and displays

Remote control



The remote has been conveniently color-coded according to component control using the following system:

- White Receiver control, TV Control
- Blue Other controls

() RECEIVER

This switches between standby and on for this receiver.

Input function buttons

Press to select control of other components (see Controlling the rest of your system on page 73).

3 Number buttons and other receiver/component controls

Use the number buttons to directly select a radio frequency (page 51) or the tracks on a CD, DVD, etc.

ENTER can be used to enter commands for TV or DTV.

Press **RECEIVER** first to access:

INPUT SELECT – Use to select the input function (page 45).

VSX-23TXH only: **HDMI OUT** – Switch the HDMI output terminal (page 71).

SIGNAL SEL – Use to select an input signal (page 61).

MCACC – Press to switch between MCACC presets

SLEEP – Use to put the receiver in sleep mode and select the amount of time before sleep (page 71).

SBch – Use to select the surround back/virtual surround back channel mode (page 59).

A.ATT - Attenuates (lowers) the level of an analog input signal to prevent distortion (page 70).

DIMMER – Dims or brightens the display (page 71).

CH LEVEL – Press repeatedly to select a channel. then use \leftarrow/\Rightarrow to adjust the level (page 92).

Press TUNER first to access:

D.ACCESS – After pressing, you can access a radio station directly using the number buttons (page 51).

CLASS – Switches between the seven banks (classes) of radio station presets (page 51).

4 TV CONTROL buttons

These buttons are dedicated to control the TV assigned to TV operation selector switch. Thus if you only have one TV to hook up to this system assign it to the TV operation selector switch (see page 74 for more on this).

♂ – Use to turn on/off the power of the TV.

INPUT – Use to select the TV input signal.

CH +/- - Use to select channels.

VOL +/- – Use to adjust the volume on your TV.

Controls and displays

5 Tuner/component control buttons/HOME MENU

These button controls can be accessed after you have selected the corresponding input function button (**DVD**, **DVR**, **TV**, etc.). The **BAND** and **T.EDIT** tuner controls are explained on page 51.

Press **RECEIVER** first to access:

AUDIO PARAMETER – Use to access the Audio options (page 66).

VIDEO PARAMETER – Use to access the Video options (page 68).

HOME MENU – Use to access the Home Menu (pages 40, 43, 64, 77, 90 and 94).

RETURN – Press to confirm and exit the current menu screen (also use to return to the previous menu with DVDs or to select closed captioning with DTV).

6 ↑/\$/←/→ (TUNE/PRESET) /ENTER

Use the arrow buttons when setting up your surround sound system (see page 77) and the Audio or Video options (page 66 or 68). Also used to control DVD menus/options and for deck 1 of a double cassette deck player. Use **TUNE** ↑ ↓ to find radio frequencies and use **PRESET** ←/→ to find preset stations (page 51).

7 Component/Receiver control buttons

The main buttons (▶, ■, etc.) are used to control a component after you have selected it using the input function buttons.

The controls above these buttons can be accessed after you have selected the corresponding input function button (for example **DVD**, **DVR** or **TV**). These buttons also function as described below.

Press TUNER first to access:

MPX – Switches between stereo and mono reception of FM broadcasts. If the signal is weak, then switching to mono will improve the sound quality (page 51).

Press **RECEIVER** first to access:

AUTO/ALC/DIRECT – Switches between Auto Surround (page 56), Auto level control mode and Stream Direct mode (page 59).

STEREO – Switches between stereo playback and Front Stage Surround Advance modes (page 58).

STANDARD – Press for Standard decoding and to switch between the various **DD** Pro Logic IIx and Neo:6 options (page 56).

ADV SURR – Use to switch between the various surround modes (page 58).

THX – Press to select a Home THX listening mode (page 57).

PHASE CTRL – Press to switch on/off Phase Control (page 61).

STATUS – Press to check selected receiver settings (page 71).

PQLS – Press to select PQLS setting (page 65).

8 AUDIO – Changes the audio or channel on DVD or BD discs.

DISP – Switches between named station presets and radio frequencies.

CH +/- - Use to select channels for DVD/DVR units.

9 REMOTE SETUP

Use to input the preset code when making remote control settings and to set the remote control mode (page 73).

10 TV CTRL

Use this button to set preset code of your TV's manufacturer when controlling TV (see *Selecting preset codes directly* on page 73 for more on this).

11 MULTI-ZONE operation selector switch

Switch to perform operations in the main zone, ZONE 2 and ZONE 3 (VSX-23TXH only) (page 70).

12 Remote control LED

Lights when a command is sent from the remote control (page 73).

13 O SOURCE

Press to turn on/off other components connected to the receiver (see page 73 for more on this).

14 MASTER VOLUME +/-

Use to set the listening volume.

15 MUTE

Mutes the sound or restores the sound if it has been muted (adjusting the volume also restores the sound).


16 RECEIVER

Switches the remote to control the receiver (used to select the white commands above the number buttons (A.ATT, etc.)). Also use this button to set up surround sound.

17 ∵ 🖰

Press to turn on/off the illumination of some of the buttons.

Front panel



1 INPUT SELECTOR dial

Use to select an input function.

2 () STANDBY/ON

Switches the receiver between on and standby. Power indicator lights when the receiver is on.

When the **KURO LINK** function is set to **ON**, the power indicator lights when the power is in standby.

3 Tuner controls

BAND – Switches between AM and FM radio bands (page 51).

TUNE +/- – Use to find radio frequencies (page 51). **PRESET +/-** – Use to find preset stations (page 51).

TUNER EDIT – Use with **TUNE +/-**, **PRESET +/-** and **ENTER** to memorize and name stations for recall (page 51).

4 PHASE CONTROL indicator – Lights to indicate Phase Control is selected (page 61).

 $\begin{tabular}{lll} \textbf{ADVANCED MCACC indicator} - \textbf{Lights when EQ} is \\ \textbf{set to ON} in the \begin{tabular}{lll} \textbf{AUDIO PARAMETER} menu (page 66). \\ \end{tabular}$

VSX-23TXH only: **PQLS indicator** – Lights when the PQLS feature is active (page 65).

HDMI indicator – Blinks when connecting an HDMI-equipped component; lights when the component is connected (page 24).

5 Character display

See Display on page 13.

6 ENTER

7 Remote sensor

Receives the signals from the remote control (see *Operating range of remote control unit* on page 9).

8 MASTER VOLUME dial

9 PHONES jack

Use to connect headphones. When the headphones are connected, there is no sound output from the speakers.

10 Listening mode buttons

AUTO SURR/ALC/STREAM DIRECT – Switches between Auto Surround (page 56), Auto level control mode and Stream Direct mode (page 59).

STEREO – Switches between stereo playback and Front Stage Surround Advance modes (page 58).

ADVANCED SURROUND – Use to switch between the various surround modes (page 58).

STANDARD SURROUND – Press for Standard decoding and to switch between the various DD Pro Logic IIx and Neo:6 options (page 56).

HOME THX – Press to select a Home THX listening mode (page 57).

11 SPEAKERS

Use to change the speaker system (page 69).

Controls and displays

12 MULTI-ZONE controls

If you've made MULTI-ZONE connections (see *MULTI-ZONE setup* on page 33) use these controls to control the sub zone from the main zone (see *Using the MULTI-ZONE controls* on page 69).

13 MCACC SETUP MIC jack

Use to connect the supplied microphone (page 41).

14 iPod/iPhone/USB terminals

Use to connect your Apple iPod as an audio and video source, or connect a USB device for audio and photo playback (page 38).


15 VSX-23TXH only: **HDMI 4 input connector**

Use for connection to compatible HDMI device (Video camera, etc.). See *Connecting an HDMI-equipped component to the front panel input* on page 37.

16 VSX-21TXH only: **VIDEO 2 INPUT terminals**

Use to connect your portable equipment such as camcorders, video games and portable audio/video equipment. See *Connecting a component to the front panel inputs* on page 38.

Display



1 SIGNAL indicators

Light to indicate the currently selected input signal. **AUTO** lights when the receiver is set to select the input signal automatically (page 61).

2 Program format indicators

Light to indicate the channels being input when PCM signals are being input. They do not indicate the audio signals being output from the receiver.

L/R - Left front/Right front channel

C - Center channel

SL/SR - Left surround/Right surround channel

LFE – Low frequency effects channel (the (()) indicators light when an LFE signal is being input)

XL/XR - Two channels other than the ones above

XC – Either one channel other than the ones above, the mono surround channel or matrix encode flag

3 Digital format indicators

Light when a signal encoded in the corresponding format is detected.

4 S.RTRV

Lights when the Sound Retriever function is active (page 66).

5 MULTI-ZONE

Lights when the MULTI-ZONE feature is active (page 69).

6 DSD PCM – Light during DSD (Direct Stream Digital) to PCM conversion with SACDs.

PCM – Lights during playback of PCM signals.

7 SOUND

Lights when any of the Midnight, Loudness or tone controls feature is selected (page 66).

Lights when Dialog Enhancement is switched on.

8 UP MIX

Lights when the Up Mix is switched on (page 60).

9 Listening mode indicators

AUTO SURROUND – Lights when the Auto Surround feature is switched on (page 56).

ALC – Lights when the ALC (Auto level control) mode is selected (page 59).

STREAM DIRECT – Lights when Direct/Pure Direct is selected (page 59).

ADV.SURROUND – Lights when one of the Advanced Surround modes has been selected (page 58).

STEREO – Lights when stereo listening is switched on (page 58).

STANDARD – Lights when one of the Standard Surround modes is switched on (page 56).

THX – Lights when one of the Home THX modes is selected (page 57).

10 (PHASE CONTROL)

Lights when the Phase Control is switched on (page 61).

Controls and displays

11 Analog signal indicators

Light to indicate reducing the level of an analog signal (page 70).

12 Tuner indicators

TUNED – Lights when a broadcast is being received. **STEREO** – Lights when a stereo FM broadcast is being received in auto stereo mode.

MONO – Lights when the mono mode is set using **MPX**.

13 🗱

Lights when the sound is muted (page 11).

14 Master volume level

Shows the overall volume level.

"---" indicates the minimum level, and "+12dB" indicates the maximum level.

15 Input function indicators

Light to indicate the input function you have selected.

16 Scroll indicators

Light when there are more selectable items when making the various settings.

17 Speaker indicators

Lights to indicate the current speaker system, **A** and/or **B** (page 69).

18 SLEEP

Lights when the receiver is in sleep mode (page 71).

19 Matrix decoding format indicators

DIDPRO LOGIC IIx – This lights to indicate DID Pro Logic II / DID Pro Logic IIx decoding (page 56).

Neo:6 – When one of the Neo:6 modes of the receiver is on, this lights to indicate Neo:6 processing (page 56).

20 MSTR

Lights during playback of DTS-HD Master Audio signal.

21 Character display

Displays various system information.

22 Remote control mode indicator

Lights to indicate the receiver's remote control mode setting. (Not displayed when set to **1**.) (page 73)

Chapter 3:


Connecting your equipment

This receiver provides you with many connection possibilities, but it doesn't have to be difficult. This page explains the kinds of components you can connect to make up your home theater system.


(Important

• Illustration shows the VSX-23TXH, however connections for the VSX-21TXH are the same except where noted.

Rear panel



VSX-23TXH



VSX-21TXH

A CAUTION

- Before making or changing the connections, switch off the power and disconnect the power cord from the power outlet. Plugging in should be the final step.
- To avoid hum, do not lay connected cables over the top of the receiver.



Connecting your equipment

1 HDMI connectors (x6 (VSX-23TXH)/x5 (VSX-21TXH))

Multiple inputs and one (VSX-21TXH)/two (VSX-23TXH) output(s) for high-quality audio/video connection to compatible HDMI devices.

- → See Connecting your TV and playback components on page 24.
- → VSX-23TXH only: See Switching the HDMI output on page 71.

2 Coaxial digital audio inputs (x2)

Use for digital audio sources, including DVD players/recorders, digital satellite receivers, CD players, etc.

→ See also *The Input Setup menu* on page 43 to assign the inputs.

3 Optical digital audio output/input(s) (x4)

Use the **OUT** jack for recording to a CD or MiniDisc recorder.

- → See Connecting other audio components on page 29.

 Use the **IN** jacks for digital audio sources, including DVD players/recorders, digital satellite receivers, CD players, etc.
- ightarrow See also *The Input Setup menu* on page 43 to assign the inputs.

4 XM Radio input

→ See Connecting an XM Radio tuner on page 32.

5 SIRIUS Radio input

→ See Connecting a SiriusConnect[™] tuner on page 32.

6 Component video connectors (x3)

Use the inputs to connect any video source that has component video output, such as a DVD player.

→ See Connecting your DVD player with no HDMI output on page 25.

Use the output to connect monitor or TV.

→ See Connecting your TV with no HDMI input on page 26.

7 ZONE 2 and ZONE 3 (VSX-23TXH only) output(s)

Use to connect a second or third (VSX-23TXH only) amplifier and monitors or TVs in a separate room.

→ See MULTI-ZONE setup on page 33.

8 Composite and S-Video monitor outputs

Use to connect monitors and TVs.

→ See Connecting your TV with no HDMI input on page 26.

9 Audio/video source inputs/(outputs) (x5)

Use for connection to audio/visual sources, such as DVD players/recorders, VCRs, etc. Each set of inputs has jacks for composite video, S-Video and stereo analog audio.

→ See Connecting an HDD/DVD recorder, VCR and other video sources on page 28.

10 Stereo analog audio source inputs/(outputs) (x3)

Use for connection to audio sources such as CD players, tape decks, turntables, etc.

→ See Connecting other audio components on page 29.

11 Multichannel analog audio inputs

7.1 channel inputs for connection to a DVD player with multichannel analog outputs.

→ See Connecting the multichannel analog inputs on page 29.

12 Multichannel pre-amplifier outputs

Use to connect separate amplifiers for front, center, surround, surround back and subwoofer channels.

→ See Connecting additional amplifiers on page 30 (see also Installing your speaker system on page 20 for powered subwoofer connection).

13 AM and FM antenna terminals

Use to connect indoor or outdoor antennas for radio broadcasts.

→ See Connecting AM/FM antennas on page 31.

14 RS-232C connector

Use for connection to a PC for graphical output when using Advanced MCACC.

→ See Connecting a PC for Advanced MCACC output on page 36.

15 Control input/output

Use to connect other Pioneer components so that you can control all your equipment from a single IR remote sensor.

→ See Operating other Pioneer components with this unit's sensor on page 35.

16 Remote input(s)/output (x3 (VSX-23TXH)/x2 (VSX-21TXH))

Use for connection to an external remote control sensor for use in a MULTI-ZONE setup, for example.

→ See Connecting an IR receiver on page 35.

17 12 V trigger jacks (total 50 mA max.) (x2)

Use to switch components in your system on and off according to the input function of the receiver.

→ See Switching components on and off using the 12 volt trigger on page 36.

18 Speaker terminals

Use for connection to the main front, center, surround and surround back speakers.

→ See Connecting the speakers on page 19.

19 AC power inlet

Connect the supplied power cord here.

→ See *Plugging in the receiver* on page 39.

R

Right

Determining the speakers' application

Surround sound with a strong sense of presence can be enjoyed by connecting 7 speakers and 1 subwoofer. It is also possible to achieve high sound quality using bi-amp connections and to enjoy music in other rooms using the MULTI-ZONE feature. High sound quality can be achieved with a minimum of two speakers.


- Be sure to connect speakers to the front left and right channels (L and R).
- The **Surr Back System** setting must be made if you use any of the connections shown below other than [1] (see *Selecting the Surr Back system* on page 22).

[1] 7.1ch surround connection (Simple connection & Best surround)

*Default setting

These connections prioritize surround sound with a speaker layout like that in a movie theater.


- Surr Back System setting: Normal (default)
- If you have six speakers, either only connect one surround back speaker (6.1 ch surround), or connect for the 7.1-channel setting as shown on the diagram below but without the center speaker.



[2] 5.1ch surround & Front Bi-amping connection (High quality surround)

Bi-amping connection of the front speakers for high sound quality with 5.1-channel surround sound.

• Surr Back System setting: Front Bi-Amp




*Bi-amp compatible speaker

[3] 5.1ch surround & ZONE 2 connection (Multi Zone)

With these connections you can simultaneously enjoy 5.1-channel surround sound in the main zone with stereo playback on another component in ZONE 2. (The selection of input devices is limited.)


Surr Back System setting: ZONE 2



[4] 5.1ch surround & Speaker B connection

With these connections you can simultaneously enjoy 5.1-channel surround sound in the main zone with stereo playback of the same sound on the B speakers.

• Surr Back System setting: Speaker B




Other speaker connection

- Your favorite speaker connections can be selected even if you have fewer than 5.1 speakers.
- When not connecting a subwoofer, connect speakers with low frequency reproduction capabilities to the front channel. (The subwoofer's low frequency component is played from the front speakers, so the speakers could be damaged.)
- After connecting, be sure to conduct the Auto MCACC (speaker environment setting) procedure. See Automatically setting up for surround sound (Auto MCACC) on page 41.


Placing the speakers

To achieve the best possible surround sound, install your speakers as shown below.


5.1 channel surround system:



6.1 channel surround system:



7.1 channel surround system:



THX speaker system setup

If you are using a THX certified subwoofer use the **THX INPUT** jack on the subwoofer (if your subwoofer has one) or switch the filter position to **THX** on your subwoofer.

See also *THX Audio Setting* on page 93 to make the settings that will give you the best sound experience when using the Home THX modes (page 57).

Some tips for improving sound quality

Where you put your speakers in the room has a big effect on the quality of the sound. The following guidelines should help you to get the best sound from your system.

- The subwoofer can be placed on the floor. Ideally, the
 other speakers should be at about ear-level when
 you're listening to them. Putting the speakers on the
 floor (except the subwoofer), or mounting them very
 high on a wall is not recommended.
- For the best stereo effect, place the front speakers 2 m to 3 m (6 ft. to 9 ft.) apart, at equal distance from the TV
- If you're using a center speaker, place the front speakers at a wider angle. If not, place them at a narrower angle.
- Place the center speaker above or below the TV so that the sound of the center channel is localized at the TV screen. Also, make sure the center speaker does not cross the line formed by the leading edge of the front left and right speakers.
- It is best to angle the speakers towards the listening position. The angle depends on the size of the room. Use less of an angle for bigger rooms.
- Surround and surround back speakers should be positioned 60 cm to 90 cm (2 ft. to 3 ft.) higher than your ears and tilted slight downward. Make sure the speakers don't face each other. For DVD-Audio, the speakers should be more directly behind the listener than for home theater playback.
- If the surround speakers cannot be set directly to the side of the listening position with a 7.1-channel system, the surround effect can be enhanced by turning off the Up Mix function (see Setting the Up Mix function on page 60).
- Try not to place the surround speakers farther away from the listening position than the front and center speakers. Doing so can weaken the surround sound effect.

Connecting the speakers

Each speaker connection on the receiver comprises a positive (+) and negative (-) terminal. Make sure to match these up with the terminals on the speakers themselves.




CAUTION

- These speaker terminals carry HAZARDOUS LIVE **voltage**. To prevent the risk of electric shock when connecting or disconnecting the speaker cables. disconnect the power cord before touching any uninsulated parts.
- Make sure that all the bare speaker wire is twisted together and inserted fully into the speaker terminal. If any of the bare speaker wire touches the back panel it may cause the power to cut off as a safety measure.

Bare wire connections

- Twist exposed wire strands together. (fig. A)
- Loosen terminal and insert exposed wire. (fig. B) 2
- Tighten terminal. (fig. C) 3



Banana plug connections

If you want to use speaker cables terminated with banana plugs, screw the speaker terminal fully shut, then plug the banana plug into the end of the speaker terminal.





Important

- Please refer to the manual that came with your speakers for details on how to connect the other end of the speaker cables to your speakers.
- · Use an RCA cable to connect the subwoofer. It is not possible to connect using speaker cables.




CAUTION

• Make sure that all speakers are securely installed. This not only improves sound quality, but also reduces the risk of damage or injury resulting from speakers being knocked over or falling in the event of external shocks such as earthquakes.


Installing your speaker system

At the very least, front left and right speakers only are necessary. Note that your main surround speakers should always be connected as a pair, but you can connect just one surround back speaker if you like (it must be connected to the left surround back terminal).

Standard 5.1/6.1/7.1-channel surround connections



Bi-amping your speakers



Bi-amping is when you connect the high frequency driver and low frequency driver of your speakers to different amplifiers for better crossover performance. Your speakers must be bi-ampable to do this (having separate terminals for high and low) and the sound improvement will depend on the kind of speakers you're using.

A CAUTION


- Most speakers with both High and Low terminals have two metal plates that connect the High to the Low terminals. These must be removed when you are bi-amping the speakers or you could severely damage the amplifier. See your speaker manual for more information.
- If your speakers have a removable crossover network, make sure you do not remove it for bi-amping. Doing so may damage your speakers.

Bi-wiring your speakers

Your speakers can also be bi-wired if they support biamping.

- With these connections, the **Surr Back System** setting makes no difference.
- To bi-wire a speaker, connect two speaker cords to the speaker terminal on the receiver.

Using a banana plug for the second connection is recommended.



A CAUTION

- Don't connect different speakers from the same terminal in this way.
- When bi-wiring as well, heed the cautions for biamping shown at the left.

Selecting the Surr Back system

The surround back terminals can be used for bi-amping, Speaker B and ZONE 2 connections, in addition to for the surround back speakers. Make this setting according to the application.

ZONE 2 setup

With these connections you can simultaneously enjoy 5.1-channel surround sound in the main zone with stereo playback on another component in ZONE 2.

1 Connect a pair of speakers to the surround back speaker terminals.

See Standard 5.1/6.1/7.1-channel surround connections on page 20.

2 Select 'ZONE 2' from the Surr Back System menu. See *Surround back speaker setting* on page 91 to do this.

Speaker B setup

You can listen to stereo playback in another room.

1 Connect a pair of speakers to the surround back speaker terminals.

See Standard 5.1/6.1/7.1-channel surround connections on page 20.

2 Select 'Speaker B' from the Surr Back System menu.

See Surround back speaker setting on page 91 to do this.

Bi-Amping setup

Bi-amping connection of the front speakers for high sound quality with 5.1-channel surround sound.

1 Connect Bi-amp compatible speakers to the front and surround back speaker terminals.

See Bi-amping your speakers on page 21.

2 Select 'Front Bi-Amp' from the Surr Back System menu.

See Surround back speaker setting on page 91 to do this.

About the audio connection

There are several types of audio input and output terminals on this receiver. The receiver selects the first available signal in the following order when you choose **AUTO** as the input signal:

	Types of cables and terminals	Transferable audio signals
Sound signal priority	HDMI	HD audio
Sound sign	Digital (Coaxial) Digital (Optical)	Conventional digital audio
	RCA (Analog) (White/Red)	Conventional analog audio

• With an HDMI cable, video and audio signals can be transferred in high quality over a single cable.


A CAUTION

- When connecting optical cables, be careful when inserting the plug not to damage the shutter protecting the optical socket.
- When storing optical cable, coil loosely. The cable may be damaged if bent around sharp corners.

About the video converter

The video converter ensures that all video sources are output through all of the **MONITOR OUT** jacks. The only exception is HDMI: since this resolution cannot be downsampled, you must connect your monitor/TV to the receiver's HDMI video outputs when connecting this video source.¹

If several video components are assigned to the same input function (see *The Input Setup menu* on page 43), the converter gives priority to HDMI, component, S-Video, then composite (in that order).



 For optimal video performance, THX recommends switching Digital Video Conversion (in Setting the Video options on page 68) OFF.

This product incorporates copyright protection technology that is protected by method claims of certain U.S. patents and other intellectual property rights owned by Macrovision Corporation and other rights owners. Use of this copyright protection technology must be authorized by Macrovision Corporation, and is intended for home and other limited viewing uses only unless otherwise authorized by Macrovision Corporation. Reverse engineering or disassembly is prohibited.

🕢 Note


- 1 If the video signal does not appear on your TV or flat panel TV, try adjusting the resolution settings on your component or display. Note that some components (such as video game units) have resolutions that may not be converted. In this case, try switching Digital Video Conversion (in Setting the Video options on page 68) **OFF**.
- The signal input resolutions that can be converted from the component video input for the HDMI output are 480i/576i, 480p/576p, 720p and 1080i. 1080p signal cannot be converted.
- Only signals with an input resolution of 480i/576i can be converted from the component video input for the composite and S-Video **MONITOR OUT**.

Connecting your TV and playback components

Connecting using HDMI

If you have an HDMI or DVI (with HDCP) equipped component (Blu-ray disc player, etc.), you can connect it to this receiver using a commercially available HDMI cable.


If the TV and playback components support the Pioneer KURO LINK feature, the convenient KURO LINK functions can be used (see *KURO LINK* on page 63).



- When connecting a Blu-ray disc player, connect the player to the receiver's BD IN terminal.
- VSX-23TXH only: When connecting to an HDMI/DVI-compatible monitor or a flat panel TV using the HDMI OUT 2 terminal, switch the HDMI output setting to HDMI OUT 2 or HDMI OUT ALL. See Switching the HDMI output on page 71.
- The **HDMI** indicator lights on the front panel when an HDMI-equipped component is connected.
- For input components, connections other than HDMI connections are also possible (see *Connecting your DVD player with no HDMI output* on page 25).
- If your Blu-ray disc player offers multi-channel analog audio outputs, see *Connecting the multichannel analog inputs* on page 29.
- The sound of the TV cannot be heard over the receiver
 if the TV is connected using an HDMI cable.
 If you want to listen to the sound of the TV over the
 receiver, connect the receiver and TV with audio
 cables. When making digital connections with a
 coaxial cable at this time, the digital input setting
 must be made (see *The Input Setup menu* on
 page 43).

Connecting your DVD player with no HDMI output

This diagram shows connections of a TV (with HDMI input) and DVD player (or other playback component with no HDMI output) to the receiver.




- If you want to listen to the sound of the TV over the receiver, connect the receiver and TV with audio
- Component video should give superior picture quality when compared to composite or S-Video. You can also take advantage of progressive scan video (if your source and TV are both compatible), which delivers a very stable, flicker-free picture. See the manuals that came with your TV and source component to check whether they are compatible with progressive-scan video.
- If your DVD player offers multi-channel analog audio outputs, see *Connecting the multichannel analog inputs* on page 29.

Connecting your equipment

Connecting your TV with no HDMI input

This diagram shows connections of a TV (with no HDMI input) and DVD player (or other playback component) to the receiver.

• With these connections, the picture is not output to the TV even if the DVD player is connected with an HDMI cable. Connect the DVD player's video signals using a composite, S-Video or component cord.



- Connect using an HDMI cable to listen to HD audio on the receiver. Do not use an HDMI cable to input video signals.
 - Depending on the video component, it may not be possible to output signals connected by HDMI and other methods simultaneously, and it may be necessary to make output settings. Please refer to the operating instructions supplied with your component for more information.
- Component video should give superior picture quality
 when compared to composite or S-Video. You can also
 take advantage of progressive scan video (if your
 source and TV are both compatible), which delivers a
 very stable, flicker-free picture. See the manuals that
 came with your TV and source component to check
 whether they are compatible with progressive-scan
 video.
- If your DVD player has multichannel analog outputs, you can connect these instead. See also *Connecting* the multichannel analog inputs on page 29.

Connecting your equipment

• The input functions below are assigned by default to the receiver's different input terminals. Refer to *The Input Setup menu* on page 43 to change the assignments if other connections are used. For example, the BD terminal is fixed to **BD** input; no other audio and video signals can be input to this terminal.

Input function	Input Terminals			
	Digital	HDMI	Component	
DVD	COAX-1		IN 1	
BD		(BD)		
TV/SAT	OPT-1			
DVR	OPT-2		IN 2	
VIDEO ^a /VIDEO 1 ^b	OPT-3			
HDMI 1		(HDMI-1)		
HDMI 2		(HDMI-2)		
HDMI 3		(HDMI-3)		
HDMI 4 ^a (front panel)		(HDMI-4)		
CD	COAX-2			

a. VSX-23TXH only b. VSX-21TXH only

About HDMI¹

The HDMI connection transfers uncompressed digital video, as well as almost every kind of digital audio that the connected component is compatible with, including DVD-Video, DVD-Audio, SACD, Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio (see below for limitations), Video CD/Super VCD and CD. See *About the video converter* on page 23 for more on HDMI compatibility.

This receiver incorporates High-Definition Multimedia Interface (HDMI™) technology.

This receiver supports the functions described below through HDMI connections.

- Digital transfer of uncompressed video (contents protected by HDCP (1080p/24, 1080p/60, etc.))
- Deep Color signal transfer²
- x.v.Color signal transfer²
- Input of multi-channel linear PCM digital audio signals (192 kHz or less) for up to 8 channels
- Input of the following digital audio formats:

 Dolby Digital, Dolby Digital Plus, DTS, High bitrate audio (Dolby TrueHD, DTS-HD Master Audio), DVD-Audio, CD, SACD (DSD signal), Video CD, Super VCD
- Synchronized operation with components using the KURO LINK function (see KURO LINK on page 63)

HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC.

"x.v.Color" and x.v.Color logo are trademarks of Sony Corporation.


Note

- 1 An HDMI connection can only be made with DVI-equipped components compatible with both DVI and High Bandwidth Digital Content Protection (HDCP). If you choose to connect to a DVI connector, you will need a separate adaptor (DVI→HDMI) to do so. A DVI connection, however, does not support audio signals. Consult your local audio dealer for more information.
- If you connect a component that is not compatible with HDCP, an **HDCP ERROR** message is displayed on the front panel display. Some components that are compatible with HDCP still cause this message to be displayed, but so long as there is no problem with displaying video this is not a malfunction.
- Depending on the component you have connected, using a DVI connection may result in unreliable signal transfers.
- This receiver supports SACD, Dolby Digital Plus, Dolby TrueHD and DTS-HD Master Audio. To take advantage of these formats, however, make sure that the component connected to this receiver also supports the corresponding format.
- 2 Signal transfer is only possible when connected to a compatible component.

Connecting an HDD/DVD recorder, VCR and other video sources

This receiver has two sets of audio/video inputs and outputs suitable for connecting analog or digital video devices, including HDD/DVD recorders and VCRs.


When you set up the receiver you'll need to tell the receiver which input you connected the recorder to (see also *The Input Setup menu* on page 43).



Connecting a satellite/cable receiver or other set-top box

Satellite and cable receivers, and terrestrial digital TV tuners are all examples of so-called 'set-top boxes'.


When you set up the receiver you'll need to tell the receiver which input you connected the set-top box to (see *The Input Setup menu* on page 43).



VSX-23TXH

Connecting the multichannel analog inputs

For DVD Audio and SACD playback, your DVD player may have 5.1 channel analog outputs. Make sure that the player is set to output multichannel analog audio.



VSX-23TXH

 If your player has 7.1-channel analog outputs, the player's surround back output terminals are not used. Please refer to the operating instructions supplied with your component for more information.

Connecting other audio components


This receiver has both digital and analog inputs, allowing you to connect audio components for playback.

This receiver features five stereo audio-only inputs. One of these inputs have corresponding outputs for use with audio recorders.

Most digital components also have analog connections.

Connecting your equipment

When you set up the receiver you'll need to tell the receiver which input you connected the component to (see also The Input Setup menu on page 43).




- If your turntable has line-level outputs (i.e., it has a built-in phono pre-amp), connect it to the CD inputs instead.
- If you're connecting a recorder, connect the analog audio outputs to the analog audio inputs on the recorder

About the WMA9 Pro decoder

This unit has an on-board Windows Media™ Audio 9 Professional¹ (WMA9 Pro) decoder, so it is possible to playback WMA9 Pro-encoded audio using HDMI, coaxial or optical digital connection when connected to a WMA9 Pro-compatible player. However, the connected DVD player, set-top box, etc. must be able to output WMA9 Pro format audio signals through a coaxial or optical digital output.

Connecting additional amplifiers

This receiver has more than enough power for any home use, but it's possible to add additional amplifiers to every channel of your system using the pre-outs. Make the connections shown below to add amplifiers to power vour speakers.



- You can use the additional amplifier on the surround back channel pre-outs for a single speaker as well. In this case plug the amplifier into the left (L (Single)) terminal only.
- The sound from the surround back terminals will depend on how you have configured the Surround back speaker setting on page 91.
- To hear sound only from the pre-outs, switch the speaker system to **OFF**, or simply disconnect any speakers that are connected directly to the receiver.


If you're not using a subwoofer, change the front speaker setting (see Speaker Setting on page 91) to LARGE.

Note

- 1 Windows Media and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other
- With WMA9 Pro, sound problems may occur depending on your computer system. Note that WMA9 Pro 96 kHz sources will be downsampled to 48 kHz.

Connecting AM/FM antennas

Connect the AM loop antenna and the FM wire antenna as shown below. To improve reception and sound quality, connect external antennas (see *Connecting external antennas* below).



- 1 Pull off the protective shields of both AM antenna wires.
- 2 Push open the tabs, then insert one wire fully into each terminal, then release the tabs to secure the AM antenna wires.
- 3 Fix the AM loop antenna to the attached stand.

To fix the stand to the antenna, bend in the direction indicated by the arrow (fig. a) then clip the loop onto the stand (fig. b).

- If you plan to mount the AM antenna to a wall or other surface, secure the stand with screws (fig. c) before clipping the loop to the stand. Make sure the reception is clear.
- 4 Place the AM antenna on a flat surface and in a direction giving the best reception.
- 5 Connect the FM wire antenna in the same way as the AM loop antenna.

For best results, extend the FM antenna fully and fix to a wall or door frame. Don't drape loosely or leave coiled up.


Connecting external antennas

To improve FM reception connect an external FM antenna to the **FM UNBAL 75** Ω .




To improve AM reception, connect a 5 m to 6 m (16 ft. to 20 ft.) length of vinyl-coated wire to the $AM\ LOOP$ terminals without disconnecting the supplied AM loop antenna.

For the best possible reception, suspend horizontally outdoors.



Connecting an XM Radio tuner


After purchasing an XM Mini-Tuner and Home Dock (both sold separately), you will also need to activate the XM Radio service to begin receiving broadcasts.



• For instructions on playing the XM Radio, see *Listening to XM Radio* on page 52.

Connecting a SiriusConnect™ tuner

To receive SIRIUS Satellite Radio broadcasts, you will need to activate your SiriusConnect™ tuner.




You will also need to connect the antenna and AC adapter to the SiriusConnect™ tuner.

• For instructions on playing the SIRIUS Radio, see *Listening to SIRIUS Radio* on page 54.

MULTI-ZONE setup

This receiver can power up to two (*VSX-21TXH*)/three (*VSX-23TXH*) independent systems in separate rooms after you have made the proper MULTI-ZONE connections. An example MULTI-ZONE setup is shown below, but the number of MULTI-ZONE connections (and the way you choose to connect them) depends on how you want to set up your system.



Different sources can be playing in two (VSX-21TXH)/three (VSX-23TXH) zones at the same time or, depending on your needs, the same source can also be used. The main and sub zone(s) have independent power (the main zone power can be off while one (or both) of the sub zone(s) is on) and the sub zone(s) can be controlled by the remote or front panel controls. However, you may need to specify the volume settings in ZONE Audio Setup on page 95.

Making MULTI-ZONE connections

It is possible to make these connections if you have a separate TV and speakers for your primary (**ZONE 2**) sub zone (and a separate amplifier¹ (and speakers) for your secondary (**ZONE 3**) sub zone (*VSX-23TXH only*)). You will also need a separate amplifier if you are not using the *MULTI-ZONE setup using speaker terminals (ZONE 2*) on page 34 for your primary sub zone. There are two primary sub zone setups possible with this system. Choose whichever works best for you.

MULTI-ZONE listening options

The following table shows the signals that can be output to sub zone(s):

Sub zone	Input functions available
ZONE 2	Analog audio signals (AUDIO ZONE 2 OUT). ^a With video signals, ^b the composite video (VIDEO ZONE 2 OUT) signals can be output.
ZONE 3 (VSX-23TXH only)	Analog audio signals (AUDIO ZONE 3 OUT). a.c

a.Any analog signal. (This does not apply for the MULTI CH IN input.) b.JPEG files cannot be played with the USB input.

c.iPod/USB, XM or SIRIUS Radio function cannot be selected for ZONE 3.


Note

¹ You can't use sound controls (such as the tone controls or Midnight listening) or any surround modes with a separate amplifier in the sub zone. You can, however, use the features available with your sub zone amplifier.

Basic MULTI-ZONE setup (ZONE 2)

Connect a separate amplifier to the AUDIO ZONE 2 OUT jacks and a TV monitor to the VIDEO ZONE 2 OUT jack, both on this receiver.

You should have a pair of speakers attached to the sub zone amplifier as shown below.




MULTI-ZONE setup using speaker terminals (ZONE 2)

You must select **ZONE 2** in *Surround back speaker setting* on page 91 to use this setup. Note that the sound in the sub zone will be temporarily interrupted when controlling the main zone (for example, changing the input function or starting playback).

• Connect a TV monitor to the VIDEO ZONE 2 OUT jacks on this receiver.

You should have a pair of speakers attached to the surround back speaker terminals as shown below.




Secondary MULTI-ZONE setup (ZONE 3)

(VSX-23TXH only)

• Connect a separate amplifier to the AUDIO ZONE 3 OUT jacks on this receiver.


You should have a pair of speakers attached to the sub zone amplifier as shown below.



Connecting an IR receiver

If you keep your stereo components in a closed cabinet or shelving unit, or you wish to use the sub zone remote control in another zone, you can use an optional IR receiver (such as a Niles or Xantech unit) to control your system instead of the remote sensor on the front panel of this receiver. ¹

1 Connect the IR receiver sensor to the IR IN jack on the rear of this receiver.



2 Connect the IR IN jack of another component to the IR OUT jack on the rear of this receiver to link it to the IR receiver.

Please see the manual supplied with your IR receiver for the type of cable necessary for the connection.

 If you want to link a Pioneer component to the IR receiver, see Operating other Pioneer components with this unit's sensor below to connect to the CONTROL jacks instead of the IR OUT jack.

Operating other Pioneer components with this unit's sensor

Many Pioneer components have **SR CONTROL** jacks which can be used to link components together so that you can use just the remote sensor of one component. When you use a remote control, the control signal is passed along the chain to the appropriate component.²


Important

- Note that if you use this feature, make sure that you also have at least one set of analog audio, video or HDMI jacks connected to another component for grounding purposes.
- 1 Decide which component you want to use the remote sensor of.

When you want to control any component in the chain, this is the remote sensor at which you'll point the corresponding remote control.

2 Connect the CONTROL OUT jack of that component to the CONTROL IN jack of another Pioneer component.

Use a cable with a mono mini-plug on each end for the connection.




Continue the chain in the same way for as many components as you have.

Note

- 1 Remote operation may not be possible if direct light from a strong fluorescent lamp is shining on the IR receiver remote sensor window.
- Note that other manufacturers may not use the IR terminology. Refer to the manual that came with your component to check for IR compatibility.
- If using two remote controls (at the same time), the IR receiver's remote sensor takes priority over the remote sensor on the front panel.
- 2 If you want to control all your components using this receiver's remote control, see Setting the remote to control other components on page 73.
 - If you have connected a remote control to the **CONTROL IN** jack (using a mini-plug cable), you won't be able to control this unit using the remote sensor.

Switching components on and off using the 12 volt trigger

You can connect components in your system (such as a screen or projector) to this receiver so that they switch on or off using 12 volt triggers when you select an input function. However, you must specify which input functions switch on the trigger using the *The Input Setup menu* on page 43. Note that this will only work with components that have a standby mode.



• Connect the 12 V TRIGGER jack of this receiver to the 12 V trigger of another component.

Use a cable with a mono mini-plug on each end for the connection.

• The trigger maximum power is DC OUT 12 V/50 mA. After you've specified the input functions that will switch on the trigger, you'll be able to switch the component on or off just by pressing the input function(s) you've set on page 43.

Connecting a PC for Advanced MCACC output

When using Auto MCACC (page 78) or Acoustic Calibration EQ Professional (page 83) to calibrate the reverb characteristics of your listening room, the 3D graphs of the reverb characteristics in your listening room (before and after calibration) can be checked on a computer screen by connecting the receiver to the computer and using a special application to transfer the data. The various MCACC parameters can also be checked on the computer.

Use a commercially-available RS-232C cable to connect the RS-232C jack on your computer to the 9-pin RS-232C jack on the back panel of this receiver (the cable must be cross type, female–female).

The software to output the results is available from the support area of the Pioneer website (http://www.pioneerelectronics.com/PUSA/

Home+Entertainment+Custom+Install). Instructions for using the software are also available here. If you have any questions regarding, please contact the Customer Support Division of Pioneer.

Please make sure your system meets the following requirements:

- The computer must be a PC functioning with one of the following operating systems: Microsoft[®] Windows[®] Vista Home Basic/Home Premium/ Ultimate SP1, Windows[®] XP Professional/Home Edition SP3 or Windows[®] 2000 Professional SP4.
- The monitor must have a display resolution of 800 x 600 dots (SVGA) or greater.
- The computer must be equipped with at least one RS-232C port.²
- System must have internet access.

Microsoft[®], Windows[®]Vista, Windows[®]XP and Windows[®]2000 are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Note


¹ Triggered connections with up to two devices compatible with 12 volt triggers can be made with this receiver.

² Laptops and other computers not equipped with an RS-232C port can be connected via USB port using a commercially available USB to RS-232C converter cable (USB to serial converter cable). For instructions on COM port connections and settings, contact the manufacturer of your computer.

Connect your computer to the RS-232C jack on the rear panel of the receiver.

Make sure that the receiver and all connected components are switched off and disconnected from the power outlet when you do this.¹

Use a commercially-available cable to connect the RS-232C jack on your computer to the 9-pin RS-232C jack on this receiver. See the documentation provided with the Advanced MCACC application for more information.




Connecting an HDMI-equipped component to the front panel input

(VSX-23TXH only)

There is an HDMI input terminal on the front panel. High quality pictures can be viewed via the receiver simply by connecting an HDMI-equipped video camera with a single HDMI cable. HDMI-equipped components other than video cameras can also be connected to this terminal.

- Push down on the **PUSH OPEN** tab to access the front panel input.
- Select this input using INPUT SELECT (remote) or the INPUT SELECTOR dial (front panel) to select HDMI 4.




¹ The various parameters and the reverb characteristics data used for display on the computer are not cleared when the power is turned off (see *Output PC* on page 88).

Connecting a component to the front panel inputs

(VSX-21TXH only)

The front panel inputs comprise a composite video jack (**VIDEO**) and stereo analog audio inputs (**AUDIO L/R**). You can use these connections for any kind of audio/ video component, but they are especially convenient for portable equipment such as camcorders, video games and portable audio/video equipment.

- Push down on the PUSH OPEN tab to access the front panel inputs.
- Select these inputs using INPUT SELECT (remote) or the INPUT SELECTOR dial (front panel) to select VIDEO 2.




Connecting an iPod


This receiver has a dedicated iPod terminal that will allow you to control playback of audio content from your iPod using the controls of this receiver.

- Switch the receiver into standby then use the supplied iPod cable to connect your iPod to the iPod/ iPhone/USB terminal on the front panel of this receiver.
 - Push down on the PUSH OPEN tab to access the iPod/iPhone/USB terminal.
 - It is also possible to connect using the cable included with the iPod, but in this case it is not possible to view pictures via the receiver.
 - For the cable connection, refer to also the operating instructions for iPod.
 - For instructions on playing the iPod, see *Playing an iPod* on page 46.

VSX-23TXH:



VSX-21TXH:




Connecting a USB device


It is possible to playback files using the USB interface on the front of this receiver.

- Switch the receiver into standby then connect your USB device to the USB terminal on the front panel of this receiver.
 - Push down on the PUSH OPEN tab to access the USB terminal
 - For instructions on playing the USB device, see *Playing a USB device* on page 48.

VSX-23TXH:



VSX-21TXH:



Plugging in the receiver

Only plug in after you have connected all your components to this receiver, including the speakers.

- 1 Plug the supplied power cord into the AC IN socket on the back of the receiver.
- 2 Plug the other end into a power outlet.¹



CAUTION


- Handle the power cord by the plug part. Do not pull out the plug by tugging the cord, and never touch the power cord when your hands are wet, as this could cause a short circuit or electric shock. Do not place the unit, a piece of furniture, or other object on the power cord or pinch the cord in any other way. Never make a knot in the cord or tie it with other cables. The power cords should be routed so that they are not likely to be stepped on. A damaged power cord can cause a fire or give you an electric shock. Check the power cord once in a while. If you find it damaged, ask your nearest Pioneer authorized independent service company for a replacement.
- Do not use any power cord other than the one supplied with this unit.
- Do not use the supplied power cord for any purpose other than that described below.
- The receiver should be disconnected by removing the mains plug from the wall socket when not in regular use, e.g., when on vacation.
- Make sure the blue O STANDBY/ON light has gone out before unplugging.
- If you have connected speakers with a 6 Ω impedance, change the impedance setting before turning on the power.

¹ After this receiver is connected to an AC outlet, a 2 second to 10 second HDMI initialization process begins. You cannot carry out any operations during this process. The **HDMI** indicator in the front panel display blinks during this process, and you can turn on this receiver once it has stopped blinking. When you set the **KURO LINK** mode to **OFF**, you can skip this process. For details about the **KURO LINK** feature, see *KURO LINK* on page 63.

Chapter 4: Basic Setup

Switching the speaker impedance

We recommend using speakers of 8 Ω with this system, but it is possible to switch the impedance setting if you plan to use speakers with a 6 Ω impedance rating.



- 1 Switch the receiver into standby.
- 2 While holding down ENTER on the front panel, press \circlearrowleft STANDBY/ON.

The display shows **RESET** ◀ **NO** ▶.


Use TUNE +/- (or \uparrow/\downarrow on the remote control) to select SPEAKER $\blacktriangleleft 8\Omega \triangleright$, and then use PRESET +/- (or \leftarrow/\Rightarrow on the remote control) to select SPEAKER 8Ω or SPEAKER 6Ω .

- SPEAKER 8Ω Use this setting if your speakers are rated at 8 Ω or more.
- SPEAKER 6Ω Use this setting if your speakers are rated at $6\ \Omega$.

Changing the OSD display language (OSD Language)

The language used on the Graphical User Interface screen can be changed.

 The explanations in these operating instructions are for when English is selected for the GUI screen.



- **1 Switch on the receiver and your TV.** Use **O RECEIVER** to switch on.
- 2 Press RECEIVER on the remote control, then press HOME MENU.


A Graphical User Interface (GUI) screen appears on your TV. Use ↑/↓/←/→ and ENTER to navigate through the screens and select menu items. Press RETURN to exit the current menu.

- 3 Select 'System Setup' from the HOME MENU.
- 4 Select 'OSD Language' from the System Setup menu.





- 5 Select the desired language.
 - Enalish
 - French
 - German
 - Italian
 - Spanish
 - Dutch
 - Russian
- 6 Select 'OK' to change the language.



The setting is completed and the **System Setup** menu reappears automatically.

Automatically setting up for surround sound (Auto MCACC)

The Auto MCACC Setup measures the acoustic characteristics of your listening area, taking into account ambient noise, speaker connection and speaker size, and tests for both channel delay and channel level. After you have set up the microphone provided with your system, the receiver uses the information from a series of test tones to optimize the speaker settings and equalization for your particular room.

Make sure you do this before moving on to *Playing a source* on page 45.



Important

- Make sure the microphone and speakers are not moved during the Auto MCACC Setup.
- Using the Auto MCACC Setup will overwrite any existing settings for the MCACC preset you select.
- Before using the Auto MCACC Setup, the headphones should be disconnected and the iPod/ USB, XM or SIRIUS Radio function should not be selected as an input function.



A CAUTION

• The test tones used in the Auto MCACC Setup are output at high volume.




1 Switch on the receiver and your TV. Use & RECEIVER to switch on.

2 Connect the microphone to the MCACC SETUP MIC jack on the front panel.


 Push down on the PUSH OPEN tab to access the MCACC SETUP MIC jack.

Make sure there are no obstacles between the speakers and the microphone.

VSX-23TXH:




VSX-21TXH:



If you have a tripod, use it to place the microphone so that it's about ear level at your normal listening position. If you do not have a tripod, use some other object to install the microphone.¹

The Full Auto MCACC display appears once the microphone is connected.²



Note

1 It may not be possible to measure correctly if the microphone is placed on a table, sofa, etc.

- 2 You can't use the **HOME MENU** when the iPod/USB, XM or SIRIUS Radio input function is selected (in either the main or sub zone).
 - VSX-23TXH: When you set ZONE 2, ZONE 3 or ZONE 2&3 to ON (page 69), you can't use the HOME MENU.
 - VSX-21TXH: When you set ZONE 2 to ON (page 69), you can't use the HOME MENU.
 - If you leave the GUI screen for over five minutes, the screen saver will appear.

3 Select Surr Back System setting, 1 select an MCACC preset², press <u>RECEIVER</u> and then select START.³ Select Normal (Surround back), Speaker B, Front Bi-Amp or ZONE 2 for the Surr Back System setting according to connections to the surround back speaker terminals.

4 Follow the instructions on-screen.


Make sure the microphone is connected, and if you're using a subwoofer, make sure it is switched on and set to a comfortable volume level.


5 Wait for the test tones to finish, then confirm the speaker configuration in the GUI screen.

A progress report is displayed on-screen while the receiver outputs test tones to determine the speakers present in your setup. Try to be as quiet as possible while it's doing this. ⁴

If no operations are performed for 10 seconds while the speaker configuration check screen is being displayed, the Auto MCACC Setup will resume automatically. In this case, you don't need to select '**OK**' and press **ENTER** in step 6.

 With error messages (such as Too much ambient noise! or Check microphone.) select RETRY after checking for ambient noise (see Problems when using the Auto MCACC Setup below) and verifying the mic connection. If there doesn't seem to be a problem, you can simply select GO NEXT and continue.





The configuration shown on-screen should reflect the actual speakers you have.

- If you see an ERR message (or the speaker configuration displayed isn't correct), there may be a problem with the speaker connection.
 If selecting RETRY doesn't work, turn off the power and check the speaker connections. If there doesn't seem to be a problem, you can simply use ↑/↓ to select the speaker and ←/→ to change the setting
- If Reverse Phase is displayed, the speaker's wiring (+ and -) may be inverted. Check the speaker connections.⁵

and continue.

- If the connections were wrong, turn off the power, disconnect the power cord, then reconnect properly.
 After this, perform the Full Auto MCACC procedure again.
- If the connections were right, select GO NEXT and continue.

6 Make sure 'OK' is selected, then press ENTER.

A progress report is displayed on-screen while the receiver outputs more test tones to determine the optimum receiver settings for Channel Level, Speaker Distance, Standing Wave and Acoustic Cal EQ.

Again, try to be as quiet as possible while this is happening. It may take 3 to 10 minutes.

7 The Auto MCACC Setup procedure is completed and the Home Menu menu reappears automatically.⁶

Be sure to disconnect the microphone from this receiver upon completion of the Auto MCACC Setup.

The settings made in the Auto MCACC Setup should give you excellent surround sound from your system, but it is also possible to adjust these settings manually using *The Advanced MCACC menu* on page 77 or *The system and the other setup* on page 90.⁷

- 1 If you are planning on bi-amping your front speakers, or setting up a separate speaker system in another room, read through Surround back speaker setting on page 91 and make sure to connect your speakers as necessary before continuing to step 4.
- If you have THX-certified speakers, select **Return**, then select **Auto MCACC** for the THX speaker setting. See *Automatic MCACC* (Expert) on page 78 for more on this.
- 2 The six MCACC presets are used for storing surround sound settings for different listening positions. Simply choose an unused preset for now (you can rename it later in *Data Management* on page 88).
- 3 Note that correction curves are saved only when set to **SYMMETRY**. Select **Return**, then select **Auto MCACC** to save other correction curves (such as **ALL CH ADJ** and **FRONT ALIGN**). See *Automatic MCACC (Expert*) on page 78 for more on this.
- 4 Do not adjust the volume during the test tones. This may result in incorrect speaker settings.
- 5 If the speaker is not pointed to the microphone (listening position) or when using speakers that affect the phase (dipole speakers, reflective speakers, etc.), **Reverse Phase** may be displayed even if the speakers are properly connected.
- 6 You can also choose to view the settings from the MCACC Data Check screen. See Checking MCACC Data on page 86 for more on this.
- 7 Depending on the characteristics of your room, sometimes identical speakers with cone sizes of around 12 cm will end up with different size settings. You can correct the setting manually using the *Manual speaker setup* on page 90.
- The subwoofer distance setting may be farther than the actual distance from the listening position. This setting should be accurate (taking delay and room characteristics into account) and generally does not need to be changed.
- If Auto MCACC Setup measurement results are incorrect due to the interaction of the speakers and viewing environment, we recommend adjusting the settings manually.

Problems when using the Auto MCACC Setup

If the room environment is not optimal for the Auto MCACC Setup (too much background noise, echo off the walls, obstacles blocking the speakers from the microphone) the final settings may be incorrect. Check for household appliances (air conditioner, fridge, fan, etc.), that may be affecting the environment and switch them off if necessary. If there are any instructions showing in the front panel display, please follow them.

 Some older TVs may interfere with the operation of the microphone. If this seems to be happening, switch off the TV when doing the Auto MCACC Setup.

The Input Setup menu

You only need to make settings in the **Input Setup** menu if you didn't hook up your digital equipment according to the default settings (see *Input function default and possible settings* on page 44). In this case, you need to tell the receiver what equipment is hooked up to which terminal so the buttons on the remote control correspond to the components you've connected.




1 Switch on the receiver and your TV. Use & RECEIVER to switch on.

2 Press RECEIVER on the remote control, then press HOME MENU.

A Graphical User Interface (GUI) screen appears on your TV. Use $\uparrow / \downarrow / \leftarrow / \rightarrow$ and **ENTER** to navigate through the screens and select menu items. Press **RETURN** to confirm and exit the current menu.

- 3 Select 'System Setup' from the HOME MENU.
- 4 Select 'Input Setup' from the System Setup menu.





Select the input function that you want to set up.

The default names correspond with the names next to the terminals on the rear panel (such as **DVD** or **VIDEO**) which, in turn, correspond with the names on the remote control.

6 Select the input(s) to which you've connected your component.

For example, if your DVD player only has an optical output, you will need to change the **DVD** input function's **Digital In** setting from **COAX-1** (default) to the optical input you've connected it to. The numbering (**OPT-1** to **3**) corresponds with the numbers beside the inputs on the back of the receiver.


If your component is connected via a component video cable to an input terminal other than the default, you must tell the receiver which input terminal your component is connected to, or else you may see the S-Video or composite video signals instead of the component video signals.

1

7 When you're finished, proceed to the settings for other inputs.

There are three optional settings in addition to the assignment of the input jacks:

- Input Name You can choose to rename the input function for easier identification. Select Rename to do so, or Default to return to the system default.
- Input Skip When set to ON, that input is skipped when selecting the input using INPUT SELECT or the front panel INPUT SELECTOR dial. (DVD and other inputs can be still be selected directly with the input function buttons.)
- 12V Trigger1/2 After connecting a component to one of the 12 volt triggers (see Switching components on and off using the 12 volt trigger on page 36), select MAIN, ZONE 2, ZONE 3 (VSX-23TXH only) or OFF for the corresponding trigger setting to switch it on automatically along with the (main or sub) zone specified.



8 When you're finished, press RETURN. You will return to the **System Setup** menu.

¹ For high-definition video (using component video connections), or when digital video conversion is switched off (in *Setting the Video options* on page 68), you must connect your TV to this receiver using the same type of video cable as you used to connect your video component.

Input function default and possible settings

The terminals on the receiver generally correspond to the name of one of the input functions. If you have connected components to this receiver differently from (or in addition to) the defaults below, see The Input Setup menu on page 43 to tell the receiver how you've connected up. The dots (●) indicate possible assignments.

Innut function	Input Terminals		
Input function	Digital	HDMI	Component
DVD	COAX-1	●a	IN 1
BD		(BD) ^b	
TV/SAT	OPT-1	●a	•
DVR	OPT-2	● ^a	IN 2
VIDEO ^c /VIDEO 1 ^d	OPT-3	●a	•
VIDEO 2 ^d			
HDMI 1		(HDMI-1)	
HDMI 2		(HDMI-2)	
HDMI 3	(HDMI-3)		
HDMI 4 ^c	(HDMI-4) ^b		
iPod/USB			
XM			
CD	COAX-2		
CD-R/TAPE	•		
TUNER			
MULTI CH IN	_	●a	
SIRIUS	•		

a. With \mathbf{KURO} \mathbf{LINK} set to $\mathbf{ON},$ assignments cannot be made (see KURO LINK on page 63).

b.This assignment is fixed and cannot be changed.


c. VSX-23TXH only d. VSX-21TXH only

Chapter 5: Basic playback

Playing a source

SELECTOR dial.²

Here are the basic instructions for playing a source (such as a DVD disc) with your home theater system.



1 Switch on your system components and receiver. Start by switching on the playback component (for

example a DVD player), your TV¹ and subwoofer (if you have one), then the receiver (press & **RECEIVER**).

- Make sure the setup microphone is disconnected.
- 2 Select the input function you want to play. You can use the input function buttons on the remote control, **INPUT SELECT**, or the front panel **INPUT**
- 3 Press RECEIVER, then press AUTO/ALC/DIRECT (AUTO SURR/ALC/STREAM DIRECT) to select 'AUTO SURROUND' and start playback of the source.³

If you're playing a Dolby Digital or DTS surround sound DVD disc, you should hear surround sound. If you are playing a stereo source, you will only hear sound from the front left/right speakers in the default listening mode.

• See also Listening to your system on page 56 for information on different ways of listening to sources.

It is possible to check on the front panel display whether or not multi-channel playback is being performed properly.

When using a surround back speaker, DID+PLIIX MOVIE is displayed when playing Dolby Digital 5.1-channel signals, and DTS+Neo:6 is displayed when playing DTS 5.1-channel signals.

When not using a surround back speaker, **DOLBY DIGITAL** is displayed when playing Dolby Digital 5.1-channel signals.

If the display does not correspond to the input signal and listening mode, check the connections and settings.

4 Use the volume control to adjust the volume level. Turn down the volume of your TV so that all sound is coming from the speakers connected to this receiver.

Playing a source with HDMI connection

• Use INPUT SELECT to select the HDMI input you've connected to (for example, HDMI 1).

You can also perform the same operation by using the **INPUT SELECTOR** dial on the front panel or by pressing **HDMI** on the remote control repeatedly.

- Set the HDMI parameter in Setting the Audio options on page 66 to THROUGH if you want to hear HDMI audio output from your TV or flat panel TV (no sound will be heard from this receiver).
- If the video signal does not appear on your TV or flat panel TV, try adjusting the resolution settings on your component or display. Note that some components (such as video game units) have resolutions that may not be converted. In this case, use an analog video connection.
- You can't hear HDMI audio through this receiver's digital out jack.

- 1 Make sure that the TV's video input is set to this receiver (for example, if you connected this receiver to the **VIDEO** jacks on your TV, make sure that the **VIDEO** input is now selected).
- 2 If you need to manually switch the input signal type press SIGNAL SEL (page 61).
- 3 You may need to check the digital audio output settings on your DVD player or digital satellite receiver. It should be set to output Dolby Digital, DTS and 88.2 kHz / 96 kHz PCM (2 channel) audio, and if there is an MPEG audio option, set this to convert the MPEG audio to PCM.
 - Depending on your DVD player or source discs, you may only get digital 2 channel stereo and analog sound. In this case, the receiver must be set to a multichannel listening mode (see *Listening in surround sound* on page 56 if you need to do this) if you want multichannel surround sound.

Selecting the multichannel analog inputs

If you have connected a decoder or a DVD player as above, you must select the analog multichannel inputs for surround sound playback.1

1 Make sure you have set the playback source to the proper output setting.

For example, you might need to set your DVD player to output multichannel analog audio.

2 Use INPUT SELECT to select MULTI CH IN.

You can also use the INPUT SELECTOR dial on the front panel.

• Depending on the DVD player you're using, the analog output level of the subwoofer channel may be too low. In this case, the output level of the subwoofer can be increased by 10 dB in the Multi Ch In Setup in Other Setup. For details, see Multi Channel Input Setup on page 94.

Playing an iPod

This receiver has a dedicated iPod terminal that will allow you to control playback of audio content from your iPod using the controls of this receiver.2

Switch on the receiver and your TV.

See Connecting an iPod on page 38.


 It is also possible to operate the iPod on the iPod itself, without using the TV screen. For details, see Switching the iPod controls on page 47.

2 Press iPod USB on the remote control to switch the receiver to the iPod/USB.


Loading appears in the GUI screen while the receiver verifies the connection and retrieves data from the iPod.

When the display shows iPod top menu you're ready to play music from the iPod.3

Main Zone:



Sub Zone:



Playing back audio files stored on an iPod

To navigate songs on your iPod, you can take advantage of the GUI screen of your TV connected to this receiver. You can also control all operations for music in the front panel display of this receiver.

Finding what you want to play

When your iPod is connected to this receiver, you can browse songs stored on your iPod by playlist, artist name, album name, song name, genre or composer, similar to using your iPod directly.

Use \uparrow/\downarrow to select a category, then press ENTER to browse that category.

 To return to the previous level any time, press RETURN.

2 Use ↑/↓ to browse the selected category (e.g., albums).


Use ←/→ to move to previous/next levels.

- 1 When playback from the multichannel inputs is selected, only the volume and channel levels can be set.
 - You can't listen to your speaker B system during playback from the multichannel inputs.
- With MULTI CH IN inputs, it is possible to play pictures simultaneously. For details, see Multi Channel Input Setup on page 94.
- 2 This system is compatible with the audio and video of the iPod nano, iPod fifth generation (audio only), iPod classic, iPod touch and iPhone. However, some of the functions may be restricted for some models. The system is not compatible with the iPod shuffle.
- · Compatibility may vary depending on the software version of your iPod and iPhone. Please be sure to use the latest available software
- iPod and iPhone are licensed for reproduction of non-copyrighted materials or materials the user is legally permitted to reproduce.
- Features such as the equalizer cannot be controlled using this receiver, and we recommend switching the equalizer off before connecting.
- · Pioneer cannot under any circumstances accept responsibility for any direct or indirect loss arising from any inconvenience or loss of recorded material resulting from the iPod failure.
- . When listening to a track on the iPod in the main zone, it is possible to control the sub zone, but not to listen to a different track in the sub zone from the one playing in the main zone.
- 3 The controls of your iPod will be inoperable when connected to this receiver.
- 4 Note that characters that cannot be displayed on this receiver are displayed as #.
- This feature is not available for photos or video clips on your iPod. To display video clips, switch iPod operation to the iPod (see Switching the iPod controls on page 47).


Basic playback

3 Continue browsing until you arrive at what you want to play, then press ► to start playback.¹

• Main Zone:



· Sub Zone:



Navigation through categories on your iPod looks like this:

```
Playlists → Songs
Artists → Albums → Songs
Albums → Songs
Songs
Podcasts
Genres → Artists → Albums → Songs
Composers → Albums → Songs
Audiobooks
Shuffle Songs
```



 You can play all of the songs in a particular category by selecting the All item at the top of each category list. For example, you can play all the songs by a particular artist.

Basic playback controls

The following table shows the basic playback controls for your iPod. Press **iPod USB** to switch the remote control to the iPod/USB operation mode.

Button	What it does
>	Press to start playback.
	If you start playback when something other than a song is selected, all the songs that fall into that category will play.
II	Pauses/unpauses playback.
◄◄/▶▶	Press and hold during playback to start scanning.
	Press to skip to previous/next track.
(Press repeatedly to switch between Repeat One , Repeat All and Repeat Off .
><	Press repeatedly to switch between Shuffle Songs , Shuffle Albums and Shuffle Off .
DISP	Press repeatedly to change the song playback information displayed in the front panel display.
ENTER	When browsing, press to move to next levels. During playback, press to set the play and pause modes.
RETURN	When browsing, press to move to previous levels.
←/→	When browsing, press to move to previous/next levels.
1/↓	During Audiobook playback, press to switch the playback speed: Faster ↔ Normal ↔ Slower
TOP MENU	Press to return to the iPod top menu screen.

Switching the iPod controls²

You can switch over the iPod controls between the iPod and the receiver.

1 Press iPod CTRL to switch the iPod controls.³

This enables operation and display on your iPod, and this receiver's remote control and GUI screen become inactive.

2 Press iPod CTRL again to switch back to the receiver controls.

¹ If you're in the song category, you can also press ENTER to start playback.

² You cannot use this function, when an iPod of fifth generation or iPod nano of first generation is connected.

³ When this function is set, iPod images cannot be played on this receiver. However, when video clips recorded on the iPod are played, the playback picture is displayed.

Playing a USB device

It is possible to playback files¹ using the USB interface on the front of this receiver.

1 Switch on the receiver and your TV.

See Connecting a USB device on page 39.2

2 Press iPod USB on the remote control to switch the receiver to the iPod/USB.

Loading appears in the GUI screen as this receiver starts recognizing the USB device connected.³ When the display shows **USB Top** menu you're ready to playback from the USB device.

• Main Zone:



Sub Zone:



(Important

If an **Over Current** message lights in the display, the power requirements of the USB device are too high for this receiver. Try following the points below:


- Switch the receiver off, then on again.
- Reconnect the USB device with the receiver switched off.
- Use a dedicated AC adapter (supplied with the device) for USB power.

If this doesn't remedy the problem, it is likely your USB device is incompatible.

Playing back audio files stored on a USB memory device

The maximum number of levels that you can select in Step 2 (below) is 8. Also, you can display and play back up to 30 000 folders and files within a USB memory device.⁴

Use ↑/↓ to select 'Music' from the USB Top menu.




2 Use \uparrow/\downarrow to select a folder, then press ENTER to browse that folder.

 To return to the previous level any time, press RETURN.

3 Continue browsing until you arrive at what you want to play, then press ► to start playback.⁵

• Main Zone:



• Sub Zone:

Track Title

Track Title

Random On

Playing time

Artist Name

Album Title

Album Title

Track number

Playing time

Artist name

Album title

Track title or File name

- 1 Compatible USB devices include external magnetic hard drives, portable flash memory (particularly keydrives) and digital audio players (MP3 players) of format FAT16/32. It is not possible to connect this unit to a personal computer for USB playback.
- Pioneer cannot guarantee compatibility (operation and/or bus power) with all USB mass storage devices and assumes no responsibility for any loss of data that may occur when connected to this receiver.
- 2 Make sure the receiver is in standby when disconnecting the USB device.
- 3 When a USB memory device with a large capacity is connected, it may take some time to read all the contents.
- This receiver does not support a USB hub.
- 4 Note that characters that cannot be displayed on this receiver are displayed as #.
- 5 If the file selected cannot be played back, this receiver automatically skips to the next file playable.
 - When the file currently being played back has no title assigned to it, the file name is displayed in the GUI screen instead; when neither the album name nor the artist name is present, the row is displayed as a blank space.
 - Playback stops when the last song in a USB memory device is played back to the end.
 - Copyrighted audio files cannot be played back on this receiver.
- DRM-protected audio files cannot be played back on this receiver.

Basic playback controls

The following table shows the basic playback controls for your USB memory device. Press **iPod USB** to switch the remote control to the iPod/USB operation mode.

Button	What it does
>	Press to start playback.
II	Pauses/unpauses playback.
44/>>	Press and hold during playback to start scanning.
	Press to skip to previous/next track.
ightharpoons	Press repeatedly to switch between Repeat One , Repeat Folder , Repeat All and Repeat Off .
><	Press repeatedly to switch between $\bf Random\ On$ and $\bf Random\ Off.$
DISP	Press repeatedly to change the song playback information displayed in the front panel display.
ENTER	When browsing, press to move to next levels. During playback, press to set the play and pause modes.
RETURN	When browsing, press to move to previous levels.
←/→	When browsing, press to move to previous/next levels.
TOP MENU	Press to return to the USB Top menu.

Playing back photo files stored on a USB memory device¹

1 Use **↑**/**↓** to select 'Photos' from the USB Top menu.



2 Use ↑/↓ to select a folder, then press ENTER to browse that folder.

• To return to the previous level any time, press **RETURN**.

3 Continue browsing until you arrive at what you want to play, then press ▶ to start playback.²

The selected content is displayed in full screen and starts a slideshow.

After a slideshow launches, pressing **ENTER** toggles between play and pause (only when **Theme** on the Slideshow Setup is set to **Normal (OFF)**).

Basic playback controls


Button(s)	What it does
ENTER, ►	Starts displaying a photo and playing a slideshow.
RETURN, ←	Stops the Player and returns to the previous menu.
l◀◀ª	Displays the previous photo content.
▶ ▶I ^a	Displays the next photo content.
II ^a	Pauses/unpauses the slideshow.
DISP ^a	Displays the photo information.

 a. You can only use this button when **Theme** on the Slideshow Setup is set to **Normal (OFF)**

Slideshow Setup

Make the various settings for playing slideshows of photo files here.

1 Use ↑/↓ to select 'Slideshow Setup' from the USB Top menu.





2 Select the setting you want.

- Theme Add various effects to the slideshow.
- Interval Set the interval for switching the photos. This may not be available depending on the **Theme** setting.
- **BGM** Play music files stored on the USB device while displaying photos.
- Music Select Select the folder containing the music files to be played when BGM is set to ON.
- 3 When you're finished, press RETURN.

You will return to the **USB Top** menu.

¹ Photo files cannot be played in the sub zone.

² If the slideshow is left in the pause mode for five minutes, the list screen reappears.

Basic playback

About playable file formats

The USB function of this receiver supports the following file formats. Note that some file formats are not available for playback although they are listed as playable file formats.

Music files

Category	Extension	Stream		
MP3 ^a	.mp3	MPEG-1, 2, 2.5 Audio Layer-3	Sampling frequency	8 kHz to 48 kHz
			Quantization bitrate	16 bit
			Channel	2 ch
			Bitrate	8 kbps to 320 kbps
			VBR/CBR	Supported/Supported
WAV	.wav	LPCM	Sampling frequency	32 kHz, 44.1 kHz, 48 kHz
			Quantization bitrate	8 bit, 16 bit
			Channel	2 ch, Monaural
WMA	.wma	WMA8/9 ^b	Sampling frequency	8 kHz to 48 kHz
			Quantization bitrate	16 bit
			Channel	2 ch
			Bitrate	8 kbps to 320 kbps
			VBR/CBR	Supported/Supported

a. "MPEG Layer-3 audio decoding technology licensed from Fraunhofer IIS and Thomson multimedia."

Photo files


Category	Extension		
JPEG	.jpg .jpeg .jpe	Format	Meeting the following conditions: • Baseline JPEG format (including files recorded in Exif/DCF format) • Y:Cb:Cr - 4:4:4 ^a , 4:2:2 or 4:2:0
	.jif .jfif	Resolution	30 to 8192 pixels vertical, 40 to 8192 pixels horizontal

a. The maximum playable resolution for 4:4:4 is 5120 x 8192 pixels.

b. Files encoded using Windows Media Codec 9 may be playable but some parts of the specification are not supported; specifically, Pro, Lossless, Voice.

Listening to the radio

The following steps show you how to tune in to FM and AM radio broadcasts using the automatic (search) and manual (step) tuning functions. If you already know the frequency of the station you want, see *Tuning directly to a station* below. Once you are tuned to a station you can memorize the frequency for recall later—see *Saving station presets* below for more on how to do this.



- 1 Press TUNER to select the tuner.
- 2 Use BAND to change the band (FM or AM), if necessary.

Each press switches the band between FM and AM.

3 Tune to a station.

There are three ways to do this:

Automatic tuning – To search for stations in the currently selected band, press and hold TUNE ↑/↓ for about a second. The receiver will start searching for the next station, stopping when it has found one. Repeat to search for other stations.

Manual tuning – To change the frequency one step at a time, press **TUNE** \uparrow / \downarrow .

High speed tuning – Press and hold **TUNE** ↑/↓ for high speed tuning. Release the button at the frequency you want.

Improving FM sound

If the **TUNED** or **STEREO** indicator doesn't light when tuning to an FM station because the signal is weak, press **MPX** to switch the receiver into mono reception mode. This should improve the sound quality and allow you to enjoy the broadcast.

Using Neural THX

This feature uses Neural Surround™, THX® technologies to achieve optimal surround sound from FM radio.

 While listening to FM radio, press AUTO/ALC/ DIRECT for Neural THX listening.

See About Neural – THX Surround on page 110 for more on this.

The **Neural THX** mode can be selected also with **STANDARD**.

Tuning directly to a station

Sometimes, you'll already know the frequency of the station you want to listen to. In this case, you can simply enter the frequency directly using the number buttons on the remote control.

- 1 Press TUNER to select the tuner.
- 2 Use BAND to change the band (FM or AM), if necessary.

Each press switches the band between FM and AM.

- 3 Press D.ACCESS (Direct Access).
- 4 Use the number buttons to enter the frequency of the radio station.

For example, to tune to **106.00** (FM), press **1**, **0**, **6**, **0**, **0**. If you make a mistake halfway through, press **D.ACCESS** twice to cancel the frequency and start over.

Saving station presets

If you often listen to a particular radio station, it's convenient to have the receiver store the frequency for easy recall whenever you want to listen to that station. This saves the effort of manually tuning in each time. This receiver can memorize up to 63 stations, stored in seven banks, or classes (A to G) of 9 stations each. When saving an FM frequency, the **MPX** setting (see above) is also stored.

1 Tune to a station you want to memorize. See *Listening to the radio* above for more on this.

See Listerling to the radio above for more of

2 Press T.EDIT (TUNER EDIT).

The display shows **PRESET MEMORY**, then a blinking memory class.

3 Press CLASS to select one of the seven classes, then press PRESET ←/⇒ to select the station preset you want.

You can also use the number buttons to select a station preset.

4 Press ENTER.

After pressing **ENTER**, the preset class and number stop blinking and the receiver stores the station.

Naming station presets

For easier identification, you can name your station presets.

1 Choose the station preset you want to name.

See Listening to station presets below for how to do this.

2 Press T.EDIT (TUNER EDIT).

The display shows **PRESET NAME**, then a blinking cursor at the first character position.

3 Input the name you want.

Choose from the following characters for a name up to eight characters long.

ABCDEFGHIJKLMNOPQRSTUVWXYZ abcdefghijklmnopqrstuvwxyz 0123456789

!"#\$%&'()*+,-./:;<=>?@[\]^_{|}~[space]

Use \uparrow/\downarrow to select a character, \leftarrow/\rightarrow to set the position, and **ENTER** to confirm your selection.



- To erase a station name, simply repeat steps 1 to 3 and input eight spaces instead of a name.
- Once you have named a station preset, you can press DISP when listening to a station to switch the display between name and frequency.

Listening to station presets

You will need to have some presets stored to do this. See *Saving station presets* on page 51 if you haven't done this already.

- Press TUNER to select the tuner.
- 2 Press CLASS to select the class in which the station is stored.

Press repeatedly to cycle through classes A to G.

- 3 Press PRESET ←/→ to select the station preset you want.
 - You can also use the number buttons on the remote control to recall the station preset.

Listening to Satellite Radio

To listen to Satellite Radio, you'll need to connect either a SIRIUS or XM Satellite Radio tuner (sold separately) to your satellite-ready receiver. Satellite Radio is available to residents of the US (except Alaska and Hawaii) and Canada

Satellite Radio delivers a variety of commercial-free music from categories ranging from Pop, Rock, Country, R&B, Dance, Jazz, Classical and many more plus coverage of all the top professional and college sports including play by play games from select leagues and teams. Additional programming includes expert sports talk, uncensored entertainment, comedy, family programming, local traffic and weather and news from your most trusted sources.

Whether you purchase a SIRIUS or XM tuner, you'll need to activate and subscribe to begin enjoying the service.

Easy to follow installation and setup instructions are provided with the satellite tuners. Whichever service you choose, there are a variety of programming packages available, including the option of adding "The Best of SIRIUS" programming to your XM tuner or "The Best of XM" programming to your SIRIUS tuner, enabling you to enjoy the most popular programming among both services. The "Best of" packages are not available to SIRIUS or XM Canada subscribers at this time.

Family friendly packages are also available to restrict channels featuring content that may be inappropriate for children.

To subscribe to XM, U.S. customers should visit xmradio.com or call 1-800-XMRADIO (1-800-967-2346); Canadian customers should visit xmradio.ca or call XM Listener Care at 1-877-GETXMSR (1-877-438-9677).

To subscribe to SIRIUS, U.S. and Canadian customers can call 1-888-539-SIRI (1-888-539-7474) or visit sirius.com (US) or siriuscanada.ca (Canada).

Listening to XM Radio

For more details, see About SIRIUS and XM on page 111.

Press XM to switch to the XM RADIO input.


For best reception, you may need to move the XM Mini-Tuner antenna near a window (the southernmost window should produce the best results).

 If after pressing XM the display shows Check XM Tuner or Check Antenna, try disconnecting the receiver and tuner connections, and then plugging them back in.¹


Basic playback

After connecting, you will be able to use this receiver to select channels and navigate categories using the GUI screen.¹ The information displayed is as follows:

• Main Zone:




• Sub Zone:




Selecting channels and browsing by genre

From the XM Channel Guide, you can browse XM Radio channels in the order that they appear, or you can narrow your channel search by genre.²

• Main Zone:



• Sub Zone:



Press ↑/↓ to enter the XM Channel Guide, then navigate through the channels one at time with ↑/↓, then press ENTER to listen to the XM radio broadcast.

- To browse by genre, first press CATEGORY, use ↑/↓
 to select a genre, then press ENTER.
- To cancel and exit any time, press **RETURN**.



- You can select channels directly by pressing
 D.ACCESS, then the three-digit channel number.
- You can press DISP to change XM Radio information in the front panel display.
- The currently selected channel is automatically chosen (without pressing **ENTER**) after 5 seconds.

Using XM HD Surround

XM HD Surround uses Neural Surround™, THX® technologies to achieve optimal surround sound from XM radio. XM HD Surround Sound is available on select XM channels only.

• While listening to XM Radio, press AUTO/ALC/ DIRECT for XM HD Surround listening.

See About Neural – THX Surround on page 110 for more on this.

XM HD Surround can be selected also with **STANDARD**.

Saving channel presets

This receiver can memorize up to 63 channels, stored in seven banks, or classes (A to G) of 9 channels each.³

1 Select the channel you want to memorize. See *Selecting channels and browsing by genre* above.

2 Press T.EDIT.

The display shows a blinking memory class.

3 Press CLASS to select one of the seven classes, then press ←/→ to select the channel preset you want.

You can also use the number buttons to select a preset.

• The default for all presets is XM1.

4 Press ENTER.

After pressing **ENTER**, the preset class and number stop blinking and the receiver stores the XM channel.



 You can also press **MEMORY** during reception display to save the information of up to five songs. See *Using the XM Menu* below to recall this information.

¹ It's easiest if you have your TV switched on to take advantage of the GUI screens. You can, however, use just the front panel display to do everything if you prefer.

² Select **0** (**RADIO ID**) from the GUI screen to check the Radio ID of the XM Mini-Tuner.

³ You can reset the channel presets and memory in Resetting the system on page 72.

Listening to channel presets

1 Press CLASS to select the class in which the channel is stored.

Press repeatedly to cycle through classes A to G.

- 2 Press ←/⇒ to select the channel preset you want.
 - You can also use the number buttons on the remote control to recall the channel preset.

Using the XM Menu

The XM Menu provides additional XM Radio features.¹

- 1 Press TOP MENU.
- 2 Use ↑/↓ to select a menu item, then press ENTER. Choose from the following menu items:
 - Channel Skip/Add Use ↑/↓ and ENTER to select channels you would like to remove/restore from/to the channel guide.
 - Antenna Aiming Check the strength of satellite and terrestrial reception.
 - Memory Recall Use ↑/↓ to browse your saved song information (see *Tip* on page 55).
- 3 When you're finished press TOP MENU to return to the reception display.

Listening to SIRIUS Radio

For more details, see About SIRIUS and XM on page 111.


Press SIRIUS to switch to the SIRIUS input.

For best reception, you may need to move the SiriusConnect™ tuner antenna near a window (refer to the manual for the SiriusConnect™ Home tuner for antenna placement recommendations).²


If after pressing SIRIUS the display shows Antenna Error, try disconnecting the antenna and reconnecting.³ If the display shows Check Sirius Tuner, check the connection of the AC adapter and this receiver to the SiriusConnect™ tuner.

After connecting, you will be able to use this receiver to select channels and navigate categories using the GUI screen. 4 The information displayed is as follows:

Main Zone:



· Sub Zone:



Note

1 You can reset the Channel Skip/Add settings in Resetting the system on page 72.


- 2 In order to activate your radio subscription, you will need the SIRIUS ID (SID) which uniquely identifies your tuner. The SID may be found on a sticker located on the packaging, or on the bottom of the tuner itself. The label will have a printed 12-digit SID number. When you have located the SID, write it down in the space provided near the end of this manual. Contact SIRIUS on the internet at: https://activate.siriusradio.com
 - Follow the prompts to activate your subscription, or you can also call SIRIUS toll-free at 1-888-539-SIRIUS (1-888-539-7474).
 - Select 0 (SIRIUS ID) from the GUI screen to check the Radio ID of the SiriusConnect™ tuner (see Selecting channels and browsing by genre below).
- 3 You can check the strength of reception in Using the SIRIUS Menu on page 55.
- 4 It's easiest if you have your TV switched on to take advantage of the GUI screens. You can, however, use just the front panel display to do everything if you prefer.

Basic playback

Selecting channels and browsing by genre

From the SIRIUS Channel Guide, you can browse SIRIUS Radio channels in the order that they appear, or you can narrow your channel search by genre.

· Main Zone:



· Sub Zone:



- Press ↑/↓ to enter the SIRIUS Channel Guide, then navigate through the channels one at time with ↑/↓, then press ENTER to listen to the SIRIUS radio broadcast.
 - To browse by genre, first press CATEGORY, use ↑/↓
 to select a genre, then press ENTER.
 - To cancel and exit any time, press RETURN.



- You can select channels directly by pressing
 D.ACCESS, then the three-digit channel number.
- You can press **DISP** to change SIRIUS Radio information in the front panel display.
- The currently selected channel is automatically chosen (without pressing ENTER) after 10 seconds.

Saving channel presets

This receiver can memorize up to 63 channels, stored in seven banks, or classes (A to G) of 9 channels each.

1 Select the channel you want to memorize.

See Selecting channels and browsing by genre above.

2 Press T.EDIT.

The display shows a blinking memory class.

3 Press CLASS to select one of the seven classes, then press ←/→ to select the channel preset you want.

You can also use the number buttons to select a preset.

4 Press ENTER.

After pressing **ENTER**, the preset class and number stop blinking and the receiver stores the SIRIUS channel.



 You can also press **MEMORY** during reception display to save the information of up to five songs. See *Using the SIRIUS Menu* below to recall this information.¹

Listening to channel presets

1 Press CLASS to select the class in which the channel is stored.

Press repeatedly to cycle through classes A to G.

- 2 Press ←/⇒ to select the channel preset you want.
 - You can also use the number buttons on the remote control to recall the channel preset.

Using the SIRIUS Menu

The SIRIUS Menu provides additional SIRIUS Radio features

- 1 Press TOP MENU.
- 2 Use ↑/↓ to select a menu item, then press ENTER. Choose from the following menu items:
 - Channel Skip/Add Use ↑/↓ and ENTER to select channels you would like to remove/restore from/to the channel guide.
 - Parental Lock Use ↑/↓ and ENTER to select channels you would like to place under parental lock. Channels put under parental lock are not displayed in the Channel Guide, but may be accessed by directly inputting their channel number and providing the parental lock password.
 - Antenna Aiming Check the strength of satellite and terrestrial reception.
 - Memory Recall Use ↑/↓ to browse your saved song information (see *Tip* above).
 - Password Set Set the parental lock password.
- 3 When you're finished press TOP MENU to return to the reception display.

Chapter 6:

Listening to your system

Important

• The listening modes and many features described in this section may not be available depending on the current source, settings and status of the receiver.

• When an **ALC** is selected, the effect level can be adjusted using the **EFFECT** parameter in Setting the Audio options on page 66.

Auto playback

There are many ways to listen back to sources using this receiver, but for the simplest, most direct listening option is the Auto Surround feature. The receiver automatically detects what kind of source you're playing and selects multichannel or stereo playback as necessary.



While listening to a source, press RECEIVER, then press AUTO/ALC/DIRECT (AUTO SURR/ALC/STREAM DIRECT)² for auto playback of a source.

AUTO SURROUND shows briefly in the display before showing the decoding or playback format. Check the digital format indicators in the front panel display to see how the source is being processed.

- If the source is Dolby Digital, DTS, or Dolby Surround encoded, the proper decoding format will automatically be selected and shows in the display.
- When listening to the FM radio, the Neural THX feature is selected automatically (see Using Neural THX on page 51 for more on this).

ALC - In the Auto level control (ALC) mode, this receiver equalizes playback sound levels.

Listening in surround sound

Using this receiver, you can listen to any source in surround sound. However, the options available will depend on your speaker setup and the type of source you're listening to.

If you connected surround back speakers, see also Using surround back channel processing on page 59.

Standard surround sound

The following modes provide basic surround sound for stereo and multichannel sources.3



While listening to a source, press RECEIVER, then press STANDARD (STANDARD SURROUND).4

If necessary, press repeatedly to select a listening mode.

• If the source is Dolby Digital, DTS, or Dolby Surround encoded, the proper decoding format will automatically be selected and shows in the display.

With two channel sources, you can select from:5

• DD Pro Logic IIx MOVIE – Up to 7.1 channel sound, especially suited to movie sources

- 1 Stereo surround (matrix) formats are decoded accordingly using Neo:6 CINEMA or DD Pro Logic IIx MOVIE (see Listening in surround sound above for more on these decoding formats).
- The Auto Surround feature is canceled if you connect headphones.
- 2 For more options using this button, see Using Stream Direct on page 59.
- The AUTO SURROUND mode cannot be selected in the following cases:
- When MULTI CH IN input is selected.
- When the HDMI audio output parameter is set to THROUGH in Setting the Audio options on page 66.
- 3 In modes that give 6.1 channel sound, the same signal is heard from both surround back speakers.
- 4 The STANDARD listening mode cannot be selected in the following cases:
 - When headphones are plugged in.
 - When MULTI CH IN input is selected.
- When the HDMI audio output parameter is set to THROUGH in Setting the Audio options on page 66.
- 5 If surround back channel processing (page 59) is switched OFF, or the surround back speakers are set to NO (this happens automatically if the Surround back speaker setting on page 91 is set to anything but Normal), DD Pro Logic IIx becomes DD Pro Logic II (5.1 channel sound).

Listening to your system

- DD Pro Logic IIx MUSIC Up to 7.1 channel sound, especially suited to music sources¹
- DD Pro Logic IIx GAME Up to 7.1 channel sound, especially suited to video games
- DD Pro Logic 4.1 channel surround sound (sound from the surround speakers is mono)
- Neo:6 CINEMA 7.1 channel sound, especially suited to movie sources
- Neo:6 MUSIC 7.1 channel sound, especially suited to music sources²
- Neural THX Up to 7.1 channel sound, especially suited to music sources³

With multichannel sources, if you have connected surround back speaker(s) and have selected **SBch ON**, you can select (according to format):

- DD Pro Logic IIx MOVIE See above (only available when you're using two surround back speakers)
- DI Pro Logic IIx MUSIC See above
- Dolby Digital EX Creates surround back channel sound for 5.1 channel sources and provides pure decoding for 6.1 channel sources (like Dolby Digital Surround EX)
- DTS-ES Allows you to hear 6.1 channel playback with DTS-ES encoded sources
- DTS Neo:6 Allows you to hear 6.1 channel playback with DTS encoded sources

Using the Home THX modes

THX and Home THX are technical standards created by THX Ltd. for cinema and home theater sound. Home THX is designed to make home theater audio sound more like what you hear in a cinema.

Different THX options will be available depending on the source and the setting for surround back channel processing (see *Using surround back channel processing* on page 59 for more on this).



 Press <u>RECEIVER</u>, then press THX (HOME THX) to select a listening mode.⁴

With two channel sources, press **THX** repeatedly to select a matrix-decoding process for the **THX CINEMA** mode (see *Using surround back channel processing* on page 59 for an explanation of each process):

- □□ Pro Logic IIx MOVIE+THX CINEMA
- □□ Pro Logic+THX CINEMA
- Neo:6 CINEMA+THX CINEMA
- □ Pro Logic IIx MUSIC+THX MUSIC
- Neo:6 MUSIC+THX MUSIC
- □ Pro Logic IIx GAME+THX GAMES
- THX Select2 GAMES⁵

With multichannel sources, press **THX (HOME THX)** repeatedly to select from:⁶

- **THX Surround EX** Allows you to hear 6.1 or 7.1 channel playback with 5.1 channel sources⁷
- DD Pro Logic IIx MOVIE+THX CINEMA⁵
- THX Select2 CINEMA⁵ Allows you to hear 7.1 channel playback with 5.1 channel sources
- □ Pro Logic IIx MUSIC+THX MUSIC
- THX Select2 MUSIC⁵—This mode is suited not only for sources recorded in Dolby Digital and DTS, but also to all multi-channel music sources (DVD-Audio, etc.).
- **THX Select2 GAMES**⁵ This mode is suited to playing the sound of games.

- 1 When listening to 2-channel sources in Dolby Pro Logic IIx Music mode, there are three further parameters you can adjust: **C.WIDTH**, **DIMENSION** and **PANORAMA**. See *Setting the Audio options* on page 66 to adjust them.
- 2 When listening to 2-channel sources in Neo:6 Cinema or Neo:6 Music mode, you can also adjust the center image effect (see Setting the Audio options on page 66).
- 3 Neural THX can be selected for 2-channel signals for which the input signal is PCM (48 kHz or less), Dolby Digital, DTS or analog 2-channel sources.
- 4 When the function is set to TUNER, iPod/USB, PHONO, XM or SIRIUS, it is not possible to select DD Pro Logic IIx GAME+THX GAMES or THX Select2 GAME.
 - The THX mode cannot be selected in the following cases:
 - When headphones are plugged in.
- When MULTI CH IN input is selected.
- When the **HDMI** audio output parameter is set to **THROUGH** in Setting the Audio options on page 66.
- When playing an SACD, Da Pro Logic IIx MUSIC+THX MUSIC, Neo:6 MUSIC+THX MUSIC and THX Select2 MUSIC can be selected. 5 Unavailable with only one surround back speaker connected.
- 6 THX CINEMA, THX MUSIC and THX GAMES can be selected when surround back processing is set to SBch OFF, when there is no surround back speaker, or when playing 6.1- and 7.1-channel sources.
- THX CINEMA, THX MUSIC and THX GAMES can be selected when there are only front speakers and THX GAMES cannot be selected when the function is set to TUNER, iPod/USB, PHONO, XM or SIRIUS.
- 7 When playing DTS-encoded sources, Neo:6 CINEMA+THX CINEMA can be selected, not THX Surround EX.

Using the Advanced surround effects

The Advanced surround effects can be used for a variety of additional surround sound effects. Most Advanced Surround modes are designed to be used with film soundtracks, but some modes are also suited for music sources. Try different settings with various soundtracks to see which you like.



- Press RECEIVER, then press ADV SURR (ADVANCED SURROUND) repeatedly to select a listening mode.1
 - ACTION Designed for action movies with dynamic soundtracks
 - DRAMA Designed for movies with lots of dialog
 - SCI-FI Designed for science fiction with lots of special effects
 - MONO FILM Creates surround sound from mono soundtracks
 - ENT.SHOW Suitable for musical sources
 - EXPANDED Creates an extra wide stereo field²
 - TV SURROUND Provides surround sound for both mono and stereo TV sources
 - ADVANCED GAME Suitable for video games
 - **SPORTS** Suitable for sports programs
 - **CLASSICAL** Gives a large concert hall-type sound
 - ROCK/POP Creates a live concert sound for rock and/or pop music
 - UNPLUGGED Suitable for acoustic music sources
 - EXT.STEREO Gives multichannel sound to a stereo source, using all of your speakers
 - **PHONES SURR** When listening through headphones, you can still get the effect of overall surround.



 When an Advanced Surround listening mode is selected, the effect level can be adjusted using the **EFFECT** parameter in *Setting the Audio options* on page 66.

Listening in stereo

When you select **STEREO**, you will hear the source through just the front left and right speakers (and possibly your subwoofer depending on your speaker settings). Dolby Digital, DTS and WMA9 Pro multichannel sources are downmixed to stereo.



While listening to a source, press RECEIVER, then press STEREO for stereo playback.3

Press repeatedly to switch between:

- STEREO The audio is heard with your surround settings and you can still use the Midnight, Loudness, and Tone functions.
- F.S.SURR FOCUS See Using Front Stage Surround Advance below for more on this.
- F.S.SURR WIDE See Using Front Stage Surround Advance below for more on this.

Using Front Stage Surround Advance


The Front Stage Surround Advance function allows you to create natural surround sound effects using just the front speakers and the subwoofer.



- 1 Depending on the source and the sound mode you have selected, you may not get sound from the surround back speakers in your setup. For more on this, refer to Using surround back channel processing on page 59.
- If you press ADV SURR when the headphones are connected, the PHONES SURR mode will automatically be selected.
- 2 Use with Dolby Pro Logic for a stereo surround effect (stereo field is wider than Standard modes with Dolby Digital sources).
- 3 The STEREO, F.S.SURR FOCUS and F.S.S WIDE mode cannot be selected in the following cases:
- When **MULTI CH IN** input is selected.
- When the HDMI audio output parameter is set to THROUGH in Setting the Audio options on page 66.
- · When headphones are plugged in, the F.S.SURR FOCUS and F.S.SURR WIDE are cannot be selected.

Listening to your system

- While listening to a source, press RECEIVER, then press STEREO to select Front Stage Surround Advance modes.
 - **STEREO** See *Listening in stereo* above for more on this.
 - F.S.SURR FOCUS Use to provide a rich surround sound effect directed to the center of where the front left and right speakers sound projection area converges.
 - F.S.SURR WIDE Use to provide a surround sound effect to a wider area than FOCUS mode. 1



Using Stream Direct

Use the Stream Direct modes when you want to hear the truest possible reproduction of a source. All unnecessary signal processing is bypassed, and you're left with the pure analog or digital sound source.



• While listening to a source, press <u>RECEIVER</u>, then press AUTO/ALC/DIRECT (AUTO SURR/ALC/STREAM DIRECT) to select the mode you want.²

Check the digital format indicators in the front panel display to see how the source is being processed.

- AUTO SURROUND See Auto playback on page 56.
- ALC Listening in Auto level control mode (page 56).
- DIRECT Sources are heard according to the settings made in the Surround Setup (speaker setting, channel level, speaker distance, acoustic calibration EQ, and X-curve), as well as with dual mono, the input attenuator, and any sound delay settings. You will hear sources according to the number of channels in the signal.


 PURE DIRECT – Analog sources are heard without any digital processing. No sound is output from the Speaker B in this mode.

Using surround back channel processing

Default setting: SBch ON

You can have the receiver automatically use 6.1 or 7.1 decoding for 6.1 encoded sources (for example, Dolby Digital EX or DTS-ES), or you can choose to always use 6.1 or 7.1 decoding (for example, with 5.1 encoded material). With 5.1 encoded sources, a surround back channel will be generated, but the material may sound better in the 5.1 format for which it was originally encoded (in which case, you can simply switch surround back channel processing off).

 With a 7.1-channel surround system, audio signals that have undergone matrix decoding processing through surround back channel processing to which the Up Mix function is added are output from the surround back speakers.



• Press RECEIVER, then press SBch repeatedly to cycle the surround back channel options.

Each press cycles through the options as follows:

- **SBch ON** Matrix decoding processing for generating the surround back component from the surround component is turned on.
- SBch AUTO Matrix decoding processing for generating the surround back component from the surround component is switched automatically. Matrix decoding processing is only performed when surround back channel signals are detected in the input signals.
- **SBch OFF** Matrix decoding processing for generating the surround back component from the surround component is turned off.

Note

1 When using **F.S.SURR WIDE**, a better effect can be obtained if the **Full Auto MCACC** procedure under **Advanced MCACC** is performed. For more on this, refer to *Automatically setting up for surround sound (Auto MCACC)* on page 41.

2 When headphones are plugged in, the AUTO SURROUND and DIRECT are cannot be selected.

Using the Virtual Surround Back mode

· Default setting: OFF

When you're not using surround back speakers, selecting this mode allows you to hear a virtual surround back channel through your surround speakers. You can choose to listen to sources with no surround back channel information, or if the material sounds better in the format (for example, 5.1) for which it was originally encoded, you can have the receiver only apply this effect to 6.1 encoded sources like Dolby Digital EX or DTS-ES.¹

Press SBch repeatedly to cycle the virtual surround back channel options.

Each press cycles through the options as follows:


- VirtualSB ON Virtual Surround Back is always used (for example, on 5.1 encoded material)
- VirtualSB AUTO Virtual Surround Back is automatically applied to 6.1 encoded sources (for example, Dolby Digital EX or DTS-ES)
- VirtualSB OFF Virtual Surround Back mode is switched off


Setting the Up Mix function

In a 7.1-channel surround system with surround speakers placed directly at the sides of the listening position, the surround sound of 5.1-channel sources is heard from the side. The Up Mix function mixes the sound of the surround speakers with the surround back speakers so that the surround sound is heard from diagonally to the rear as it should be.²

 Using the Up Mix function is effective when the speakers in the 7.1-channel surround system are set up as recommended in the example on page 18. Depending on the positions of the speakers and the sound source, in some cases it may not be possible to achieve good results. In this case, set the setting to OFF

R





- 1 Switch the receiver into standby.
- 2 While holding down ENTER on the front panel, press & STANDBY/ON.

The display shows **RESET** \triangleleft **NO** \triangleright .

Use **TUNE** +/- (or ↑/↓ on the remote control) to select **UP MIX** ◀ **ON** ▶, and then use **PRESET** +/- (or ←/→ on the remote control) to select **ON** or **OFF**.

3 Press ENTER to confirm.

• When set to **ON**, the **UP MIX** indicator on the front panel lights.


🕢 Note

- 1 You can't use the Virtual Surround Back mode when the headphones are connected to this receiver or when any of the stereo, Front Stage Surround Advance or Stream Direct mode is selected.
- You can only use the Virtual Surround Back mode if the surround speakers are on and the SB setting is set to NO or if Front Bi-Amp, Speaker B or ZONE 2 is selected at Surr Back System.
- The Virtual Surround Back mode cannot be applied to sources that do not have surround channel information.
- 2 Set to **ON** regardless of this setting when playing DTS-HD signals.
- May automatically be set to OFF even when set to ON, depending on the input signal and listening mode.

Selecting MCACC presets

• Default setting: MEMORY 1

If you have calibrated your system for different listening positions¹, you can switch between settings to suit the kind of source you're listening to and where you're sitting (for example, watching movies from a sofa, or playing a video game close to the TV).




• While listening to a source, press $\overline{\text{RECEIVER}}$, then press MCACC.

Press repeatedly to select one of the six MCACC presets². See *Data Management* on page 88 to check and manage your current settings.

Choosing the input signal

On this receiver, it is possible to switch the input signals for the different inputs as described below.³



 Press <u>RECEIVER</u>, then press <u>SIGNAL</u> <u>SEL</u> to select the input signal corresponding to the source component.

Each press cycles through the options as follows:

- AUTO The receiver selects the first available signal in the following order: HDMI; DIGITAL; ANALOG.
- **ANALOG** Selects an analog signal.
- **DIGITAL** Selects an optical or coaxial digital signal.
- **HDMI** Selects an HDMI signal.⁴

 PCM – For PCM input signals.⁵ The receiver selects the first available signal in the following order: HDMI; DIGITAL.

When set to **DIGITAL**, **HDMI** or **AUTO** (only selected **DIGITAL** or **HDMI**), the indicators light according to the signal being decoded, as follows:

- DID DIGITAL lights with Dolby Digital decoding.
- DO DIGITAL PLUS lights with Dolby Digital Plus decoding.
- DI TrueHD lights with Dolby TrueHD decoding.
- DTS lights with DTS decoding.
- DTS HD lights with DTS-HD decoding.
- MSTR lights with DTS-HD Master Audio decoding.
- 96/24 lights with DTS 96/24 decoding.
- **WMA9 Pro** lights to indicate that a WMA9 Pro signal is being decoded.
- HDMI is not assigned by default. To select an HDMI signal, conduct the input setup procedure (see *The* Input Setup menu on page 43).

Better sound using Phase Control

This receiver's Phase Control feature uses phase correction measures to make sure your sound source arrives at the listening position in phase, preventing unwanted distortion and/or coloring of the sound.

During multichannel playback, LFE (Low-Frequency Effects) signals as well as low-frequency signals in each channel are assigned to the subwoofer or the other most appropriate speaker. At least in theory, however, this type of processing involves a group delay that varies with frequency, resulting in phase distortion where the low-frequency sound is delayed or muffled by the conflict with other channels. With the Phase Control mode switched on, this receiver can reproduce powerful bass sound without deteriorating the quality of the original sound (see illustration below).

Note


- 1 Different presets might also have separate calibration settings for the same listening position, depending on how you're using your system. These presets can be set in *Automatically setting up for surround sound (Auto MCACC)* on page 41 or *Automatic MCACC (Expert)* on page 78, either of which you should have already completed.
- 2 These settings have no effect when headphones are connected.
- You can also press ←/→ to select the MCACC preset.
- 3 This receiver can only play back Dolby Digital, PCM (32 kHz to 192 kHz), DTS (including DTS 96/24) and WMA9 Pro digital signal formats. The compatible signals via the HDMI terminals are: Dolby Digital, DTS, WMA9 Pro, PCM (32 kHz to 192 kHz), Dolby TrueHD, Dolby Digital Plus, DTS-EXPRESS, DTS-HD Master Audio, SACD and DVD Audio (including 192 kHz). With other digital signal formats, set to **ANALOG** (the

MULTI CH IN and TUNER).

- You may get digital noise when a LD or CD player compatible with DTS is playing an analog signal. To prevent noise, make the proper digital connections (page 29) and set the signal input to **DIGITAL**.
- Some DVD players don't output DTS signals. For more details, refer to the instruction manual supplied with your DVD player.
- 4 When the HDMI audio output parameter is set to THROUGH, the sound will be heard through your TV, not from this receiver.
- 5 This is useful if you find there is a slight delay before **AUTO** recognizes the PCM signal on a CD, for instance.
- When PCM is selected, noise may be output during playback of non-PCM sources. Please select another input signal if this is a problem.


Listening to your system

Phase Control OFF



- · Rhythms blurred and difficult to hear
- · Bass sound with loss of depth
- Sound of musical instruments with no reality

Phase Control ON



- · Rhythms with crystal-like clarity
- · Bass sound with no loss of depth
- · Sound of musical instruments with superb reality

Phase Control technology provides coherent sound reproduction through the use of phase matching ¹ for an optimal sound image. The default setting is on and we recommend leaving Phase Control switched on for all sound sources.



• Press RECEIVER, then press PHASE CTRL (PHASE CONTROL) to switch on phase correction.

The **PHASE CONTROL** indicator on the front panel lights.

Mote

- 1 Phase matching is a very important factor in achieving proper sound reproduction. If two waveforms are 'in phase', they crest and trough together, resulting in increased amplitude, clarity and presence of the sound signal. If a crest of a wave meets a trough, then the sound will be 'out of phase' and an unreliable sound image will be produced.
- The **PHASE CONTROL** feature is available even when the headphones are plugged in.
- If your subwoofer has a phase control switch, set it to the plus (+) sign (or 0°). However, the effect you can actually feel when **PHASE CONTROL** is set to **ON** on this receiver depends on the type of your subwoofer. Set your subwoofer to maximize the effect. It is also recommended you try changing the orientation or the place of your subwoofer.
- Set the built-in lowpass filter switch of your subwoofer to off. If this cannot be done on your subwoofer, set the cutoff frequency to a higher value.
- If the speaker distance is not properly set, you may not have a maximized **PHASE CONTROL** effect.
- The **PHASE CONTROL** mode cannot be set to **ON** in the following cases:
- When the **PURE DIRECT** mode is switched on.
- When the **MULTI CH IN** input is selected.
- When the HDMI audio output parameter is set to THROUGH in Setting the Audio options on page 66.

Chapter 7: **KURO LINK**

Synchronized operation with a KURO LINK-compatible Pioneer flat panel TV or Blu-ray disc player or with a component of another make that supports the KURO LINK function is possible when the component is connected to the receiver using an HDMI cable.

For details about concrete operations, settings, etc., refer to the operating instructions for each component.

- You cannot use this function with components that do not support KURO LINK.
- We do not guarantee this receiver will work with Pioneer KURO LINK-compatible components or components of other makes that support the KURO LINK function. We do not guarantee that all synchronized operations will work with components of other makes that support the KURO LINK function.
- Use a High Speed HDMI™ cable when you want to use the KURO LINK function. The KURO LINK function may not work properly if a different type of HDMI cable is used.

Making the KURO LINK connections

You can use synchronized operation for a connected flat panel TV and up to four (VSX-23TXH)/three (VSX-21TXH) other components.

Be sure to connect the flat panel TV's audio cable to the audio input of this unit.

For details, see Connecting your TV and playback components on page 24.

(Important

- When connecting this system or changing connections, be sure to switch the power off and disconnect the power cord from the wall socket. After completing all connections, connect the power cords to the wall socket.
- After this receiver is connected to an AC outlet, a 2 second to 10 second HDMI initialization process begins. You cannot carry out any operations during initialization. The HDMI indicator on the display unit blinks during initialization, and you can turn this receiver on once it has stopped blinking.
- To get the most out of this function, we recommend that you connect your HDMI component not to a flat panel TV but rather directly to the HDMI terminal on this receiver.

- VSX-23TXH only: To use the KURO LINK function, connect this receiver and flat panel TV using the HDMI OUT 1 terminal. Connecting the KURO LINK compatible component using the HDMI OUT 2 terminal may result in malfunction. If this happens, turn off the KURO LINK compatible component's KURO LINK setting.
- While the receiver is equipped with four (VSX-23TXH)/ three (VSX-21TXH) HDMI inputs, the KURO LINK function can only be used with up to three DVD or Blu-ray disc players or up to three DVD or Blu-ray disc recorders.

Cautions on the KURO LINK function

- Connect the TV directly to this receiver. Interrupting a direct connection with other amps or an AV converter (such as an HDMI switch) can cause operational errors
- Only connect components (Blu-ray disc player, etc.) you intend to use as a source to the HDMI input of this receiver. Interrupting a direct connection with other amps or an AV converter (such as an HDMI switch) can cause operational errors.
- When KURO LINK is set to ON, HDMI Input is automatically set to OFF.
- If a listening mode other than AUTO SURROUND, ALC, DIRECT, PURE DIRECT or STEREO is selected while the PQLS effect is enabled, the PQLS effect is disabled
- When this receiver is connected by HDMI cable to a Pioneer player that is compatible with the PQLS function via HDMI connection and HDMI reauthentication is performed (the HDMI indicator blinks), the PQLS effect is enabled and the listening mode is set to AUTO SURROUND if a listening mode other than AUTO SURROUND, ALC, DIRECT, PURE DIRECT or STEREO is selected.
- When the receiver's KURO LINK is turned ON, even if the receiver's power is in the standby mode, it is possible to output the audio and video signals from a player via HDMI to the TV without producing sound from the receiver, but only when a KURO LINKcompatible component (Blu-ray disc player, etc.) and compatible TV are connected. In this case, the receiver's power turns on and the power and HDMI indicators light.

About connections with a product of a different brand that supports the KURO LINK function

The synchronized operations below can be used when the receiver's KURO LINK function is connected to a TV of a brand other than Pioneer that supports the KURO LINK function. (Depending on the TV, however, some of the KURO LINK functions may not work.)

- You can set whether to output the sound over the speakers connected to the receiver or over the TV's speakers using the TV's menu screen.
- You can adjust the receiver's volume or mute the sound using the TV's remote control.
- When the TV's power is set to standby, the receiver's power is also set to standby. (Only when the input for a component connected to the receiver by HDMI connection is selected or when watching the TV.)
- The sound of TV programs or an external input connected to the TV can also be output from the speakers connected to the receiver. (This requires connection of an optical digital cable, etc., in addition to the HDMI cable.)


The synchronized operations below can be used when the receiver's KURO LINK function is connected to a player or recorder of a brand other than Pioneer that supports the KURO LINK function.

 When playback starts on the player or recorder, the receiver's input switches to the HDMI input to which that component is connected.

See the Pioneer website for the latest information on the models of non-Pioneer brands and products that support the KURO LINK function.


KURO LINK Setup

You must adjust the settings of this receiver as well as KURO LINK-compatible connected components in order to make use of the KURO LINK function. For more information see the operating instructions for each component.





- 1 Press RECEIVER, then press Home Menu.
- 2 Select 'System Setup', then press ENTER.
- 3 Select 'Other Setup', then press ENTER.





4 Select the 'KURO LINK' setting you want.

Choose whether to set this unit's KURO LINK function **ON** or **OFF**. You will need to set it to **ON** to use the KURO LINK function.

When using a component that does not support the KURO LINK function, set this to **OFF**.

- ON Enables the KURO LINK function. When this unit's power is turned off and you have a supported source begin playback while using the KURO LINK function, the audio and video output from the HDMI connection are output from the flat panel TV.
- OFF The KURO LINK is disabled. Synchronized operations cannot be used. When this unit's power is turned off, audio and video of sources connected via HDMI are not output.

5 Select the 'Display Power Off' setting you want.

If the TV's power is turned off while using the KURO LINK function, the receiver's power is also turned off (all power off function). This function can be disabled.

- YES The all power off function is enabled. The
 receiver's power turns off together with the TV's power.
 This function only works when the input for a
 component connected to the receiver by HDMI
 connection is selected or when watching the TV.
- NO The all power off function is disabled. The receiver's power is not affected when the TV's power is turned off.
- 6 When you're finished, press HOME MENU. You will finish to HOME MENU.

Setting the PQLS function

PQLS (Precision Quartz Lock System) is a digital audio signal transfer control technology using the KURO LINK function. It offers higher-quality audio playback by controlling audio signals from the receiver to a PQLS compatible player, etc. This enables removing jitter that has a negative effect on the quality of the sound and is generated upon transmission.

- VSX-23TXH only: On players compatible with PQLS Multi Surround, PQLS works for all sources. Set the player's audio output to Linear PCM.
- On players compatible with PQLS 2 ch Audio, PQLS only works when playing CDs.

To use the PQLS function, set PQLS in the player's Setup Navigator to **AUTO**.

Please refer to the operating instructions supplied with your player for more information.

This function is activated when **KURO LINK** is set to **ON**.



Press <u>RECEIVER</u>, then press PQLS to select PQLS setting.

The setting is displayed on the front panel display.

- PQLS AUTO PQLS is enabled. A precision quartz controller in this receiver eliminates distortion caused by timing errors (jitter), giving you the best possible digital-to-analog conversion when you use the HDMI interface. This is valid as an HDMI function for PQLS-compatible players.
- PQLS OFF PQLS is disabled.

Before using synchronization

Once you have finished all connections and settings, you must:

- 1 Put all components into standby mode.
- 2 Turn the power on for all components, with the power for the flat panel TV being turned on last.
- 3 Choose the HDMI input to which the TV is connected to this receiver, and see if video output from connected components displays properly on the screen or not.
- 4 Check whether the components connected to all HDMI inputs are properly displayed.

Synchronized amp mode

The synchronized amp mode can be set from the KURO LINK-compatible TV's remote control. See the explanation below for operations in the synchronized amp mode.

These functions are set from the TV's menu screen. For more information, refer to the operating instructions of the KURO LINK-compatible TV.

Synchronized amp mode operations

When using the synchronized amp mode, the KURO LINK-compatible component connected to the receiver operates in sync as described below.

- The receiver's volume can be set and the sound can be muted using the TV's remote control.
- When the TV's power is set to standby, the receiver's power is also set to standby. (Only when the input for a component connected to the receiver by HDMI connection is selected or when watching the TV.)
- The receiver's input switches automatically when the KURO LINK-compatible component is played.
- The receiver's input switches automatically when the TV's channel is switched.
- The synchronized amp mode remains in effect even if the receiver's input is switched to a component other than one connected by HDMI.

The operations below can also be used on Pioneer KURO LINK-compatible flat panel TVs.

- When the receiver's volume is adjusted or the sound is muted, the volume status is displayed on the flat panel TV's screen.
- When the OSD language is switched on the flat panel TV, the receiver's language setting also switches accordingly.

Canceling synchronized amp mode

- When the synchronized amp mode is canceled, the receiver's power turns off if you were viewing an HDMI input or a TV program on the TV.
- When in the synchronized amp mode, the synchronized amp mode is canceled when the receiver's power is turned off. To turn the synchronized amp mode back on, select the synchronized amp mode using the TV's remote control.
- When in the synchronized amp mode, the synchronized amp mode is canceled if an operation that produces sound from the TV is performed from the TV's menu screen, if the receiver's HDMI output setting is changed, etc.

Chapter 8: Using other functions

Setting the Audio options

There are a number of additional sound settings you can make using the AUDIO PARAMETER menu. The defaults, if not stated, are listed in bold.

Important

- Note that if a setting doesn't appear in the AUDIO PARAMETER menu, it is unavailable due to the current source, settings and status of the receiver.
- Press RECEIVER, then press AUDIO PARAMETER.
- 2 Use **↑**/**↓** to select the setting you want to adjust.

Depending on the current status/mode of the receiver, certain options may not be able to be selected. Check the table below for notes on this.

3 Use \leftarrow/\Rightarrow to set it as necessary.

See the table below for the options available for each setting.

Press RETURN to confirm and exit the menu.

Setting	What it does	Option(s)
MCACC (MCACC preset)	Selects your favorite MCACC preset memory when multiple preset memories are saved. When an MCACC preset memory has been renamed, the given name is displayed.	M1. MEMORY 1 to M6. MEMORY 6 Default: M1. MEMORY 1
EQ (Acoustic	Switches on/off the effects of EQ Pro.	ON
Calibration EQ)		OFF ^a
S-WAVE	Switches on/off the effects of	ON
(Standing Wave)	Standing Wave Control.	OFF
DELAY (Sound	Some monitors have a slight delay when showing video, so the	0.0 to 10.0
Delay)	soundtrack will be slightly out of sync with the picture. By adding a	$(frames)$ $1 \ second = 30$
	bit of delay, you can adjust the sound to match the presentation	frames (NTSC) Default: 0.0
	of the video.	
MIDNIGHT	Allows you to hear effective surround sound of movies at low	MIDNIGHT/ LOUDNESS
	volumes.	OFF
LOUDNESS	Used to get good bass and treble	MIDNIGHT ON
	from music sources at low volumes.	LOUDNESS ON

Setting	What it does	Option(s)
TONE	Applies the treble and bass tone controls to a source, or bypasses	BYPASS
(Tone Control)	them completely.	ON
BASS ^C	Adjusts the amount of bass.	-6 to +6 (dB)
		Default: 0 (dB)
TREBLE ^C	Adjusts the amount of treble.	-6 to +6 (dB)
		Default: 0 (dB)
S.RTRV	With the Sound Retriever	OFF ^d
(Sound Retriever)	function, DSP processing is used to compensate for the loss of	ON
iverilevel)	audio data upon compression,	
	improving the sound's sense of	
	density and modulation.	
DNR	May improve the quality of sound	OFF
(Digital Noise	in a noisy source (for example, video tape with lots of background	ON
Reduction)	noise) when switched on.	
DIALOG E.	Localizes dialog in the center	OFF
(Dialog	channel to make it stand out from	ON
Enhancem	other background sounds in a TV or movie soundtrack.	
ent) DUAL	Specifies how dual mono	CH1-Channel
(Dual	encoded Dolby Digital	1 is heard only
Mono)	soundtracks should be played.	CH2-Channel
	Dual mono is not widely used, but	2 is heard only
	is sometimes necessary when two languages need to be sent to	CH1 CH2 –
	separate channels.	Both channels
		heard from front speakers
DRC	Adjusts the level of dynamic	AUTO ^e
(Dynamic	range for movie soundtracks	MAX
Range	optimized for Dolby Digital, DTS,	MID
Control)	Dolby Digital Plus, Dolby TrueHD, DTS-HD and DTS-HD Master	OFF
	Audio (you may need to use this	OFF
	feature when listening to	
	surround sound at low volumes).	
LFE (LFE	Some Dolby Digital and DTS audio sources include ultra-low	0dB / -5dB/ -10dB/ -15dB/
(LFE Attenuate)	bass tones. Set the LFE attenuator	–100B/ –130B/ –20dB
,	as necessary to prevent the ultra-	OFF
	low bass tones from distorting the	
	sound from the speakers. The LFE is not limited when set to	
	0 dB, which is the recommended	
	value. When set to -5 dB, -10 dB,	
	–15 dB or –20 dB, the LFE is	
	limited by the respective degree. When OFF is selected, no sound	
	is output from the LFE channel.	

Using other functions

Setting	What it does	Option(s)
SACD	Brings out detail in SACDs by	0dB
GAIN ^f	maximizing the dynamic range (during digital processing).	+6 dB
HDMI ⁹ (HDMI Audio)	Specifies the routing of the HDMI audio signal out of this receiver (amp) or through to a TV or flat panel TV. When THROUGH is selected, no sound is output from this receiver.	AMPLIFIER THROUGH
A.DELAY	This feature automatically	OFF
(Auto delay)	corrects the audio-to-video delay between components connected with an HDMI cable. The audio delay time is set depending on the operational status of the display connected with an HDMI cable. The video delay time is automatically adjusted according to the audio delay time. h	ON
C.WIDTH ⁱ (Center Width) (Applicable only when using a center speaker)	Provides a better blend of the front speakers by spreading the center channel between the front right and left speakers, making it sound wider (higher settings) or narrower (lower settings).	0 to 7 Default: 3
DIMENSION	Adjusts the depth of the surround sound balance from front to back, making the sound more distant (minus settings), or more forward (positive settings).	-3 to +3 Default: 0
PANORAMA	Extends the front stereo image to include the surround speakers for a 'wraparound' effect.	OFF ON
C.IMAGE ^j (Center Image) (Applicable only when using a center speaker)	Adjusts the center image to create a wider stereo effect with vocals. Adjust the effect from 0 (all center channel sent to front right and left speakers) to 10 (center channel sent to the center speaker only).	0 to 10 Defaults: Neo:6 MUSIC: 3 Neo:6 CINEMA: 10
EFFECT	Sets the effect level for the currently selected Advanced Surround or ALC mode (each mode can be set separately).	10 to 90 Defaults: 50 (90 for EXT.STEREO only)

- a. When EQ OFF is selected, the MCACC indicator does not light.
 b. This setting is only displayed when the listening mode is Stereo, Auto surround (STEREO) or ALC (STEREO).
 - This setting is disabled in THX listening modes.
- c.The adjustment can be made only when **TONE** is set to **ON**.
- d.With the iPod/USB input function, by default S.RTRV is set to ON. e.The initially set AUTO is only available for Dolby TrueHD signals. Select MAX or MID for signals other than Dolby TrueHD.
- f. You shouldn't have any problems using this with most SACD discs, but if the sound distorts, it is best to switch the gain setting back to **0** dB.

- g.• HDMI Audio setting cannot be switched while performing synchronized amp mode operations.
 - The synchronized amp mode must be turned on in order to play the receiver's HDMI audio and video input signals from the TV with the receiver's power in the standby mode. See *Synchronized amp mode* on page 65.
- h.This feature is only available when the connected display supports the automatic audio/video synchronizing capability ('lipsync') for HDMI. If you find the automatically set delay time unsuitable, set A.DELAY to OFF and adjust the delay time manually. For more details about the lipsync feature of your display, contact the manufacturer directly.
- i. Only when listening to 2-channel sources in Dolby Pro Logic IIx Music/Dolby Pro Logic II Music mode.
- j. Only when listening to 2-channel sources in Neo:6 MUSIC/CINEMA mode.

Setting the Video options

There are a number of additional picture settings you can make using the **VIDEO PARAMETER** menu. The defaults, if not stated, are listed in bold.

Important

- Note that if an option cannot be selected on the VIDEO PARAMETER menu, it is unavailable due to the current source, setting and status of the receiver.
- These functions do not affect inputs other than DVD. TV/SAT, DVR, VIDEO (VSX-21TXH), VIDEO1 and 2 (VSX-23TXH).
- Press RECEIVER, then press VIDEO PARAMETER.
- 2 Use **↑**/↓ to select the setting you want to adjust.

Depending on the current status/mode of the receiver, certain options may not be able to be selected. Check the table below for notes on this.

3 Use ←/→ to set it as necessary.

See the table below for the options available for each settina.

Press RETURN to confirm and exit the menu.

Setting	What it does	Option(s)
V.CONV	Converts video signals for output	ON
(Digital Video Conversion)	from the MONITOR OUT jacks (including HDMI OUT connector) for all video types (see page 23).	OFF
RES ^a	Specifies the output resolution of	AUTO
(Resolution)	the video signal (when analog video input signals are output at	PURE
	the HDMI OUT connector, select	480p/576p
	this according to the resolution of your monitor and the images you wish to watch).	720p
		1080i
	wish to waterly.	1080p
ASP ^b	Specifies the aspect ratio when	THROUGH
(Aspect)	analog video input signals are output at the HDMI output. Make your desired settings while checking each setting on your display (if the image doesn't match your monitor type, cropping or black bands appear).	NORMAL


PCINEMACIA (PureCinema) for film material when the video output is set to progressive. Usually set to AUTO; but try switching to OFF if the picture appears unnatural. Additionally, certain PAL movie video (576i, 25 frames/second STB video output or DVD disc playback, etc.) that contain film progressive material cannot be recognized as such by this receiver. P.MOTIONC.d (Progressive quality when video output is set to Motion) YNRC Adjusts the amount of noise reduction (NR) applied to the Y (brightness) component. DETAILC Adjusts how sharp edges appear. Adjusts the sharpness of the high-frequency (detailed) elements in the picture. BRIGHTC (Brightness) CONTRAST c Adjusts the red/green balance. CHROMAC Adjusts saturation from dull to bright. CHROMAC Chroma AUTO PAL OFF AUTO PAL OFF AUTO PAL OFF AUTO PAL OFF OFF OFF AUTO PAL OFF OFF OFF AUTO PAL OFF OFF OFF OFF OFF OFF OFF O	Setting	What it does	Option(s)
(PureCinema) for film material when the video output is set to progressive. Usually set to AUTO; but try switching to OFF if the picture appears unnatural. Additionally, certain PAL movie video (576i, 25 frames/second STB video output or DVD disc playback, etc.) that contain film progressive material cannot be recognized as such by this receiver. P.MOTION ^{c,d} Adjusts the motion and still picture quality when video output is set to progressive quality when video output is set to progressive. YNR ^c Adjusts the amount of noise reduction (NR) applied to the Y (brightness) component. DETAIL ^c Adjusts how sharp edges appear. SHARP ^{c,e} (Sharpness) frequency (detailed) elements in the picture. BRIGHT ^c (Brightness) CONTRAST c Adjusts the contrast between light and dark. HUE ^{c,f} Adjusts saturation from dull to bright. CHROMA ^c (Chroma PAL OFF OFF OFF OFF OFF OFF OFF O			
Usually set to AUTO; but try switching to OFF if the picture appears unnatural. Additionally, certain PAL movie video (576i, 25 frames/second STB video output or DVD disc playback, etc.) that contain film progressive material cannot be recognized as such by this receiver. P.MOTION ^{c,d} Adjusts the motion and still picture quality when video output is set to progressive Motion) YNR ^c Adjusts the amount of noise reduction (NR) applied to the Y (brightness) component. DETAIL ^c Adjusts how sharp edges appear. Adjusts the sharpness of the high-frequency (detailed) elements in the picture. BRIGHT ^c Adjusts the overall brightness. CONTRAST c Adjusts the contrast between light and dark. HUE ^{c,f} Adjusts the red/green balance. CHROMA ^c Adjusts saturation from dull to bright. CHROMA ^c Adjusts saturation from dull to bright. CHROMA ^c Adjusts saturation from dull to Default: 0		for film material when the video	PAL
(Progressive Motion) progressive. YNR° Adjusts the amount of noise reduction (NR) applied to the Y (brightness) component. DETAIL° Adjusts how sharp edges appear. —4 to +4 Default: 0 SHARP°.e (Sharpness) frequency (detailed) elements in the picture. BRIGHT° Adjusts the overall brightness. —6 to +6 Default: 0 CONTRAST c Adjusts the contrast between light and dark. HUE°.f Adjusts saturation from dull to bright. CHROMA° (Chroma bright.		Usually set to AUTO ; but try switching to OFF if the picture appears unnatural. Additionally, certain PAL movie video (576i, 25 frames/second STB video output or DVD disc playback, etc.) that contain film progressive material cannot be recognized as	OFF
reduction (NR) applied to the Y (brightness) component. DETAIL ^c Adjusts how sharp edges appear. —4 to +4 Default: 0 SHARP ^{c,e} (Sharpness) Adjusts the sharpness of the high-frequency (detailed) elements in the picture. BRIGHT ^c Adjusts the overall brightness. —6 to +6 Default: 0 CONTRAST c Adjusts the contrast between light and dark. Default: 0 HUE ^{c,f} Adjusts the red/green balance. —6 to +6 Default: 0 CHROMA ^c (Chroma Adjusts saturation from dull to bright. —6 to +6 Default: 0	(Progressive	quality when video output is set to	
SHARP ^{c,e} (Sharpness) Adjusts the sharpness of the high-frequency (detailed) elements in the picture. BRIGHT ^c (Brightness) Adjusts the overall brightness. CONTRAST c Adjusts the contrast between light and dark. HUE ^{c,f} Adjusts the red/green balance. CHROMA ^c (Chroma Adjusts saturation from dull to bright. Default: 0 Default: 0 -6 to +6 Default: 0	YNR ^c	reduction (NR) applied to the Y	
(Sharpness) frequency (detailed) elements in the picture. BRIGHT	DETAIL ^C	Adjusts how sharp edges appear.	
(Brightness) CONTRAST c Adjusts the contrast between light c and dark. HUE ^{c,f} Adjusts the red/green balance. CHROMA ^c (Chroma Adjusts saturation from dull to bright. Default: 0 Default: 0 Cell Chroma Default: 0 Default: 0		frequency (detailed) elements in	
c and dark. Default: 0 HUE ^{c,f} Adjusts the red/green balance6 to +6 Default: 0 CHROMA ^c (Chroma Adjusts saturation from dull to bright. Default: 0		Adjusts the overall brightness.	
CHROMA ^c Adjusts saturation from dull to Chroma bright. Default: 0 Default: 0 Default: 0			
(Chroma bright. Default: 0	HUE ^{c,f}	Adjusts the red/green balance.	
20101/		*	

- a. When set to a resolution with which the TV (monitor) is not compatible, no picture is output. Also, in some cases no picture will be output due to copyright protection signals. In this case, change the setting
- When AUTO is selected, the resolution is selected automatically according to the capacity of the TV (monitor) connected by HDMI. When PURE is selected, the signals are output with the same resolution as when input (At this time, video signals are only output from the same type of terminals to which they were input).
- When a display is connected by HDMI, if this is set to something other than PURE and 480i/576i analog signals are input, 480p/576p signals are output from the component output terminals.
- · Conversion to 1080p is only performed for 480i, 576i, 480p and 576p input signals.
- b. If the image doesn't match your monitor type, adjust the aspect ratio on the source component or on the monitor.
 - . This cannot be set when the resolution is set to PURE.
 - NORMAL setting is only displayed when 480i/p or 576i/p video signals are being input.
- c. This setting is only displayed when 480i or 576i video signals are being input.
- d.This setting is only valid for component outputs.
- e. This setting is not valid for HDMI output(s).
- f. This setting is not displayed for component inputs.

- 1 All of the setting items can be set for each input function.
- Setting items other than V.CONV can only be selected when V.CONV is set to ON.

Switching the speaker system

If you selected **Speaker B** in *Surround back speaker* setting on page 91, three speaker system settings are possible using **SPEAKERS**. If you selected **Normal**, **Front Bi-Amp** or **ZONE 2**, the button will simply switch your main speaker system on or off. The options below are for the **Speaker B** setting only.¹



Use SPEAKERS on the front panel to select a speaker system setting.


As mentioned above, if you have selected **Normal**, the button will simply switch your main speaker system (A) on or off.

Press repeatedly to choose a speaker system option:

- SP►A Sound is output from speaker system A and the same signal is output from the pre-out terminals.
- SPPB Sound is output from the two speakers connected to speaker system B. Multichannel sources will not be heard. The same signal is output from the surround back channel pre-out terminals.
- SP►AB Sound is output from speaker system A (up to 5 channels, depending on the source), the two speakers in speaker system B, and the subwoofer. The sound from speaker system B will be the same as the sound from speaker system A (multichannel sources will be downmixed to 2 channels).
- SP► (off) No sound is output from the speakers. The same sound is output from the pre-out terminals (including from your subwoofer, if connected) as when selecting speaker system A (above).

Using the MULTI-ZONE controls

The following steps use the front panel controls to adjust the sub zone volume and select sources. See *MULTI-ZONE remote controls* on page 70.



Press MULTI-ZONE ON/OFF on the front panel.

Each press selects a MULTI-ZONE option:

- **ZONE 2 ON** Selects your primary (**ZONE 2**) sub zone
- VSX-23TXH only: **ZONE 2&3 ON** Select both sub zones
- VSX-23TXH only: ZONE 3 ON Selects your secondary (ZONE 3) sub zone
- MULTI ZONE OFF Switches the MULTI-ZONE feature off

The **MULTI-ZONE** indicator lights when the MULTI-ZONE control has been switched ON.

2 Press MULTI-ZONE CONTROL on the front panel to select the sub zone(s) you want.

VSX-23TXH only: If you selected **ZONE 2&3 ON** above, you can toggle between **ZONE 2** and **ZONE 3**.

When the receiver is on,² make sure that any operations for the sub zone are done while **ZONE** and your selected sub zone(s) show in the display. If this is not showing, the front panel controls affect the main zone only.

3 Use the INPUT SELECTOR dial to select the source for the zone you have selected.

For example, **ZONE 2 CD-R** sends the source connected to the **CD-R** inputs to the primary (**ZONE 2**) sub room.

 If you select **TUNER**, you can use the tuner controls to select a preset station (see *Saving station presets* on page 51 if you're unsure how to do this).³

🕢 Note

- 1 The subwoofer output depends on the settings you made in *Manual speaker setup* on page 90. However, if **SP►B** is selected above, no sound is heard from the subwoofer (the LFE channel is not downmixed).
- Depending on the settings in Surround back speaker setting on page 91 output from the surround back pre-out terminals may change.
- All speaker systems (except Speaker B connections) are switched off when headphones are connected.
- 2 If the receiver is in standby, the display is dimmed, and ZONE and your selected sub zone(s) continue to show in the display.
- 3 The tuner cannot be tuned to more than one station at a time. Therefore, changing the station in one zone also changes the station in the other zone. Please be careful not to change stations when recording a radio broadcast.

4 Use the MASTER VOLUME dial to adjust the volume for the zone you have selected.

This is only possible if you selected the Variable volume control in ZONE Audio Setup on page 95.1

5 When you're finished, press MULTI-ZONE CONTROL again to return to the main zone controls.

You can also press MULTI-ZONE ON/OFF on the front panel to switch off all output to the sub zone(s).2

MULTI-ZONE remote controls

Set the MULTI-ZONE operation switch to **ZONE 2** or **ZONE 3** (VSX-23TXH only) to operate the corresponding zone.

The following table shows the possible MULTI-ZONE remote controls:


Button	What it does
Ф	Switches on/off power in the sub zone.
INPUT SELECT	Use to select the input function in the sub zone.
Input function buttons	Use to select the input function directly (this may not work for some functions) in the sub zone.
MASTER VOLUME +/-	Use to set the listening volume in the sub zone.
MUTE	Mutes the sound or restores the sound if it has been muted (adjusting the volume also restores the sound).

Making an audio or a video recording

You can make an audio or a video recording from the built-in tuner, or from an audio or video source connected to the receiver (such as a CD player or TV).3

Keep in mind you can't make a digital recording from an analog source or vice-versa, so make sure the components you are recording to/from are hooked up in the same way (see Connecting your equipment on page 15 for more on connections).

Since the video converter is not available when making recordings (from the video OUT jacks) make sure to use the same type of video cable for connecting your recorder as you used to connect your video source (the one you want to record) to this receiver. For example, you must connect your recorder using Component video if your source has also been connected using Component video. For more information about video connections, see Connecting an HDD/DVD recorder, VCR and other video sources on page 28.



1 Select the source you want to record.

Use the input function buttons (or **INPUT SELECT**).

- If necessary, press RECEIVER, then press SIGNAL **SEL** to select the input signal corresponding to the source component (see Choosing the input signal on page 61 for more on this).
- 2 Prepare the source you want to record. Tune to the radio station, load the CD, video, DVD etc.

3 Prepare the recorder.


Insert a blank tape, MD, video etc. into the recording device and set the recording levels.

Refer to the instructions that came with the recorder if you are unsure how to do this. Most video recorders set the audio recording level automatically—check the component's instruction manual if you're unsure.

Start recording, then start playback of the source component.

Reducing the level of an analog signal

The input attenuator lowers the input level of an analog signal when it's too strong. You can use this if you find that the OVER indicator lights often or you can hear distortion in the sound.4



Press RECEIVER, then press A.ATT to switch the input attenuator on or off.


Mote

- 1 The volume levels of the main and sub zone(s) are independent.
- 2 You won't be able to switch the main zone off completely unless you've switched off the MULTI-ZONE control first.
- If you don't plan to use the MULTI-ZONE feature for a while, turn off the power in both the sub and main rooms so that this receiver is in standby.
- 3 The receiver's volume, Audio parameters (the tone controls, for example), and surround effects have no effect on the recorded signal.
 - Some digital sources are copy-protected, and can only be recorded in analog.
- Some video sources are copy-protected. These cannot be recorded.
- 4 The attenuator isn't available with digital sources, or when using the Stream Direct (ANALOG DIRECT) modes.

Using other functions

Using the sleep timer

The sleep timer switches the receiver into standby after a specified amount of time so you can fall asleep without worrying about the receiver being left on all night. Use the remote control to set the sleep timer.




• Press <u>RECEIVER</u>, then press <u>SLEEP</u> repeatedly to set the sleep time.



 You can check the remaining sleep time at any time by pressing SLEEP once. Pressing repeatedly will cycle through the sleep options again.¹

Dimming the display

You can choose between four brightness levels for the front panel display. Note that when selecting sources, the display automatically brightens for a few seconds.




• Press <u>RECEIVER</u>, then press DIMMER repeatedly to change the brightness of the front panel display.

Switching the HDMI output

(VSX-23TXH only)

Set which terminal to use when outputting video and audio signals from the HDMI output terminals (**HDMI OUT ALL, HDMI OUT 1** or **HDMI OUT 2**).

The HDMI OUT1 terminal is compatible with the KURO LINK function.



• Press RECEIVER, then press HDMI OUT.

Please wait a while when **Please wait ...** is displayed.

The output switches among **HDMI OUT ALL**, **HDMI OUT 1** and **HDMI OUT 2** each time the button is pressed.²

Checking your system settings


Use the status display screen to check your current settings for features such as surround back channel processing and your current MCACC preset.



1 Press RECEIVER, then press STATUS to check the system settings.

These appear on the front panel display.³

The front panel display shows each of the following settings for three seconds each:



2 When you're finished, press STATUS again to switch off the display.

Ø Note

- You can also switch off the sleep timer simply by switching off the receiver.
- The sleep timer is valid for all zones. If any zone is on, the sleep timer continues functioning.
- 2 Synchronized amp mode on page 65 is canceled when the HDMI output is switched. If you wish to use the synchronized amp mode, switch to **HDMI OUT 1**, then select the synchronized amp mode on the flat panel TV using the flat panel TV's remote control.
 - When the power is turned off then back on after switching the HDMI output, the input is set to a setting between HDMI1 and HDMI3 (VSX-21TXH)/4 (VSX-23TXH), or BD.
- 3 If the Pure Direct mode is switched on, some settings above will show **OFF**, even though they are on.

Using other functions

Resetting the system

Use this procedure to reset all the receiver's settings to the factory default. Use the front panel controls to do this. Set **MULTI-ZONE** to **OFF**.

- Disconnect the iPod and USB memory device from the receiver beforehand.
- 1 Switch the receiver into standby.
- 2 While holding down ENTER on the front panel, press \circlearrowleft STANDBY/ON.

The display shows **RESET** ◀ **NO** ►.

3 Select 'RESET' using PRESET +/-, then press ENTER on the front panel.

The display shows **RESET? OK**.

4 Press ENTER to confirm.

OK appears in the display to indicate that the receiver has been reset to the factory default settings.

 Note that all settings will be saved, even if the receiver is unplugged.

Default system settings

Setting		Default		
Digital Video Conversion		ON		
SPEAKERS		А		
Surround Back System		Normal		
Speaker System	Front	SMALL		
	Center	SMALL		
	Surr	SMALL		
	SB	SMALLx2		
	SW	YES		
Crossover		80 Hz		
X-Curve		OFF		
THX Audio Setting		4 ft<		
DIMMER		Brightest		
Inputs				
See Input function default and possible settings on page 44.				
MULTI-ZONE				
ZONE 2/ZONE 3 (VSX-23TXH only) Volume Level		Variable		
ZONE 2/ZONE 3 (VSX-23TXH only) Volume		–60 dB		
HDMI				
HDMI Audio		Amp		
HDMI output (VSX-23TXH only)		HDMI OUT ALL		
KURO LINK		ON		

Setting		Default
DSP		
Surround back channel Processing		ON
Phase Control		ON
Sound Retriever	iPod/USB function	ON
	Other functions	OFF
Sound Delay		0.0 frame
Dual Mono		CH1
DRC		AUTO
SACD Gain		0 dB
LFE Attenuate		0 dB
Auto delay		OFF
Up Mix		ON
Digital Safety		OFF
Effect Level	EXT.STEREO	90
	Other modes	50
DID PL II Music Options	Center Width	3
	Dimension	0
	Panorama	OFF
Neo:6 Options	Center Image	Neo:6 MUSIC: 3
		Neo:6 CINEMA: 10
All Inputs	Listening Mode	AUTO
	(2 ch)	SURROUND
	Listening Mode	AUTO
	(x ch)	SURROUND
	Listening Mode (HP) SIEKEU

See also Setting the Audio options on page 66 for other default DSP settings.

zer eettinger				
MCACC				
MCACC Position Memory		M1: MEMORY 1		
Channel Level (M1 to M6)		0.0 dB		
Speaker Distance (M1 to M6)		10'00"		
Standing Wave (M1 to M6)	ATT of all channels/ filters	0.0 dB		
	SWch Trim	0.0 dB		
EQ Data (M1 to M6)	All channels/bands	0.0 dB		
	EQ Trim	0.0 dB		


Chapter 9:

Controlling the rest of your system

Operating multiple receivers

The remote control included with this receiver can be used to operate up to three other receivers (of the same model as this receiver) in addition to this receiver. The receiver to be operated is switched by inputting the preset code to set the remote control setting.

• Set the remote modes on the receivers before using this function (see *Remote Control Mode Setup* on page 96).



- 1 Check the operation selector switch to MAIN.
- 2 Press RECEIVER.
- 3 Press and hold REMOTE SETUP, then release it after the LED flashes twice.
- 4 Use the number buttons to enter the 5-digit preset code (see below).

• Receiver 1: 6 1 9 3 5 (Default)

Receiver 2: 6 2 6 3 0
Receiver 3: 6 2 6 3 1
Receiver 4: 6 2 6 3 2

When the preset code is fully input, the LED flashes once to indicate that the setting is completed.

To operate another receiver, start over from step 1 to input its preset code.

Setting the remote to control other components

Most components can be assigned to one of the input function buttons (such as ${\bf DVD}$ or ${\bf CD}$) using the component's manufacturer preset code stored in the remote.

However, there are cases where only certain functions may be controllable after assigning the proper preset code, or the codes for the manufacturer in the remote control will not work for the model that you are using.



- You can cancel or exit any of the steps by pressing **RECEIVER**. To go back a step, press **RETURN**.
- After one minute of inactivity, the remote automatically exits the operation.

Selecting preset codes directly

1 Press the input function button for the component you want to control.¹

When assigning preset codes to **TV CONTROL**, press **TV CTRL** here.

- 2 Press and hold REMOTE SETUP, then release it after the LED flashes twice.
- 3 Use the number buttons to enter the 5-digit preset code.

See Preset code list on page 113.

When the preset code is fully input, the LED flashes once to indicate that the setting is completed.

4 Repeat steps 1 through 3 for the other components you want to control.

To try out the remote control, switch the component on or off (into standby) by pressing **& SOURCE**. If it doesn't seem to work, select the next code from the list (if there is one).

Resetting the remote control presets

This will erase all preset remote control preset codes and programmed buttons.

- 1 Check the operation selector switch to MAIN.
- 2 Press RECEIVER.
- 3 Press and hold REMOTE SETUP, then release it after the LED flashes twice.
- 4 Use the number buttons to enter 9, 8, 1.

The LED flashes four times to indicate that the resetting is completed.


Default preset codes

Input function button	Preset code
DVD	3 1 5 7 1
BD	3 2 4 4 2
DVR	22306
HDMI	3 2 4 4 2
TV	1 4 0 0 1
CD	7 0 4 6 8
CD-R	7 1 0 8 7
VIDEO	20058
TV CTRL	1 4 0 0 1
RECEIVER	61935

Controls the components

This remote control can control components after entering the proper codes (see *Setting the remote to control other components* on page 73 for more on this). Use the input function buttons to select the component.

 The TV CONTROL buttons on the remote control are dedicated to control the TV assigned to the TV CTRL button. If you have two TVs, assign the main TV to the TV CTRL button.



Controlling the rest of your system

Button(s)	TV	TV (Monitor)	BD/DVD	HDD/DVR	VCR	SAT/CATV
් SOURCE	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF
Number buttons	numerics	numerics	numerics	numerics	numerics	numerics
• (dot)	• (dot)	KURO LINK	CLEAR	+	-	*
ENTER (CLASS)	ENTER	CH ENTER	ENTER	ENTER	-	ENTER
×	EXIT/INFO	EXIT	TOP MENU	TOP MENU	-	LIST
£	TOOLS/GUIDE/ EPG	USER MENU	TOOLS	GUIDE	-	GUIDE
↑ / ↓ / ← / →	1/↓/←/→	↑ / ↓ / ← / →	↑ / ↓ / ← / →	1/↓/←/→	-	1/↓/←/→
ENTER	ENTER	ENTER	ENTER	ENTER	-	ENTER
•	HOME MENU	HOME MENU	HOME MENU	HOME MENU	-	HOME / MENU
	RETURN	RETURN	RETURN	RETURN	-	RETURN
HDD (Red)	Red	Red	-	HDD	-	Red
DVD (Green)	Green	Green	-	DVD	-	Green
(Yellow)	Yellow	Yellow	-	VCR	-	Yellow
★ (Blue)	Blue	Blue	MENU	MENU	-	Blue
>	-	-	>	>	>	>
II	-	AUTO SETUP	II	II	II	II
	-	FREEZE				
44	-	-	44	44	44	44
>>	-	-	>>	>>	>>	>>
 44	ANT	AV SELECTION	 44	 44	-	 44
▶▶ I	-	SCREEN SIZE	▶▶	▶▶ I	-	▶▶
AUDIO	AUDIO	AUDIO	AUDIO	AUDIO	AUDIO	AUDIO
DISP	DISPLAY	DISPLAY	DISPLAY	DISPLAY	-	DISPLAY/INFO
CH +/-	CH+/-	CH+/-	OUTPUT RESOLUTION+/-a	CH+/-	CH+/-	CH+/-
■ + >>	-	-	-	-	-	RECORD

a. Controls for BD.

Controlling the rest of your system

Button(s)	LD	CD/CD-R/SACD	MD/DAT	TAPE
Ů SOURCE	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF	POWER ON/OFF
Number buttons	numerics	numerics	numerics	-
• (dot)	+10	>10/CLEAR	CLEAR ^c	CLEAR
ENTER (CLASS)	ENTER	DISK/ENTER	OPEN/CLOSE ^c	ENTER
×	TOP MENU	-	-	MS←
£	-	LEGATO LINK ^b	-	MS→
↑ / ↓ / ← / →	1/↓/←/→	-	-	II/ ■ /◀◀/▶▶
ENTER	ENTER	-	-	-
•	-	SACD SETUP ^b	-	-
◆ 1	RETURN	-	-	-
>	>	>	>	>
II	II	II	II	II
44	44	44	44	44
>>	>>	>>	>>	>>
44	 44	 44	 44	 44
▶▶	▶▶	▶▶	▶▶	▶▶
AUDIO	AUDIO	PURE AUDIO ^b	-	-
DISP	DISPLAY/INFO	TIME ^b	-	-

b. Controls for SACD. c. Controls for MD.

Button(s)	TV (Projector)
් SOURCE	POWER ON
1	MOVIE
2	STANDARD
3	DYNAMIC
4	USER1
5	USER2
6	USER3
7	COLOR+
8	SHARP+
9	GAMMA
0	COLOR-
• (dot)	SHARP-
ENTER (CLASS)	COLOR TEMP
×	EXIT
£	INFO
1/↓/←/→	↑ / ↓ / ← / →
↑ / ↓ / ← / → ENTER	1 / ↓ / ← / → ENTER
ENTER	ENTER TEST HIDE
ENTER 🙃	ENTER TEST
ENTER	ENTER TEST HIDE
ENTER D S	ENTER TEST HIDE MENU
ENTER	ENTER TEST HIDE MENU HDMI1
ENTER S S A	ENTER TEST HIDE MENU HDMI1 HDMI2
ENTER S S X 44	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO S-VIDEO
ENTER	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO
ENTER	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO S-VIDEO BRIGHT- BRIGHT+
ENTER	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO S-VIDEO BRIGHT- BRIGHT+ POWER OFF
ENTER	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO S-VIDEO BRIGHT- BRIGHT+ POWER OFF ASPECT
ENTER	ENTER TEST HIDE MENU HDMI1 HDMI2 COMP. VIDEO S-VIDEO BRIGHT- BRIGHT+ POWER OFF

Chapter 10:

The Advanced MCACC menu

Making receiver settings from the Advanced MCACC menu

The Advanced MCACC (Multi Channel ACoustic Calibration) system was developed in Pioneer's laboratories with the aim of making it possible for home users to perform adjustments of the same level as in a studio easily and with high precision. The acoustic characteristics of the listening environment are measured and the frequency response is calibrated accordingly to allow high precision, automatic analysis and optimal calibration of the sound field to bring it closer to a studio environment than ever before. Furthermore, while it was previously difficult to eliminate standing waves, this receiver is equipped with a standing wave control function using a unique process to perform acoustic analysis and reduce their influence.

This section describes how to calibrate the sound field automatically and fine-adjust the sound field data manually.



1 Switch on the receiver and your TV. Use & RECEIVER to switch on.¹

 If headphones are connected to the receiver, disconnect them.


2 Press RECEIVER on the remote control, then press HOME MENU.²

A Graphical User Interface (GUI) screen appears on your TV. Use $\uparrow / \downarrow / \leftarrow / \Rightarrow$ and **ENTER** to navigate through the screens and select menu items. Press **RETURN** to confirm and exit the current menu.

 Press HOME MENU at any time to exit the HOME MENU. 3 Select 'Advanced MCACC' from the HOME MENU, then press ENTER.



4 Select the setting you want to adjust.



- Full Auto MCACC See Automatically setting up for surround sound (Auto MCACC) on page 41 for a quick and effective automatic surround setup.
- Auto MCACC See Automatic MCACC (Expert) on page 78 for a more detailed MCACC setup.
- Manual MCACC Fine-tunes your speaker settings and customize the Acoustic Calibration EQ (see Manual MCACC setup on page 80).
- Demo No settings are saved and no errors occur.
 When the speakers are connected to this receiver,
 the test tone is output repeatedly. Press RETURN to
 cancel the test tone.

Note

1 Make sure not to switch off the power when using the HOME MENU.

- 2 You can't use the **HOME MENU** when the iPod/USB, XM or SIRIUS Radio input function is selected (in either the main or sub zone).
 - VSX-23TXH: When you set ZONE 2, ZONE 3 or ZONE 2&3 to ON (page 69), you can't use the HOME MENU.
 - VSX-21TXH: When you set ZONE 2 to ON (page 69), you can't use the HOME MENU.

Automatic MCACC (Expert)

If your setup requires more detailed settings than those provided in Automatically setting up for surround sound (Auto MCACC) on page 41, you can customize your setup options below. You can calibrate your system differently for up to six different MCACC presets¹, which are useful if you have different listening positions depending on the type of source (for example, watching movies from a sofa, or playing a video game close to the TV).2

Important

- Make sure the microphone/speakers are not moved during the Auto MCACC Setup.
- Using the Auto MCACC Setup will overwrite any existing settings for the MCACC preset you select.3
- The screen saver will automatically appear after five minutes of inactivity.

CAUTION

 The test tones used in the Auto MCACC Setup are output at high volume.

THX®

THX is a trademark of THX Ltd., which may be registered in some jurisdictions. All rights reserved.

Select 'Auto MCACC' from the Advanced MCACC 1 menu, then press ENTER.

If the **Advanced MCACC** screen is not displayed, refer to Making receiver settings from the Advanced MCACC menu on page 77.






2 Select the parameters you want to set.

Use \uparrow/\downarrow to select the item, then use \leftarrow/\Rightarrow to set.






- Auto MCACC The default is ALL (recommended), but you can limit the system calibration to only one setting (to save time) if you want. 4 The available options are ALL, Keep SP System, 5 Speaker Setting, Channel Level, Speaker Distance and EQ Pro & S-Wave.
- EQ Type (only available when the Auto MCACC Menu above is **EQ Pro & S-Wave**) – This determines how the frequency balance is adjusted.

After a single calibration is performed, each of the following three correction curves can be stored separately in the MCACC memory. **SYMMETRY** (default) implements symmetric correction for each pair of left and right speakers to flatten the frequency-amplitude characteristics. **ALL CH ADJ** is a 'flat' setting where all the speakers are set individually so no special weighting is given to any one channel. FRONT ALIGN⁶ sets all speakers in accordance with the front speaker settings (no equalization is applied to the front left and right channels).

- THX Speaker (only available when the Auto MCACC Menu above is ALL or Speaker Setting) – Select YES if you are using THX speakers (set all speakers to **SMALL**), otherwise leave it set to **NO**.
- STAND.WAVE Multi-Point (only available when the Auto MCACC Menu above is EQ Pro & S-Wave) – In addition to measurements at the listening position. you can use two more reference points for which test tones will be analyzed for standing waves. This is useful if you want to get a balanced 'flat' calibration for several seating positions in your listening area. Place the microphone at the reference point indicated on-screen and note the last microphone placement will be at your main listening position:

- 1 These are stored in memory and referred to as **MEMORY1** to **MEMORY6** until you rename them in *Data Management* on page 88.
- 2 You may also want to have separate calibration settings for the same listening position, depending on how you're using your system.
- 3 Except in cases where you are only adjusting one parameter (i.e. channel level) from the Auto MCACC menu (step 2).
- 4 The EQ Pro & S-Wave measurement is also taken when Keep SP System or EQ Pro & S-Wave is selected. See Acoustic Calibration EQ Professional on page 83 for more on this.
 - Either effect of Acoustic Calibration EQ Professional and Standing Wave can be switched on and off in the respective MCACC preset. For details, see Setting the Audio options on page 66.
- 5 The Keep SP System option allows you to calibrate your system while leaving your current speaker setting (page 91) unchanged.
- 6 If you selected ALL as your Auto MCACC menu, you can specify the MCACC preset where you want to save the ALL CH ADJ and FRONT ALIGN settings
- 7 Switch the Multi-Point setting NO if you only use one listening position.




3 Connect the microphone to the MCACC SETUP MIC jack on the front panel.


 Push down on the PUSH OPEN tab to access the MCACC SETUP MIC jack.

Make sure there are no obstacles between the speakers and the microphone.

VSX-23TXH:



VSX-21TXH:



If you have a tripod, use it to place the microphone so that it's about ear level at your normal listening position. If you do not have a tripod, use some other object to install the microphone. 1

4 When you're finished setting the options, select START then press ENTER.

5 Follow the instructions on-screen.

- Make sure the microphone is connected.
- If you're using a subwoofer, it is automatically detected every time you switch on the system. Make sure it is on and the volume is turned up.
- See *Problems when using the Auto MCACC Setup* on page 43 for notes regarding high background noise levels and other possible interference.

6 Wait for the Auto MCACC Setup to finish outputting test tones.


A progress report is displayed on-screen while the receiver outputs test tones to determine the speakers present in your setup. Try to be as quiet as possible while it's doing this.


- Do not adjust the volume during the test tones. This
 may result in incorrect speaker settings.
- With error messages (such as Too much ambient noise! or Check microphone) select RETRY after checking for ambient noise (see Problems when using the Auto MCACC Setup on page 43) and verifying the mic connection. If there doesn't seem to be a problem, you can simply select GO NEXT and continue.

7 If necessary, confirm the speaker configuration in the GUI screen.²

The configuration shown on-screen should reflect the actual speakers you have.

If no operations are performed for 10 seconds while the speaker configuration check screen is being displayed, the Auto MCACC Setup will resume automatically. In this case, you don't need to select '**OK**' and press **ENTER** in step 8.






¹ It may not be possible to measure correctly if the microphone is placed on a table, sofa, etc.


² This screen is only shown if you selected ALL or Speaker Setting from the Auto MCACC menu.

- If you see an **ERR** message (or the speaker configuration displayed isn't correct), there may be a problem with the speaker connection. If selecting **RETRY** doesn't work, turn off the power and check the speaker connections. If there doesn't seem to be a problem, you can simply use 1/1 to select the speaker and ←/→ to change the setting and continue.
- If **Reverse Phase** is displayed, the speaker's wiring (+ and -) may be inverted. Check the speaker connections.
 - If the connections were wrong, turn off the power, disconnect the power cord, then reconnect properly. After this, perform the Full Auto MCACC procedure
 - If the connections were right, select GO NEXT and continue.

8 Make sure 'OK' is selected, then press ENTER.

A progress report is displayed on-screen while the receiver outputs more test tones to determine the optimum receiver settings for channel level, speaker distance, and Acoustic Calibration EQ.





Again, try to be as quiet as possible while this is happening. It may take 3 to 7 minutes.

 If you selected a STAND.WAVE Multi-Point setup (in step 2), you will be asked to place the mic at the 2nd and 3rd reference points before finally placing it at your main listening position.

9 The Auto MCACC Setup procedure is completed and the Advanced MCACC menu reappears automatically.

The settings made in the Auto MCACC Setup should give you excellent surround sound from your system, but it is also possible to adjust these settings manually using the Manual MCACC setup menu (starting below) or Manual SP Setup menu (starting on page 90).²

You can also choose to view the settings by selecting individual parameters from the MCACC Data Check screen:

- **Speaker Setting** The size and number of speakers you've connected (see page 91 for more on this)
- Channel Level The overall balance of your speaker system (see page 81 or 92 for more on this)
- **Speaker Distance** The distance of your speakers from the listening position (see page 82 or 93 for more on this)3
- **Standing Wave** Filter settings to control lower 'boomy' frequencies (see page 82 for more on this)
- Acoustic Cal EQ Adjustments to the frequency balance of your speaker system based on the acoustic characteristics of your room (see page 83 for more on this)
- Output PC The data transfer mode with the connected computer is set. The graphs of the reverb characteristics before and after calibration and the various MCACC parameters can be checked (see Output PC on page 88 for more on this).

Press **RETURN** after you have finished checking each screen. When you're finished, select RETURN to go back to the **HOME MENU**.

Be sure to disconnect the microphone from this receiver upon completion of the Auto MCACC Setup.

Manual MCACC setup

You can use the settings in the Manual MCACC setup menu to make detailed adjustments when you're more familiar with the system. Before making these settings, you should have already completed Automatically setting up for surround sound (Auto MCACC) on page 41.

You only need to make these settings once (unless you change the placement of your current speaker system or add new speakers).



• The test tones used in the **Manual MCACC** setup are output at high volume.

- 1 If the speaker is not pointed to the microphone (listening position) or when using speakers that affect the phase (dipole speakers, reflective speakers, etc.), Reverse Phase may be displayed even if the speakers are properly connected.
- 2 Depending on the characteristics of your room, sometimes identical speakers with cone sizes of around 12 cm will end up with different size settings. You can correct the setting manually using the Manual speaker setup on page 90.
 - The subwoofer distance setting may be farther than the actual distance from the listening position. This setting should be accurate (taking delay and room characteristics into account) and generally does not need to be changed.
- · If Auto MCACC Setup measurement results are incorrect due to the interaction of the speakers and viewing environment, we recommend adjusting the settings manually.
- 3 Since the distance measurements have been set according to the sound characteristics of your speakers, there are cases where (for optimal surround sound) the actual distance may differ from the speaker distance setting.


(Important

- You will need to first specify the MCACC preset you want to adjust by pressing **MCACC** before pressing **HOME MENU** (step 2 in *Making receiver settings from the Advanced MCACC menu* on page 77).
- For some of the settings below, you'll have to connect
 the setup microphone to the front panel and place it
 about ear level at your normal listening position.
 Press HOME MENU to display the HOME MENU
 before you connect the microphone to this receiver. If
 the microphone is connected while the HOME
 MENU is not being displayed, the display will change
 to the Full Auto MCACC under Advanced MCACC.
- See Problems when using the Auto MCACC Setup on page 43 for notes regarding high background noise levels and other possible interference.
- If you're using a subwoofer, switch it on and turn up the volume to the middle position.

1 Select 'Manual MCACC' from the Advanced MCACC menu.

See Making receiver settings from the Advanced MCACC menu on page 77 if you're not already at this screen.





2 Select the setting you want to adjust.

If you're doing this for the first time, you might want to make these settings in order.

- Fine Channel Level Make fine adjustments to the overall balance of your speaker system (see Fine Channel Level below).
- Fine SP Distance Make precise delay settings for your speaker system (see Fine Speaker Distance below)
- **Standing Wave** Control overly resonant low frequencies in your listening room (see *Standing Wave* on page 82).

The last two settings are specifically for customizing the parameters explained in *Acoustic Calibration EQ Adjust* on page 83:

- **EQ Adjust** Manually adjust the frequency balance of your speaker system while listening to test tones (see *Acoustic Calibration EQ Adjust* on page 83).
- **EQ Professional** Calibrate your system based on the direct sound coming from the speakers and make detailed settings according to your room's reverb characteristics (see *Acoustic Calibration EQ Professional* on page 83).


Fine Channel Level

• Default setting: 0.0dB (all channels)

You can achieve better surround sound by properly adjusting the overall balance of your speaker system. You can adjust the Channel Level of each speaker in 0.5 dB increments. The following setting can help you make detailed adjustments that you may not achieve using the *Manual speaker setup* on page 90.

1 Select 'Fine Channel Level' from the Manual MCACC setup menu.


The volume increases to the 0.0 dB reference level.





2 Adjust the level of the left channel.


This will be the reference speaker level, so you may want to keep the level around **0.0dB** so that you'll have plenty of room to adjust the other speaker levels.



• After pressing **ENTER**, test tones will be output.

3 Select each channel in turn and adjust the levels (+/-10.0 dB) as necessary.

Use ←/→ to adjust the volume of the speaker you selected to match the reference speaker. When it sounds like both tones are the same volume, press ↓ to confirm and continue to the next channel.



- For comparison purposes, the reference speaker will change depending on which speaker you select.
- If you want to go back and adjust a channel, simply use ↑/↓ to select it.

4 When you're finished, press RETURN.


You will return to the Manual MCACC setup menu.

Fine Speaker Distance

• Default setting: 10'00" (all speakers)

For proper sound depth and separation with your system, it is necessary to add a slight bit of delay to some speakers so that all sounds will arrive at the listening position at the same time. You can adjust the distance of each speaker in 1/2 inch increments. The following setting can help you make detailed adjustments that you may not achieve using the *Manual speaker setup* on page 90.

1 Select 'Fine SP Distance' from the Manual MCACC setup menu.






2 Adjust the distance of the left channel from the listening position.

3 Select each channel in turn and adjust the distance as necessary.

Use ←/→ to adjust the delay of the speaker you selected to match the reference speaker. The delay is measured in terms of speaker distance from 0'00-1/2" to 45'00".



Listen to the reference speaker and use it to measure the target channel. From the listening position, face the two speakers with your arms outstretched pointing at each speaker. Try to make the two tones sound as if they are arriving simultaneously at a position slightly in front of you and between your arm span.¹



When it sounds like the delay settings are matched up, press **\(\bigs \)** to confirm and continue to the next channel.

- For comparison purposes, the reference speaker will change depending on which speaker you select.
- If you want to go back and adjust a channel, simply use ↑/↓ to select it.

4 When you're finished, press RETURN.

You will return to the **Manual MCACC** setup menu.


Standing Wave

Default setting: ON²/ATT 0.0dB (all filters)

Acoustic standing waves occur when, under certain conditions, sound waves from your speaker system resonate mutually with sound waves reflected off the walls in your listening area. This can have a negative effect on the overall sound, especially at certain lower frequencies. Depending on speaker placement, your listening position, and ultimately the shape of your room, it results in an overly resonant ('boomy') sound. The Standing Wave Control uses filters to reduce the effect of overly resonant sounds in your listening area. During playback of a source, you can customize the filters used for Standing Wave Control for each of your MCACC presets.³

1 Select 'Standing Wave' from the Manual MCACC setup menu.





- 1 If you can't seem to achieve this by adjusting the distance setting, you may need to change the angle of your speakers very slightly.
- For better audibility, the subwoofer emits a continuous test tone (oscillating pulses are heard from your other speakers). Note that it may be difficult to compare this tone with the other speakers in your setup (depending on the low frequency response of the reference speaker).
- 2 You can switch on or off the Standing Wave and Acoustic Calibration EQ feature in the **AUDIO PARAMETER** menu. See Setting the Audio options on page 66 for more on this.
- 3 Since they will be overwritten, you may want to save the standing wave settings made with the Auto MCACC Setup to another MCACC preset.
- Standing Wave control filter settings cannot be changed during playback of sources using the HDMI connection.
- When Standing Wave is selected for an MCACC preset memory where STAND.WAVE is set to OFF in the AUDIO PARAMETER, STAND.WAVE ON is automatically selected.

2 Adjust the parameters for the Standing Wave Control.

- Filter Channel Select the channel to which you will apply the filter(s): MAIN (all except center channel and subwoofer), Center or SW (subwoofer).
- TRIM (only available when the filter channel above is SW) – Adjust the subwoofer channel level (to compensate for the difference in output post-filter).
- Freq/Q/ATT These are the filter parameters where
 Freq represents the frequency you will be targeting
 and Q is the bandwidth (the higher the Q, the
 narrower the bandwidth, or range) of the attenuation
 (ATT, the amount of reduction to the targeted
 frequency).

3 When you're finished, press RETURN.


You will return to the Manual MCACC setup menu.

Acoustic Calibration EQ Adjust


• Default setting: **ON**¹/**0.0dB** (all channels/bands)

Acoustic Calibration Equalization is a kind of room equalizer for your speakers (excluding the subwoofer). It works by measuring the acoustic characteristics of your room and neutralizing the ambient characteristics that can color the original source material (providing a 'flat' equalization setting). If you're not satisfied with the adjustment provided in *Automatically setting up for surround sound (Auto MCACC)* on page 41 or *Automatic MCACC (Expert)* on page 78, you can also adjust these settings manually to get a frequency balance that suits your tastes.

1 Select 'EQ Adjust' from the Manual MCACC setup menu.



2 Select the channel(s) you want and adjust to your liking.



Use **↑**/**↓** to select the channel.

Use \leftarrow/\Rightarrow to select the frequency and \uparrow/\downarrow to boost or cut the EQ. When you're finished, go back to the top of the screen and press \leftarrow to return to **Ch**, then use \uparrow/\downarrow to select the channel.

 The OVER! indicator shows in the display if the frequency adjustment is too drastic and might distort. If this happens, bring the level down until OVER! disappears from the display.

🙀 Тір

Changing the frequency curve of one channel too drastically will affect the overall balance. If the speaker balance seems uneven, you can raise or lower channel levels using test tones with the TRIM feature. Use ↑/ ↓ to select TRIM, then use ←/→ to raise or lower the channel level for the current speaker.

3 When you're finished, press RETURN.

You will return to the **Manual MCACC** setup menu.

Acoustic Calibration EQ Professional

This setup minimizes the unwanted effects of room reverberation by allowing you to calibrate your system based on the direct sound coming from the speakers. It can also provide you with a graphical output of the frequency response of your room.²

How to use Acoustic Calibration EQ Professional

If you find that lower frequencies seem overly reverberant in your listening room (i.e. it sounds 'boomy'), or that different channels seem to exhibit different reverb characteristics, select **EQ Pro & S-Wave** (or **ALL**) for the **Auto MCACC** setting in *Automatic MCACC (Expert)* on page 78 to calibrate the room automatically. This should provide a balanced calibration that suits the characteristics of your listening room.

If you still aren't satisfied with the results, the manual **Advanced EQ Setup** (below) provides a more customized calibration of your system using the direct sound of the speakers. This is done with the help of a graphical output that can be displayed on-screen, or using a computer (with software available from Pioneer — see *Output PC* on page 88).

¹ When EQ Adjust is selected for an MCACC preset memory where EQ is set to OFF in the AUDIO PARAMETER, EQ ON is automatically selected.

² This system allows you to customize your system calibration with the help of a graphical output that can be displayed on-screen, or using a computer (with software available from Pioneer—see *Output PC* on page 88 for more on this).

How to interpret the graphical output


The graph shows decibels on the vertical axis and time (in milliseconds) on the horizontal axis. A straight line indicates a flat-response room (no reverb), whereas a sloping line indicates the presence of reverberation when outputting test tones. The sloping line will eventually flatten out when the reverberant sound stabilizes (this usually takes about 100 ms or so).

By analyzing the graph, you should be able to see how your room is responding to certain frequencies. Differences in channel level and speaker distance are taken into account automatically (compensation is provided for comparison purposes), and the frequency measurements can be examined both with and without the equalization performed by this receiver.¹

Setting Acoustic Calibration EQ Professional according to your room characteristics

Using the manual setup, you can set the time period at which the frequency response is analyzed, pinpointing the time that is best for system calibration with your particular room characteristics.


The graph below shows the difference between conventional acoustic calibration and professional calibration (the gray circle indicates the point where the microphone captures sound during frequency analysis).



As soon as audio is output from your speaker system, it is influenced by room characteristics, such as walls, furniture, and the dimensions of the room. The sooner the frequency analysis, the less it is influenced by the room. We recommend an earlier time setting of **30-50ms** to compensate for two major factors that will influence the sound of most rooms:


Reverberance of high vs. low frequencies – Depending on your room, you may find that lower frequencies seem overly reverberant compared to higher frequencies (i.e. your room sounds 'boomy').

frequencies seem overly reverberant compared to higher frequencies (i.e. your room sounds 'boomy'). This may result in a skewed frequency analysis if the measurement is done too late.



Reverb characteristics for different channels -

Reverb characteristics can be somewhat different for each channel. Since this difference increases as the sound is influenced by the various room characteristics, it is often better to capture a frequency analysis early on for smoother mixing of channel frequencies/sounds.




If your room isn't affected by the factors above, it is often not necessary to make a **30-50ms** setting. Later time settings may provide a more detailed sound experience with your speaker system. It is best to try and see what works best for your particular room.

Note that changing the room (for example, moving furniture or paintings) will affect the calibration results. In such cases, you should recalibrate your system.

Using Acoustic Calibration EQ Professional

1 Select 'EQ Professional', then press ENTER.





Note

1 Note that due to an effect known as 'group delay', lower frequencies will take longer to be generated than higher frequencies (this is most obvious when comparing the frequencies at 0 ms). This initial slope is not a problem (i.e. excessive reverb) with your listening room.

The Advanced MCACC menu

- 2 Select an option and press ENTER.
 - Reverb Measurement Use this to measure the reverb characteristics before and after calibration. (For graphical output using a PC, see Connecting a PC for Advanced MCACC output on page 36 to connect an RS-232C cable before selecting this option.)
 - Reverb View You can check the reverb measurements made for specified frequency ranges in each channel.¹ This can also be used to compare the reverb characteristics before and after calibration.²
 - Advanced EQ Setup Use this to select the time period that will be used for frequency adjustment and calibration, based on the reverb measurement of your listening area. Note that customizing system calibration using this setup will alter the settings you made in Automatically setting up for surround sound (Auto MCACC) on page 41 or Automatic MCACC (Expert) on page 78 and is not necessary if you're satisfied with these settings.
- 3 If you selected 'Reverb Measurement', select EQ ON or OFF, and then START.




The following options determine how the reverb characteristics of your listening area are displayed in **Reverb View** and **Output PC** (see *Connecting a PC for Advanced MCACC output* on page 36):

- **EQ OFF** You will see the reverb characteristics of your listening area *without* the equalization performed by this receiver (before calibration).
- EQ ON You will see the reverb characteristics of your listening area with the equalization performed by this receiver (after calibration).³ Note that the EQ response may not appear entirely flat due to adjustments necessary for your listening area.⁴

When the reverb measurement is finished, you can select **Reverb View** to see the results on-screen. See *Professional Calibration EQ graphical output* on page 102 for troubleshooting information.

4 If you selected 'Reverb View', you can check the reverb characteristics for each channel. Press RETURN when you're done.



The reverb characteristics are displayed when the **Full Auto MCACC** or **Reverb Measurement** measurements are conducted.⁵


Use ←/→ to select the channel, frequency and calibration setting you want to check. Use ↑/↓ to go back and forth between the three. The reverb characteristics graph before and after EQ calibration can be displayed by selecting **Calibration:** Before / After. Note that the markers on the vertical axis indicate decibels in 2 dB steps.

∅ Note

- If the **Reverb View** procedure is performed after the *Automatically setting up for surround sound (Auto MCACC)* on page 41 or **Reverb Measurement** operation, depending on the standing wave control setting, differences may appear on the reverb graph. With the Auto MCACC function, the reverberations are measured with the standing waves controlled, so the reverb characteristics graph shows the characteristics with the effect of the standing waves eliminated. By contrast, the **Reverb Measurement** function measures the reverberations without controlling the standing waves, so the graph indicates the reverb characteristics including the effect of the standing waves. If you wish to check the reverb characteristics of the room itself (with the standing waves as such), we recommend using the **Reverb Measurement** function.
- 2 The reverb characteristics after calibration can be displayed even after performing the **Full Auto MCACC** function (*Automatically setting up for surround sound (Auto MCACC*) on page 41). In this case, the display shows the predicted reverb characteristics after calibration. If the measurements are taken using the Reverb Measurement command (page 85) with the equalizer on, the actually measured reverb characteristics after calibration are displayed.
- 3 The calibration corresponding to the currently selected MCACC preset will be used when EQ ON is selected. To use another MCACC preset, exit the HOME MENU and press MCACC to select it before pressing HOME MENU.
- The predicted reverb characteristics after calibration can be acquired with the **Full Auto MCACC** function (*Automatically setting up for surround sound (Auto MCACC*) on page 41), but here the actually measured reverb characteristics after calibration can be acquired.
- 4 After auto calibration with EQ Type: SYMMETRY (Full Auto MCACC, etc.), the graph for the inferred reverb characteristics can be displayed by selecting Reverb View. To display the actually measured reverb characteristics after EQ calibration, measure with EQ ON.
- 5 The **After** display when measurements have been made using the **Full Auto MCACC** or **Auto MCACC** (ALL) function shows the graph for the inferred reverb characteristics after **EQ Type: SYMMETRY** calibration.
- 6 The reverb characteristics graph is overwritten each time the reverberations are measured. **No Data** is displayed if there is no reverb characteristic data, for example before measurements have been taken.

5 If 'Advanced EQ Setup' is selected, select the MCACC memory to be stored, then enter the desired time setting for calibration, and then select START.

Based on the reverb measurement above, you can choose the time period that will be used for the final frequency adjustment and calibration. Even though you can make this setting without reverb measurement, it is best to use the measurement results as a reference for your time setting. For an optimal system calibration based on the direct sound coming from the speakers, we recommend using the **30-50ms** setting.





Use \leftarrow/\rightarrow to select the setting. Use \uparrow/\downarrow to switch between them.

Select the setting from the following time periods (in milliseconds): **0-20ms**, **10-30ms**, **20-40ms**, **30-50ms**, **40-60ms**, **50-70ms** and **60-80ms**. This setting will be applied to all channels during calibration.

When you're finished, select **START**. It will take about 2 to 4 minutes for the calibration to finish.

After the Acoustic Calibration Equalization is set, you are given the option to check the settings on-screen.

Checking MCACC Data


At the procedure of *Automatically setting up for surround sound (Auto MCACC)* on page 41, the procedure of *Automatic MCACC (Expert)* on page 78 or after fine-adjusting at *Manual MCACC setup* on page 80, you can check your calibrated settings using the GUI screen or, if a computer is connected, on the computer's screen.

1 Press RECEIVER, then press HOME MENU.

A Graphical User Interface (GUI) screen appears on your TV. Use ↑/↓/←/→ and ENTER to navigate through the screens and select menu items. Press RETURN to confirm and exit the current menu.

2 Select 'MCACC Data Check' from the HOME MENU.






- 3 Select the setting you want to check.
- Speaker Setting Used to check the settings of the speaker systems. See Speaker Setting below for more on this.
- Channel Level Used to check the output level of the different speakers. See Channel Level below for more on this.
- **Speaker Distance** Used to check the distance to the different speakers. See *Speaker Distance* below for more on this.
- **Standing Wave** Used to check the standing wave control filter settings. See *Standing Wave* on page 87 for more on this.
- Acoustic Cal EQ Used to check the calibration values of the listening environment's frequency response. See Acoustic Cal EQ on page 87 for more on this.
- Output PC See Output PC on page 88 for more on this.
- 4 Press RETURN to go back to MCACC Data Check menu, repeating steps 2 and 3 to check other settings.
- 5 When you're finished, press RETURN.
 You will return to the **HOME MENU**.

Speaker Setting

Use this to display the speaker size and number of speakers. See *Speaker Setting* on page 91 for more on this.

1 Select 'Speaker Setting' from the MCACC Data Check menu.




2 Select the channel you want to check.

Use ↑/↓ to select the channel. The corresponding channel on the layout diagram is highlighted.

Channel Level

Use this to display the level of the various channels. See *Channel Level* on page 92 for more on this.

1 Select 'Channel Level' from the MCACC Data Check menu.




2 When 'MCACC' is highlighted, use ←/→ to select the MCACC preset you want to check.

The level of the various channels set at the selected MCACC preset is displayed. '---' is displayed for channels that are not connected.

Speaker Distance

Use this to display the distance from the different channels to the listening position. See *Speaker Distance* on page 93 for more on this.

1 Select 'Speaker Distance' from the MCACC Data Check menu.




2 When 'MCACC' is highlighted, use ←/⇒ to select the MCACC preset you want to check.

The distance from the various channels set at the selected MCACC preset is displayed. '---' is displayed for channels that are not connected.

Standing Wave

Use this to display the standing wave related adjustment values for the various MCACC memories. See *Standing Wave* on page 82 for more on this.

1 Select 'Standing Wave' from the MCACC Data Check menu.



2 When 'Filter Channel' is highlighted, use ↑/↓ to select the channel for which you want to check standing wave control.


The standing wave related calibration value for the selected channel stored at the selected MCACC preset and its graph are displayed.

3 Press ← to highlight 'MCACC', then use ↑/↓ to select the MCACC preset you want to check.

Acoustic Cal EQ

Use this to display the calibration values for the frequency response of the various channels set in the different MCACC presets. See *Acoustic Calibration EQ Adjust* on page 83 for more on this.

1 Select 'Acoustic Cal EQ' from the MCACC Data Check menu.



2 When 'Ch' is highlighted, use ↑/↓ to select the channel.

The calibration value for the frequency response of the selected channel stored at the selected MCACC preset and its graph are displayed.

3 Press ← to highlight 'MCACC', then use ↑/↓ to select the MCACC preset you want to check.

Output PC

Before continuing, make sure you have completed step 2 in Checking MCACC Data on page 86. The data measured with the Advanced MCACC function is transmitted to the connected computer. The 3D graphs of the reverb characteristics before and after calibration and the MCACC results (parameters) can be checked.

1 Select 'Output PC' from MCACC Data Check menu and press ENTER.

When the receiver is ready for transmission, Start the MCACC application on your PC shows on the GUI screen.



2 Start the MCACC application on your computer.

Follow the instructions provided with the application. It will take about ten seconds for the transmission to complete, then you will be able to analyze the output on your computer. The various parameters and the reverb characteristics data used for display on the computer are not cleared when the power is turned off. If the reverb characteristics are re-measured, however, the data is overwritten.2

3 When you're finished, press RETURN.

You will return to the MCACC Data Check menu. Continue with other operations in the MCACC Data **Check** menu if necessary. Press **RETURN** again to exit the MCACC Data Check menu.

Data Management


This system allows you to store up to six MCACC presets, allowing you to calibrate your system for different listening positions (or frequency adjustments for the same listening position). This is useful for alternate settings to match the kind of source you're listening to and where you're sitting (for example, watching movies from a sofa, or playing a video game close to the TV).


From this menu you can copy from one preset to another. name presets for easier identification and clear any ones vou don't need.

1 Press RECEIVER, then press HOME MENU.

A Graphical User Interface (GUI) screen appears on your TV. Use $\uparrow/\downarrow/\leftarrow/\Rightarrow$ and **ENTER** to navigate through the screens and select menu items. Press RETURN to confirm and exit the current menu.

2 Select 'Data Management' from the HOME MENU.





- Select the setting you want to adjust.
 - Memory Rename Name your MCACC presets for easy identification (see Renaming MCACC presets
 - MCACC Memory Copy Copy settings from one MCACC preset to another (see Copying MCACC preset data below).
 - MCACC Memory Clear Clear any MCACC presets that you don't want (see Clearing MCACC presets on page 89).

- 1 To transmit data, the receiver and computer must be connected using an RS-232C cable and a special application must be installed on the computer. See Connecting a PC for Advanced MCACC output on page 36 for more on this.
- 2 Only one set of reverb characteristics is stored on the receiver. If you wish to compare several different measurement results, transmit the data to the computer each time reverb measurements are taken.
- 3 This can be done in Automatically setting up for surround sound (Auto MCACC) on page 41 or Automatic MCACC (Expert) on page 78, either of which you should have already completed.

Renaming MCACC presets

If you have several different MCACC presets that you're using, you may want to rename them for easier identification.

1 Select 'Memory Rename' from the Data Management setup menu.





2 Select the MCACC preset you want to rename, then select an appropriate preset name.

Use \uparrow/\downarrow to select the preset, then \leftarrow/\Rightarrow to select a preset name.


3 Repeat for as many MCACC presets as necessary, then press RETURN when you're finished.


You will return to the **Data Management** setup menu.

Copying MCACC preset data

If you want to manually adjust the Acoustic Calibration EQ (see *Manual MCACC setup* on page 80), we recommend copying your current settings¹ to an unused MCACC preset. Instead of just a flat EQ curve, this will give you a reference point from which to start.

1 Select 'MCACC Memory Copy' from the Data Management setup menu.





- 2 Select the setting you want to copy.
 - All Data Copies all the settings of the selected MCACC preset memory.
 - Level & Distance Copies only the channel level and speaker distance settings of the selected MCACC preset memory.
- 3 Select the MCACC preset you'll be copying the settings 'From', then specify where you want to copy them ('To').

Make sure you don't overwrite an MCACC preset you're currently using (this can't be undone).

4 Select 'OK' to confirm and copy the settings.

When MCACC Memory Copy? is displayed, select YI

When **MCACC Memory Copy?** is displayed, select **YES**. If **NO** is selected, the memory is not copied.

Completed! shows in the GUI screen to confirm the MCACC preset has been copied, then you automatically return to the **Data Management** setup menu.

Clearing MCACC presets

If you are no longer using one of the MCACC presets stored in memory, you can choose to clear the calibration settings of that preset.

1 Select 'MCACC Memory Clear' from the Data Management setup menu.





2 Select the MCACC preset you want to clear.

Make sure you don't clear an MCACC preset you're currently using (this can't be undone).

3 Select 'OK' to confirm and clear the preset. When MCACC Memory Clear? is displayed, select YES. If NO is selected, the memory is not cleared.

Completed! shows in the GUI screen to confirm the MCACC preset has been cleared, then you automatically return to the **Data Management** setup menu.

Chapter 11:

The system and the other setup

Making receiver settings from the System Setup menu


The following section describes how to change the speaker-related settings manually and make various other settings (input selection, OSD language selection,




- Switch on the receiver and your TV. Use the & RECEIVER button to switch on. 1
 - If headphones are connected to the receiver. disconnect them.
- 2 Press RECEIVER, then press HOME MENU.²

A Graphical User Interface (GUI) screen appears on your TV. Use $\uparrow/\downarrow/\leftarrow/\Rightarrow$ and ENTER to navigate through the screens and select menu items. Press RETURN to confirm and exit the current menu.

- Press **HOME MENU** at any time to exit the **HOME** MENU.
- 3 Select 'System Setup' from the HOME MENU, then press ENTER.



Select the setting you want to adjust.



- Manual SP Setup Sets the type of connection used for surround back terminals and the size, number distance and overall balance of the connected speakers (see Manual speaker setup below).
- Input Setup Specifies what you've connected to the digital, HDMI and component video inputs (see The Input Setup menu on page 43).
- OSD Language The GUI screen's display language can be changed (see Changing the OSD display language (OSD Language) on page 40).
- Other Setup Changes customized settings to reflect how you are using the receiver (see *The Other* Setup menu on page 94).

Manual speaker setup

This receiver allows you to make detailed settings to optimize the surround sound performance. You only need to make these settings once (unless you change the placement of your current speaker system or add new speakers).

These settings are designed to customize your system, but if you're satisfied with the settings made in Automatically setting up for surround sound (Auto MCACC) on page 41, it isn't necessary to make all of these settings.

CAUTION

The test tones used in the **Manual SP Setup** are output at high volume.

Select 'Manual SP Setup', then press ENTER.

See Making receiver settings from the System Setup menu above if you're not already at this screen.





Select the setting you want to adjust.

If you are doing this for the first time, you may want to adjust these settings in order:

Note

1 Make sure not to switch off the power when using the System Setup menu.

- 2 You can't use the **HOME MENU** when the iPod/USB, XM or SIRIUS Radio input function is selected (in either the main or sub zone).
 - VSX-23TXH: When you set ZONE 2, ZONE 3 or ZONE 2&3 to ON (page 69), you can't use the HOME MENU.
- VSX-21TXH: When you set ZONE 2 to ON (page 69), you can't use the HOME MENU.

- Surr Back System Specifies how you are using your surround back speakers (see below).
- Speaker Setting Specifies the size and number of speakers you've connected (see below).
- Channel Level Adjusts the overall balance of your speaker system (page 92).
- Speaker Distance Specifies the distance of your speakers from the listening position (page 93).
- **X-Curve** Adjusts the tonal balance of your speaker system for movie soundtracks (page 93).
- **THX Audio Setting** Specifies whether you are using a THX speaker setup (page 93).
- 3 Make the adjustments necessary for each setting, pressing RETURN to confirm after each screen.

Surround back speaker setting


• Default setting: Normal

There are several ways you can use the surround back speaker channels with this system. In addition to a normal home theater setup where they are used for the surround back speakers, they can be used for bi-amping the front speakers or as an independent speaker system in another room.

1 Select 'Surr Back System' from the Manual SP Setup menu.

See Making receiver settings from the System Setup menu on page 90 if you're not already at this screen.





2 Select the surround back speaker setting.

- Normal Select for normal home theater use with surround back speakers in your main (speaker system A) setup.
- **Speaker B** Select to use the (surround back) B speaker terminals to listen to stereo playback in another room (see *Switching the speaker system* on page 69).
- Front Bi-Amp Select this setting if you're biamping your front speakers (see *Bi-amping your speakers* on page 21).
- ZONE 2 Select to use the (surround back) B speaker terminals for an independent system in another zone (see *Using the MULTI-ZONE controls* on page 69).

3 When 'Setting Change?' is displayed, select Yes.

If **No** is selected, the setting is not changed.

You will return to the **Manual SP Setup** menu.

Speaker Setting

Use this setting to specify your speaker configuration (size, number of speakers and crossover frequency)¹. It is a good idea to make sure that the settings made in *Automatically setting up for surround sound (Auto MCACC)* on page 41 are correct. Note that this setting applies to all MCACC presets, and cannot be set independently.

1 Select 'Speaker Setting' from the Manual SP Setup menu.





2 Choose the set of speakers that you want to set, then select a speaker size.

Use ←/→ to select the size (and number) of each of the following speakers:²

- Front Select LARGE if your front speakers reproduce bass frequencies effectively, or if you didn't connect a subwoofer. Select SMALL to send the bass frequencies to the subwoofer.
- Center Select LARGE if your center speaker reproduces bass frequencies effectively, or select SMALL to send bass frequencies to the other speakers or subwoofer. If you didn't connect a center speaker, choose NO (the center channel is sent to the front speakers).
- Surr Select LARGE if your surround speakers reproduce bass frequencies effectively. Select SMALL to send bass frequencies to the other speakers or subwoofer. If you didn't connect surround speakers choose NO (the sound of the surround channels is sent to the front speakers or a subwoofer).

Ø Note

1 If you're using a THX speaker setup, set all speakers to SMALL.

2 If you select **SMALL** for the front speakers the subwoofer will automatically be fixed to **YES**. Also, the center, surround and surround back speakers can't be set to **LARGE** if the front speakers are set to **SMALL**. In this case, all bass frequencies are sent to the subwoofer.


- SB Select the number of surround back speakers you have (one, two or none). Select LARGEx2 or LARGEx1 if your surround back speakers reproduce bass frequencies effectively. Select SMALLx2 or SMALLx1 to send bass frequencies to the other speakers or subwoofer. If you didn't connect surround back speakers choose NO.
- **SW** LFE signals and bass frequencies of channels set to **SMALL** are output from the subwoofer when **YES** is selected. Choose the **PLUS** setting if you want the subwoofer to output bass sound continuously or you want deeper bass (the bass frequencies that would normally come out the front and center speakers are also routed to the subwoofer). If you did not connect a subwoofer choose **NO** (the bass frequencies are output from other speakers).
- **3 Select 'X.OVER' and set the crossover frequency.** Frequencies below this point will be sent to the subwoofer (or **LARGE** speakers).
- **4** When you're finished, press RETURN. You will return to the **Manual SP Setup** menu.

Channel Level

Using the channel level settings, you can adjust the overall balance of your speaker system, an important factor when setting up a home theater system.

1 Select 'Channel Level' from the Manual SP Setup menu.





2 Select a setup option.

- MANUAL Move the test tone manually from speaker to speaker and adjust individual channel levels.
- AUTO Adjust channel levels as the test tone moves from speaker to speaker automatically.

3 Confirm your selected setup option.

The test tones will start after you press **ENTER**.



4 Adjust the level of each channel using ←/→.

If you selected **MANUAL**, use **↑**/**↓** to switch speakers. The **AUTO** setup will output test tones in the order shown on-screen:



Adjust the level of each speaker as the test tone is emitted.⁴

5 When you're finished, press RETURN. You will return to the Manual SP Setup menu.



You can change the channel levels by press
 RECEIVER, then press CH LEVEL, and then using ←/

→ on the remote control.⁵

- 1 If you selected Speaker B, ZONE 2 or Front Bi-Amp (in Surround back speaker setting on page 91) you can't adjust the surround back settings.
 - If the surround speakers are set to NO, the surround back speakers will automatically be set to NO.
- If you select one surround back speaker only, make sure that speaker is hooked up to the left surround back terminal.
- 2 If you have a subwoofer and like lots of bass, it may seem logical to select LARGE for your front speakers and PLUS for the subwoofer. This may not, however, yield the best bass results. Depending on the speaker placement of your room you may actually experience a decrease in the amount of bass due low frequency cancellations. In this case, try changing the position or direction of speakers. If you can't get good results, listen to the bass response with it set to PLUS and YES or the front speakers set to LARGE and SMALL alternatively and let your ears judge which sounds best. If you're having problems, the easiest option is to route all the bass sounds to the subwoofer by selecting SMALL for the front speakers.
- 3 This setting decides the cutoff between bass sounds playing back from the speakers selected as LARGE, or the subwoofer, and bass sounds playing back from those selected as SMALL. It also decides where the cutoff will be for bass sounds in the LFE channel.
- If you're using a THX speaker setup, confirm that the crossover frequency is set to 80Hz.
- 4 If you are using a Sound Pressure Level (SPL) meter, take the readings from your main listening position and adjust the level of each speaker to 75 dB SPL (C-weighting/slow reading).
- The subwoofer test tone is output at low volumes. You may need to adjust the level after testing with an actual soundtrack.
- 5 The channel level cannot be adjusted using this procedure while making settings on **HOME MENU**.

Speaker Distance

For good sound depth and separation from your system, you need to specify the distance of your speakers from the listening position. The receiver can then add the proper delay needed for effective surround sound.

1 Select 'Speaker Distance' from the Manual SP Setup menu.





2 Adjust the distance of each speaker using ←/→.

You can adjust the distance of each speaker in 1/2 inch increments.

3 When you're finished, press RETURN.

You will return to the Manual SP Setup menu.




 For best surround sound, make sure the surround back speakers are the same distance from the listening position.

X-Curve

Most soundtracks mixed for cinema sound too bright when played back in large rooms. The X-Curve setting acts as a kind of re-equalization for home theater listening, and restores proper tonal balance of movie soundtracks.¹

1 Select 'X-Curve' from the Manual SP Setup menu.



2 Choose the X-Curve setting you want.

Use ←/→ to adjust the setting. The X-Curve is expressed as a downwards slope in decibels per octave, starting at 2 kHz. The sound becomes less bright as the slope increases (to a maximum of **–3.0dB/oct**). Use the following guidelines to set the X-Curve according to your room size:

Room size (ft ²)	≤400	≤550	≤650	≤800	≤2200	≤12000
X-Curve (dB/oct)	-0.5	-1.0	-1.5	-2.0	-2.5	-3.0

- If you select **OFF**, the frequency curve will be flat and the X-Curve has no effect.
- 3 When you're finished, press RETURN.


THX Audio Setting

This menu allows the user to adjust various THX features including Loudness Plus, SB Speaker Position, THX Select2 Subwoofer (on/off), and Boundary Gain Control. Please see page 109 for a details regarding these THX features.

1 Select 'THX Audio Setting' from the Manual SP setup menu.



2 Select either ON or OFF for THX Loudness Plus setting.




3 Specify the distance of your surround back speakers from each other.



- 0-1 ft Surround back speakers within 1 foot apart (best for THX surround sound).
- >1- 4 ft Surround back speakers between 1 and 4 feet apart.
- 4 ft< Surround back speakers more than 4 feet apart (default).


¹ Since the principal is the same, X-Curve isn't applied when you're using any of the Home THX modes (see *Using the Home THX modes* on page 57).

4 Specify whether your subwoofer is THX Select2 certified or not.



If your subwoofer isn't THX Select2 certified, but you still want to switch boundary gain compensation on, select **YES** here, but the effect might not work properly.

5 Select either ON or OFF for Boundary Gain Compensation (BGC) setting.



6 When you're finished, press RETURN. You will return to the Manual SP Setup menu.


The Other Setup menu

The **Other Setup** menu is where you can make customized settings to reflect how you are using the receiver.

1 Press RECEIVER on the remote control, then press HOME MENU.

A Graphical User Interface (GUI) screen appears on your TV. Use $\uparrow / \downarrow / \leftarrow / \rightarrow$ and **ENTER** to navigate through the screens and select menu items. Press **RETURN** to confirm and exit the current menu.

- 2 Select 'System Setup' from the HOME MENU.
- 3 Select 'Other Setup', then press ENTER.





4 Select the setting you want to adjust.

If you are doing this for the first time, you may want to adjust these settings in order:

• **KURO LINK Setup** – Synchronizes this receiver with your Pioneer component supporting KURO LINK (see *KURO LINK Setup* on page 64).

- Multi Ch In Setup Specifies the optional settings for a multi-channel input (page 94).
- **ZONE Audio Setup** Specifies the volume setting for a MULTI-ZONE setup (page 95).
- **Power ON Level Setup** Specifies the volume level set when the power is turned on (page 95).
- Volume Limit Setup Limits the maximum volume (page 95).
- Remote Control Mode Setup Sets this receiver's remote control mode (page 96).
- Flicker Reduction Adjusts the way the GUI screen looks (page 96).
- 5 Make the adjustments necessary for each setting, pressing RETURN to confirm after each screen.

Multi Channel Input Setup

You can adjust the level of the subwoofer for a multichannel input. Also, when the multi-channel input is selected as an input function, you can display the video images of other input functions. In the Multi Channel Input Setup, you can assign a video input to the multichannel input.

1 Select 'Multi Ch In Setup' from the Other Setup




- 2 Select the 'SW Input Gain' setting you want.
- **0dB** Outputs sound of the subwoofer at the level originally recorded on the source.
- +10dB Outputs sound of the subwoofer at the level increased by 10 dB.



3 Select the 'Video Input' setting you want.

When the multi-channel input is selected as an input function, you can display the video images of other input functions. The video input can be selected from the following: **DVD**, **TV/SAT**, **DVR**, **VIDEO**, **OFF**.



4 When you're finished, press RETURN. You will return to the **Other Setup** menu.

ZONE Audio Setup

If you've made MULTI-ZONE connections (see *Using the MULTI-ZONE controls* on page 69), you may need to specify your volume setting.

1 Select 'ZONE Audio Setup' from the Other Setup menu.





2 Select the volume level setting of ZONE 2¹ and ZONE 3 (VSX-23TXH only).

- Variable Use this setting if you've connected a power amplifier in the sub room (this receiver is simply being used as a pre-amp) and you will be using this receiver's controls to adjust the volume.
- Fixed Use this setting if you've connected a fully integrated amplifier (such as another Pioneer VSX receiver) in the sub room and want to use that receiver's volume controls.

With the **Fixed** setting, the source is sent from this receiver at maximum volume, so make sure the volume is quite low in the sub zone at first, and then experiment to find the correct level.

3 When you're finished, press RETURN.

You will return to the **Other Setup** menu.

Power ON Level Setup

The volume can be set so that it is always set to the same level when the receiver's power is turned on.

1 Select 'Power ON Level Setup' from the Other Setup menu.





2 Select the Power ON Level setting you want.

- LAST When the power is turned on, the volume is set to the same level as when the power was last turned off.
- "---" When the power is turned on, the volume is set to minimum level.
- **-80.0dB** to **+12.0dB** Specify the volume to be set when the power is turned, in steps of 0.5 dB.

It is not possible to set a volume level greater than the value specified at Volume Limit Setup.

3 When you're finished, press RETURN.


You will return to the **Other Setup** menu.

Volume Limit Setup

Use this function to limit the maximum volume. The volume cannot be increased above the level set here, even by operating **MASTER VOLUME** button (or the dial on the front panel).

$1 \quad \text{Select 'Volume Limit Setup' from the Other Setup menu.} \\$





2 Select the Volume Limit setting you want.

- **OFF** The maximum volume is not limited.
- -20.0dB/-10.0dB/0.0dB The maximum volume is limited to the value set here.

3 When you're finished, press RETURN.

You will return to the **Other Setup** menu.

Remote Control Mode Setup

· Default setting: 1

This sets this receiver's remote control mode to prevent erroneous operation when multiple units of the receiver are being used.1

Select 'Remote Control Mode Setup' from the Other Setup menu.





- Select the Remote Control Mode setting you want.
- Select "OK" to change the remote control mode. 3
- 4 Follow the instructions on the screen to change the remote control's setting.

See Operating multiple receivers on page 73.

5 When you're finished, press RETURN.

You will return to the **Other Setup** menu.

Flicker Reduction Setup

· Default setting: 4

The GUI screen's resolution can be increased. If you feel the GUI screen is hard to see, try changing this setting. Note this setting only affects the GUI screen; it has no influence on the video output.

Select 'Flicker Reduction Setup' from the Other Setup menu.





- Select the Flicker Reduction setting you want.
- When you're finished, press RETURN.

You will return to the **Other Setup** menu.

Chapter 12:

Additional information

Speaker Setting Guide

In order to achieve an even better surround effect, it is important to accurately position the speakers and make their volume and tone characteristics uniform so as to finely focus the multi-channel sound.

The three major elements in positioning the speakers are **distance**, **angle** and **orientation** (the direction in which the speakers are pointing).

Distance: The distance of all the speakers should be equal.

Angle: The speakers should be horizontally symmetrical. **Orientation**: The orientation should be horizontally symmetrical.

In most homes, however, it is not possible to achieve this environment. For the distance, on this receiver it is possible to automatically correct the speaker distance electrically to a precision of 1/2 inch using the Auto MCACC Setup function (page 41).

Step 1: Speaker layout and distance adjustment

Use speaker stands or the like to make sure the speakers are steady, and leave at least 10 cm (4 inches) from the surrounding walls. Position the speakers attentively so that the speakers on the left and right are at equal angles from the listening position (center of the adjustments). (We recommend using cords, etc., when adjusting the layout.) Ideally all the speakers should be equidistant from the listening position.

😭 Tip

 If the speakers cannot be set at equal distances (on a circle), use the Auto MCACC Setup speaker distance correction and Fine Speaker Distance functions to make them equalize the distance artificially.

Step 2: Adjusting the speaker height

Adjust the heights (angles) of the different speakers.

Adjust so that the front speaker units reproducing midand high frequencies is roughly at the height of the ears.

If the center speaker cannot be set at the same height as the front speakers, adjust its angle of elevation to point it to the listening position.

Set surround speaker 1 so that it is not under the height of the ears.

Step 3: Adjusting the speaker orientation

If the left and right speakers are not pointing in the same direction, the tone will not be the same on the right and left, and as a result the sound field will not be reproduced properly. However, if all the speakers are pointed towards the listening position, the sound field will seem cramped. Testing by the Pioneer Multi-channel Research Group has shown that a good sense of sound positioning can be achieved by pointing all the speakers towards an area 30 cm (12 inches) to 80 cm (31 inches) behind the listening position (between the surround speakers and the listening position).

However, the sense of sound positioning can differ according to the conditions in the room and the speakers being used. In smaller environments in particular (when the front speakers are close to the listening position), with this method the speakers will be pointed too inward. We suggest you use this example of installation as reference when trying out different installation methods.

Step 4: Positioning and adjusting the subwoofer

Placing the subwoofer between the center and front speakers makes even music sources sound more natural (If there is only one subwoofer, it doesn't matter if it is placed on the left or right side). The low bass sound output from the subwoofer is not directional and there is no need to adjust the height. Normally the subwoofer is placed on the floor. Put it in a position at which it will not cancel out the bass sound output from the other speakers. Also note that placing it near a wall may result in sympathetic vibrations with the building that could excessively amplify the bass sound.

If the subwoofer must be installed near a wall, place it at an angle so that it is not parallel to the wall surface. This can help reduce any sympathetic vibrations, but depending on the shape of the room this could result in standing waves. However, even if standing waves are generated, their influence on the sound quality can be prevented using the Auto MCACC's standing wave control function (page 87).

Step 5: Default settings with the Auto MCACC Setup (auto sound field correction) function

It is more effective to perform the Auto MCACC Setup (page 41) procedure once the adjustments described above have been completed.


🔐 Tip

 The distance to the subwoofer may be slightly larger than the distance actually measured with a tape measure, etc. This is because this distance is corrected for electric delay, and is not a problem.

Positional relationship between speakers and monitor

Position of front speakers and monitor


The front speakers should be as equidistant as possible to the monitor.




Position of center speaker and monitor

Since mostly dialogs are output from the center speaker, keeping the center speaker as close as possible to the screen makes the overall sound more natural. For TVs using Braun tubes, however, when installing the center speaker on the floor, adjust its angle of elevation to point it towards the listening position.

Installation on floor





- If the center speaker is not of the shielded type, install it away from the TV.
- When installing the center speaker on top of the monitor, place it facing slightly downwards towards the listening position.

Troubleshooting

Incorrect operations are often mistaken for trouble and malfunctions. If you think that there is something wrong with this component, check the points below. Sometimes the trouble may lie in another component. Investigate the other components and electrical appliances being used. If the trouble cannot be rectified even after exercising the checks listed below, ask your nearest Pioneer authorized independent service company to carry out repair work.



• If the unit does not operate normally due to external effects such as static electricity disconnect the power plug from the outlet and insert again to return to normal operating conditions.

Power

Symptom	Remedy
The power does not turn on.	Make sure that the power cord is plugged in to an active power outlet.
	 Try disconnecting from the power outlet, then plugging back in.
Power cannot be turned off.	ullet Set the remote control's MULTI-ZONE operation selector switch to ZONE 2 or ZONE 3 (VSX-23TXH
(ZONE 2 ON or ZONE 3 ON (<i>VSX-23TXH only</i>) is displayed.)	only), then press O RECEIVER to switch the sub zone off.
The receiver suddenly switches off or the PHASE CONTROL	• Check that there are no loose strands of speaker wire touching the rear panel or another set of wires. If so, re-attach the speaker wires, making sure there are no stray strands.
indicator blinks.	$ \bullet \ \text{The receiver may have a serious problem. Disconnect from the power and call a Pioneer authorized independent service company.} $
During loud playback the power suddenly switches off.	• Turn down the volume.
	• Lower the 63 Hz and 125 Hz equalizer levels in the Manual MCACC setup on page 80.
	• Switch on the digital safety feature. While holding down ENTER on the front panel, press
	O STANDBY/ON to set this receiver to the standby mode. Use TUNE +/- to select D.SAFETY
	⊲OFF ▶, and then use PRESET +/ − to select 1 or 2 (select D.SAFETY ⊲OFF ▶ to deactivate this feature). If the power switches off even with 2 switched on, turn down the volume. With 1 or 2 on, some features may be unavailable.
The unit does not respond	• Try switching the receiver off, then back on again.
when the buttons are pressed.	Try disconnecting the power cord, then connect again.

Symptom	Remedy
No sound	
Display blinks 12V TRG ERR.	• An error has arisen in the 12 V trigger jacks. Reconnect accurately then turn the power back on.
The Receiver suddenly power off or the blue indicator at the center of the receiver flashes.	The power unit is damaged. Unplug the receiver from the wall and call a Pioneer authorized independent service company.
AMP OVERHEAT and the power indicator flash and the power turns off.	 Allow the unit to cool down in a well-ventilated place before switching back on. Wait at least 1 minute, then try turning the power on again.
The ADVANCED MCACC indicator flashes and power turns off.	• There is a problem with the receiver's power unit. The receiver may have a serious problem. Unplug the receiver from the wall and call a Pioneer authorized independent service company.
AMP ERR blinks in the display, then the power automatically switches off. The ADVANCED MCACC blinks and the power does not turn on.	• The receiver may have a serious problem. Do not try switching the receiver on. Unplug the receiver from the wall and call a Pioneer authorized independent service company.
Symptom	Remedy

 Check the volume, mute setting (press MUTE) and speaker setting (press SPEAKERS). Make sure the correct input function is selected. Check that the MCACC setup microphone is disconnected. Make sure the correct input signal is selected (press SIGNAL SEL). Note that when PCM is selected, you won't be able to hear any other signal format. Check that the source component is connected properly (see Connecting your equipment on page 15). Check that the stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround/center speakers are not set to NO (see Speaker Setting on page 91). Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). Check the speaker connections (see Connecting the speakers on page 19). Of the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). Check the speaker connections (see Connecting the speakers on page 19). 						
 Make sure the correct input function is selected. No sound output from the front speakers. Make sure the correct input signal is selected (press SIGNAL SEL). Note that when PCM is selected, you won't be able to hear any other signal format. Check that the source component is connected properly (see Connecting your equipment on page 15). Check that the speakers are connected properly (see Connecting the speakers on page 19). No sound from the surround or center speakers. Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround/center speakers are not set to NO (see Speaker Setting on page 91). Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). Check that the surround/center speakers are set to LARGE or SMALL (see Speaker Setting on page 91). Mo sound from surround back Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing on page 59). If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). Check the speaker connections (see Connecting the speakers on page 19). If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround back channel processing is set to SBch ON and a surround mode is selected (see Listening i	Symptom	Remedy				
No sound output from the front speakers. **Oheck that the MCACC setup microphone is disconnected.** **Alake sure the correct input signal is selected (press SIGNAL SEL). Note that when PCM is selected, you won't be able to hear any other signal format. **Check that the source component is connected properly (see *Connecting your equipment* on page 15).** **No sound from the surroundor** **Check that the speakers are connected properly (see *Connecting the speakers* on page 19).** **No sound from the surroundor** **Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround/center speakers are not set to *NO** (see *Speaker Setting* on page 95).** **Check the channel level settings (see *Channel Level* on page 92).** **Check the speaker connections (see *Connecting the speakers* on page 19).** **No sound from surround back** **Speakers.** **No sound from surround back** **If the source is Dobly Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to *SBch Auto**, there will be no sound from the surround back speakers. In this case, set to *SBch ON** (see *Using surround back channel processing is set to *SBch Auto**, there will be no sound from the surround back speakers on thave 6.1 playback channels, make sure that surround back channel processing is set to *SBch ON** (see *Using in surround sound on page 56).** **Oheck the speaker connections (see *Connecting the speakers* on page 19).** **If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to *SBch ON** (see *Speaker* Setting* on page 59).** **Oheck that the subwoofer is connected properly, switched on and the volume turned up.** **If your subwoofer** has a sleep function, make sure it is switched off.** **Oheck that the subwoofer setting is *YES** or *PLUS** (see *Speake	No sound is output when an	• Check the volume, mute setting (press MUTE) and speaker setting (press SPEAKERS).				
• Make sure the correct input signal is selected (press SIGNAL SEL). Note that when PCM is selected, you won't be able to hear any other signal format. • Check that the source component is connected properly (see Connecting your equipment on page 15). • Check that the speakers are connected properly (see Connecting the speakers on page 19). • Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround listening modes (see Listening in surround sound on page 56). • Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). • Check the speaker connections (see Connecting the speakers on page 19). No sound from surround back speaker connections (see Connecting the speakers on page 19). • Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). • Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). • If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround	input function is selected.	Make sure the correct input function is selected.				
No sound from the correct in but sign in a selected properly (see Connecting your equipment on page 15). • Check that the source component is connected properly (see Connecting your equipment on page 15). • Check that the speakers are connected properly (see Connecting the speakers on page 19). No sound from the surround or center speakers. • Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround listening modes (see Listening in surround sound on page 56). • Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). • Check the channel level settings (see Channel Level on page 92). • Check the speaker connections (see Connecting the speakers on page 19). • Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). • Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). • If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing on page 59). • If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back speakers on page 59). • Check that the subwoofer is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. • Check that the Subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer is connected properly is the speaker Setting on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on pa		Check that the MCACC setup microphone is disconnected.				
No sound from the surround or center speakers. No sound from the surround or center speakers. **Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround listening modes (see Listening in surround sound on page 56). **Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). **Check the channel level settings (see Channel Level on page 92). **Check the speaker connections (see Connecting the speakers on page 19). **No sound from surround back** **Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). **Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). **If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). **Check that speaker connections (see Connecting the speakers on page 19). **To be channel processing is SBch ON and a surround mode is selected (see Listening in surround sound on page 56). **Check that the subwoofer is connected properly, switched on and the volume turned up. **If your subwoofer has a sleep function, make sure it is switched off. **Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). **If there is very little low frequency information in the source material, c	speakers.	1 0				
Check that the Stereo listening mode or the Front Stage Surround Advance mode isn't selected; select one of the surround listening modes (see Listening in surround sound on page 56). Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). Check the channel level settings (see Channel Level on page 92). Check the speaker connections (see Connecting the speakers on page 19). Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing on page 59). If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON (see Using surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). Check the speaker connections (see Connecting the speakers on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. O Check that the subwoofer setting is YES or PLUS (see Speaker Setting on page 91). If he crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66).						
select one of the surround listening modes (see Listening in surround sound on page 56). • Check that the surround/center speakers are not set to NO (see Speaker Setting on page 91). • Check the channel level settings (see Channel Level on page 92). • Check the speaker connections (see Connecting the speakers on page 19). No sound from surround back speakers. • Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). • Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). • If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing on page 59). • If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). • Check the speaker connections (see Connecting the speakers on page 19). • Check the speaker connections (see Connecting the speakers on page 19). • Check that the subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). • Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66).		• Check that the speakers are connected properly (see Connecting the speakers on page 19).				
No sound from surround back speakers. * Check that the surround back speakers are set to LARGE or SMALL (see Speaker Setting on page 91). * Make sure surround back channel processing is set to SBch ON (see Using surround back channel processing on page 59). * If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing on page 59). * If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). * Check the speaker connections (see Connecting the speakers on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. * Check that the subwoofer is connected properly, switched on and the volume turned up. * If your subwoofer has a sleep function, make sure it is switched off. * Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). * The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). * If there is very little low frequency information in the source material, change your speaker setting to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). * Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66).	No sound from the surround or center speakers.	select one of the surround listening modes (see <i>Listening in surround sound</i> on page 56). • Check that the surround/center speakers are not set to NO (see <i>Speaker Setting</i> on page 91). • Check the channel level settings (see <i>Channel Level</i> on page 92).				
page 91). • Make sure surround back channel processing is set to SBch ON (see <i>Using surround back channel processing</i> on page 59). • If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto , there will be no sound from the surround back speakers. In this case, set to SBch ON (see <i>Using surround back channel processing</i> on page 59). • If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see <i>Listening in surround sound</i> on page 56). • Check the speaker connections (see <i>Connecting the speakers</i> on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. • Check that the subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer setting is YES or PLUS (see <i>Speaker Setting</i> on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see <i>Speaker Setting</i> on page 91). • If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on page 91). • Check that the LFE channel is not set to OFF , or a very quiet setting (see <i>Setting the Audio options</i> on page 66).		• Check the speaker connections (see <i>Connecting the speakers</i> on page 19).				
 Processing on page 59). If the source is Dolby Surround EX or DTS-ES with no flag to indicate 6.1 compatibility, then with surround back channel processing set to SBch Auto, there will be no sound from the surround back speakers. In this case, set to SBch ON (see Using surround back channel processing on page 59). If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see Listening in surround sound on page 56). Check the speaker connections (see Connecting the speakers on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. Check that the subwoofer is connected properly, switched on and the volume turned up. If your subwoofer has a sleep function, make sure it is switched off. Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66). 	No sound from surround back speakers.	· · · · · · · · · · · · · · · · ·				
surround back channel processing set to SBch Auto , there will be no sound from the surround back speakers. In this case, set to SBch ON (see <i>Using surround back channel processing</i> on page 59). • If the source does not have 6.1 playback channels, make sure that surround back channel processing is set to SBch ON and a surround mode is selected (see <i>Listening in surround sound</i> on page 56). • Check the speaker connections (see <i>Connecting the speakers</i> on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. • Check that the subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer setting is YES or PLUS (see <i>Speaker Setting</i> on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see <i>Speaker Setting</i> on page 91). • If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on page 91). • Check that the LFE channel is not set to OFF , or a very quiet setting (see <i>Setting the Audio options</i> on page 66).						
processing is set to SBch ON and a surround mode is selected (see <i>Listening in surround sound</i> on page 56). • Check the speaker connections (see <i>Connecting the speakers</i> on page 19). If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. No sound from subwoofer. • Check that the subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer setting is YES or PLUS (see <i>Speaker Setting</i> on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see <i>Speaker Setting</i> on page 91). • If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on page 91). • Check that the LFE channel is not set to OFF , or a very quiet setting (see <i>Setting the Audio options</i> on page 66).		surround back channel processing set to SBch Auto , there will be no sound from the surround back				
If only one surround back speaker is connected, make sure it's connected to the left channel speaker terminal. • Check that the subwoofer is connected properly, switched on and the volume turned up. • If your subwoofer has a sleep function, make sure it is switched off. • Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). • The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). • If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). • Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66).		processing is set to SBch ON and a surround mode is selected (see <i>Listening in surround sound</i> on				
 If your subwoofer has a sleep function, make sure it is switched off. Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66). 		If only one surround back speaker is connected, make sure it's connected to the left channel speaker				
 Make sure that the Subwoofer setting is YES or PLUS (see Speaker Setting on page 91). The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see Speaker Setting on page 91). If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). Check that the LFE channel is not set to OFF, or a very quiet setting (see Setting the Audio options on page 66). 	No sound from subwoofer.					
 The crossover frequency may be set too low; try setting it higher to match the characteristics of your other speakers (see <i>Speaker Setting</i> on page 91). If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES, or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on page 91). Check that the LFE channel is not set to OFF, or a very quiet setting (see <i>Setting the Audio options</i> on page 66). 						
your other speakers (see Speaker Setting on page 91). • If there is very little low frequency information in the source material, change your speaker settings to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see Speaker Setting on page 91). • Check that the LFE channel is not set to OFF , or a very quiet setting (see Setting the Audio options on page 66).						
to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on page 91). • Check that the LFE channel is not set to OFF , or a very quiet setting (see <i>Setting the Audio options</i> on page 66).						
on page 66).		to Front: SMALL / Subwoofer: YES , or Front: LARGE / Subwoofer: PLUS (see <i>Speaker Setting</i> on				
Check the speaker level settings (see Channel Level on page 92).						
		• Check the speaker level settings (see <i>Channel Level</i> on page 92).				

Symptom	Remedy
No sound from one speaker.	• Check the speaker connection (see Connecting the speakers on page 19).
	• Check the speaker level settings (see Channel Level on page 92).
	• Check that the speaker hasn't been set to NO (see Speaker Setting on page 91).
	• The channel may not be recorded in the source. By using one of the advanced effect listening mode, you may be able to create the missing channel (see <i>Listening in surround sound</i> on page 56).
Sound is produced from	• Check that the input signal type is set to DIGITAL (see <i>Choosing the input signal</i> on page 61).
analog components, but not from digital ones (DVD, LD,	• Make sure that the digital input is assigned correctly for the input jack the component is connected to (see <i>The Input Setup menu</i> on page 43).
CD-ROM, etc.).	Check the digital output settings on the source component.
	• If the source component has a digital volume control, make sure this is not turned down.
	• Make sure that the multichannel analog inputs are not selected. Select any other input function.
No sound is output or a noise is	Check that your DVD player is compatible with Dolby Digital/DTS discs.
output when Dolby Digital/DTS	• Check the digital output settings of your DVD player. Make sure that the DTS signal output is set
software is played back.	to On.
	• If the source component has a digital volume control, make sure this is not turned down.
No sound when using the HOME MENU .	If the HDMI input function is selected, sound is muted until exiting the HOME MENU .

Other audio problems

Symptom Broadcast stations cannot be	Remedy For FM broadcasts
selected automatically, or there is considerable noise in	 Fully extend the FM wire antenna, adjust the position for best reception and secure to a wall, etc. Use an outdoor antenna for better reception (see page 31).
radio broadcasts.	For AM broadcasts
	Adjust the position and direction of the AM antenna.
	• Use an outdoor antenna for better reception (see page 31).
	• Noise may be caused by interference from other equipment, such as a fluorescent light, motor, etc. Switch off or move the other equipment, or move the AM antenna.
A multichannel DVD source appears to be downmixed to 2 channels during playback.	• Make sure that the multichannel analog inputs are selected (see Selecting the multichannel analog inputs on page 46).
Noise is output when scanning a DTS CD.	 This is not a malfunction of the receiver. The scan function of your player alters the digital information, making it unreadable, resulting in noise being output. Lower the volume when scanning.
When playing a DTS format LD there is audible noise on the soundtrack.	Make sure that the input signal type is set to DIGITAL (see <i>Choosing the input signal</i> on page 61).
Can't record audio.	 You can only make a digital recording from a digital source, and an analog recording from an analog source.
	• For digital sources, make sure that what you're recording isn't copy protected.
	• Check that the OUT jacks are properly connected to the recorders input jacks (see <i>Connecting other audio components</i> on page 29).
Subwoofer output is very low.	• To route more signal to the subwoofer, set it to PLUS or set the front speakers to SMALL (see <i>Speaker Setting</i> on page 91).
Everything seems to be set up correctly, but the playback sound is odd.	• The speakers may be out of phase. Check that the positive/negative speaker terminals on the receiver are matched with the corresponding terminals on the speakers (see <i>Connecting the speakers</i> on page 19).
The PHASE CONTROL feature doesn't seem to have an audible effect.	 If applicable, check that the lowpass filter switch on your subwoofer is off, or the lowpass cutoff is set to the highest frequency setting. If there is a PHASE setting on your subwoofer, set it to 0° (or depending on the subwoofer, the setting where you think it has the best overall effect on the sound). Make sure the speaker distance setting is correct for all speakers (see <i>Speaker Distance</i> on page 93).
Noise or hum can be heard even when there is no sound being input.	Check that personal computers or other digital components connected to the same power source are not causing interference.

Symptom	Remedy
Can't select some Input functions by the INPUT SELECTOR on the front panel or the INPUT SELECT button on the remote control.	 Make sure that the Input Skip settings in the INPUT SETUP menu. Make sure that the HDMI Input assign in the INPUT SETUP menu then try OFF.
There seems to be a time lag between the speakers and the output of the subwoofer.	• See Automatically setting up for surround sound (Auto MCACC) on page 41 to set up your system again using MCACC (this will automatically compensate for a delay in the subwoofer output).
The maximum volume available (shown in the front panel display) is lower than the +12dB maximum.	Check that the Volume Limit is set to OFF (see <i>Volume Limit Setup</i> on page 95).
Video	
Symptom	Remedy
No image is output when an	Check the video connections of the source component (see page 28).
input is selected.	• For HDMI, or when digital video conversion is set to OFF and a TV and another component are connected with different cords (in <i>Setting the Video options</i> on page 68), you must connect your TV to this receiver using the same type of video cable as you used to connect your video component.
	 Make sure the input assignment is correct for components connected using component video, HDMI or S-Video cables (see The Input Setup menu on page 43).
	Check the video output settings of the source component.
	Check that the video input you selected on your TV is correct.
	 Some components (such as video game units) have resolutions that may not be converted. If adjusting this receiver's Resolution setting (in Setting the Video options on page 68) and/or the resolution settings on your component or display doesn't work, try switching Digital Video Conversion (in Setting the Video options on page 68) OFF.
Can't record video.	Check that the source is not copy-protected.
	• The video converter is not available when making recordings. Check that the same type of video cable is used for connecting both the recorder and the video source (the one you want to record) to this receiver.
Noisy, intermittent, or distorted picture.	• Sometimes a video deck may output a noisy video signal (during scanning, for example), or the video quality may just be poor (with some video game units, for example). The picture quality may also depend on the settings, etc. of your display device. Switch off the video converter and reconnect the source and display device using the same type of connection (component, S-Video or composite), then start playback again.
Video signals are not output from the component terminal.	When a monitor only compatible with resolutions of 480i is connected to the component terminal and another monitor is connected to the HDMI terminal, the video signals may not be output to the monitor connected to the component terminal. If this happens, do the following: — Turn off the power of the monitor connected to the HDMI terminal.
	- Set RES on the VIDEO PARAMETER menu to PURE (page 68).
Settings	
Symptom	Remedy
The Auto MCACC Setup continually shows an error.	 The ambient noise level may be too high. Keep the noise level in the room as low as possible (see also <i>Problems when using the Auto MCACC Setup</i> on page 43). If the noise level cannot be kept low enough, you will have to set up the surround sound manually (page 90). When using only one surround back speaker, connect it to the SURROUND BACK L (Single) terminals.

Settings	
Symptom	Remedy
The Auto MCACC Setup continually shows an error.	 The ambient noise level may be too high. Keep the noise level in the room as low as possible (see also <i>Problems when using the Auto MCACC Setup</i> on page 43). If the noise level cannot be kept low enough, you will have to set up the surround sound manually (page 90). When using only one surround back speaker, connect it to the SURROUND BACK L (Single)
	terminals.
	 To use a 5.1-channel speaker set, use the surround speakers for the surround channel, not the surround back channel.
	 Make sure there are no obstacles between the speakers and the microphone.
	• If Reverse Phase is displayed, try the following:
	 The speaker's wiring (+ and -) may be inverted. Check the speaker connections.
	 Depending on the type of speakers and their installation conditions, Reverse Phase may be displayed even if the speakers are properly connected. If this happens, select GO NEXT and continue.
	 If the speaker is not pointed to the microphone (listening position) or when using speakers that affect the phase (dipole speakers, reflective speakers, etc.), it may not be possible to properly identify the polarity.
•	

Symptom	Remedy
After using the Auto MCACC Setup, the speaker size setting is incorrect.	 There may have been some low frequency noise in the room from an air-conditioner, motor, etc. Switch off all other appliances in the room and use Auto MCACC Setup again. Depending on a number of factors (room size, speaker placement, etc.) this may occur in some cases. Change the speaker setting manually in <i>Speaker Setting</i> on page 91, and use the ALL (Keep SP System) option for the Auto MCACC menu in <i>Automatic MCACC (Expert)</i> on page 78 if this is a recurring problem.
Can't adjust the Fine Speaker Distance setting (page 82) properly.	• Check that the speakers are all in phase (make sure the positive (+) and negative (-) terminals are matched up properly).
The display shows KEY LOCK ON when you try to make settings.	• With the receiver in standby, press & STANDBY/ON while holding down SPEAKERS to disable the key lock.
Most recent settings have been erased.	 The power cord was disconnected from the wall while adjusting this setting. Settings are only stored if all the zones are turned off. Turn off all the zones before unplugging the power cord.
The various system settings are not stored.	• Make sure the blue & STANDBY/ON light has gone out before unplugging.

Professional Calibration EQ graphical output		
Symptom	Remedy	
The EQ response displayed in the graphical output following calibration does not appear	 There are cases where the graph does not appear flat (even when selecting ALL CH ADJ in the Auto MCACC Setup) due to adjustments made to compensate for room characteristics to achieve optima sound. 	
entirely flat.	• Areas of the graph may appear identical (before and after) when there is little or no adjustment needed.	
	• The graph may appear to have shifted vertically when comparing before and after measurements	
EQ adjustments made using the <i>Manual MCACC setup</i> on page 80 do not appear to change the graphical output.	Despite level adjustments being made, the filters used for analysis may not display these adjustments in the graphical output. However, these adjustments are taken this into account by the filters dedicated to overall system calibration.	
Lower frequency response curves do not seem to have been calibrated for SMALL speakers.	 Low frequencies used in bass management (the subwoofer channel) will not change for speakers that have been specified as SMALL in the configuration, or do not output these frequencies. Calibration is performed, but due to your speakers' low frequency limitations, no measurable sound is output for display. 	

Display

Symptom	Remedy	
The display is dark or off.	Press DIMMER repeatedly to select a different brightness.	
After making an adjustment the display goes off.	Press DIMMER repeatedly to select a different brightness.	
You can't get DIGITAL to display when using SIGNAL	• Check the digital connections and make sure that the digital inputs are assigned correctly (see <i>The Input Setup menu</i> on page 43).	
SEL.	 If the multichannel analog inputs are selected, select a different input function. 	
DID DIGITAL or DTS does not	These indicators does not light if playback is paused.	
light when playing Dolby/DTS software.	Check the playback (especially the digital output) settings of the source component.	
When playing Dolby Digital or	Check that the player is connected using a digital connection.	
DTS sources, the receiver's	• Make sure that the receiver is set to AUTO or DIGITAL (see <i>Choosing the input signal</i> on page 61).	
format indicators do not light.	• Check that the player isn't set up so that Dolby Digital and DTS sources are converted to PCM.	
	• Ensure that if there are several audio tracks on the disc, the Dolby Digital or DTS is selected.	
When playing certain discs, none of the receiver's format indicators light.	The disc may not contain 5.1/6.1 channel material. Check the disc packaging for more on what audio tracks are recorded on the disc.	
When playing a disc with the	• Make sure that the receiver is set to AUTO or DIGITAL (see <i>Choosing the input signal</i> on page 61).	
listening mode set to Auto Surround or ALC, DD PL II or Neo:6 appear on the receiver.	• If a two channel soundtrack is currently playing (including Dolby Surround encoded), then this is not a malfunction. Check the disc packaging for details about the audio tracks available.	

Symptom Remedy During playback of a Surround • The source may be Dolby Surround EX/DTS-ES software, but it has no flag to indicate it is 6.1 EX or DTS-ES source on the compatible. Set to **SBch ON** (see Using surround back channel processing on page 59), then switch **SBch AUTO** setting, **EX** or **ES** to the THX Surround EX or Standard EX listening mode (see Listening in surround sound on page 56). does not appear, or the signal is not properly processed. During playback of DVD-Audio, • This will occur when playing DVD-Audio material over the HDMI connection. This is not a the display shows PCM. The power turns off • See the **Power** section (page 98). automatically and some indicator flashes, or some indicator flashes and the power does not turn on.

Remote control

Symptom	Remedy
Cannot be remote controlled.	• Set a 5-digit preset code corresponding to the receiver to be operated in the remote control (see Operating multiple receivers on page 73).
	• Check whether the receiver's remote control mode is properly set (see <i>Remote Control Mode Setup</i> on page 96).
	 Try replacing the batteries in the remote control (see Loading the batteries on page 9). Be sure to operate within 7 m (23 ft.) and a 30° angle of the remote sensor on the front panel (see Operating range of remote control unit on page 9). Check that there are no obstacles between the receiver and the remote control. Make sure that there is no fluorescent or other strong light shining on to the remote sensor. Check the connections of the CONTROL IN jack (see Operating other Pioneer components with this unit's sensor on page 35).
Other components can't be operated with the system remote.	 If the battery ran down, the preset codes may have been cleared. Re-enter the preset codes. The preset code may be incorrect. Redo the procedure for entering preset codes.

HDMI

Symptom	Remedy		
The HDMI indicator blinks continuously.	Check all the points below.		
No picture or sound.	• This receiver is HDCP-compatible. Check that the components you are connecting are also HDCP-compatible. If they are not, please connect them using the component, S-Video or composite video jacks.		
	• Depending on the connected source component, it's possible that it will not work with this receiver (even if it is HDCP-compatible). In this case, connect using the component, S-Video or composite video jacks between source and receiver.		
	If the problem still persists when connecting your HDMI component directly to your monitor, please consult the component or monitor manual or contact the manufacturer for support.		
	• If video images do not appear on your TV or flat panel TV, try adjusting the resolution, Deep Color or other setting for your component.		
	 While analog video signals are being output over HDMI, use a separate connection for audio output. 		
	When this receiver reproduces MULTI CH IN audio sources with the HDMI setting set to THROUGH, you cannot hear audio output from all channels. In this case, make a digital or analog audio connection.		
	• To output signals in Deep Color, use an HDMI cable (High Speed HDMI™ Cable) to connect this receiver to a component or TV with the Deep Color feature.		
No picture.	Try changing the Resolution setting (in Setting the Video options on page 68).		
	• VSX-23TXH only: Set the HDMI output setting to the connected HDMI OUT terminal (in Switching the HDMI output on page 71).		
No sound, or sound suddenly	Check that the HDMI AV setting is set to AMP/THROUGH .		
ceases.	• If the component is a DVI device, use a separate connection for the audio.		
	• If analog video is being output over HDMI, please use a separate connection for the audio.		
	Check the audio output settings of the source component.		

Symptom	Remedy
Noisy or distorted picture.	 Sometimes a video deck may output a noisy video signal (during scanning, for example), or the video quality may just be poor (with some video game units, for example). The picture quality may also depend on the settings, etc. of your display device. Switch off the video converter and reconnect the source and display device using the same type of connection (component, S-Video or composite), then start playback again. If the problem still persists when connecting your HDMI component directly to your monitor, please consult the component or monitor manual or contact the manufacturer for support.
HDCP ERROR shows in the display.	Check whether or not the connected component is compatible with HDCP. If it is not compatible with HDCP, reconnect the source device using a different type of connection (component, S-Video or composite). Some components that are compatible with HDCP still cause this message to be displayed, but so long as there is no problem with displaying video, this is not a malfunction.
Amp-linked operation not possible using KURO LINK function.	 Check the HDMI connections. The cable may be damaged. Select ON for the KURO LINK setting (see KURO LINK Setup on page 64). Turn the TV's power on before turning on this receiver's power. Set the TV side KURO LINK setting to ON. VSX-23TXH only: Connect the TV to the HDMI OUT 1 terminal and set the HDMI output to HDMI OUT 1. Then turn on first the TV's power, then this receiver's power.

Important information regarding the HDMI connection

There are cases where you may not be able to route HDMI signals through this receiver (this depends on the HDMI-equipped component you are connecting—check with the manufacturer for HDMI compatibility information).

If you aren't receiving HDMI signals properly through this receiver (from your component), please try one of the following configurations when connecting up.

Configuration A

Use component video cables to connect the video output of your HDMI-equipped component to the receiver's component video input. The receiver can then convert the analog component video signal to a digital HDMI signal for transmission to the display. For this configuration, use the most convenient connection (digital is recommended) for sending audio to the receiver. See the operating instructions for more on audio connections.



The picture quality will change slightly during conversion.

Configuration B

Connect your HDMI-equipped component directly to the display using an HDMI cable. Then use the most convenient connection (digital is recommended) for sending audio to the receiver. See the operating instructions for more on audio connections. Set the display volume to minimum when using this configuration.



- If your display only has one HDMI terminal, you can only receive HDMI video from the connected component.
- Depending on the component, audio output may be limited to the number of channels available from the connected display unit (for example audio output is reduced to 2 channels for a monitor with stereo audio limitations).
- If you want to switch the input function, you'll have to switch functions on both the receiver and your display unit.
- Since the sound is muted on the display when using the HDMI connection, you must adjust the volume on the display every time you switch input functions.

USB interface

Symptoms	Causes	Remedies
The folders/files stored on a USB memory device are not displayed.	The folders/files are currently stored in a region other than the FAT (File Allocation Table) region.	Store the folders/files in the FAT region.
	The number of levels in a folder is more than 8.	Limit the maximum number of levels in a folder to 8 (page 48).
	There are more than 30 000 folders/files stored in a USB memory device.	Limit the maximum number of folders/files stored in a USB memory device to 30 000 (page 48).
	The audio files are copyrighted.	Copyrighted audio files stored on a USB memory device cannot be played back (page 48).
A USB memory device is not recognized.	The USB memory device does not support the mass storage class specifications.	Try using a USB memory device compatible with the mass storage class specifications. Note that there are cases where even the audio files stored on a USB memory device compatible with the mass storage class specifications are not played back on this receiver (page 48).
		Connect the USB memory device and switch on this receiver (page 39).
	A USB hub is currently being used.	This receiver does not support a USB hub (page 48).
	This receiver recognizes the USB memory device as a fraud.	Switch off and on again this receiver.
A USB memory device is connected and displayed, but the audio files stored on the USB memory device cannot be played back.	Some formats of a USB memory device, including FAT 12, NTFS, and HFS, cannot be played back on this receiver.	Check whether the format of your USB memory device is either FAT 16 or FAT 32. Note that the FAT 12, NTFS, and HFS formats cannot be played back on this receiver (page 48).
	The file format cannot be properly played back on this receiver.	See the list of file formats that can be played back on this receiver (page 50).

XM radio messages

Message	Cause	Action
Check XM Tuner	The XM Mini-Tuner is not installed or not fully seated in the XM Mini-Tuner Home Dock or the XM Mini-Tuner dock is not connected to this receiver.	Confirm the XM Mini-Tuner is fully seated in the dock and check the XM Mini-Tuner Home Dock cable is connected to this receiver.
Check Antenna	The XM antenna is not connected to the XM Mini- Tuner Home Dock or the XM antenna cable is damaged.	Check that the XM antenna is securely connected to the XM Mini-Tuner Home Dock and check the antenna cable for damage. Replace the XM antenna if the cable is damaged.
Loading	The XM Mini-Tuner is acquiring audio or program information from the XM satellite signal. This message can also occur in weak XM signal conditions. Note that this receiver may not respond to some buttons while this message is displayed.	This message should disappear in a few seconds in good signal conditions. If you see this message often, reposition the XM antenna for better signal reception. Use the Antenna Aiming option to optimize the antenna position.
No Signal	The XM Mini-Tuner is not receiving the XM satellite signal. Something may be blocking the XM antenna's view of the satellites or the antenna is not properly aimed.	Check for antenna obstructions and reposition the XM antenna to get better signal reception. Use the Antenna Aiming option to optimize the antenna position. See instructions supplied with the XM Mini-Tuner and Home Dock for antenna installation information.
Off Air	The XM channel you selected is not currently broadcasting.	Check back later.

Message	Cause	Action
CH Unauthorized	You selected an XM channel that is blocked or cannot be received with your XM subscription package.	Consult the latest channel guide at www.xmradio.com for the current list of channels. For information on receiving this channel, visit www.xmradio.com or contact XM Satellite Radio at 1-800-967-2346.
CH Unavailable	The selected channel is not available. The channel may have been reassigned to a different channel number. This message may occur initially with a new radio or a radio that has not received XM's signal for an extended period.	Consult the latest channel guide at www.xmradio.com for the current list of channels. For cases of a new radio or a radio that has not received XM's signal for an extended period, allow the radio to receive the XM satellite signal for at least 5 minutes and then try to select the channel again.
	No artist name or song title is available for this selection.	No action required.
Upgrade XM Tuner	The connected XM CNP-1000 is incompatible. This receiver features advanced technology that is designed for use with the XM Mini-Tuner.	Contact XM Listener Care (1-800-967-2346) and ask about upgrading your XM CNP-1000 to an XM MiniTuner. Have this receiver's model name and CNP-1000 XM Radio ID number ready beforehand, and explain that this receiver is displaying the message Upgrade XM Tuner . If you already have an XM Mini-Tuner connected and you see this message, turn off this receiver, make sure the XM Mini-Tuner is properly seated in the Mini-Tuner Home Dock, and then turn this receiver on again. If the message reappears, contact XM Listener Care and explain the issue that you're experiencing and the corrective actions you've tried.
XM Power Error	A short-circuit occurring in the antenna or surrounding antenna cable.	Make sure that there is nothing unusual with the antenna or antenna cable. Switch the power off, then back on again.

SIRIUS radio messages

J	9	
Message	Cause	Action
Antenna Error	The SIRIUS antenna is not properly connected.	Check that the antenna cable is attached securely.
Check Sirius Tuner	The SiriusConnect™ tuner is not properly connected.	Check that the 8 pin mini DIN cable and AC Adapter are attached securely.
Acquiring Signal	The SIRIUS signal is too weak at the current location.	Check for antenna obstructions and reposition the SIRIUS antenna to get better signal reception. Use the Antenna Aiming option to optimize the antenna position.
Subscription Updating	Unit is updating subscription.	Wait until the encryption code has been updated.
Updating Channels	Unit is updating channels.	Wait until the encryption code has been updated.
Invalid Channel	Selected channel is not available/does not exist.	Select another channel.
Firmware Updating	The SiriusConnect™ tuner's firmware is being updated.	Wait for updating to finish.

If the problem is not solved after the troubleshooting above, if the screen freezes unexpectedly or if the buttons on the remote control or front panel stop working completely, do the following:

- Press & STANDBY/ON on the front panel to turn off the power, then turn the power back on.
- If the power cannot be turned off, press and hold \circ **STANDBY/ON** on the front panel for over 10 seconds. The power will turn off. (In this case, the various settings made on the receiver may be cleared.)

Surround sound formats

Below is a brief description of the main surround sound formats you'll find on DVDs, satellite, cable and terrestrial broadcasts, and video cassettes.

Dolby

The Dolby technologies are explained below. See www.dolby.com for more detailed information.



Dolby Digital

Dolby Digital is a multichannel digital audio coding system widely used in cinemas, and in the home for DVD and digital broadcast soundtracks. It can deliver up to six discrete audio channels, comprising five full range channels and a special LFE (low frequency effects) channel used mainly for deep, rumbling sound effects; hence the term "5.1-channel" Dolby Digital.

In addition to the format features above, Dolby Digital decoders offer downmixing for compatibility with mono, stereo and Dolby Pro Logic audio from a number of bit rates and channels. Another feature, called Dialog Normalization, attenuates programs based on the average level of dialog in a program relative to its peak level (also known as Dialnorm) in order to achieve uniform playback level.

Dolby Digital Surround EX

Dolby Digital Surround EX (the EX stands for EXtended) is an extension of Dolby Digital encoding whereby a surround back channel is matrixed into the surround left/right channels for 6.1 channel playback. This allows for compatibility with Dolby Digital 5.1 channel decoding, as well as for decoding using Dolby Digital EX.

Dolby Pro Logic IIx and Dolby Surround

Dolby Pro Logic IIx is an improved version of the Dolby Pro Logic II (and Dolby Pro Logic) *decoding* system. Using the innovative "steering logic" circuit, this system extracts surround sound from sources as follows:

- **Dolby Pro Logic** 4.1 channel sound (mono surround) from any stereo source
- **Dolby Pro Logic II** 5.1 channel sound (stereo surround) from any stereo source
- Dolby Pro Logic IIx 6.1 or 7.1 channel sound (stereo surround and surround back) from two channel or 5.1 (and 6.1) channel sources

With two channel sources, the ".1" subwoofer channel is generated by bass management in the receiver.

Dolby Surround is an *encoding* system which embeds surround sound information within a stereo soundtrack, which a Dolby Pro Logic decoder can then use for enhanced surround listening with greater sound detail.

Dolby Digital Plus

Dolby Digital Plus is the next-generation audio technology for all high-definition programming and media. It combines the efficiency to meet future broadcast demands with the power and flexibility to realize the full audio potential expected in the upcoming high-definition era. Built on Dolby Digital, the multichannel audio standard for DVD and HD broadcasts worldwide, Dolby Digital Plus was designed for the next-generation A/V receivers but remains fully compatible with all current A/V receivers.

Dolby Digital Plus delivers multi-channel audio programs of up to 7.1 channels (*) and supports multiple programs in a single encoded bitstream with the maximum bit rate potential of up to 6 Mbps and the maximum bit rate performance of up to 3 Mbps on HD DVD and 1.7 Mbps on Blu-ray Disc, and it outputs Dolby Digital bitstreams for playback on existing Dolby Digital systems. Dolby Digital Plus can accurately reproduce the sound originally intended by directors and producers.

It also features multi-channel sound with discrete channel output, interactive mixing and streaming capability in advanced systems. Supported by High-Definition Media Interface (HDMI), a single-cable digital connection is possible for high-definition audio and video.

Dolby TrueHD

Dolby TrueHD is the next-generation lossless encoding technology developed for high-definition optical discs in the upcoming era. Dolby TrueHD delivers tantalizing sound that is bit-for-bit identical to the studio master, unlocking the true high-definition entertainment experience on high-definition optical discs in the next generation. When coupled with high-definition video, Dolby TrueHD offers an unprecedented home theater experience with stunning sound and high-definition picture.

It supports bit rates of up to 18 Mbps and records up to 8 full-range channels (*) individually with 24-bit/96 kHz audio. It also features extensive metadata including dialogue normalization and dynamic range control. Supported by High-Definition Media Interface (HDMI), a single-cable digital connection is possible for high-definition audio and video.

HD DVD and Blu-ray Disc standards currently limit their maximum number of audio channels to eight, whereas Dolby Digital Plus and Dolby TrueHD support more than eight audio channels.

Manufactured under license from Dolby Laboratories. Dolby, Pro Logic, Surround EX and the double-D symbol are trademarks of Dolby Laboratories.

DTS

The DTS technologies are explained below. See www.dtstech.com for more detailed information.



DTS Digital Surround

DTS Digital Surround is a 5.1-channel audio coding system from DTS Inc. now widely used for DVD-Video, DVD-Audio, 5.1 music discs, digital broadcasts, and video games. It can deliver up to six discrete audio channels, comprising five full range channels, including an LFE channel. Higher sound quality is achieved through the use of a low compression rate, and high rates of transmittance during playback.

DTS-ES

DTS-ES (the ES stands for Extended Surround) is a decoder that is capable of decoding both DTS-ES Discrete 6.1 and DTS-ES Matrix 6.1 encoded sources. DTS-ES Discrete 6.1 gives 'true' 6.1 channel sound, with a completely separate (discrete) surround back channel. DTS-ES Matrix 6.1 has a surround back channel matrixed into the surround left/right channels. Both sources are also compatible with a conventional DTS 5.1 channel decoder.

DTS Neo:6

DTS Neo:6 can generate 7.1 channel surround sound from any matrixed stereo source (such as video or TV) and from 5.1 channel sources. It uses both the channel information already encoded into the source, as well as its own processing to determine channel localization (with two channel sources, the ".1" subwoofer channel is generated by bass management in the receiver). Two modes (Cinema and Music) are available using DTS Neo:6 with two channel sources.

DTS 96/24

DTS 96/24 is an extension of the original DTS Digital Surround which offers high quality 96 kHz/24-bit audio using a DTS 96/24 decoder. This format is also fully backward compatible with all existing decoders. This means that DVD players can play this software using a conventional DTS 5.1 channel decoder.

DTS-EXPRESS

DTS-EXPRESS is a low-bitrate encoding technology supporting up to 5.1 channels with fixed data transfer rates. This format is incorporated with sub audio on HD DVD and secondary audio on Blu-ray Disc while boasting the potential applicability to upcoming broadcasts and memory audio contents.

DTS-HD Master Audio

DTS-HD Master Audio is a technology that delivers master audio sources recorded in a professional studio to listeners without any loss of data, preserving audio quality. DTS-HD Master Audio adopts variable data transfer rates, facilitating data transfer to the maximum rate of 24.5 Mbps in the Blu-ray disc format, 18.0 Mbps in the HD-DVD format, which by far exceeds that of a standard DVD. These high data transfer rates enable lossless transmission of 96 kHz/24-bit 7.1-channel audio sources without deteriorating the quality of the original sound. DTS-HD Master Audio is an irreplaceable technology that can reproduce sound faithfully as intended by the creator of music or movies.

Manufactured under license under U.S. Patent #'s: 5,451,942; 5,956,674; 5,974,380; 5,978,762; 6,226,616; 6,487,535; 7,212,872; 7,333,929; 7,392,195; 7,272,567 & other U.S. and worldwide patents issued & pending. DTS is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademarks of DTS, Inc. © 1996-2008 DTS, Inc. All Rights Reserved.

Windows Media Audio 9 Professional

Windows Media Audio 9 Professional (WMA9 Pro) is a discrete surround format developed by Microsoft Corporation.



Windows Media and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

About iPod





"Made for iPod" means that an electronic accessory has been designed to connect specifically to iPod and has been certified by the developer to meet Apple performance standards.

"Works with iPhone" means that an electronic accessory has been designed to connect specifically to iPhone and has been certified by the developer to meet Apple performance standards.

Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

iPod is a trademark of Apple Inc., registered in the U.S. and other countries. iPhone is a trademark of Apple Inc.

About THX

The THX technologies are explained below. See www.thx.com for more detailed information.



THX Cinema processing

THX is an exclusive set of standards and technologies established by THX Ltd. THX grew from George Lucas' personal desire to make your experience of the film soundtrack, in both movie theatres and in your home theatre, as faithful as possible to what the director intended. Movie soundtracks are mixed in special movie theatres called dubbing stages and are designed to be played back in movie theatres with similar equipment and conditions. This same soundtrack is then transferred directly onto Laserdisc, VHS tape, DVD, etc., and is not changed for playback in a small home theatre environment. THX engineers developed patented technologies to accurately translate the sound from the movie theatre environment into the home, correcting the tonal and spatial errors that occur. On this product, when the THX indicator is on, THX features are automatically added in Cinema modes (e.g. THX Cinema, THX Surround EX).

Re-Equalization

The tonal balance of a film soundtrack will be excessively bright and harsh when played back over audio equipment in the home because film soundtracks were designed to be played back in large movie theaters using very different professional equipment. Re-Equalization restores the correct tonal balance for watching a movie soundtrack in a small home environment.

Timbre Matching

The human ear changes our perception of a sound depending on the direction from which the sound is coming. In a movie theatre, there is an array of surround speakers so that the surround information is all around you. In a home theatre, you use only two speakers located to the side of your head. The Timbre Matching feature filters the information going to the surround speakers so that they more closely match the tonal characteristics of the sound coming from the front speakers. This ensures seamless panning between the front and surround speakers.

Adaptive Decorrelation

In a movie theatre, a large number of surround speakers help create an enveloping surround sound experience, but in a home theatre there are usually only two speakers. This can make the surround speakers sound like headphones that lack spaciousness and envelopment. The surround sounds will also collapse into the closest speaker as you move away from the middle seating position. Adaptive Decorrelation slightly changes one surround channel's time and phase relationship with respect to the other surround channel. This expands the listening position and creates—with only two speakers—the same spacious surround experience as in a movie theatre.

Advanced Speaker Array (ASA)

ASA is a proprietary THX technology which processes the sound fed to 2 side and 2 back surround speakers to provide the optimal surround sound experience. When you set up your home theater system using all eight speaker outputs (Left, Center, Right, Surround Right, Surround Back Right, Surround Back Left, Surround Left and Subwoofer) placing the two Surround Back speakers close together facing the front of the room will provide the largest sweet spot. If for practical reasons you have to place the Surround Back speakers apart, you will need to go THX Audio Set-up screen and choose the setting that most closely corresponds to the speaker spacing, which will re-optimize the surround sound-field.

ASA is used in three new modes: THX Select2 CINEMA. THX Select2

MUSIC and THX Select2 GAMES.

Boundary Gain Compensation™

Depending on the listener's and the subwoofer's position, the listener may experience an excessive bass effect. This feature compensates for excessive bass resulting from a boundary gain effect. This feature is designed to operate when used with a subwoofer certified to THX Select2" specifications.

• THX Loudness Plus Description

THX Loudness Plus is a new volume control technology featured in THX Ultra2 Plus ™ and THX Select2 Plus ™ Certified amplifiers. With THX Loudness Plus, home theater audiences can now experience the rich details in a surround mix at any volume level. A consequence of turning the volume below Reference Level is that certain sound elements can be lost or perceived differently by the listener. THX Loudness Plus compensates for the tonal and spatial shifts that occur when the volume is reduced by intelligently adjusting ambient surround channel levels and frequency response. This enables users to experience the true impact of soundtracks regardless of the volume setting. THX Loudness Plus is automatically applied when listening in any THX listening mode. The new THX Cinema, THX Music, and THX Games modes are tailored to apply the proper THX Loudness Plus settings for each type of content.

THX Select2 Plus

Before any home theatre component can be THX Select2 Plus certified, it must incorporate all the features above and also pass a rigorous series of quality and performance tests. Only then can a product feature the THX Select2 Plus logo, which is your guarantee that the Home Theatre products you purchase will give you superb performance for many years to come. THX Select2 Plus requirements cover every aspect of the product including pre-amplifier and power amplifier performance and operation, and hundreds of other parameters in both the digital and analog domain.

THX Surround EX

THX Surround EX - Dolby Digital Surround EX is a joint development of Dolby Laboratories and the THX Ltd. In a movie theater, film soundtracks that have been encoded with Dolby Digital Surround EX technology are able to reproduce an extra channel which has been added during the mixing of the program. This channel, called Surround Back, places sounds behind the listener in addition to the currently available front left, front center, front right, surround right, surround left and subwoofer channels. This additional channel provides the opportunity for more detailed imaging behind the listener and brings more depth, spacious ambience and sound localization than ever before. Movies that were created using the Dolby Digital Surround EX technology, when released into the home

consumer market may exhibit wording to that effect on the packaging. A list of movies created using this technology can be found on the Dolby web site at www.dolby.com.

Only amplifier and controller products bearing the THX Surround EX logo, when in the THX Surround EX mode, faithfully reproduce this new technology in the home.

This product may also engage the "THX Surround EX" mode during the playback of 5.1 channel material that is not Dolby Digital Surround EX encoded. In such case the information delivered to the Surround Back channel will be program dependent and may or may not be very pleasing depending on the particular soundtrack and the tastes of the individual listener.

THX Music

For the replay of multi-channel music the THX MusicMode should be selected. In this mode THX ASA processing is applied to the surround channels of all 5.1 encoded music sources such as DTS, Dolby Digital and DVD-Audio to provide a wide stable rear soundstage.

THX Games

For the replay of stereo and multi-channel game audio the THX Games Mode should be selected. In this mode THX ASA processing is applied to the surround channels of all 5.1 and 2.0 encoded game sources such as analog, PCM, DTS and Dolby Digital. This accurately places all game audio surround information, providing a full 360 degree playback environment. THX Games Mode is unique as it gives you a smooth transition of audio in all points of the surround field.

THX Select2 Cinema

THX Select2 Cinema mode plays 5.1 movies using all 8 speakers giving you the best possible movie watching experience. In this mode, ASA processing blends the side surround speakers and back surround speakers providing the optimal mix of ambient and directional surround sounds.

DTS-ES (Matrix and 6.1 Discrete) and Dolby Digital Surround EX encoded soundtracks will be automatically detected in Select2 Cinema mode if the appropriate flag has been encoded.

Some Dolby Digital Surround EX soundtracks are missing the digital flag that allows automatic switching. If you know that the movie that you are watching is encoded in Surround EX, you can manually select the THX Surround EX playback mode, otherwise THX Select Cinema mode will apply ASA processing to provide optimum replay.

THX Select2 Music

For the playback of multi-channel music the THX Select2 Music mode should be selected. In this mode THX ASA processing is applied to the surround channels of all 5.1 encoded music sources such as DTS, Dolby Digital and DVD-Audio to provide a wide stable rear soundstage.

THX Select2 Games

For the playback of stereo and multi-channel game audio the THX Select2 Games mode should be selected. In this mode THX ASA processing is applied to the surround channels of all 5.1 and 2.0 encoded game sources such as analog, PCM, DTS and Dolby Digital. This accurately places all game audio surround information, providing a full 360 degree playback environment. THX Select2 Games mode is unique as it gives you a smooth transition of audio in all points of the surround field.

THX, the THX logo and Select2 Plus are trademarks of THX Ltd. which may be registered in some jurisdictions. All rights reserved. All other trademarks are the property of their respective owners.

About Neural – THX Surround



Neural-THX® Surround is taking surround sound to the next level. This revolutionary new technology delivers the rich envelopment and discrete image detail of surround sound in a format that is fully compatible with stereo from various content sources. Neural-THX Surround enables 5.1, 6.1 and 7.1-channel support for gaming, movies and digital music. By unmasking the audio details, typically lost by other playback modes, audiences will experience the deep ambience and subtle details of movies, music and games.

Neural-THX Surround has been chosen as the official surround sound format for TV sports broadcasting, 7.1 games, Music Direct Internet streaming as well as leading FM/HD radio stations worldwide. And with this technology being used by sound designers during content creation, as well as embedded into playback devices, Neural-THX Surround promises a listening experience that is true to the original mix

For additional information, please visit www.neuralsurround.com. This product is manufactured under license from Neural Audio Corporation and THX Ltd. PIONEER Corporation hereby grants the user a non-exclusive, non-transferable, limited right of use to this product under USA and foreign patent, patent pending and other technology or trademarks owned by Neural Audio Corporation and THX Ltd. "Neural Surround", "Neural Audio", "Neural" and "NRL" are trademarks and logos owned by Neural Audio Corporation, THX is a trademark of THX Ltd., which may be registered in some jurisdictions. All rights reserved.

About SIRIUS and XM





XMHD

SIRIUS, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. and its subsidiaries. All other marks and logos are the property of their respective owners. All rights reserved. SIRIUS and XM subscriptions sold separately. Taxes and a one-time activation fee may apply. XM tuners and home docks or SIRIUS tuners (each sold separately) are required to receive the SIRIUS or XM satellite radio service. All programming and fees subject to change. It is prohibited to copy, decompile, disassemble, reverse engineer, hack, manipulate or otherwise make available any technology or software incorporated in receivers compatible with the SIRIUS or XM Satellite Radio Systems. Service not available in Alaska and Hawaii.

SIRIUS, XM and all related marks and logos are trademarks of Sirius XM Radio Inc. and its subsidiaries. All rights reserved. Service not available in Alaska and Hawaii.

Record the SiriusConnect™ tuner ID below for reference.				
Record the XM Radio ID below for reference.				

Note: The XM Radio ID does not use the letters "I", "O", "S" or "F".

Auto Surround, ALC and Stream Direct with different input signal formats

The following charts show what you will hear with different input signal formats, depending on the Stream Direct mode (see *Using Stream Direct* on page 59) you have selected.

Stereo (2 channel) signal formats

Input signal format	Auto Surround / ALC / DIRECT	PURE DIRECT
ound Back speaker(s): Connected		
Dolby Digital Surround	□□ Pro Logic IIx MOVIE	□□ Pro Logic llx MOVIE
DTS Surround	Neo:6 CINEMA	Neo:6 CINEMA
Other stereo sources	Stereo playback	Stereo playback
Analog sources	As above	ANALOG DIRECT (stereo)
PCM sources	As above	Stereo playback
DVD-A sources	As above	As above
SACD sources	As above	As above
ound Back speaker(s): Not connected		
Dolby Digital Surround	□□ Pro Logic II MOVIE	DD Pro Logic II MOVIE
DTS Surround	Neo:6 CINEMA	Neo:6 CINEMA
Other stereo sources	Stereo playback	Stereo playback
Analog sources	As above	ANALOG DIRECT (stereo)
PCM sources	As above	Stereo playback
DVD-A sources	As above	As above
SACD sources	As above	As above

Multichannel signal formats

Input signal format	Auto Surround / ALC	PURE DIRECT / DIRECT
ırround Back speaker(s): Connected		
Dolby Digital EX (6.1 channel flagged)	Dolby Digital EX DD Pro Logic llx MOVIE ^a	Dolby Digital EX DD Pro Logic llx MOVIE ^a
DTS-ES (6.1 channel sources/6.1 channel flagged)	DTS-ES (Matrix/Discrete)	DTS-ES (Matrix/Discrete)
DTS sources (5.1 channel encoding)	DTS+Neo:6	Straight decoding
DTS-HD sources	Straight decoding	As above
Other 6.1/7.1 channel sources	As above	As above
Other 5.1 channel sources	Dolby Digital EX DD Pro Logic llx MOVIE ^a	As above
urround Back speaker(s): Not connected		
DVD-A sources/Multi-ch PCM	Straight decoding	Straight decoding
SACD sources (5.1 channel encoding)	As above	As above
Other 5.1/6.1/7.1 channel sources	As above	As above

 $a. Unavailable \ with \ only \ one \ surround \ back \ speaker \ connected.$

Preset code list

You should have no problem controlling a component if you find the manufacturer in this list, but please note that there are cases where codes for the manufacturer in the list will not work for the model that you are using. There are also cases where only certain functions may be controllable after assigning the proper preset code.

Granada 10037


Grundy 10180

Grunpy 10180

Hannspree 11351

Hanseatic 10556

Haier 11748



TV

General Pioneer 10166, 10679, 11260, **A-Mark** 10047, 10054, 10160 A.R. Systems 10556 Accuscan 10047 Admiral 10047, 10054, 10017, 10051, 10093, 10463, 10180 Adventuri 10000 **Agna** 10150 **Aiko** 10092 Akai 10812, 11675, 10060, 10702, 10145, 10672 Alba 10037 Alfide 10672 Ambassador 10150 America Action 10180 American High 10000, 10060 Amstrad 1017 Amtron 10000, 10180 **Anam** 10180 AOC 10180, 11365 Apex Digital 10156, 10765, **AR** 10556 Audinac 10180 Audiovox 10451, 10180, 10092, 10623, 10802, 10875 Aventura 10171 Barco 10556 Baysonic 10180 **Beaumark** 10017, 10178 Bell & Howell 10054, 10154, BenQ 11574 Blue Sky 10556 Bradford 10180 Brockwood 10178 Broksonic 10236, 10463, 10180 Byd:sign 11309 Capehart 10017, 10178, 10092 **Carver** 10054 **CCE** 10037 Celebrity 10000 Celera 10765 **Changhong** 10156, 10765 Cineral 10451, 10092 Citek 10047 Citizen 10000, 10054, 10451. 10463, 10180, 10060, 10171, 10092 Clarion 10180 Classic 10092 Colortyme 10047, 10054, 10017,

10060. 10178

```
Commercial Solutions 11447,
Conic 10178
Contec 10180
Craig 10180, 10171
Crosley 10000, 10054, 10180,
Crown 10093, 10180, 10672
Crown Mustang 10672
Curtis Mathes 10000, 10047
   10054, 10154, 10051, 10451,
10093, 10180, 10060, 10702,
  10178, 10145, 10166, 10037,
CXC 10180
Daewoo 11755, 10451, 10178, 10092, 11661, 10623, 10661, 10672, 11756
Dayton 10092
Daytron 10178, 10092
Dell 11264, 11080, 11178, 11403
Denon 10145
Dumont 10017, 10180, 10178
Durabrand 10463, 10180, 10178,
Dwin 10093
Dynex 11463, 12049
Faton 10060
Electroband 10000
Electrograph 11755
Electrohome 10000, 10154,
   10463, 10150, 10178
Element 11687
Emerald 10178
Emerson 10047, 10017, 10154,
   10451, 10236, 10463, 10180,
  10150, 10178, 10171, 10623,
  11394
Envision 11365
ESA 10812, 10171
Ferguson 10625
Fisher 10000, 10054, 10154
Fortress 10093
Fujitsu 10809, 10683, 10853
Funai 10000, 10180, 10171, 11271
Futuretech 10180
Gateway 11755, 11756
GE 10000, 11447, 10047, 10051, 10451, 10060, 10178, 11147
Gemini 10047
GFM 10171
Gibralter 10000, 10017
GoldStar 10047, 10054, 10178,
Goodmans 10037
Gradiente 10053
```

```
Harley Davidson 10000, 10180,
   10060, 10178
Harman/Kardon 10054
Harvard 10180
Havermy 10093
Heathkit 10017
Helios 10865
Hello Kitty 10451
Hewlett Packard 11494, 11101,
Hitachi 10000, 11643, 10047, 10054, 10017, 10051, 11145,
   10145, 11576
HP 11494, 11101, 11502
Hyundai 10865
Ima 10236, 10180, 10178
Infinity 10054
Innova 10037
Insignia 11423, 11564, 10171, 11517, 11710, 12049
Inteq 10017, 10145
JBL 10054
JCB 10000
Jinxing 10037, 10556
JVC 10054, 10053, 10160, 10650,
   10731, 11253, 11601, 11633,
   11774
Kamp 10017, 10180
KDS 11498, 11687
KEC 10180, 10060
Kenwood 10180
Kioto 10556
KLH 10156, 10180, 10765
Konka 10180
KTV 10463, 10180
Lark 10154
LG 11423, 10054, 10017, 11265, 10060, 10178, 10037, 10856, 11178, 11663, 11768
Lloyd's 10236, 10180
Loewe 10633
Logik 10236, 10180
Lumatron 10037, 10556 LXI 10000, 10047, 10054, 10017,
   10154, 10156, 10051, 10093,
  10060, 10053, 10178, 10171, 10166, 10037
```

```
MAG 11498, 11687
Grundig 10037, 10672, 10683
                                                                                                              Magnasonic 10000, 10054,
                                                                                                                      10156, 10093, 10092
                                                                                                              Magnavox 10000, 10250, 11454,
                                                                                                                     надначож тогоог, тогоо, тогоо
Hallmark 10236, 10180, 10178
                                                                                                              Majestic 10017
                                                                                                             Marantz 11454, 10054, 10037, 10556, 10704, 10855, 11398
                                                                                                              Mark 10037
                                                                                                              Matsui 10037
                                                                                                              Matsushita 10250, 10051, 10650
                                                                                                              Maxent 11755, 11211, 11756,
                                                                                                              Megatron 10047, 10178, 10145
                                                                                                              Memorex 10154, 10463, 10180,
                                                                                                                      10150, 10178, 10037
                                                                                                              Mermaid 10037
                                                                                                              MGA 10150, 10178
                                                                                                              MGN Technology 10178
                                                                                                              Micro Genius 10150
                                                                                                             Midland 10047, 10017, 10051
Minato 10037, 10556
                                                                                                              Mitsubishi 10154, 11250, 10093, 10150, 10178, 10160, 10836
                                                                                                              Motorola 10054, 10051, 10093,
                                                                                                              MTC 10180, 10060, 10092
                                                                                                              Multitech 10180
                                                                                                              NAD 10156, 10178, 10166, 10037,
                                                                                                                       11156
                                                                                                              National 10226
                                                                                                             NEC 10047, 10178, 10704, 11398, 11704, 11797
                                                                                                              NetTV 11755
                                                                                                              Nikko 10178, 10092
                                                                                                              Nikkodo 10178, 10092
                                                                                                              Norcent 11365
                                                                                                              NTC 10092
                                                                                                              Nyon 10000
                                                                                                              Olevia 11610, 11144, 11240,
                                                                                                                     11331
                                                                                                              Onwa 10180
                                                                                                             Optimus 10250, 10154, 10093, 10180, 10150, 10178, 10166,
                                                                                                              Optonica 10093
                                                                                                              Orion 10017, 10236, 10463.
                                                                                                                      10180, 10178, 11463
                                                                                                              Pace 10092
                                                                                                              Pacific 10037, 10556
                                                                                                             Panasonic 11480, 10250, 10054, 10156, 10051, 10236, 10226,
```

10650, 11310, 11636, 11650

	5. H. 10000 10100		- 44500
Paxonic 10060	Starlite 10236, 10180	Akai 10812, 11675	Petters 11523
PCE 10156, 10060	Superscan 10093, 10864	Daewoo 10661	Philips 11454, 11744
Penney 10000, 10250, 10047, 10156, 10051, 10060, 10178,	Supreme 10000 SV2000 10054	Dell 11264	Polaroid 11523, 11276, 11498, 11687, 11766
10037	SVA 10587, 10865	Electrograph 11755	
Petters 11523	Sylvania 10000, 11864, 10047,	ESA 10812	RCA 10047, 11781, 12187
Philco 10054, 10463, 10145,	10054, 10154, 10051, 10178,	Fujitsu 10809, 10683, 10853	Sampo 11755
10171, 11271, 11394	10171, 10092, 10037, 11271,	Funai 11271	Samsung 10812, 10766, 10814,
Philips 11454, 10054, 10171,	11314, 11394	Gateway 11755, 11756	12051 Sanyo 11142
10037, 10556, 10605, 10690, 11254, 11506, 11744	Symphonic 10000, 10180, 10178, 10171	Haier 11748	Sceptre 11217, 11360
Pilot 10051, 10060, 10178	Syntax 11610, 11144, 11240,	Helios 10865	Sharp 10818, 10093
Polaroid 11523, 10765, 10865.	11331	Hewlett Packard 11502	Sony 10810, 11685
11276, 11314, 11498, 11687,	Tandy 10093	Hitachi 11643	Superscan 10864
11766	Tatung 10000, 10051, 10037,	HP 11502	SVA 10587
Portland 10451, 10092	11101, 11756	Insignia 11564	Sylvania 11864, 10171, 11271,
Precision 10236, 10180	Teac 10154, 10037	JVC 10731	11314, 11394 Symphonic 10171
Prism 10250, 10051 Proscan 11447, 10047	Technics 10250, 10054, 10051,		Syntax 11610, 11144, 11240,
Protec 10037	10226	LG 11423, 10178, 10856	11331
Proton 10178	Techwood 10250, 10051, 10060 Teknika 10054, 10463, 10180,	Magnavox 11866	Toshiba 11524, 10845, 11656
Proview 11498, 11687	10150, 10060, 10178, 10092	Marantz 10704, 11398 Maxent 11755, 11757	Vidikron 11398
ProVision 10037, 10556	Telecolor 10017	Mitsubishi 10836	Viewsonic 10857, 10864, 10885
Pulsar 10017, 10092	Telefunken 10702, 10625	NEC 11398, 11704	Vizio 11758, 10864, 10885, 11756
Pulser 10178, 10092	Tevion 10037, 10556	NetTV 11755	Westinghouse 11712, 10885,
Quartz 10150, 10178	Thomas 10047, 10178		10889, 10890, 11282, 11577
Quasar 10250, 10051, 10650	Thomson 11447, 10047, 10625	Panasonic 11480, 10250, 10650 Philips 10690, 11744	Wyse 11365
R-Line 10037	TMK 10236, 10180, 10178 TNCi 10017	Polaroid 10865, 11276	Zenith 11265
Rabbit 10047	Tocom 10156	Runco 11398	
RadioShack 10047, 10154, 10180,	Toshiba 11524, 10154, 10156,		HDTV
10150, 10178 RCA 10000, 11547, 11447, 10047,	11256, 10150, 11265, 10060,	Sampo 11755	Pioneer 10679
10054, 10051, 10093, 10178,	11145, 10145, 10166, 10650,	Samsung 10812, 12051 Sanyo 11142	Mitsubishi 10150
10090, 10679, 11047, 11147,	10845, 11156, 11656, 11704	Sony 10810, 10000	Olevia 11610
11247, 11781, 12187	Totevision 10051 Toyomenka 10178	SVA 10865	
Realistic 10047, 10154, 10180,	Truetone 10250, 10051	Sylvania 11271, 11394	Panasonic 10250, 10650
10150, 10178 Revox 10037	TVS 10463	Tatung 11101, 11756	RCA 11447
Runco 10017, 10060, 11398	Ultra 10092	Toshiba 10650, 11704	Samsung 10812, 10702
Sampo 11755, 10047, 11756	Universal 10047	Viewsonic 11755	Toshiba 11256
Samsung 10812, 10047, 10054,	Universum 10037	Vizio 11758, 11756	Rear Projection TV
10017, 10154, 10060, 10702,	V 11755, 10864, 10885, 11756	Zenith 10178	Akai 10812, 10702
10178, 12051, 11619, 11235,	Victor 10053, 10160	LCD	Apex Digital 10765
11060, 10814, 10766, 10650, 10587, 10037	Vidikron 10054, 11398, 11633	LCD	Hitachi 11145
Sanky 10060	Vidtech 10178 Viewsonic 11755, 10857, 10864,	Pioneer 11260	
Sansui 10463, 10060, 10171	10885	Akai 11675	JVC 11601
Sanyo 10000, 11755, 10047,	Viking 10060	AOC 11365	Mitsubishi 11250
10054, 10154, 10463, 10171, 10037, 11142	Viore 10054	Apex Digital 10890, 11217 Audiovox 10180, 10802, 10875	Panasonic 10250
Saville 10060	Vizio 11758, 11755, 10864, 10885,		RCA 11447
Sceptre 11217, 11360	11756	Byd:sign 11309	Samsung 10812
Scotch 10178	Wards 10000, 10047, 10054,	Dell 11264, 11080, 11178	Sony 10810
Scott 10236, 10180, 10178	10017, 10154, 10051, 10093, 10236, 10178, 10166, 10037,	Dynex 12049	Toshiba 10156, 11656
Sears 10000, 10047, 10054, 10017,	11156	Element 11687	
10154, 10156, 10051, 10093, 10060, 10053, 10178, 10171,	Waycon 10156	Emerson 11394 Envision 11365	TV/DVD Combination
10166, 10037	Welton 10178		Akai 11675
Seleco 11351	Westinghouse 10000, 11712, 10451, 10885, 10889, 10890.	Funai 10171	Dynex 12049
Sharp 10818, 10054, 10093,	11282, 11577	Haier 11748	Emerson 11394
10180, 11393	White Westinghouse 10451,	Hannspree 11351 Hitachi 11643	Insignia 12049
Sheng Chia 10093 Shivaki 10178, 10037, 10556	10236, 10463, 10623, 10889		Magnavox 11866
Siemens 10145	World 10451, 10236, 10463,	Insignia 11564, 11517, 11710, 12049	•
Signature 10047, 10093	10180	JVC 11601, 11774	Polaroid 11523, 11766
Simpson 10178	Wyse 11365		RCA 12187
Singer 10060, 10092	XR-1000 10154, 10180, 10171	LG 11423, 10856, 11178, 11768	Sylvania 11864, 11394
Sky-North 10037 Solar Drape 10000	Yamaha 10650	Magnavox 11866, 10802, 11365	Toshiba 11524
Sony 10810, 10000, 10017, 10154,	Zenith 10000, 10812, 11423,	Marantz 10855 Maxent 11755, 11211, 11757	TV/VCR Combination
10150, 10053, 11651, 11685	10047, 10017, 10093, 10463, 11265, 10178, 11145, 10145,	Mitsubishi 11250	America Action 10180
Soundesign 10180, 10178	10171, 10092, 10037, 10160	NEC 11797	Audiovox 10180
Spectravision 10156, 10178		Norcent 11365	Emerson 10236
Spectroniq 11498, 11687 Squareview 10171	Plasma Television	Olevia 11610, 11144, 11240,	LINEISON 10200
SR2000 10154, 10171	Pioneer 10679, 11260, 11398, 11633, 14000, 14001, 14003,	11331	
SSS 10180	14004	Panasonic 11480, 10650	

DVR/VCR

General

Pioneer 20162, 20081, 20042 20067, 20058, 22306, 22465, 22466, 22467

A-Mark 20037, 20000, 20278 **ABS** 21972 Accurian 20000

Admiral 20060, 20039 Adventura 20037, 20000 Aiko 20278 Aiwa 20037, 20000

Alba 20278 Alienware 21972 Allegro 20039 America Action 20278 American High 20035, 20081 Amstrad 20000 **Anam National 20226**

Astra 20035 Audio-Technica 20058 Audiovox 20037, 20278, 20038

Avis 20000 Bell & Howell 20035, 20039,

Broksonic 20348, 21479

Calix 20037 Candle 20037, 20038 Canon 20035 Carver 20035, 20081 **CCE** 20278 Cineral 20278

Citizen 20035, 20037, 20000,

Classic 20037

Colortyme 20060, 20035, 20045,

Colt 20000 Craig 20037 Criterion 20000

Crosley 20035, 20081, 20000 **Crown** 20278 Curtis Mathes 20060, 20035, 20162, 20000, 20278

CyberPower 21972

Daewoo 20037, 20045, 20278

Daytron 20037, 20278 **Dell** 21972 Denon 20081, 20042 DirecTV 20739 **Dual** 20000 **Durabrand** 20039, 20038

Dynatech 20000 **Electrohome** 20060, 20037, 20000 20043

Electrophonic 20037 **Emerex** 20032

Emerson 20037, 20000, 20043, 20278, 20348, 21479, 21593

Fisher 20039, 20000 Fuji 20035, 20033 Fujitsu 20000

Funai 20037, 20000, 20278, 21593

Garrard 20000 Gateway 21972

GE 20060, 20035, 20000, 20807 Gemini 20060

Genexxa 20037, 20000, 20278 GFM 21593

Go Video 20614 GoldStar 20035, 20037, 20039. 20000, 20278, 20038

Goodmans 20037, 20081, 20000,

Gradiente 20000 Granada 20081, 20042 Grundia 20081, 20226

Harley Davidson 20000 Harman/Kardon 20081, 20038 **Hewlett Packard** 21972 HI-Q 20035, 20000

Hitachi 20035, 20037, 20045, 20000, 20042

Howard Computers 21972 **HP** 21972 **Hughes Network Systems**

Humax 20739 Hush 21972 Hytek 20000 **iBUYPOWER** 21972

Instant Replay 20035, 20226 Jensen 20067 JVC 20067, 20058, 21162

KEC 20037, 20278 Kenwood 20067, 20038 Kodak 20035, 20037 **KTV** 20000

LG 20037, 20038 Lifetec 20348 Linksys 21972 Lloyd's 20000, 20038 Loewe 20081 Logik 20000 Lumatron 20278

LXI 20037, 20000, 20042, 20067

Magnasonic 20037, 20000, 20278 Magnavox 20035, 20037, 20039, 20081, 20000, 20226, 20618,

Marantz 20035, 20081, 20038 Marta 20037

Matsui 20037, 20348

Matsushita 20035, 20162, 20081,

Media Center PC 21972 Medion 20348 MEI 20035

Memorex 20035, 20162, 20037, 20039, 20000, 20278, 20348, 21162

Metz 20037 MGA 20060, 20043 Microsoft 21972 Mind 21972

Minolta 20042 Mitsubishi 20060, 20000, 20042, 20067, 20043, 20807

Motorola 20035 MTC 20000 MTX 20000

Multitech 20039, 20000

NAD 20058 NEC 20067, 20038 Nikko 20037, 20278 Nikkodo 20037, 20278 Niveus Media 21972

Northgate 21972 Olympus 20035, 20162, 20226 Onkyo 20222

Optimus 21062, 20035, 20162, 20037, 20000, 20058, 21162 Orion 20000, 20278, 21479

Panama 20035

Panasonic 21062, 20035, 20162, 20000, 20225, 20226, 20614, 20616, 21162, 21244, 21293, 21562

Penney 20035, 20162, 20037, 20081, 20000, 20042, 20067, 20038

Pentax 20042 **Philco** 20035, 20081, 20000 **Philips** 20739, 20035, 20162 20081, 20045, 20000, 20616, 20618

Pilot 20037 Polk Audio 20081 Portland 20278 Presidian 21593 Proscan 20060 Protec 20000 Pulsar 20039, 20278

Quartz 20035 Quasar 20035, 20162, 20226,

RadioShack 20035, 20162, 20037, 20000, 21162

Radix 20037 Randex 20037

RCA 20060, 20035, 20045, 20000, 20042, 20058, 20807, 20880 Realistic 20035, 20162, 20037,

20000, 20278, 21162 ReplayTV 20614, 20616 Ricavision 21972

Runco 20039 **Samsung** 20739, 20060, 20045, 20000, 20038, 21014

Sanky 20039 Sansui 20000, 20067, 21479

Sanyo 20000 Scott 20045, 20043

Sears 20060, 20035, 20162, 20037, 20039, 20033, 20045, 20000, 20042, 20067, 20043, 20058

Sharp 20032, 20000, 20807

Shintom 20039, 20000 Siemens 20037

Signature 20060, 20035, 20037, 20000

Singer 20037

Sonic Blue 20614, 20616 Sony 20032, 20035, 20033, 20000, 20067, 20226, 20636, 21972

Soundmaster 20000 Stack 9 21972 STS 20042 SV2000 20000 **SVA** 20000

Sylvania 20035, 20081, 20000, 20043, 21593

Symphonic 20000, 21593 Systemax 21972

Tagar Systems 21972 Tandy 20000

Tashiko 20037 **Tatung** 20081, 20000, 20067 **Teac** 20000, 20067

Technics 20035, 20162, 20037,

Teknika 20035, 20037, 20000 **Thomas** 20000

Thomson 20060

Tisonic 20278 Tivo 20739, 20618, 20636, 21996

TMK 20000 TNIX 20037 Toshiba 20045, 20000, 20043. 21972, 21996

Tosonic 20278 Totevision 20037 Touch 21972 Trix 20037

Ultra 20045, 20278 Vector 20045

Vector Research 20038 Victor 20067 Video Concepts 20045 Videomagic 20037 Videosonic 20000 Viewsonic 21972 Villain 20000

Voodoo 21972 Wards 20060, 20035, 20037. 20081, 20033, 20045, 20000, 20042, 20043, 20038, 20058 White Westinghouse 20000,

XR-1000 20035, 20000

Yamaha 20038 Zenith 20037, 20039, 20033, 20000, 20278, 21479 **ZT Group** 21972

PVR

Pioneer 22306, 22465, 22466, 22467

Alienware 21972 CyberPower 21972 **Dell** 21972

DirecTV 20739 Gateway 21972 **Go Video** 20614

Hewlett Packard 21972 **Howard Computers** 21972

Hughes Network Systems

Humax 20739 Hush 21972 **iBUYPOWER** 21972

Linksys 21972 Media Center PC 21972 Microsoft 21972 Mind 21972

Niveus Media 21972 Northgate 21972 Panasonic 20614, 20616

Philips 20739, 20618 RCA 20880

ReplayTV 20614, 20616

Samsung 20739 **Sonic Blue** 20614, 20616 Sony 20636, 21972 Stack 9 21972 Systemax 21972

Tagar Systems 21972 Tivo 20739, 20618, 20636 Toshiba 21972, 21996 Touch 21972

Viewsonic 21972 Voodoo 21972 **ZT Group** 21972

DVD

General

Pioneer 30525, 30571, 30142, 30631, 30632, 31460, 31512, 31571, 32442

3D LAB 30503, 30539

A-Trend 30714

Accurian 30675, 31416

Acoustic Solutions 30730

Adcom 31094 **AFG** 30788

Aiwa 30533, 30641

Akai 30695, 30770, 30899

Alba 30672 Alco 30790

Allegro 30869 **Amphion Media Works** 30872

Amstrad 30713 **AMW** 30872

Apex Digital 30533, 30672, 30794, 30796, 30797, 30830, 31004, 31020, 31056, 31061

Arrgo 31023 Audiovox 30790 Awa 30730

BBK 31224

Bel Canto Design 31571 Black Diamond 30713

Blue Parade 30571 Blue Sky 30695, 30713

Brandt 30651 Broksonic 30695, 30868

Bush 30690

California Audio Labs 30490 Cambridge Soundworks 30690

Cat 30789 Celestial 31020

Centrex 30672, 31004 Cinea 30831

CineVision 30869, 31483 Citizen 30695, 31277, 31587,

Clairtone 30571 Clatronic 30788

Coby 30778, 30852, 31086, 31107, 31321, 31351

Craig 30831

Creative 30503, 30539

CyberHome 30714, 30816, 30874, 1023, 31024, 31129, 31502,

Daewoo 30784, 30714, 30770, 30869, 31172

Dansai 30770 **Daytek** 30872 **Decca** 30770

Denon 30490, 30634, 31634,

Denver 30778 Diamond 30768 Digitor 31005 Digitrex 30672 **Disney** 30675, 31270

Dual 30675 **Durabrand** 30713, 31023

DVD2000 30521 Electrohome 32116

Elta 30690 Emerson 30591, 30675, 30821,

Enterprise 30591 Entivo 30503, 30539

Enzer 30770 ESA 30821, 31268 Firstline 30651 Fisher 30670

Funai 30675, 31268, 31334

Gateway 31158 **GE** 30522, 30815 **GFM** 30675, 31268

Go Video 30573, 30744, 30741, 30783, 30869, 31044, 31075, 31158, 31304, 31483

GoldStar 30741, 30869 Goodmans 30790 Gradiente 30490, 30651 **Grundig** 30539, 30775

H & B 30850

Harman/Kardon 30582, 30702

Hello Kitty 30831 **HIMAX** 30843

Hitachi 30573, 30664, 31247,

31664, 31748 Hiteker 30672 Hoyo 30665 Humax 31500, 31588

Hyundai 30850 iLo 31348, 31472

Initial 31472 Insignia 30675, 31268, 32095,

Integra 30571, 31769, 30627,

31634, 32147 **IRT** 30783

Jaton 30665 JBL 30702 JMB 30695

JSI 31423 **JVC** 30558, 30623, 30867, 31164, 31275, 31550

iWin 31051

Kawasaki 30790 Kenwood 30490, 30534 Kiss 30665, 30841

KLH 30790, 31020, 31149 Kloss 30533

Koss 30651, 31061, 31423 Kreisen 31421

Landel 30826 **Lasonic** 30627, 30789

Lecson 31533 **LG** 30591, 30741, 30869 Limit 30768

LiteOn 31058, 31158, 31416,

Loewe 30511, 30741 Logix 30783

Magnasonic 30651, 30675 Magnavox 30503, 30539, 30646, 30675, 30713, 30821, 31140, 31268, 31354, 31472, 31506

Marantz 30503, 30539, 30675 McIntosh 31533, 31273 **Medion** 30651

Memorex 30695, 30831, 31270 MiCO 30723, 30751

Microsoft 30522, 32083 Minato 30752

Mintek 31472 Mitsubishi 31521, 30521 Monyka 30665 Mustek 30730

Myryad 30894 **NAD** 30741 **Naiko** 30770 Nakamichi 31222 NEC 30785, 30869 Next Base 30826 Nintaus 31051

Norcent 30872, 31107 Onkyo 30503, 31769, 30627,

30612, 31612, 31627, 32147 **Oppo** 30575, 31224, 31525

Optimus 30571 Oritron 30651 Pacific 30768

Palsonic 30672, 30852

Panasonic 30490, 30503, 30571, 30632, 30703, 31010, 31011, 31362, 31462, 31490, 31579, 31641, 31762

Philco 30675, 30690, 30733 Philips 30503, 30539, 32056 32084, 30646, 30585, 30675, 30713, 30854, 31158, 31260, 31267, 31340, 31354, 31506

PianoDisc 31024 Polaroid 31020, 31061, 31086 Polk Audio 30539

Portland 30770 Presidian 30675 Proceed 30672 Proscan 30522 ProVision 30778

Owestar 30651

Radionette 30741 RadioShack 30571 **Raite** 30665

RCA 30522, 30571, 31769, 30790, 30822, 31022

Realistic 30571 Redstar 30763 Reoc 30752 Rio 30869 Rotel 30623, 31178

Rowa 31004

Saba 30651 Sampo 30752

Samsung 30490, 30573, 30744, 30199, 30820, 30899, 31044, 31075, 31748, 32329

Sansui 30695 Sanyo 30670, 30675, 30695,

Schmartz 32367 Schneider 30783 Schwaiger 30752 Sensory Science 31158

Sharp 30630, 30675, 30752, 31256, 32250 Sherwood 30770

Shinsonic 30533 **Singer** 30751 Skyworth 30898, 32148

Slim Art 30784 **SM Electronic** 30690, 30730

Sonic Blue 30573, 30783, 30869 **Sony** 31533, 30533, 30864, 31033, 31069, 31070, 31431, 31516, 31536

Superscan 30821 Sylvania 30675, 30821, 31268,

Symphonic 30675, 30821, 31268.

TAG McLaren 30894 **Tatung** 30770 Teac 30571, 30759, 30790 Technics 30490, 30703

Technika 30770 Technosonic 30730 Tevion 3065 Theta Digital 30571

Thomson 30522, 30511, 30551 **Tivo** 31503, 31512, 31588

Tokai 30665

Toshiba 30503, 30573, 30539, 31769, 30695, 31045, 31154, 31503, 31510, 31515, 31588, 31608, 32277 **Tredex** 30843

Unimax 30770 United 30730, 30788 Universum 30591, 30779 **Urban Concepts** 30503, 30539

V 31064, 31226 Venturer 30790 Vizio 31064, 31226 Xbox 30522, 32083

Yamaha 30490, 30539, 30646, 30545, 30497, 30817

Yamakawa 30665, 30710, 30872 Zenith 30503, 30591, 30741,

Zeus 30784

Blu-rav

Pioneer 30142, 32442

Denon 32258

Insignia 30675, 32428 Integra 32147

LG 30741

Magnavox 30675 Onkyo 32147 Panasonic 31641

Philips 32084 **Sharp** 32250

Sony 31516 Sylvania 30675 **HD-DVD**

Integra 31769 **LG** 30741

Microsoft 32083 Onkvo 31769

Toshiba 31769, 31515

Xbox 32083

RCA 31769

DVD-R

Pioneer 30631, 31460, 31512

Accurian 30675, 31416 Apex Digital 31056 Citizen 32116

Coby 31086

CyberHome 31129, 31502

Electrohome 32116 Funai 30675, 31334 Gateway 31158

Go Video 30741, 31158, 31304 **Humax** 31588 iLo 31348

JVC 31164, 31275 Kreisen 31421

LG 30741

LiteOn 31158, 31416

Magnavox 30646, 30675, 31506

Panasonic 30490, 31010, 31011,

Philips 30646, 31340

Polaroid 31086

RCA 30522

Samsung 30490 **Sanyo** 30670

Sensory Science 31158 Sharp 30675

Sony 31033, 31069, 31070, 31431, 31536

Sylvania 30675

Toshiba 31510, 31588, 32277

Zenith 30741

DVD/PVR Combination Pioneer 30631, 31512

Humax 31500, 31588

LG 30741

Panasonic 30490, 31010, 31011

Philips 31340

RCA 30522

Sharp 31256 Sony 31033, 31069, 31070, 31536

Sylvania 30675

Tivo 31512

Toshiba 31503, 31510, 31588

DVD/VCR Combination

Pioneer 31460

Accurian 30675

Allegro 30869 Apex Digital 31061 **Broksonic** 30695

CineVision 30869, 31483

Daewoo 30869 Emerson 30675

Funai 30675

GFM 30675

Go Video 30744, 30741, 30869, 31044, 31075, 31483

GoldStar 30741

Hitachi 30664 JVC 30867, 31164, 31550

LG 30741 LiteOn 31656

Polk Audio 70157

Proton 70157

OED 70157

70468

Rotel 70157

SAF 70157

Quad 70157

Quasar 70029

RadioShack 70000, 70032, 70180,

Realistic 70000, 70032, 70087, 70180, 70468 **Revox** 70157

RCA 70032, 70053, 70468

Sansui 70000, 70157

Sanyo 70000, 70087

Sharp 70037, 70180

Sonic Frontiers 70157

Sony 70000, 70100, 71364

Sherwood 70180

Sugden 70157

Sylvania 70157

Tandy 70032 **Teac** 70180

Technics 70029

Symphonic 70180

TAG McLaren 70157

Magnavox 30675 Memorex 30695 Panasonic 31762 Philips 30675, 31267 Polaroid 31061 Presidian 30675

RCA 30522, 30822

Samsung 30820, 31044, 31075

Sansui 30695 **Sanyo** 30670 Sharp 30630

Sony 30864, 31033, 31069, 31070.

Sylvania 30675 Symphonic 30675 Toshiba 30503 Zenith 30741, 30869

CD

General

Pioneer 71063, 70032, 71087, 70468, 73468

Aiwa 70157 Arcam 70157

Audio Research 70157

Cairn 70157

California Audio Labs 70029 Cambridge Soundworks 70157

Carver 70157 **Curtis Mathes** 70032 Denon 70034, 70766

DKK 70000 **DMX Electronics** 70157

Fisher 70000

Genexxa 70032 Grundig 70157

Harman/Kardon 70100, 70157

Hitachi 70032

Inkel 70157, 70180 Integra 70101

JVC 70032, 70072

Kenwood 70626, 70000, 70029,

70028, 70037 Krell 70157

Linn 70157

Magnavox 70157

Marantz 70626, 70029, 70157,

Matsui 70157

MCS 70029

Memorex 70000, 70032, 70468

Micromega 70157 Miro 70000

Mission 70157 Modulaire 70000, 70032, 70087.

70180 70468 Myryad 70157

NSM 70157

Onkyo 70868, 71327, 70101. 70102, 70138, 70381, 71322, 71393

Optimus 71063, 70000, 70032, 70037, 70087, 70468

Panasonic 70029, 70388, 70752 **Penney** 70029

Philips 70626, 70157

Thule Audio 70157

Victor 70072

Wards 70032, 70157, 70053,

Yamaha 70868, 70036, 71292 Yorx 70000

CD-R

Pioneer 71087 Kenwood 70626 Marantz 70626

Onkyo 71322, 71323 Philips 70626 **RCA** 70053

Sony 70000, 70100, 71364

Yamaha 71292

Pioneer 71063 Onkyo 70868 **Optimus** 71063

Satellite Set Top Box

General

Pioneer 00329, 01308

Akai 00200 Allsat 00200

Amstrad 00847, 01113

Asat 00200 Austar 00642, 00879, 01176

Bell ExpressVu 00775 **British Sky Broadcasting** 00847

Canal 00853 Chaparral 00216 Crossdigital 01109

DirecTV 01377, 00392, 00566, 18eC V 01377, 00392, 00306, 00639, 01639, 01142, 00247, 00749, 01749, 00819, 01856, 01076, 01108, 00099, 01109, 01392, 01414, 01442, 01609, 01640

Dish Network System 00775,

Dishpro 00775, 01505, 01775

Echostar 00775, 01505, 01775 Esat 00879

Expressvu 00775, 01775 Fortec Star 01821

Foxtel 00879 Funai 01377

GE 00566 **GOI** 00775, 01775 Gradiente 00887

Grundig 00173, 00847 Hitachi 00749, 00819 Houston 00775

HTS 00775, 01775 **Hughes Network Systems** 1142, 00749, 01749, 01442

Humax 01781, 01790 Indovision 00887

Innova 00099

ISkyB 00887

JVC 00775, 00492, 01775

LG 01414

Magnavox 00722 Marantz 00200 Mitsubishi 00749

Netsat 00099, 00887 Nokia 00723

Omega 00887

Pace 00847, 00887, 01175

Panasat 00879

Panasonic 00247, 00701, 00847 Pansat 01807 Philips 00775, 01142, 00749,

01749, 01076, 00722, 00099, 00200, 00847, 01442 Proscan 00392, 00566

RadioShack 00775, 00566 RCA 00775, 00392, 00566, 01142, 00143, 01291, 01392, 01442

Sagem 00820, 01114 Samsung 01377, 01142, 01276, 01108, 01109, 01442, 01609

Siemens 00173

SKY 00099, 00847, 00887, 01175 Sony 00639, 01639, 00847, 01640

Star 00887 Televisa 00887

Thomson 00392, 00566 Tivo 01142, 01442 Toshiba 00749, 01749, 00790

TPS 00820

UltimateTV 01392, 01640 Uniden 00722

ViewSat 01232 Zenith 01856, 01810

SAT/PVR Combination

Bell ExpressVu 00775

DirecTV 01377, 00392, 00639, 01142, 01076, 00099, 01392, 01442, 01640

Dish Network System 00775,

Dishpro 00775, 01505 **Echostar** 00775, 01505

Expressvu 00775

RCA 01392

01142, 01442 **Philips** 01142, 01442 **Proscan** 00392

Hughes Network Systems

01142, 01442 **Tivo** 01142, 0 1 00392 **Zenith** 01810

Samsung 01442 **Sony** 00639, 01640 **Tivo** 01142, 01442

Cable Set Top Box

General

Pioneer 01877, 00877, 00144, 00533, 01021, 01782

A-Mark 00008, 00144 ABC 00237, 00008 Acorn 00237 Action 00237 Active 00237 Active 00237

Amino 01602, 01822 **Archer** 00237 **BCC** 00276

Century 00008 Cisco 01877, 00877, 01982

Digeo 02187 **Director** 00476 **Fosgate** 00276 **GE** 00144

Comcast 01982

General Instrument 00476,

00810, 00276 GoldStar 00144 Hitachi 00008

i3 Micro 01602 Insight 00476, 00810 Jerrold 00476, 00810, 00276

Macab 00817 Memorex 00000

Motorola 01376, 00476, 00810, 00276, 01106

Myrio 01602, 01822 **Noos** 00817

Nova Vision 00008 Novaplex 00008 Ono 01068

Pace 01877, 00877, 00237, 00008, 01060, 01068

Panasonic 00000, 00008, 00144, 00107, 01982

00107, 01982 **Paragon** 00000, 00008, 00525 **Penney** 00000

Philips 01305, 00317 Pulsar 00000

Quasar 00000 RCA 01256 Regal 00276 Runco 00000

Samsung 00144 Scientific Atlanta 01877, 00877,

00237, 00000, 00008 Sejin 01602 Sony 01006 Sprucer 00144 Supercable 00276 Thomson 01256

Toshiba 00000 United Cable 00276 **US Electronics** 00276, 00008

Videoway 00000 Zenith 00000, 00525

Cable/PVR Combination

Pioneer 01877 Amino 01822 Cisco 01877, 01982 Comcast 01982 Digeo 02187

General Instrument 00810

Motorola 01376, 00810, 01106

Myrio 01822 Pace 01877, 00237 Panasonic 01982 RCA 01256

Scientific Atlanta 01877

Laser Disc Player

Pioneer 30241, 32447 **Denon** 30241 **Magnavox** 30241

Mitsubishi 30241

Cassette Deck

Pioneer 40027, 42446

Aiwa 40029 Carver 40029 Denon 40076 Grundig 40029 **Harman/Kardon** 40029 **JVC** 40244

Kenwood 40070 Magnavox 40029 Marantz 40029 Onkyo 40135 Optimus 40027 Philips 40029 Polk Audio 40029 RCA 40027

Sansui 40029 Sony 40243 Wards 40027 Yamaha 40097

Digital Tape

Pioneer 40019 **Onkyo** 40019

Video Accessory

Pioneer 01010 2Wire 02045 ABS 01272 Accurian 01653 ADB 02586 Alienware 01272 Amino 01481 AT&T 02045

CyberPower 01272 Epson 01563 Gateway 01272 Hewlett Packard 01272 Howard Computers 01272 HP 01272 Hush 01272

iBUYPOWER 01272 Insignia 01415 KoolConnect 01481

LG 01415 Linksys 01272 Magnavox 01563 Media Center PC 01272 Microsoft 02049, 01272 Mind 01272 Motorola 01998, 01363 Niveus Media 01272 Northgate 01272 Panasonic 01120 Philco 01563

Ricavision 01272

Samsung 01190, 01490

Sharp 01010

Sony 01272, 01324

Stack 9 01272

Surp West 01481

SureWest 01481 Sylvania 01563 Systemax 01272 Tagar Systems 01272 Toshiba 01272 Touch 01272 Viewsonic 01272, 01329

Voodoo 01272 Xbox 02049 Zenith 01415 ZT Group 01272

Specifications

Amplifier section

Continuous average power output of 110 watts* per channel, min., at 8 ohms, from 20 Hz to 20 000 Hz with no more than 0.09 %** total harmonic distortion.

W
el
Ω,
d)

Input (Sensitivity/Impedance)
LINE
Output (Level/Impedance)
REC
Signal-to-Noise Ratio (IHF, short circuited, A network)
LINE
Signal-to-Noise Ratio [EIA, at 1 W (1 kHz)]
LINE

Tuner Section

Frequency Range (FM)	. 87.5 MHz to 108 MHz
Antenna Input (FM)	\dots 75 Ω unbalanced
Frequency Range (AM)	530 kHz to 1700 kHz
Antenna (AM) Lo	op antenna (balanced)

Video Section Signal level

	Composite/S-Video	1 Vp-p (75 Ω)
	Component Video	Y: 1.0 Vp-p (75 Ω),
		PB, PR: 0.7 Vp-p (75 Ω)
_	and the second s	

(Video convert off)

Digital In/Out Section

HDMI terminal19-pin (Not DVI)
HDMI output type 5 V, 100 mA
USB terminal USB2.0 Full Speed (Type A)
iPod terminal

Integrated control section

Control (SR) terminal Ø 3.5 Min	i-jack (MONO)
Control (IR) terminal Ø 3.5 Min	i-jack (MONO)
IR signalHigh Active (High	gh Level: 2.0 V)
12 V Trigger terminal Ø 3.5 Min	i-jack (MONO)
12 V Trigger output type	V, Total 50 mA
RS-232C cable type 9-pin, cross type,	female-female

Miscellaneous

Power requirements	Ηz
Power consumption400 \	W
In standby 0.45 W (KURO LINK OF	F)
0.65 W (KURO LINK ON	V)
Dimensions 420 mm (W) x 173 mm (H) x 433 mm (E	
(16 ⁹ /16 in. (W) x 16 ¹³ /16 in. (H) x 17 ¹ /16 in. (D)))
Weight (without package) VSX-23TXH: 13.5 kg (29.8 II	b)
VSX-21TXH: 13.3 kg (29.3 ll	b)

Furnished Parts Number

MCACC Setup microphone (APM7009)	1
Remote control unit (AXD7545)	1
AA/IEC R6 dry cell batteries	2
iPod cable (ADE7129)	1
AM loop antenna	1
FM wire antenna	1
Power cord (ADG7111)	1
Warranty card	1
These operating instructions	

Note

• Specifications and the design are subject to possible modifications without notice, due to improvements.

Cleaning the unit

- Use a polishing cloth or dry cloth to wipe off dust and dirt.
- When the surface is dirty, wipe with a soft cloth dipped in some neutral cleanser diluted five or six times with water, and wrung out well, and then wipe again with a dry cloth. Do not use furniture wax or cleansers.
- Never use thinners, benzine, insecticide sprays or other chemicals on or near this unit, since these will corrode the surface.

Our philosophy

Pioneer is dedicated to making your home theater listening experience as close as possible to the vision of the moviemakers and mastering engineer when they created the original soundtrack. We do this by focusing on three important steps:

- 1 Designing with carefully selected components so as to transmit the original soundtrack accurately
- 2 Allowing for customized acoustic calibration according to any listening area
- 3 Tuning that transmits soul

This product includes FontAvenue $^{\otimes}$ fonts licensed by NEC corporation. FontAvenue is a registered trademark of NEC Corporation

Index

Numerics

12V trigger 36

Α

Acoustic Cal EQ 87 Acoustic Calibration EQ 66 Acoustic Calibration EQ Adjust 83 Acoustic Calibration EQ Professional 83 Advanced MCACC 77-89 Output PC 36, 88 Advanced surround 58 Analog attenuator 70 Aspect 68 Audio cable 22 **AUDIO PARAMETER 66** Auto delay 67

Auto level control (ALC) 56, 112

В

Bass 66 Bi-amp 17, 21, 22, 91 Bi-wiring 21 Brightness 68

Auto MCACC 41, 78

Auto surround 56, 112

C

Center Image 67 Center Width 67 Channel Level 87, 92 Chroma Level 68 Contrast 68 CONTROL jack 35

D

Data Management 88 Deep Color 27 Default system settings 72 Demo 77 Detail 68 Dialog Enhancement 66 Digital Noise Reduction 66 Digital Video Conversion 68 Dimension 67 Display 13, 71, 102 Dolby 56, 107 DTS 56, 108 Dual Mono 66

Dynamic Range Control 66

F

Effect 67

Fine Channel Level 81 Fine Speaker Distance 82 Flicker Reduction 96 Front Stage Surround Advance 58

Н

HDCP 27 HDMI 24-27, 37, 45, 63-65, 71, 103 HDMI Audio 67 Hue **68**

Input function 45 Default and possible settings 44 Input Setup 43-44 Input signal 61 iPod **38, 46-47, 108** Switching controls 47 IR jack 35

K

KURO LINK 27, 63-65

L

LFE Attenuate 66 Loudness 66

Manual MCACC 80 Manual speaker setup 90 MCACC Data 86 MCACC preset 61, 66, 89 Midnight 66 Multi Zone 17, 20, 22, 33-34, 69, 91, 95 Multichannel analog input 29, 46, 94

Neural THX 51, 110

OSD Language (GUI) 40

P

Panorama 67 Phase control 61 Placing 18 Play 45 Power cord 39 Power ON Level 95 POLS 65 Pre-out 30 Preset code 113 Progressive Motion 68 Pure direct 59

PureCinema 68

R

Recording 70 Remote control 9, 10, 73-76, 96, 103, 113 Reset 72 Resolution 68

S

SACD Gain 67 Setup microphone 41, 79 Sharpness 68 Sleep timer 71 Sound Delay 66 Sound Retriever 66 Speaker 17-22.97 Speaker B 17, 20, 22, 69, 91 Speaker Distance 87, 93 Speaker impedance 40 Speaker Setting 87, 91 Standard surround 56 Standing Wave 66,82 Status 71 Stream direct 59, 112 Streo 58 Surround back channel processing 59 Surround back speaker 91 Synchronized amp mode 65 System Setup 90

T

THX 18, 78, 93, 109 Home THX 57 Tone Control 66 Treble 66 Troubleshooting 98 Tuner **31, 51-52**

U

Up Mix 60 USB **39, 48-50, 105** Playable file formats 50

V

Video cable 23 Video converter 23 VIDEO PARAMETER 68 Volume Limit 95

W

WMA9 108 WMA9 Pro 30

X

x.v.Color 27 X-Curve **93**

YNR **68**





Dear Customer:

Selecting fine audio equipment such as the unit you've just purchased is only the start of your musical enjoyment. Now it's time to consider how you can maximize the fun and excitement your equipment offers. This manufacturer and the Electronic Industries Association's Consumer Electronics Group want you to get the most out of your equipment by playing it at a safe level. One that lets the sound come through loud and clear without annoying blaring or distortion-and, most importantly, without affecting your sensitive hearing.

Sound can be deceiving. Over time your hearing "comfort level" adapts to higher volumes of sound. So what sounds "normal" can actually be loud and harmful to your hearing. Guard against this by setting your equipment at a safe level BEFORE your hearing adapts.

To establish a safe level:

- Start your volume control at a low setting.
- Slowly increase the sound until you can hear it comfortably and clearly, and without distortion.

Once you have established a comfortable sound level:

· Set the dial and leave it there.

Taking a minute to do this now will help to prevent hearing damage or loss in the future. After all, we want you listening for a lifetime.

We Want You Listening For A Lifetime

Used wisely, your new sound equipment will provide a lifetime of fun and enjoyment. Since hearing damage from loud noise is often undetectable until it is too late, this manufacturer and the Electronic Industries Association's Consumer Electronics Group recommend you avoid prolonged exposure to excessive noise. This list of sound levels is included for your protection.

Decibel Level Example

- 30 Quiet library, soft whispers
- 40 Living room, refrigerator, bedroom away from traffic
- 50 Light traffic, normal conversation, quiet office
- 60 Air conditioner at 20 feet, sewing machine
- 70 Vacuum cleaner, hair dryer, noisy restaurant
- 80 Average city traffic, garbage disposals, alarm clock at two feet.

THE FOLLOWING NOISES CAN BE DANGEROUS UNDER CONSTANT EXPOSURE

- 90 Subway, motorcycle, truck traffic, lawn mower
- 100 Garbage truck, chain saw, pneumatic drill
- 120 Rock band concert in front of speakers, thunderclap
- 140 Gunshot blast, jet plane
- 180 Rocket launching pad

Information courtesy of the Deafness Research Foundation.





S001 En

Should this product require service in the U.S.A. and you wish to locate the nearest Pioneer Authorized Independent Service Company, or if you wish to purchase replacement parts, operating instructions, service manuals, or accessories, please call the number shown below.

1 - 800 - 421 - 1404

Please do not ship your product to Pioneer without first calling the Customer Support at the above listed number for assistance.

Pioneer Electronics Service, Inc. P.O. BOX 1760, Long Beach, CA 90801-1760, U.S.A.

For warranty information please see the Limited Warranty sheet included with your product.

Should this product require service in Canada, please contact a Pioneer Canadian Authorized Dealer to locate the nearest Pioneer Authorized Service Company in Canada. Alternatively, please contact the Customer Satisfaction Department at the following address:

Pioneer Electronics of Canada, Inc. Customer Satisfaction Department 300 Allstate Parkway, Markham, Ontario L3R 0P2 1-877-283-5901 905-479-4411

For warranty information please see the Limited Warranty sheet included with your product.

Si ce produit doit être réparé au Canada, veuillez vous adresser à un distributeur autorisé Pioneer du Canada pour obtenir le nom du Centre de Service Autorisé Pioneer le plus près de chez-vous. Vous pouvez aussi contacter le Service à la clientèle de Pioneer:

Pioneer Électroniques du Canada, Inc. Service Clientèle 300, Allstate Parkway, Markham, Ontario L3R 0P2 1-877-283-5901 905-479-4411

Pour obtenir des renseignements sur la garantie, veuillez vous reporter au feuillet sur la garantie restreinte qui accompagne le produit.

S018 C EF

Register Your Product on

http://www.pioneerelectronics.com (US) http://www.pioneerelectronics.ca (Canada)

PIONEER CORPORATION

4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153-8654, Japan

PIONEER ELECTRONICS (USA) INC.

P.O. BOX 1540, Long Beach, California 90801-1540, U.S.A. TEL: (800) 421-1404

PIONEER ELECTRONICS OF CANADA, INC.

300 Allstate Parkway, Markham, Ontario L3R 0P2, Canada TEL: 1-877-283-5901, 905-479-4411

PIONEER EUROPE NV

Haven 1087, Keetberglaan 1, B-9120 Melsele, Belgium TEL: 03/570.05.11

PIONEER ELECTRONICS ASIACENTRE PTE. LTD.

253 Alexandra Road, #04-01, Singapore 159936 TEL: 65-6472-7555

PIONEER ELECTRONICS AUSTRALIA PTY. LTD.

178-184 Boundary Road, Braeside, Victoria 3195, Australia, TEL: (03) 9586-6300

PIONEER ELECTRONICS DE MEXICO S.A. DE C.V.

Blvd.Manuel Avila Camacho 138 10 piso Col.Lomas de Chapultepec, Mexico, D. F. 11000 TEL: 55-9178-4270 K002 B En

Published by Pioneer Corporation. Copyright © 2009 Pioneer Corporation. All rights reserved.