


Camera Dimension Interface





Indicator status	Explain
Light on	Camera not connected
Light flashing fast	Network connection error
Light flashing slowly	Network connection ok

Installation(top loaded)



Quick operation

5.1 Equipment connection power supply

Connect the AC Adapter to the camera and to an electrical socket. When the indicator light in the blue light state and Speaker broadcast started successfully. It's means that the startup is completed and the network configuration is performed.

5.2 Download and install mobile APP Scan the QR code below to download the APP and the client may search for "EasyLive plus" in the app store. Then complete according to the instructions.



prompts code to complete registration and login.

interface, and enter the E-mail address and verify according to the

APP download OR code

5.3 Account registration and login Open EasyLive Plus ,click the registration button in the account login

Note: When selecting wireless connection and wired connection, the router needs to connect

5.4 Quick configuration of camera connection WIFI

camera according to the prompts, as shown in the figure

There are two ways to add:

wireless network:

network cable:

prompt.

Connect your phone to Wi-Fi network, and open EasyLive Plus click "Add new device", select "WIFI camera", and scan the QR code of the camera

(1) Wireless connection, the camera connects to the router through WiFi

(2) Wired connection, the camera is connected to the router through the

The two adding methods can be completed according to the mobile APP

bottom sticker or the box sticker, complete the addition of the device

Internet, the camera is connected to the Internet after the addition is successful



Unit:mm

Tiandy

This device complies with part 15 of the FCC Rules.

Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

FCC Radiation Exposure Statement This equipment complies with FCC radiation exposure limits set forth for uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna and transmitter.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates,

uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference

to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be

determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.

- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver
- Consult the dealer or an experienced radio/TV technician for help.

Safety Instruction

These instructions are intended to ensure that user can use the product correctly to avoid danger and property loss. Please carefully read this guidance and keep it for future reference before operating the device. The manual is designed to instruct users to facilitate installation. The interface in details depends on the exact product.

The latest version will be updated regularly according to the software and hardware improvement of our product.

Updated information will be updated in the latest version of this manual without prior notice.

The precaution measure is divided into "Warnings" and



Warnings

Follow these safeguards to prevent serious injury or death.

☑. Input voltage should meet both the SELV (Safety Extra

Low Voltage)

🛛. Contact the distributor for abnormal operation. Do Not disassemble or may cause irreversible damage to the device.

modify the devices in any way.

M. Moisture must be avoided for indoor devices in case of Mre and electriche loss caused by weak password.

🕅. Install the equipment on the ceiling to ensure that it can withstand atsurveillance least X times the weight of the equipment.

X. Moisture must be avoided for indoor devices in case of Xre and electricamage of ordinary Micro SD cards.



Follow these precautions to prevent potential injury or material damage N. Original package must be used for shipment and management to avoid high pressure, high vibration and imprisonments

Avoid direct contact with image sensor. Cover the dust cap while not

🛮 Do not aim the camera at the extra bright places (light, sunlight, lase Manual. The updated contents will be re extra bright places (light, sunlight, lase Manual). in case of a ecting the endurance of CMOS at the same time.

N. Do not place the camera in extremely hot, cold, dusty or damp locations, and do not expose it to high electromagnetism radiation.

A. To avoid heat accumulation, good ventilation is required for operating real product shall prevail.

the surrounding electromagnetic sensitive equipment to prevent

electromagnetic interference.

⊠. Keep the camera away from liquid while on using.

Original package during shipment is strongly recommended.

M. Any replacement of the device battery or the use of a mismatched type

🗵 Modify the default login password when 🖾 rst login the device to avoid (for example, in the case of some lithium battery types):

XX. When the Micro SD is used, it is recommended to use a special video

Micro SD card to avoid after sales maintenance arising from the rapid

Disclaimer

 \boxtimes . The company has tried its best to ensure the completeness and accuracy of the contents contained in the Manual. For any doubt or dispute, please refer t the company's Mnal explanation.

X. The company will keep the contents contained in this

Manual up-to-date in accordance with product enhancements and will periodically improve or update the products or procedures described in this Manual without prior notice.

 \square . The contents contained in this Manual are for reference and guidance only for users. It is not guaranteed to be exactly the same with the real product.

☒. The parts, components and accessories mentioned in this Manual are for ☐. Ensure that the installation location is kept at a su☐cient distance from stration purposes only and do not represent the con☐gurations of your purchased model.



Caution: Risk of explosion if the battery is replaced by an incorrect type replacement of a battery with an incorrect type that can defeat a safeguard

• disposal of a battery into Mre or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion;

* leaving a battery in an extremely high temperature surrounding environment that can result in anexplosion or the leakage of Mammable liquid or gas:

- a battery subjected to extremely low air pressure that may result in an exlosion or the leakage of Mammable liquid or gas

Warranty Card

Thank you for choosing our products. This warranty card is our company's solemn commitment to you, and based on this, the company provides you with standard warranty services. It is strongly recommended that you read the instructions carefully before using the product and operate it correctly.

Warranty Policy

The warranty applies with the warranty card supplied.

After-sales Service Policy

nis warranty is applicable to the product from the date of purchase, but the o⊠cial original purchase certiXcate shall be provided.

If the oXcial original purchase certiXcate cannot be provided or the record (date. commodit Thename) is not clear, the company will de ne the warranty period based on the product

After-sales Service Policy

According to the national regulations, users enjoy the warranty services for the quality problems within the warranty period.

· The followings shall not be covered by the warranty:

Exceeding warranty

 Physical damage due to improper use or storage Failure or damage caused during transport, loading/unloading

Repair or modi⊠cation by non-professionals

· Failure or damage caused by negligence, violation of operation rules or misoperation

· Failure or damage caused by force majeure factors (Fire.

earthquake, lightning strike) · No warranty over accessories such as fuse and battery

Products not maintained by the company

XXX high-quality service

The company reserves the right of Mnal evaluation of product failure

Tiandy

Network Video Camera Series

Ouick Start Guide



ISO 9001:2008 ISO 14001:2004 1H.30010.020042

