



Smartbright Waterproof G3 WT068C

WT068C CW LED18 L600 PSU

Smartbright Waterproof G3 WT068C, 16.5 W, 1800 lumen, 6500 K

Philips Smartbright Waterproof G3 batten offers exceptional value. It is Perfect for everyday lighting installations. Available in 3 standard sizes, it has option of Standard and through wiring version.

Product data

General Information		Power Consumption	
Light source engine type	LED	16.5 W	
CE mark	CE mark	Power Factor (Fraction)	
		0.9	
		Number of products on MCB of 16 A type B	
		1	
Light Technical		Temperature	
Luminous Flux	1,800 lumen	Ambient temperature range	
Correlated Color Temperature (Nom)	6500 K	-20 to +45 °C	
Luminous Efficacy (rated) (Nom)	110 lm/W	Controls and Dimming	
Color rendering index (CRI)	>80	Dimmable	
Light source color	865 cool daylight	No	
Optical cover/lens type	-	Control interface	
		-	
Operating and Electrical		Mechanical and Housing	
Input Voltage	220 to 240 V	Housing Material	
Line Frequency	50 or 60 Hz	Polycarbonate	
		Optical cover/lens material	
		Polycarbonate	
		Housing Color	
		White and gray	

Smartbright Waterproof G3 WT068C

Optical cover/lens finish	Opal
Overall length	598 mm
Overall width	69 mm
Overall height	74 mm
Dimensions (Height x Width x Depth)	74 x 69 x 598 mm

Approval and Application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Protection class IEC	Safety class II

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data	
Full product code	871016336059199
Order product name	WT068C CW LED18 L600 PSU
Order code	911401881380
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	911401881380
Full product name	WT068C CW LED18 L600 PSU
EAN/UPC - Case	8710163360713
EAN/UPC - Product/Case	8710163360591

Dimensional drawing

WT068C-2ft

