



General Information

Dimensions	150mm x 44mm x 24mm
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Fob Reader Operating Frequency	125KHz
Fob Reader Operating Distance	<5cm
PIN length	2 - 6 Digits
Status Indication	Red, Green, and Amber LEDs
Backlight	Keys; Blue LEDs
Tamper Facility	Yes

Outputs

Lock outputs	2
Relay Types	Normally Open & Normally Closed; Volt-Free
Operation Type	Latched & Unlatched
Unlatched Relay Time	1 - 99 Seconds
Max Switchable Load	30V @ 4A

Environmental

Ingress Protection	IP65
---------------------------	------

Power

12V - 24V AC & DC	Standby Current
80mA	Operating Current
110mA	

Construction

Material	Aluminium
Fixing	Surface
Colour	Silver

Accessories

EVBPSSBB	12V Lock power supply with battery backup
EV-EXIT	Push to Exit Release Button
EVEXITC	Contactless Exit button
EVEXITM	Push to Exit Mushroom Release Button
EXEVITMIP55	Push to Exit Mushroom Release Button IP55
EV-EBG	Green Emergency Break Glass
EXEBGEXT	External Emergency Break Glass
ENTERD	Flush Electronic Lock
ENTERD-YLR	Surface Electronic Lock
EV-ML-250	Electromagnetic Lock
EV-ML-500XT	External Electromagnetic Lock

Component Supplied

Keypad and Mounting Bracket
Screws and Wall Plugs
Diode and Capacitor
User Manual
10 x fobs