

#712SSSD40VF | #712SSSD40HF | #712MBSD40VF | #712MBSD40HF
 #712SSSD40VL | #712SSSD40HL | #712SSSD48L | #712MBSD40VL
 #712MBSD40HL | #712MBSD48L

Stainless Steel Soap Dispenser

REQUIRED TOOLS

NOT INCLUDED

- Pencil or Marking Tool
- Power Drill
- Desired Drill Bit Size
- Phillips Head Screwdriver
- Level

PARTS LIST

- Dispenser (x1)
- Dispenser Key (x1)
- Mounting Screws (x4)
- Expansion Tubes (x4)

STEP 1

Filling the Dispenser:

- This dispenser is only designed for PH neutral soap. Please only use foaming soap if you have a foaming soap dispenser and only use liquid soap if you have a liquid soap dispenser.
- Avoid using very thick liquids, abrasive cleaners, or polishes.
- When filling the dispenser, be sure to wipe off any spilled liquid as this can lead to rust.
- Never overfill the dispenser with soap.

STEP 2

Maintaining the Dispenser: Frequently clean your dispenser to maintain its appearance.

- Only use warm water to clean the inside of the dispenser, never use solvents or aggressive household cleaners like bleach or ammonia-based bathroom cleaners.
- To clean the outside of your dispenser, use a soft cloth with warm, soapy water or compatible stainless steel cleaner.
- To remove brown spots on your dispenser, rub gently with a pan cleaning pad and soapy water.

STEP 3

Installing the Dispenser:

1. First, open the lid on the top of your soap dispenser.
2. Next, place a screwdriver through the top opening to remove the screw at the back of the unit connecting the mounting plate to the dispenser.
3. Once the screw is removed, remove the mounting plate from the back of the soap dispenser and hold it up on the wall where you wish to install the dispenser. With a pencil, lightly mark the wall through the pre-drilled holes in the mounting plate to mark where you need to drill.
4. Remove the mounting plate and drill holes into the wall on top of the 3 marks made in Step 3.
5. Insert wall anchors into the drilled holes, then align the holes on the mounting plate to slide over top of the anchors. Lastly, screw into the wall anchors with a screwdriver.
6. Slide your dispenser back onto the mounting plate that is now mounted to the wall.
7. With the top opening still opened, install the screw back into the soap dispenser to reconnect the dispenser to the mounting plate.
8. Fill the dispenser with soap according to the "Filling the Dispenser" instructions.
9. Push the dispenser button to ensure it is functioning properly.