



Contents [[hide](#)]

- [1 M5STACK Atom EchoS3R Highly Integrated IoT Voice Interaction Controller](#)
- [2 Description](#)
- [3 Specifications](#)
- [4 Quick Start](#)
- [5 FCC STATEMENT](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)

M5STACK

M5STACK Atom EchoS3R Highly Integrated IoT Voice Interaction Controller



Description

Atom EchoS3R is a highly integrated IoT voice interaction controller specially designed for intelligent voice control and human-computer interaction scenarios. At its core is the ESP32-S3-PICO-1-N8R8 main control chip, which supports Wi-Fi wireless communication and comes with built-in 8MB Flash and 8MB PSRAM, meeting the diverse application development needs and providing excellent performance and scalability. The audio system employs the ES8311 monaural codec, combined with a high-sensitivity MEMS microphone and NS4150B power amplifier, to achieve clear sound pickup and high-fidelity audio output, enhancing the voice recognition and interaction experience. It is suitable for voice interaction scenarios such as AI voice assistants and smart home control.



Specifications



Specification	Parameters
SoC	Specification
PSRAM	ESP32-S3-PICO-1-N8R8@Dual-core Xtensa LX7 processor, up to 240MHz main frequency
Flash	8MB

Input Power	8MB
Audio CodeC	USB: DC 5V
MEMS Microphone	ES8311: 24-bit resolution, using I2S protocol
Power Amplifier	MSM381A3729H9BPC, Signal-to-Noise Ratio (SNR): ≥ 65 dB
Speaker	1318 cavity speaker: 1W@8 Ω
Operating Temperature	0 ~ 40°C
Product Size	24.0 x 24.0 x 16.8mm


Quick Start

Preparation


1. Visit the official Arduino website and install the Arduino IDE
<https://www.arduino.cc/en/Main/Software>
2. Add the following Board Manager URL to File → Preferences → Additional Boards Manager URLs: https://espressif.github.io/arduino-esp32/package_esp32_dev_index.json



3. Open the Boards Manager, search for “ESP32”, and click install.




4. After installation, select the board “ESP32S3 Dev Module”
5. Configure the following options. USB CDC On Boot: “Enabled”, PSRAM ”OPI PSRAM”, USB Mode: “Hardware CDC and JTAG”





Wi-Fi Scan

Select the example program “Examples” → “WiFi” → “WiFiScan”, choose the port



corresponding to your device, and click the compile and upload button in the top-left corner. After uploading is complete, open the Serial Monitor to view Wi-Fi scan information.






BLE Scan

Select the example program “Examples” → “BLE” → ”Scan”, choose the port corresponding to your device, and click the compile and upload button in the top-left corner. After uploading is complete, open the Serial Monitor to view BLE scan information.





FCC STATEMENT

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.


IMPORTANT NOTE

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet the general RF exposure requirements. The device can be used in portable exposure conditions without restriction.

Documents / Resources

	<p>M5STACK Atom EchoS3R Highly Integrated IoT Voice Interaction Controller [pdf] User Manual</p> <p>M5ATOMECHOS3R, 2AN3WM5ATOMECHOS3R, Atom EchoS3R Highly Integrated IoT Voice Interaction Controller, Atom EchoS3R, Highly Integrated IoT Voice Interaction Controller, Integrated IoT Voice Interaction Controller, IoT Voice Interaction Controller, Voice Interaction Controller, Interaction Controller, Controller</p>
---	---

References

- [User Manual](#)

M5STACK

2AN3WM5ATOMECHOS3R, Atom EchoS3R, Atom EchoS3R Highly Integrated IoT Voice Interaction Controller, controller, Highly Integrated IoT Voice Interaction Controller, Integrated IoT Voice Interaction Controller, Interaction Controller, IoT Voice Interaction Controller, M5ATOMECHOS3R, M5STACK, Voice Interaction Controller

Leave a comment

Your email address will not be published. Required fields are marked *

Comment *

Name

Email

Website

Save my name, email, and website in this browser for the next time I comment.

Post Comment

Search:

e.g. whirlpool wrf535swhz

Search

[Manuals+](#) | [Upload](#) | [Deep Search](#) | [Privacy Policy](#) | [@manuals.plus](#) | [YouTube](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.