Home » MAESTRO » MAESTRO SMC402AD Smart Controller Instructions



MAESTRO SMC402AD Smart Controller Instructions

Contents

- 1 USING INSTRUCTION
- 2 Documents /

Resources

- 2.1 References
- **3 Related Posts**

USING INSTRUCTION

The following instructions will help you transition from your MAESTRO smart home to an Amazon Alexa smart home. The Alexa smart home will allow you to maintain remote control of your ecosystem and create rooms and groups to manage your home. You'll also be able to create routines and voice commands to make your daily life easier. These instructions are designed for devices connected to your MAESTRO controller.

How to unpair your MAESTRO devices from the MAESTRO ecosystem?

It's important to unpair your devices from the MAESTRO ecosystem before pairing them with a new ecosystem.

SAT402ZB, SMT402, SMT402AD, SOR AND SORB THERMOSTATS

- 1. On the thermostat, access menu 10 by pressing the central button for three seconds. Select OFF. The icon will flash and OFF will appear on the screen.
- 2. When the icon disappears and you see °C (or °F) on the display, press the central button for three seconds. The display will stop blinking and the room temperature will be displayed.
- 3. The icon should no longer show in the upper left corner of the screen.

MAESTRO CONTROLLER

The Maestro controller (SMC402 and SMC402AD) cannot be integrated with other ecosystems as it is the brain of the Maestro ecosystem. However, you can continue to use it as a non-programmable and non-connected thermostat.

REPEATER AND AMPLIFIER

The repeater and amplifier do not need to be unpaired. They will automatically pair with the new ecosystem through the pairing procedure.

How to connect MAESTRO family Zigbee products to your 4th generation Amazon Alexa Echo? Make sure the Alexa app is installed on your smartphone or tablet. You can download the Alexa app here:

- Apple https://apps.apple.com/us/app/amazon-alexa/id944011620
- Android https://play.google.com/store/apps/details?id=com.amazon.dee.app&hl=en_US

THERMOSTATS SAT402ZB, SMT402, SMT402AD

- 1. Click on Device in the navigation bar at the bottom of the Alexa app screen.
- 2. Click on the [+] in the upper right corner of the Alexa app screen.
- 3. Choose Add a device. In the list of devices, choose Thermostat. From the list of brands, select Other and then press Zigbee.
- 4. On the thermostat, access menu 10 by pressing the central button for three seconds. Select ON. The icon will blink.
- 5. In the Alexa app, tap on Detect Devices at the bottom of the screen.
- 6. The Zigbee channel will be displayed when the connection is established, and you'll receive a notification on the Alexa app.
- 7. Press the central button for three seconds. The room temperature will be displayed. The icon should be in the upper left corner of the thermostat display.

Your thermostat is now associated with your 4th generation Amazon Alexa Echo. You'll need to repeat this process for each of the Zigbee thermostats in your home.

Documents / Resources



MAESTRO SMC402AD Smart Controller [pdf] Instructions

SMC402, SMC402AD, SAT402ZB, SMT402, SMT402AD, SMC402AD Smart Controller, SMC40 2AD, Smart Controller, Controller

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.