


matt E ARD-2-
32-TP-R-SPD
Connection
Unit



matt E ARD-2-32-TP-R-SPD Connection Unit User Guide

[Home](#) » [matt e](#) » matt E ARD-2-32-TP-R-SPD Connection Unit User Guide 

Contents

- [1 matt E ARD-2-32-TP-R-SPD Connection Unit](#)
- [2 Product Usage Instructions](#)
- [3 Frequently Asked Questions \(FAQ\):](#)
- [4 Product Features and benefits](#)
- [5 Specifications](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)
- [7 Related Posts](#)



matt E ARD-2-32-TP-R-SPD Connection Unit



Product Usage Instructions

1. **Installation:** Follow the provided installation manual to connect the unit to the three-phase power supply.
2. **Operation:** Ensure all connections are secure and follow safety guidelines when operating the unit.
3. **Maintenance:** Regularly check for any signs of damage or wear and tear. Clean the unit as needed.

Frequently Asked Questions (FAQ):

• **Q: What is the warranty period for the product?**

A: The product comes with a warranty of 1 year from the date of purchase.

• **Q: What is the Ingress Protection rating of the enclosure?**

A: The enclosure has an IP4X rating, providing protection against solid objects larger than 1mm.

• **Q: How do I ensure compliance with relevant regulations?**

A: Follow the provided guidelines and consult with a qualified electrician to ensure compliance with applicable standards and regulations.

The matt:e ARD connection centres with unique 5 pole auto reset device and built in Type 2 SPD. Simple to install, dedicated EV connection centres with built in O-PEN® technology that allows for the connection of EV charge points to the PME earthing facility without the use of earth electrodes. Helping to facilitate compliance with BS:7671. 2018 Amendment 2, 2022 Regulation 722.411.4.1.(iii).

Product Features and benefits

- Built in O-PEN® technology
- NO EARTH ELECTRODES REQUIRED
- Helps reduce disruptive and costly groundworks
- Removes the risk of striking buried services
- Simple wire in wire out connection
- Complete with Type 2 SPD
- With 2 x built in 32A TPN Type A RCBO
- Mild steel IP4X enclosure

- Standard 1 Year parts warranty.


Specifications

Input Volts	400V 50Hz
Max Load	63amps
Cable Entry Facility	Top and bottom
Terminal Capacity	25mm ²
Dimensions (H x W x D)	550mm x 360mm x 120mm
Weight	Approximately 7kG
Enclosure	Mild Steel Powder Coated
Ingress Protection	IP4X
Warranty	1 Year

...Simplifying EV connection

- T: 01543 227290
- E: info@matt-e.co.uk
- W: www.matt-e.co.uk
- matt:e Ltd, Unit 1 Langley Brook Business Park, Middleton, Tamworth B78 2BP

Documents / Resources

	matt E ARD-2-32-TP-R-SPD Connection Unit [pdf] User Guide ARD-2-32-TP-R-SPD, ARD-2-32-TP-R-SPD Connection Unit, ARD-2-32-TP-R-SPD, Connection Unit, Unit
---	---

References

- matt-e.co.uk
- [User Manual](#)

Manuals, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.