


MAX  **LIGHT**

A16 3D-4D Laser level Meter



MAX LIGHT A16 3D-4D Laser level Meter Instruction Manual

[Home](#) » [MAX LIGHT](#) » MAX LIGHT A16 3D-4D Laser level Meter Instruction Manual 

Contents

- [1 MAX LIGHT A16 3D-4D Laser level Meter](#)
- [2 FAQs](#)
- [3 specifications](#)
- [4 Daily maintenance and attention](#)
- [5 Functions and features](#)
- [6 Instructions](#)
- [7 Product diagram](#)
- [8 WARRANTY](#)
- [9 FCC](#)
- [10 Documents / Resources](#)
 - [10.1 References](#)

MAX  **LIGHT**

MAX LIGHT A16 3D-4D Laser level Meter



FAQs

Q: Can the laser beam harm human eyes?

A: The Class 2 laser crystal used in this product is harmless to the human body. However, avoid direct exposure to the laser beam.

Q: How should I clean the product?

A: Clean the shell glass frequently with a soft cloth to ensure proper light transmission. Do not wipe with organic solvents.

specifications

Laser schematic 3D omnidirectional ground and wall sticker

1. Because of Laser radiation should not look directly at the laser beam;
2. Class 2 laser crystal, harmless to the human body;
3. Forbidden to heavy press or vibrate;
4. The product shall be placed in the warehouse with ventilation, drying, heat- and fireproofing, and it is strictly prohibited to contact with corrosive material;
5. Loading, unloading, and use of products shall be handled gently, and shall not be thrown or dropped

Daily maintenance and attention

1. Daily maintenance
 1. Please store the machine in a dry, ventilated, constant temperature and dust-free place;
 2. Please wipe the shell glass frequently to ensure light transmission;
 3. when not in use for a long time, please release the locking switch for half an hour regularly to ensure that the bearing swings flexibly.
2. Attention
 1. check whether the horizontal line and vertical line are accurate before each use, otherwise, the

construction loss caused by an inaccurate laser line has nothing to do with our company;

2. nonprofessionals, do not disassemble the machine;
3. please avoid severe vibration, collision and falling of the machine;
4. please pay attention to locking the locking switch after use;
5. do not wipe the instrument with an organic solvent

Functions and features


Functions:

1. The machine is inclined to 3° and automatically leveled;
2. Alarm function beyond the safe range;
3. The magnetic damping compensation system ensures fast leveling time;
4. 360 rotatable base, equipped with fine adjustment mechanism, can make the machine quickly find the target.
5. It can be used with a tripod to adjust the working height of the machine.


Features:

1. A 360° horizontal line can be drawn on the wall;
2. Two 360° vertical lines can be drawn on the wall; (the 2D model has only one 360° vertical line)

Instructions

1. Place the instrument on the tripod, T-type wall mounting bracket or lifting platform as needed;
2. Push the main power switch forward to the ON position and the machine starts to work. The horizontal window automatically opens and produces four horizontal laser rays;
3. Touch the H key on the touch panel to control the horizontal opening and closing;
4. Touch the V key on the touch panel once, open a vertical window with one click(tick), repeat again, the second vertical window opens, and the third touch closes two vertical windows;
5. Long touch the  key for more than 3 seconds, and a click(tick) will be heard, turning on the diagonal function. At this time, you can adjust it to the angle you want without alarm or flashing. Touch this key again for more than 3 seconds, with one click(tick) to release this C function, the instrument works normally.

Note: The positive and negative terminals of the battery are properly installed. Please remove the battery if it is not used for a long time. Please charge for more than 10 hours when you use it for the first time. Please turn off the main switch after use. Please use the charger that matches the machine to charge. Please use this machine in the environment where this machine is described.




Move the measuring instrument closer to wall B (without rotating the measuring instrument), start the measuring instrument, and level the instrument. Adjust the height of the measuring instrument (with a tripod, if necessary, use the spacer), so that the intersection of the laser line is accurately projected on point II of wall B. Rotate the measuring instrument 180 degrees, but you cannot change the height of the measuring instrument, adjust the measuring instrument, let the vertical laser line pass through the point I of the wall A, let the measuring instrument level, and make a mark on the high intersection point of wall A (point III). The difference d between wall point A and point III is the actual height deviation of the measuring instrument.

You can use the following formula to calculate the maximum allowable deviation, d_{max} , $d_{max} = \text{twice the wall spacing} \times 0.2\text{mm/m}$

Example: If the wall spacing is 5 meters, then the maximum allowable deviation $d_{max} = 2 \times 5 \text{ meters} \times 0.2\text{mm/m} = 2\text{mm}$. Therefore, the distance between the marks should not exceed 2mm.

Product diagram



- Key: Horizontal line on/offline
- Key: Vertical on/offline
- Key: Press and hold for 2 seconds after the power is turned on to turn on the slash function Turn on the slash function and press and hold for 2 seconds to restore water Flat function



Note: Please use the original factory-adapted 5V charging voltage charger to charge

WARRANTY

During the warranty period, the following situations are not covered by the warranty

- Improper use leads to human damage
- Damage due to improper transportation after-sale
- Damage caused by failure to use the original accessories of the company as required
- Any self-modified, disassembled, and repaired product
- Replacement of worn parts
- Any natural wear

common problems

1. After the receiving switch is turned on, the blister backlight will flash, which is a normal phenomenon;
2. The laser line flashes to prove that the machine is not in the setting range, please adjust the level through the legs;
3. The laser line appears blurred. Please wipe the outer glass with a clean cotton cloth.

Safety precautions

1. Because of Laser radiation should not look directly at the laser beam;
2. Class 2 laser crystal, harmless to the human body;
3. Strictly forbidden to heavy press or vibrate;
4. The product shall be placed in the warehouse with ventilation, drying, heat-insulated, and fireproofing, and it is strictly prohibited to contact with corrosive materials;
5. Loading, unloading, and use of products shall be handled gently, and shall not be thrown or dropped;
6. Quality inspection certificate and packing list are attached to the packing box;

Daily maintenance and attention

1. Daily maintenance
 1. Please store the machine in a dry, ventilated, constant temperature and dust-free place;
 2. please wipe the shell glass frequently to ensure the light transmission;
 3. when not in use for a long time, please release the locking switch for half an hour regularly to ensure that the bearing swings flexibly.

Attention

1. nonprofessional, do not disassemble the machine;
2. please avoid severe vibration, collision and falling of the machine;
3. please pay attention to locking the locking switch after use;
4. do not leave the battery in the machine to avoid leakage of battery liquid
5. do not look directly at the laser line. It should be used with protective glasses;
6. do not use the instrument with organic solvent?

Certificate	
Name:	Examiner:
Model:	Date:
No.:	

User save copy(please save this part properly)

- Warranty Card The user must present a copy of the card and an official invoice at the time of warranty to confirm your warranty. service.

User name:

Mr./Ms.: _____ Age: _____

Name of the work unit: _____

Occupation: ☐ Student ☐ Worker ☐ Woodworking ☐ Metalworking
☐ Concreteworking ☐ Renovation ☐ Hardware ☐ Bydropower ☐ Engineering
☐ Others

Address: _____ Province _____ City _____ Road/Street _____ NO. _____

Zipcode: _____ Tel: _____ Fax: _____

Mobile phone: _____ Product number: _____

Date of purchase: _____ Invoice receipt number: _____

Purchase company name: _____

Purchaser`s address: _____

Purchaser`s phone: _____

Purchaser`s seal: _____

- Receipt(please fill it in and send back)
 - To ensure that you can enjoy the above warranty service, please fill in all forms and send the "receipt" back to our company within 7 days, which will take effect on the date of receiving the receipt!

User name:

Mr./Ms.: _____ Age: _____

Name of the work unit: _____

Occupation: ☐ Student ☐ Worker ☐ Woodworking ☐ Metalworking

☐ Concreteworking ☐ Renovation ☐ Hardware ☐ Bydropower ☐ Engineering

☐ Others

Address: _____ Province _____ City _____ Road/Street _____ NO. _____

Zipcode: _____ Tel: _____ Fax: _____

Mobile phone: _____ Product number: _____

Date of purchase: _____ Invoice receipt number: _____

Purchase company name: _____

Purchaser`s address: _____

Purchaser`s phone: _____

Purchaser`s seal: _____

FCC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Radiation Exposure Statement

The device has been evaluated to meet general RF exposure requirements. The device can be used in portable exposure conditions without restriction.

Documents / Resources



[MAX LIGHT A16 3D-4D Laser level Meter](#) [pdf] Instruction Manual
2BLHP-A16, 2BLHPA16, A16 3D-4D Laser level Meter, A16, 3D-4D Laser level Meter, Laser level Meter, level Meter, Meter

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.