




MEAN WELL DDR-240 Series 240W DIN Rail Type DC-DC Converter Owner's Manual

[Home](#) » [MEAN WELL](#) » MEAN WELL DDR-240 Series 240W DIN Rail Type DC-DC Converter Owner's Manual 

Contents

- 1 MEAN WELL DDR-240 Series 240W DIN Rail Type DC-DC Converter
- 2 Features
- 3 Applications
- 4 Description
- 5 Model encoding
- 6 Specification
 - 6.1 Input face
 - 6.2 Input Under-Voltage Protection
 - 6.3 Input Reverse Polarity Protection
 - 6.4 Inrush Current
 - 6.5 Hold-up Time
 - 6.6 Efficiency vs Load & Vin Curve
 - 6.7 Immunity to Environmental Conditions
 - 6.8 EN45545-2 Fire Test Conditions
 - 6.9 Mechanical Specification
 - 6.10 Installation Manual
- 7 Documents / Resources
 - 7.1 References
- 8 Related Posts



MEAN WELL DDR-240 Series 240W DIN Rail Type DC-DC Converter



Features

- Compliance to BS EN/EN50155 and BS EN/EN45545-2 railway standard
- Width only 40mm
- 2:1 wide input range
- -40-+70C wide working temperature
- 150% peak load capability
- Current sharing up to 960W(3+1)
- DC output adjustable
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- Protections: Short circuit/ Overload/Over voltage / Over temperature/ Input reverse polarity/ Input under voltage protection
- 4KVdc /O isolation(Reinforced isolation)
- DC OK relay contact
- Remote ON-OFF control
- 3 years warranty

Applications

- Bus, tram, metro or railway system
- Industrial control system
- Semi-conductor fabrication equipment
- Factory automation
- Electro-mechanical
- Wireless network
- Telecom or datacom system

GTIN CODE

MW Search: <https://www.meanwell.com/serviceGTiN.asp>

Description

DDR-240 series is a 240W DIN Rail type DC-DC converter with main features including DIN rail-type easy installation, ultra slim width (40mm), 2:1 wide input voltage, finless design, -40~+70C wide operating temperature, 4KVdc /O isolation, 150% peak load, current sharing. DC OK, adjustable output voltage and full protective functions. This series of models has various input options: 16.8-33.6V /33.6-67.2V / 67.2-154V and two output options: 24V/48V and can be used for industrial & railway control, security control, communication system and other fields. Suitable applications include to DC buck/boost regulator, increasing system insulation level and voltage drop compensation along cable...etc.

Model encoding

DDR - 240 B - 24

Output voltage(24/48Vdc)

Input voltage (B:16.8~33.6Vdc, C:33.6~67.2Vdc, D:67.2~154Vdc)

Rated wattage

Series name

Specification

MODEL		DDR-24 0B-24	DDR-24 0B-48	DDR-24 0C-24	DDR-240C-48	DDR-24 0D-24	DDR-24 0D-48	
	DC VOLTA GE	24V	48V	24V	48V	24V	48v	
	RATED C URRENT	10A	5A	10A	5A	10A	5A	
	CURRENT RANGE	0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A	
	RATED P OWER	240W	240W	240W	240W	240W	240W	
	P E A K	CURR ENT	15A	7.5A	15A	7.5A	15A	7.5A
		POW ER Note. 5	360W (3sec.)					
	RIPPLE & NOISE (m ax.) Note. 2	80mVp- p	100mVp- p	80mVp- p	100mVp-p	80mVp- p	100mVp- p	


OUT PUT	VOLTAGE ADJ. RAN GE		24 ~ 28 V	48 ~ 56V	24 ~ 28V	48 ~ 56V	24 ~ 28 V	48~ 56V
	VOLTAGE TOLERAN CE Note.3		±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	LINE REG ULATION		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	LOAD RE GULATIO N		±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	SETUP, RI SE TIME		500ms, 60ms					
	HOLD UP TIME (Typ .)		Please refer to page 6 Hold up Time(Load de-rating curve)					
INPU T	V O L T A G E R A N G E No te. 4	CON TINU OUS	16.8 ~ 33.6Vdc		33.6 ~ 67.2Vdc		67.2 ~ 154Vdc	
		100m s	14.4 ~ 16.8Vdc		28.8 ~33.6Vdc		66 ~ 67.2Vdc	
	EFFICIEN CY (Typ.)		90%	90%	91%	92%	92%	92.5%
	DC CURR ENT (Typ.)		11.2A @24Vdc		5.6A @48Vdc		2.5A @110Vdc	
	INRUSH C URRENT (Typ.)		30A					
	INTERRU PTION OF VOLTAGE SUPPLY		EN50155:2007-B/C- type comply with S2 level (10ms)@ 70% load ; D-type comply with S2 level (10ms)@ full load					
			EN50155:2017-Comply with S1 level					

PRO TEC TION	OVERLOAD Not e.5	Normally works within 150% rated output power for more than 3 seconds and then constant current protection 105~135% rated output power with auto-recovery					
	OVER VOLTAGE	28.8 ~ 35V	57.6 ~ 65.0V	28.8 ~ 35V	57.6 ~ 65V	28.8 ~ 35V	57.6 ~ 65V
		Protection type : Shut down o/p voltage, re-power on to recover					
	OVER TEMPERATURE	Shut down o/p voltage, re-power on to recover					
	UNDER VOLTAGE LOCKOUT	24Vin (B – type) :Power ON≥16.8V , OFF≤16.5V		48Vin (C – type) :Power ON≥33.6V , OFF≤33V		110Vin (D – type):Power ON≥67.2V , OFF≤65V	
FUN CTIO N	DC OK READY CONTACT RATINGS (max.)	30Vdc/1A resistive load					
	CURRENT SHARING	Up to 960W (3+1 units). Please refer to the Function Manual					
	REMOTE ON-OFF CONTROL	Please refer to the Function Manual					
ENVI RON MEN T	WORKING TEMP.	-40 ~ +70°C (Refer to “Derating Curve”)					
	WORKING HUMIDITY	5 ~ 95% RH non-condensing					
	STORAGE TEMP., HUMIDITY	-40 ~ +85, 5 ~ 95% RH non-condensing					
	TEMP. COEFFICIENT	±0.03%/°C (0 ~ 55°C)					
	VIBRATION	Component:10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes; Mounting: Compliance to IEC61373					
	OPERATING ALTITUDE Note .7	5000 meters					


SAFETY & EMC (Note 6)	SAFETY STANDARDS	IEC 62368-1, UL 62368-1, EAC TP TC 004, AS/NZS 62368.1 approved		
	WITHSTAND VOLTAGE	I/P-O/P:4KVdc I/P-FG:2.5KVdc O/P-FG:0.71KVdc		
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:>100M Ohms / 500Vdc / 25°C/ 70% RH		
	EMC EMISSION	Parameter	Standard	Test Level / Note
		Conducted	BS EN/EN55032	Class B
		Radiated	BS EN/EN55032	Class B
		Voltage Flicker	BS EN/EN61000-3-3	—
		Harmonic Current	—	—
	EMC IMMUNITY	BS EN/EN55024 , BS EN/EN61000-6-2(BS EN/EN50082-2)		
		Parameter	Standard	Test Level / Note
		ESD	BS EN/EN61000-4-2	Level 3, 8KV air ; Level 3, 6KV contact ; criteria A
		Radiated	BS EN/EN61000-4-3	Level 3, 10V/m ; criteria A
		EFT / Burst	BS EN/EN61000-4-4	Level 3, 2KV ; criteria A
		Surge	BS EN/EN61000-4-5	Level 3, 1KV/Line-Line ;Level 3, 2KV/Line-Line-FG ;criteria A
Conducted		BS EN/EN61000-4-6	Level 3, 10V ; criteria A	
Magnetic Field		BS EN/EN61000-4-8	Level 4, 30A/m ; criteria A	
RAILWAY STANDARD	Compliance to BS EN/EN45545-2 for fire protection ; Meet BS EN/EN50155 / IEC60571 including IEC61373 for shock & vibration, BS EN/EN50121-3-2 for EMC			
OTHERS	MTBF	1415.6K hrs min. Telcordia SR-332 (Bellcore) ; 189.9K hrs min. MIL-HDBK-217F (25°C)		
	DIMENSION	40*125.2*113.5mm (W*H*D)		
	PACKING	0.76Kg;20psc/16.2Kg/1.16CUFT		

NOT E	<p>1. All parameters NOT specially mentioned are measured at normal input (B:24Vdc, C:48Vdc, D:110Vdc), rated load and 25 of ambient temperature. 2. Ripple & noise are measured at 20MHz of bandwidth by using a 12 twisted pair-wire terminated with a 0.1 uf & 47 uf parallel capacitor. . tolerance: includes set up tolerance, line regulation and load regulation. Derating may be needed under low input voltage. Please check the derating curve for more details. 3 seconds max., please refer to peak loading curves. . The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies (as available on http://www.meanwell.com) 7. The ambient temperature derating of 3.5 C/1000m with fanless models and of 5C/1000m with fan models for operating altitude higher than2000m(6500ft) Product Liability Disclaimer: For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx</p>
Arr ow	<p>File Name:DDR-240-SPEC 2022-03-18</p>


■ Block Diagram



■ Derating Curve



■ Output derating VS input voltage



■ Peak Loading




Contact Close	PSU turns on / DC OK.
Contact Open	PSU turns off / DC Fail.
Contact Ratings (max.)	30V/1A resistive load.

1. Current sharing

1. Parallel operation is available by connecting the units shown as below (P+,P- are connected mutually in

parallel) :

2. The voltage difference among each output should be minimized that less than 0.2V is required.
3. The total output current must not exceed the value determined by the following equation (Output current at parallel operation) = (The rated current per unit) x (Number of unit) x 0.9.
4. In parallel operation 4 units is the maximum, please consult the manufacture for other applications.
5. When in parallel operation, the minimum output load should be greater than 3% of total output load. (Min. load > 3% rated current per unit x number of unit)



2. Remote ON-OFF Control

※ The power supply can be turned ON-OFF by using the “Remote ON-OFF” function.

Remote ON-OFF (TB1 PIN2,4)	Output Status
Open or 4 ~ 10VDC	power supply ON
Short or 0 ~ 0.8VDC	power supply OFF




Input face

There is one fuse connected in series to the positive input line, which is used to protect against abnormal surge. Fuse specifications of each model are shown as below.

Type	Fuse Type	Reference and Rating
B	Time-Lag	Conquer MST, 10A, 250V *2
C	Time-Lag	Conquer MST, 6.3A, 250V *2
D	Time-Lag	Conquer MST, 6.3A, 250V *1

Input Under-Voltage Protection

If input voltage drops below V_{imin} , the internal control IC shuts down and there is no output voltage. It recovers automatically when input voltage reaches above V_{imin} , please refer to the curve below.



Input Reverse Polarity Protection

There is a MOSFET connected in series to the negative input line. If the input polarity is connected reversely, the MOSFET opens and there will be no output to protect the unit.

Inrush Current


Inrush current is suppressed by a resistor during the initial start-up, and then the resistor is bypassed by a MOSFET to reduce power consumption after accomplishing the start-up.

Hold-up Time


EN50155: 2007 version – B/C- type comply with S2 level (10ms)@ 70% load ; D-type comply with S2 level (10ms)@ full load, Please refer to the table and curves show below for the hold up time specification.

Load Model	100% load	70% load	other load
B type (24Vin)	6ms min.	10ms min.	figure 1,2
C type (48Vin)	8ms min.	11ms min.	figure 3,4
D type (110Vin)	11ms min.	15ms min.	figure 5,6


DDR-240B-24




DDR-240B-48




DDR-240C-24




DDR-240C-48



DDR-240D-24




DDR-240D-48




Efficiency vs Load & Vin Curve

The efficiency vs load & Vin curves of each model are shown as below.


DDR-240B-24




DDR-240B-48




DDR-240C-24




DDR-240C-48



DDR-240D-24



DDR-240D-48




Immunity to Environmental Conditions

Test method	Standard	Test conditions	Status
Cooling Test	EN 50155 section 12.2.3 (Column 2, Class TX) EN 60068-2-1	Temperature: -40°C Dwell Time: 2 hrs/cycle	No damage
Dry Heat Test	EN 50155 section 12.2.4 (Column 2, Class TX) EN 50155 section 12.2.4 (Column 3, Class TX & Column 4, Class TX) EN 60068-2-2	Temperature: 70°C / 85°C Duration: 6 hrs / 10min	PASS
Damp Heat Test, Cyclic	EN 50155 section 12.2.5 EN 60068-2-30	Temperature: 25°C~55°C Humidity: 90%~100% RH Duration: 48 hrs	PASS
Vibration Test	EN 50155 section 12.2.11 EN 61373	Temperature: 19°C Humidity: 65% Duration: 10 mins	PASS
Increased Vibration Test	EN 50155 section 12.2.11 EN 61373	Temperature: 19°C Humidity: 65% Duration: 5 hrs	PASS
Shock Test	EN 50155 section 12.2.11 EN 61373	Temperature: 21± 3 °C Humidity: 65 ± 5% Duration: 30ms*18	PASS
Low Temperature Storage Test	EN 50155 section 12.2.3 (Column 2, Class TX) EN 60068-2-1	Temperature: -40°C Dwell Time: 16 hrs	PASS
Salt Mist Test	EN 50155 section 12.2.10 (Class ST4)	Temperature: 35°C± 2°C Duration: 96 hrs	PASS


EN45545-2 Fire Test Conditions

Test Items				Hazard Level	
	Items	Standard	HL1	HL2	HL3
R22	Oxygen index test	EN 45545-2:2013 EN ISO 4589-2:1996	PASS	PASS	PASS
	Smoke density test	EN 45545-2:2013 EN ISO 5659-2:2006	PASS	PASS	PASS
	Smoke toxicity test	EN 45545-2:2013 NF X70-100:2006	PASS	PASS	PASS
R24	Oxygen index test	EN 45545-2:2013 EN ISO 4589-2:1996	PASS	PASS	PASS
R25	Glow-wire test	EN 45545-2:2013 EN 60695-2-11:2000	PASS	PASS	PASS
R26	Vertical flame test	EN 45545-2:2013 EN 60695-11:2003	PASS	PASS	PASS

Mechanical Specification



■ Installation Instruction



This series fits DIN rail TS35/7.5 or TS35/15.
For installation details, please refer to the Instruction manual.

Installation Manual

Please refer to : <http://www.meanwell.com/manual.html>

Documents / Resources

	<p>MEAN WELL DDR-240 Series 240W DIN Rail Type DC-DC Converter [pdf] Owner's Manual DDR-240 Series, 240W DIN Rail Type DC-DC Converter, DDR-240 Series 240W DIN Rail Type DC-DC Converter, DIN Rail Type DC-DC Converter, Rail Type DC-DC Converter, DC-DC Converter, Converter</p>
--	---

References

- [MEAN WELL Switching Power Supply Manufacturer](#)