

METRON V2L-BY Vehicle Load Adapter User Manual

Home » METRON v2L-BY Vehicle Load Adapter User Manual



Contents

- 1 METRON V2L-BY Vehicle Load **Adapter**
- **2 Product Usage Instructions**
- **3 IMPROPER USE**
- **4 SYMBOLS USED**
- **5 GET STARTED**
- **6 TECHNICAL SPECIFICATIONS**
- **7 LIMITED WARRANTY**
- 9 Documents / Resources
 - 9.1 References
- 10 Related Posts



METRON V2L-BY Vehicle Load Adapter



INTRODUCTION

V2L-BY adapter is designed to power various standard 230 Vac electrical devices with standard household plugs (power tools, cookers, ovens, refrigerators, lights, computers, charge electric bicycles/scooters/etc and other electrical appliances) from BYD electric vehicles that feature on-board V2L (vehicle-to-load) system. Using V2L-BY in combination with Metron portable EV charger you can also charge any other electric car from your BYD car. BYD electric vehicles can usually deliver up to 2.5 kW of power, for some markets also up to 3.7 kW of power. Metron V2L-BY adapter can handle any power from 2.5 kW (Type G socket) to 3.7 kW (Type F/E socket). Any other use is not allowed and is regarded as improper use. Before using the adapter, please thoroughly read this manual and follow the instructions provided therein. Please keep the manual for future use. If you are unsure about the proper usage, please contact the manufacturer or your dealer before usage.

IMPROPER USE

Improper use can lead to property damage or personal injury. In such cases, the manufacturer and retailer accept no liability. Warranty will be voided in case of improper use.

You must not:

- · Modify/manipulate the adapter!
- Drive over the adapter!
- Draw more than 16 A (3680 W)!
- · Connect unsuitable plugs and cables!
- Use the adapter if damaged!

GENERAL SAFETY INSTRUCTIONS

- · Carefully read this security instructions before using the product!
- Never draw more than 16 A from the adapter V2L-BY!
- Children are not allowed to use the adapter.
- · Keep animals away while using the adapter.
- Avoid liquids entering the adapter. Never use the adapter if the socket or plug are wet.
- Only connect undamaged, designated and labelled plugs & cables to the adapter.

SYMBOLS USED

The following symbols are used in this manual and on the product:



This symbol indicates a danger with a risk of coursing serious injury or death or damage if not avoid ed



CE symbol is a mark of conformity indicating that a product complies with European Union directives and regulations.



This symbol signifies the requirement for separate disposal of electrical and electronic waste. See c hapter disposal.



Please read the manual before using the adapter.



Risk of electric shock due to dangerous voltage when used incorrectly.

Tamb

Do not use and store the adapter below or above the specified temperature.

GET STARTED

- Check adapter before use. Do not use the adapter if damaged!
- Socket will provide a high voltage (230 V)!
- Never draw more than 16 A from the adapter V2L-BY!
- Do not use the adapter if the socket and plug are wet.
- Only connect undamaged, designated and labelled plugs & cables to the adapter.
- Avoid using multiple adapter/power strips as they can lead to overload.
- Don't unplug before turning off.
- · Always operate in the specified order of steps.
- · Unlock the car.
- Insert Metron charging adapter V2L-BY (1).
- Now you can power various electrical devices (2).
- When you want to end "Discharging" through V2L-BY adapter simply press "unlock" on remote.
- Remove or switch off load(s) before you unplug/remove the adapter.





If the V2L-BY cuts-off power during use it may be due to an overload or low battery charge. Check the vehicle condition and charge level to determine why there is no output power.

• Vehicle to load type adapter can work with BYD electric vehicles only. It will NOT work on other electric vehicles.

TECHNICAL SPECIFICATIONS

- Vehicle side plug type Type 2
- Socket outlet types Type F (Schuko) or Type E (French) or Type G (UK) or others on request
- Maximum continuous current 16 A (13 A for Type G)
- Ingress protection rating IP44 (moisture proof)
- Operating Ambient Air Temperature Range from -40°C to +50°C
- UV resistance YES
- Dimensions [Φmax / Length] 70 mm/280 mm
- Weight 420 g

The adapter is IP rated 44, which means that the adapter is waterproof during usage. Nevertheless, please avoid the plugs to get wet and do not use the adapter if the plugs are wet.

- Never draw more than 16 A from the adapter V2L-BY!
- Do not use if plugs/sockets are wet!

CLEANING & STORAGE

Use only a dry or damp cloth for cleaning the unplugged adapter. Do not use cleaning detergents. Please secure the adapter while transporting it in your vehicle to avoid damage. Store at a dry place.

- The adapter must be completely unplugged before cleaning!
- Avoid water getting to contact parts!
- Secure adapter while transporting!

DISPOSAL

The symbol "crossed-out trash can" signifies the requirement for separate disposal of electrical and electronic waste. These devices may contain hazardous and environmentally harmful substances. Please take such devices to a designated collection point for the recycling of electrical and electronic equipment and do not dispose of them in regular household waste. You can obtain further information from local waste disposal services or the company from which you purchased the product.

GREEN PRODUCTION

All our products are produced in a carbon neutral way by using "Sustainable energy cycle" method. Production plant where we make adapters, charging cables and portable charging stations is the first fully sustainable production facility for EV charging cables. All energy needed for the heating and cooling of the building, production process and for transportation of goods and employees (except deliveries of heavy materials by trucks), is produced by 2 photovoltaic power plants and stored in 4 storage batteries. Almost all of the raw materials we use (cables, plugs) are produced in EU, to shorten supply routes and support local economy. Buying our products helps developing sustainable economy.

LIMITED WARRANTY

METRON warrants its product to the original consumer purchaser that it will repair, or replace, any product that is determined to be defective for the following terms: three (3) years from date of purchase on all components. To be eligible for repair or replacement under this warranty, the product in question must be sent back to METRON within the warranty period and the original consumer purchaser must comply with the following conditions:

- The product thereof must not have been modified or altered in any way by an unauthorized source;
- The product thereof must have been used in accordance with the user manual.

This limited warranty does not cover:

- · Damage due to improper use;
- · Accidental or intentional damage;
- Misuse, abuse, corrosion, or neglect;
- Product impaired by severe natural conditions, such as excessive hail storms, lightning strikes, tornados, flooding, ice or other natural occurrences;
- Damage due to improper packaging on return shipment.

Any and all labor charges for troubleshooting, removal or replacement of the product are not covered by this warranty and will not be honored by METRON. All shipping costs regarding repair or replacement of the product is to be pre-paid by the original consumer purchaser.

FAQ

• Q: Can the V2L-BY adapter be used with any electric vehicle?

A: No, the V2L-BY adapter is specifically designed for BYD electric vehicles with V2L support and will not work with other electric vehicles.

• Q: What should I do if the V2L-BY adapter cuts off power during use?

A: If the adapter cuts off power, it may be due to an overload or low battery charge. Check the vehicle condition and charge level to determine the issue.

Documents / Resources



METRON V2L-BY Vehicle Load Adapter [pdf] User Manual V2L-BY Vehicle Load Adapter, V2L-BY, Vehicle Load Adapter, Load Adapter

References

- <u>Metron Electric Mobility Solutions</u>
- User Manual

Manuals+, Privacy Policy