



MIKroTik RB912UAG-2HPnD-OUT BaseBox Instructions

[Home](#) » [Mikrotik](#) » MIKroTik RB912UAG-2HPnD-OUT BaseBox Instructions 

Frequency bands
terms of use



This User Manual covers BaseBox models: BaseBox 2(RB912UAG-2HPnD-OUT), BaseBox 5(RB912UAG-5HPnD-OUT), BaseBox 6 (RB912UAG-6HPnD-OUT).

The Basebox is a solid and weatherproof outdoor device based on the RB912 wireless router model. It has high power wireless and one Gigabit Ethernet connector, which supports MDI-X auto-detection. The device has two RPSMA connectors for connecting external antennas. The device is packaged with a power adapter, a PoE injector, and two mounting loops. Extra places for more RP-SMA connectors are available on the unit in this case.

Safety Warnings

Before you work on any equipment, be aware of the hazards involved with electrical circuitry, and be familiar with standard practices for preventing accidents.

Ultimate disposal of this product should be handled according to all national laws and regulations.

The Installation of the equipment must comply with local and national electrical codes.

This product is intended to be mounted outdoors on a pole. Please read the mounting instructions carefully before beginning installation. Failure to use the correct hardware and configuration or to follow the correct procedures could result in a hazardous situation for people and damage to the system.

Use only the power supply and accessories approved by the manufacturer, and which can be found in the original packaging of this product.

Read the installation instructions before connecting the system to the power source.

We cannot guarantee that no accidents or damage will occur due to the improper use of the device.

Please use this product with care and operate at your own risk!

In the case of device failure, please disconnect it from power. The fastest way to do so is by unplugging the power plug from the power outlet.

It is the customer's responsibility to follow local country regulations, including operation within legal frequency channels, output power, cabling requirements, and Dynamic Frequency Selection (DFS) requirements. All Mikrotik radio devices must be professionally installed.

This is a class A device. In a domestic environment, this product might cause radio interference in which case the user might be required to take adequate measures.

Exposure to Radio Frequency Radiation: This MikroTik equipment complies with the FCC, IC and European Union radiation exposure limits set forth for an uncontrolled environment.

First use

1. Choose your powering solution, please see the Powering section for possibilities;
2. Remove the lid, and connect the antenna to the RP-SMA connectors. Bend the cable with a large radius, so that it will be able to exit through the cable openings in the bottom of the lid. Put the lid back, with a small arrow to the front of the case;
3. Open the device's bottom door, to reveal the Ethernet connector;
4. Connect your direct input power jack if not using POE, to start up the device;
5. Connect your Ethernet cable to the Gigabit Ethernet port;
6. Download WinBox configuration tool <https://mt.lv/winbox>;
7. Open WinBox and connect to the device;
8. Default IP: is not set, user name: admin, no password, or use Neighbors tab and connect with MAC address (or, for some models, check user and wireless passwords on the sticker);
9. We recommend clicking the "Check for updates" button and updating your RouterOS software to the latest version to ensure the best performance and stability;
10. Choose your country, apply country regulation settings, and set up your password on the screen that loads.

Mounting

The device can be mounted in several ways: wall, ceiling, pole. To tighten the device to a pole, use the provided metal hose clamp.

Guide the loop around the device through the provided holes, and around the pole where it will be mounted, or use a DIN mount to attach the device to a rail:



You should avoid connecting a loose Ethernet cable to the Ethernet port, secure the cable to a wall or the pole, so that the cable weight is not pulling the port. It is recommended to secure the Ethernet cable less than 2m from the device. This is to ensure that the cable doesn't damage the port by its weight, or doesn't fall out. It is possible to connect grounding wires to the PCB board mounting holes, but to do this, you must remove the PCB from the case.

Warning! This equipment should be installed and operated with a minimum distance of 380 cm between the device and your body. Operation of this equipment in the residential environment could cause radio interference.

Powering

The device accepts power from the power jack or from the Ethernet port:

- Direct-input power jack (5.5mm outside and 2mm inside, female, pin positive plug) accepts 24 V DC.
- Ethernet port accepts passive Power over Ethernet 18-57 V DC (Please compensate voltage for loss due to cable length)

The power consumption under maximum load can reach 12 W. For BaseBox 6 model up to 23 W.

Configuration

RouterOS includes many configuration options in addition to what is described in this document. We suggest starting here to get yourself accustomed to the possibilities: <https://mt.lv/help>.

In case IP connection is not available, the Winbox tool (<https://mt.lv/winbox>) can be used to connect to the MAC address of the device from the LAN side (all access is blocked from the Internet port by default).

For recovery purposes, it is possible to boot the device from the network, see a section Reset button.

Expansion Slots and Ports

- BaseBox 2 model – 2.4 GHz, 802.11b/g/n.
- BaseBox 5 model – 5 GHz, 802.11a/n.
- BaseBox 6 model – 6 GHz, 802.11a/n.

- One 10/100/1000 Gigabit Ethernet port, supporting automatic cross/straight cable correction (Auto MDI/X), so you can use either straight or crossover cable for connecting to other network devices.
- USB type-A slot.
- One miniPCIe slot. This device might be incompatible with the R11e-LTE international modem.

The miniPCI-e slot usage

1. Remove top cover;
2. Unscrew two screws on the back of the device;



3. Open Ethernet port cover and withdraw it from the base of the device;



4. Unscrew the antenna connector;



5. Withdraw the PCB plate from the base cover;



6. Install your modem and reassemble.

Reset button

The reset button has three functions:

- Hold this button during boot time until LED light starts flashing, release the button to reset RouterOS configuration (total 5 seconds).
- Keep holding for 5 more seconds, LED turns solid, release now to turn on CAP mode. The device will now look for a CAPsMAN server (total 10 seconds).
- Or Keep holding the button for 5 more seconds until LED turns off, then release it to make the RouterBOARD look for Netinstall servers (total 15 seconds).

Regardless of the above option used, the system will load the backup RouterBOOT loader if the button is pressed before power is applied to the device. Useful for RouterBOOT debugging and recovery.

Operating system support

The device supports RouterOS software version 6. The specific factory-installed version number is indicated in the RouterOS menu /system resource. Other operating systems have not been tested.

Included parts



24V 0.8A power
adapter



Gigabit PoE injector



DIN mount (K-27)



Metal ring (one)

*DIN mount includes four screws to attach it to the back of the device.

To avoid pollution of the environment, please separate the device from household waste and dispose of it in a safe manner, such as in designated waste disposal sites. Familiarize yourself with the procedures for the proper transportation of the equipment to the designated disposal sites in your area.

Federal Communication Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a

commercial installation. 

This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications.

Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. This device and its antenna must not be co-located or operation in conjunction with any other antenna or transmitter.

IMPORTANT: Exposure to Radio Frequency Radiation.

This equipment complies with the FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance between the radiator and any part of your body, please see the table below.

Model	FCC ID	RF Exposure minimum safety distance
BaseBox 2	TV7RB912G-2HPND	142 cm
BaseBox 5	TV7RB912G-5HPNDM	375 cm
BaseBox 6	TV7RB912G-6HPND	375 cm

Antenna Installation WARNING: It is the installer's responsibility to ensure that when using the authorized antennas in the USA (or where FCC rules apply); only those antennas certified with the product are to be used. The installer should configure the output power level of antennas, according to country regulations and per antenna type. Professional installation is required for equipment with connectors to ensure compliance with health and safety issues.

Innovation, Science and Economic Development Canada

This device complies with Industry Canada's licenceexempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference,

including interference that may cause undesired operation of the device.

This Class A digital apparatus complies with Canadian ICES-003.

CAN ICES-3 (A)/NMB-3(A)

The device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems.

IMPORTANT: Exposure to Radio Frequency Radiation.

This equipment complies with the IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance between the radiator and any part of your body please see table below.

Model	IC	RF Exposure minimum safety distance
BaseBox 2	7442A-912G2HPND	142 cm
BaseBox 5	7442A-912G5HPNDM	378 cm
BaseBox 6	7442A-912G6HPNDM	378 cm





CE Declaration of Conformity

Manufacturer: Mikrotiks SIA, Unijas iela 2, Riga, Latvia, LV1039.

Hereby, Mikrotiks SIA declares that the radio equipment type RouterBOARD is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: <https://mikrotik.com/products>

Frequency bands terms of use

Frequency range (for applicable models)	Channels used	Maximum Output Power (EIRP)	Restriction
2412-2472 MHz	1 - 13	20 dBm	Without any restriction to use in all EU Member States
5150-5250 MHz	26 - 48	23 dBm	Restricted to indoor use only*
5250-5350 MHz	52 - 64	20 dBm	Restricted to indoor use only*
5470-5725 MHz	100 - 140	27 dBm	Without any restriction to use in all EU Member States

* It is the customer's responsibility to follow local country regulations, including operation within legal frequency channels, output power, cabling requirements, and Dynamic Frequency Selection (DFS) requirements. All Mikrotik radio devices must be professionally installed!

This MikroTik device meets Maximum WLAN transmit power limits per ETSI regulations. For more detailed information see Declaration of Conformity above

Please, test your antenna with our device in accreditation laboratory to be in compliance with EU rules. The information contained here is subject to change. Please visit the product page on www.mikrotik.com for the most up to date version of this document.

Contents

1 Documents / Resources

1.1 References

Documents / Resources

MIKroTik RB912UAG-2HPnD-OUT BaseBox [pdf] Instructions
RB912UAG-2HPnD-OUT BaseBox, RB912UAG-2HPnD-OUT, BaseBox

References

- [!\[\]\(b1b781be830eb908d845c527ab08d5f8_img.jpg\) MikroTik Routers and Wireless](#)
- [!\[\]\(2176a4ba510fa27404d783166e891577_img.jpg\) MikroTik Routers and Wireless - Buy](#)
- [!\[\]\(a3b1c8d49688274496e55f2751cb8993_img.jpg\) MikroTik Routers and Wireless - Products](#)
- [User Manual](#)

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.