




miliwave MWC-720 60GHz RF-BB Module with USB3.0 Interface User Manual

[Home](#) » [miliwave](#) » miliwave MWC-720 60GHz RF-BB Module with USB3.0 Interface User Manual 

Contents

- 1 MWC-720 60GHz RF-BB Module with USB3.0 Interface
- 2 Revision History
- 3 1. Introduction
- 4 2. Technical Specifications
- 5 3. Radio Specifications
- 6 4. Mechanical, Power and Environmental Specification
- 7 5. Module Throughput
- 8 6. Installation
- 9 7. FCC Statement
- 10 8. INTEGRATION INSTRUCTIONS
- 11 Documents / Resources
 - 11.1 References
- 12 Related Posts

Revision History

Date	Written by	Rev.	Description
21.06.22	Ken. Jung	1.0	MWC-720 User manual .1.0 Release
21.07.20	Ken. Jung	1.1	1.Include Typical Host Device Use Case 2.FCC Statement are modified -Minimum Distance between the radiator (antenna) and all persons from 20cm to 25.15cm

Address: 423 R&DB Center, 105 YoungTong-Gu, SuWon-Si, GyeongGi-Do,
16229 Korea

<http://www.miliwave.co.kr/>

Tel. 070-8825-0630

Fax.

Email: sales@miliwave.co.kr

Copyright © Miliwave Inc. 2020. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Miliwave Co., Ltd. All specification supplied herein are subject to change without notice at any time.

1. Introduction

1.1 Overview

Miliwave's MWC-720 module operates in the 60GHz unlicensed frequency band, IEEE802.11ad compliant, and is designed for Point to Multi-Pont (PTMP) or Point to Point (PTP) bridge wireless communication, primarily for Line-of Sight (LOS) operation. The MWC-720 module connects to a Linux based Host Communication Processor board via an available USB 3.0 port . All required drivers and firmware is pre-installed on the MWC-720 module as a self-contained device . However, the MWC-720 module would not be operational unless it is connected to the Linux-based Host Communication Processor board for PTP or PTMP bridge wireless communication.



Figure 1. MWC-720 Module

1.2 Abbreviations and Acronym Definitions

Acronym	Definition
Gbps	Giga bits per second
GHz	Giga Hertz
IEEE	Institute of Electrical and Electronics Engineers
LED	Light Emitting Diode
LoS	line-of-sight
Mbps	Mega bits per second
MCS	Modulation and Coding Scheme
MHz	Mega Hertz
PTMP	Point-to-multipoint Communication
QAM	Quadrature amplitude modulation

1.3 MWC-720 Module Description

The Miliwave's MWC-720 module in conjunction with the Host Communication Processor board can function as a PTP or PTMP bridge communication . Main characteristics of the MWC-720 module include:

- Adaptive Modulation and Link Adaptation: Up to 16QAM and MCS1-12 support
- Air Gap Phased Array Planar Antenna: EIRP 39dBm,
- Beam sweep range : Elevation 60°, Azimuth 60°
- Advanced Security: AES-128
- Compact Form Factor: 52mm x 55mm x14mm

- Connectivity: USB 3.0 Type C, 60GHz wireless

2. Technical Specifications

- Aggregate capacity: 1.4 Gbps uni-directional, 2.8 Gbps bi-directional
- Latency : less than 1 millisecond round-trip
- Security: AES-128
- I/O interface: USB 3.0(Type-C)
- Other Interface: LEDs indicators for connection status

3. Radio Specifications

- Access Technology: Single Carrier beam-forming physical layer
- Time Division Duplex
- Frequencies: 57.24GHz ~ 70.20GHz(CH1~CH6)
- Channel Bandwidth: 2.16 GHz
- Antenna:4×8 Air gap Phased Array Planar Antenna beamforming with 40 degree horizontal and 40 degree vertical
- EIRP: 39 dBm (Typical)

4. Mechanical, Power and Environmental Specification

- Dimension: 96.7mm x 52mm x22m
- Weight: 270g(with Heatsink)
- Power Consumption: 14W(Max)
- Operating Temperature: -40°C ~ +85°C
- Humidity: 5%~95%

5. Module Throughput

- MCS Index : 1-12,
- Modulation: BPSK,QPSK,16QAM
- Data Rate : Max PHY rate 4620 Mbit/s

6. Installation

The MWC-720 could only be installed with Host Communication Processor board at the factory level. There is no user serviceable parts in the MWC-720 module

7. FCC Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

b Any changes or modifications not expressly approved by the party responsible for compliance could void the

user's authority to operate this equipment.

The antenna(s) must be installed such that a minimum separation distance of at least 25.15 cm is maintained between the radiator (antenna) and all persons at all times.

8. INTEGRATION INSTRUCTIONS

List of applicable FCC rules

This module complies with part 15.255 of the FCC rules.

Summarize the specific operational use conditions 15.255(a) Operation under the provisions of this section is not permitted for the following products:

- (1) Equipment used on satellites.
- (2) Field disturbance sensors, including vehicle radar systems, unless the field disturbance sensors are employed for fixed operation, or used as short-range devices for interactive motion sensing. For the purposes of this section, the reference to fixed operation includes field disturbance sensors installed in fixed equipment, even if the sensor itself moves within the equipment.

Typical Host Device Use cases

MWC-720 Module is designed for outdoor/indoor fixed wireless host device such as Point to Point Broadband, Broadband Mesh, and WiGig to the Home.



Point-to-Point Broadband

Next generation point-to-point broadband links over 2Gb/s, 1 mile, under \$200 per node



WiGig-to-the-Home

WiGig eliminates the need to run fiber from the 'pole to the home', significantly reducing the cost of multi-gigabit internet access



Broadband Mesh

Next generation gigabit internet architecture eliminates need for fiber backbone

For more information, please contact your Miliwave (sales@miliwave.co.kr)

Limited module procedures Not applicable

Trace antenna designs Not applicable

RF exposure considerations

This module complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The module is limited to installation in mobile or fixed applications. At least 25.15 Cm of separation distance between the transmitting antenna and the user's body must be maintained at all times.

The host manual shall include the RF exposure statements.

If RF exposure statements and use conditions are not provided, then the host product manufacturer is required to take responsibility of the module through a change in FCC ID (new application).

Antennas

The module itself has antenna. (Broad band array antenna)

Label and compliance information

The module is labeled with its own FCC. If the FCC ID is not visible when the module is installed inside another

device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. In that case, the final end product must be labeled in a visible area with the following:
“Contains FCC ID: 2AVCWMWC-720”

The host manual shall include the following regulatory statement:

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user’s authority to operate this equipment.

The antenna(s) must be installed such that a minimum separation distance of at least 25.15 cm is maintained between the radiator (antenna) and all persons at all times.

Information on test modes and additional testing requirements


Testing of the host product with all the transmitters installed – referred to as the composite investigation test- is recommended, to verify that the host product meets all the applicable FCC rules. The host manufacturer can use the software to make the WiGig transmit continuously.

Additional testing, Part 15 Subpart B disclaimer

The modular transmitter is only FCC authorized for the specific rule parts (i.e., FCC transmitter rules) listed on the grant, and that the host product manufacturer is responsible for compliance to any other FCC rules that apply to the host not covered by the modular transmitter grant of certification.

The host product may need to be evaluated against the FCC Part 15B criteria for unintentional radiators in order to be properly authorized for operation as a Part 15 digital device.

Documents / Resources

	miliwave MWC-720 60GHz RF-BB Module with USB3.0 Interface [pdf] User Manual MWC-720, MWC720, 2AVCWMWC-720, 2AVCWMWC720, MWC-720 60GHz RF-BB Module with USB3.0 Interface, MWC-720, 60GHz RF-BB Module with USB3.0 Interface
---	--

References

-  [miliwave](#)