



motepro MPC2 Garage Remote compatible Programming Instructions

[Home](#) » [motepro](#) » motepro MPC2 Garage Remote compatible Programming Instructions 

Contents

- [1 motepro MPC2 Garage Remote compatible Programming](#)
- [2 MPC2 Instructions](#)
 - [2.1 Procedure if you have an existing remote](#)
 - [2.2 Procedure if you DO NOT have an existing remote](#)
- [3 WARNING](#)
- [4 Documents / Resources](#)
 - [4.1 References](#)
- [5 Related Posts](#)

motepro

motepro MPC2 Garage Remote compatible Programming



MPC2 Instructions

Procedure if you have an existing remote

1. Open the new remote by removing the two screws at the rear.
2. Open your existing remote battery cover to expose the dip switches. If you do not have an existing remote, you must find the dip switches located on the motor which are generally under the side panel.
3. Copy the switch sequence from your old remote to the new one.
4. Close both remotes and test

Procedure if you DO NOT have an existing remote

1. Open the new remote by removing the two screws at the rear.
2. Set the switches to a random sequence.
3. Press and immediately release the Code Set button on your wall control panel once. A light will illuminate.
4. Press the button on the new remote. The Code Set light will go out
5. Press the button on the new remote to ensure you have programmed it incorrectly.

WARNING

This product may contain a coin/button cell battery. Keep products and batteries away from children. The battery can cause severe or fatal injuries in 2 hours or less if swallowed or placed inside any part of the body. Seek immediate medical attention if it is suspected that a coin/button battery has been swallowed or placed inside of any part of the body.

Documents / Resources

