



MOTOROLA SOLUTIONS Enterprise Access Control Manager Appliance User Guide

[Home](#) » [Motorola Solutions](#) » MOTOROLA SOLUTIONS Enterprise Access Control Manager Appliance User Guide 



MOTOROLA SOLUTIONS

Access Control Manager™ Enterprise
Getting Started Guide



<http://avigilon.com/acm-appliances#docs>

Contents

- [1 Enterprise Access Control Manager Appliance](#)
- [2 Plug In the Appliance](#)
- [3 Connect PC to Appliance](#)
- [4 Open Web Browser](#)
- [5 Log In to the Application](#)
- [6 Edit Hostname](#)
- [7 Accept EULA](#)
- [8 License the Application](#)
- [9 Configure Port Settings](#)
- [10 Connect Appliance to Network](#)
- [11 Documents / Resources](#)
 - [11.1 References](#)

Enterprise Access Control Manager Appliance

This package includes:

- Access Control Manager Enterprise appliance



- power cords
- Front bezel
- Rails package
- Cable management kit
- Envelope containing the ACMTM software Activation ID


Plug In the Appliance

Plug the power cord into the back of the appliance and the electric plug into a surge protector or UPS. Remove the front bezel and press the power button in the upper-right of the control panel.

Power
Button




Connect Power Cord



Connect PC to Appliance

Connect a network cable directly from your PC to the Port 2 RJ-45 port on the appliance. Do not connect the PC or appliance to the local network at this point.



motorolasolutions.com/access-control

Open Web Browser


Open the web browser on the connected PC and type this IP address: 169.254.1.250



If a message indicates a connection or security error, refer to Access Control Manager Troubleshooting Browser Issues, overleaf.

Log In to the Application

When the login screen appears, enter admin for both Login and Password. Click Sign in. You must change the default password as shown:



MOTOROLA
SOLUTIONS

Access Control Manager™

You must change the default password before you can access the system.

Login:

Current password:

New password:

Confirm new password:

The Access Control Manager application main menu appears.

Edit Hostname

The default hostname for each appliance is ACM. If you need to set a specific hostname for the appliance, do so at this point before the appliance is connected to the network.

1. From the top-right corner, click  >

Appliance to display the Appliance: Edit page on the Appliance tab.

2. On the Appliance tab, enter a new Host Name.

3. Click the  Save button.

The appliance automatically restarts.



Accept EULA

After you log in the second time, accept the end user license agreement (EULA).

1. Click the link below End user license must be accepted. Accept EULA to stay in compliance.
2. Review the EULA and then select the I accept the terms of the License Agreement check box.
3. Click Submit.

License the Application


Enter the Activation ID provided in the envelope marked “IMPORTANT – DO NOT DISCARD”:

1. From the top-right corner, click  > Appliance.
2. Click the About tab.
3. Click  to open the Add Licenses dialog.

If the appliance has internet access:

1. Click the Automatic tab.
2. Enter the Activation ID.
3. Click .

If the appliance does not have internet access:

1. Click the Manual tab.
2. Enter the Activation ID.
3. Click  to generate the activation file.
4. Complete the on-screen instructions to upload the file to ACM and receive a valid license file using a computer connected to the internet.

The activation file name is:

Activation File. key


The license file name is: **capabilityResponse.bin**

5. Upload the license file to the ACM system and click

Activate Licenses


Configure Port Settings

For static IP configuration:

1. Click the Ports tab and then Port-1.
2. For static IP configuration, uncheck the Enable DHCP checkbox.
3. Enter the required values: Name, IP Address, Netmask and Network Gateway.
4. Click the  Save button.
5. Manually restart the appliance.

Connect Appliance to Network

After the appliance restarts, disconnect it from your PC. Move the appliance to its final location in the system.



Connect to Port 1


For more information about configuring your system, see the Help files provided in the Access Control Manager application.

Access Control Manager Troubleshooting Browser Issues


If the Access Control Manager application site is not found and one of these messages appears...




When using Firefox:



When using Chrome™:



When using Edge:



Tip: If you are using Edge, update your browser version before trying the following steps.



When using Safari:




Try the following steps:

1. If the Link LED on your router is not lit, ensure the Ethernet cable is connected.
2. If one of the messages shown above appears, ensure the network IP address is not set to 169.254.1.250 which is the default IP address for the appliance port in Access Control Manager.
3. To ensure the cable is connected and no conflict occurs with the IP address, type ping 169.254.1.250 at a DOS command prompt. If there is no response, double check the connection and IP address. If the connection and IP address are correct, call Avigilon Technical Support for assistance.


If a security exception screen appears...




When using Firefox:



1. Click the Advanced button.



2. Click the Add Exception... button.



3. Click the Get Certificate button.
4. Check Permanently store this exception.
5. Click the “Confirm Security Exception” button.



When using Chrome:



Click Proceed anyway.



When using Edge:

This site is not secure

This might mean that someone's trying to fool you or steal any info you send to the server. You should close this site immediately.

 [Go to your Start page](#)

Details

Your PC doesn't trust this website's security certificate.

The hostname in the website's security certificate differs from the website you are trying to visit.

Error Code: DLG_FLAGS_INVALID_CA
DLG_FLAGS_SEC_CERT_CN_INVALID

[Go on to the webpage](#) (Not recommended)

Click Go on to the webpage (Not recommended).



When using Safari:



Click the **Continue** button.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS, and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © Motorola Solutions, Inc. All rights reserved. AVIGILON, the AVIGILON logo, ACCESS CONTROL MANAGER and ACM are trademarks of Avigilon Corporation. The Chrome logo is a trademark of Google LLC. Fire Fox and the Firefox logo are trademarks of the Mozilla Foundation in the U.S. and other countries. Safari is a trademark of Apple, Inc. registered in the U.S. and other countries.



[MOTOROLA SOLUTIONS Enterprise Access Control Manager Appliance](#) [pdf] User Guide
Enterprise Access Control Manager Appliance, Enterprise, Access Control Manager Appliance,
Control Manager Appliance

References

-  [Access Control Systems & Security - Motorola Solutions](#)

Manuals+.