



MST AXON AIR BLE Module User Manual

[Home](#) » [MST](#) » MST AXON AIR BLE Module User Manual 

Contents

- [1 MST AXON AIR BLE Module](#)
- [2 Features](#)
- [3 Hardware Specifications](#)
- [4 Hardware Specifications](#)
- [5 Specification Table](#)
- [6 BLE Module Outward](#)
- [7 Final Product Sample Example](#)
- [8 Federal Communications Commission \(FCC\) Interference Statement](#)
- [9 Federal Communications Commission \(FCC\) Interference Statement](#)
- [10 Regulatory Module Integration Instructions](#)
- [11 Device Classifications](#)
- [12 FCC Definitions](#)
- [13 Simultaneous Transmission Evaluation](#)
- [14 Documents / Resources](#)
- [15 Related Posts](#)



MST AXON AIR BLE Module



Features

- Bluetooth® 5, IEEE 802.15.4-2006, 2.4 GHz transceiver. Buttons and LEDs for user interaction.
- I/O interface and NFC interface for user to expand. Support backup battery power supply.
- Support SEGGER J-Link debug interface.
- CE/FCC/IC compliant.

Hardware Specifications

<p>Bluetooth 5.0 Low Energy Standard:</p> <p>IEEE 802.15.4</p> <p>Frequency Band: 2.402GHz to 2.480GHz CH: 0~39</p> <p>Frequency Spacing: 2MHz</p> <p>Supported data rates:</p> <p>1 Mbps</p> <p>Power:</p> <p>DC 3.3V from mini PCIe interface (backup battery 225 mAh)</p>	<p>Receiver Sensitivity:</p> <p>-95 dBm sensitivity in 1 Mbps Bluetooth® low energy mode</p> <p>Antenna:</p> <p>MMCX connector *2</p> <p>CPU:</p> <p>ARM® Cortex®-M4 32-bit processor with FPU, 64 MHz</p> <p>Working Temperature:</p> <p>-20 ~ 70°C</p> <p>Storage Humidity</p> <p>10% ~ 90%</p>
--	--


Hardware Specifications

RF Work Mode: TX: Bypass Mode/Low Power Mode/High Power Mode RX: Bypass Mode/LNA Mode Antenna Select: Can select ANT1/ANT2/Sleep Mode	Beacon Transmit Configuration: Configure iBeacon/ Eddy stone / customized Beacon. Beacon Scan Scan and receive BLE beacons.
---	--

Specification Table


Item	Description
Type	BLE Module
Size mm	30 mm * 51mm
Weight g	9.7 g
Control Port	Mini PCIe
Power Supply	DC 3.3V
Antenna	2 external antennas
Bluetooth Port	Bluetooth 5.0 Low Energy
User interface	J-Link/NFC/IO Expansion
Battery Capacity mAh	225 mAh
Working Temperature	-20 C ~ 70 °C

BLE Module Outward



Number	Description
1	Antenna Connectors
2	J-Link Interface
3	Button
4	Battery
5	Mini PCIe Interface
6	IO Expansion Interface
7	NFC Interface
8	LED

Final Product Sample Example



Federal Communications Commission (FCC) Interference Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules.

These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

RF exposure warning

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

Industry Canada (IC)

CAN ICES-3 (B)/NMB-3(B)

This device complies with Industry Canada's license-exempt RSS. Operation is subject to the following two conditions:

1. This device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

IMPORTANT NOTE:

Radiation Exposure Statement: This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

Federal Communications Commission (FCC) Interference Statement

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRABLE

OPERATION.

NOTE: THE GRANTEE IS NOT RESPONSIBLE FOR ANY CHANGES OR MODIFICATIONS NOT EXPRESSLY APPROVED BY THE PARTY RESPONSIBLE FOR COMPLIANCE. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

For additional hosts other than the specific host originally granted with a limited module, a Class II permissive change is required on the module grant to register the additional host as a specific host also approved with the module. The host must meet the necessary requirements to satisfy the module limiting conditions: shield and power supply regulation.

The module is limited to OEM installation ONLY. The OEM integrator is responsible for ensuring the end-user has no manual instructions to remove or install-module.

Regulatory Module Integration Instructions

This module has been granted modular approval for mobile applications. OEM integrators for host products may use the module in their final products without additional FCC / IC (Industry Canada) certification if they meet the following conditions. Otherwise, additional FCC / IC approvals must be obtained.

- The host product with the module installed must be evaluated for simultaneous transmission requirements.
- The user manual for the host product must clearly indicate the operating requirements and conditions that must be observed to ensure compliance with current FCC / IC RF exposure guidelines.
- A label must be affixed to the outside of the host product with the following statements: To comply with FCC / IC regulations limiting both maximum RF output power and human exposure to \
- RF radiation, the maximum antenna gain including cable loss in a mobile-only exposure condition must not exceed the specification as below.

Antenna Type	Model No.	Manufacturer	Frequency Band (MHz)	Ant 0 Gain (dBi)
Omni Antenna	ANT795-4MX	SIEMENS	2402 ~ 2480	2.5

This device contains FCC ID: N73-AP60-BLE

This equipment contains equipment certified under IC: 7449B-AP60BLE

The final host/module combination may also need to be evaluated against the FCC Part 15B criteria for unintentional radiators in order to be properly authorized for operation as a Part 15 digital device.

If the final host/module combination is intended for use as a portable device (see classifications below) the host manufacturer is responsible for separate approvals for the SAR requirements from FCC Part 2.1093 and RSS-102.

Device Classifications

Since host devices vary widely with design features and configurations module integrators shall follow the guidelines below regarding device classification and simultaneous transmission and seek guidance from their preferred regulatory test lab to determine how regulatory guidelines will impact the device compliance. Proactive management of the regulatory process will minimize unexpected schedule delays and costs due to unplanned testing activities.

The module integrator must determine the minimum distance required between their host device and the user's body. The FCC provides device classification definitions to assist in making the correct determination. Note that these classifications are guidelines only; strict adherence to a device classification may not satisfy the regulatory requirement as near-body device design details may vary widely. Your preferred test lab will be able to assist in determining the appropriate device category for your host product and if a KDB or PBA must be submitted to the FCC.

Note, the module you are using has been granted modular approval for mobile applications. Portable applications may require further RF exposure (SAR) evaluations. It is also likely that the host/module combination will need to undergo testing for FCC Part 15 regardless of the device classification. Your preferred test lab will be able to assist in determining the exact tests which are required on the host/module combination.

FCC Definitions

Mobile: (§2.1091) (b) — A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. Per §2.1091d(d)(4) In some cases (for example, modular or desktop transmitters), the potential conditions of use of a device may not allow easy classification of that device as either Mobile or Portable. In these cases, applicants are responsible for determining minimum distances for compliance for the intended use and installation of the device based on evaluation of either specific absorption rate (SAR), field strength, or power density, whichever is most appropriate.

This module has not been evaluated or approved for simultaneous transmission as it is impossible to determine the exact multi-transmission scenario that a host manufacturer may choose. Any simultaneous transmission condition established through module integration into a host product must be evaluated per the requirements in KDB447498D01(8) and KDB616217D01, D03 (for laptop, notebook, netbook, and tablet applications). These requirements include, but are not limited to:

- ## Documents / Resources

Manuals+.