

NANLITE FC-60B LED Bi Color Spot Light



# NANLITE FC-60B LED Bi Color Spot Light User Manual

[Home](#) » [NANLITE](#) » NANLITE FC-60B LED Bi Color Spot Light User Manual 

## Contents

- [1 NANLITE FC-60B LED Bi Color Spot Light](#)
- [2 Product Information](#)
- [3 Product Usage Instructions](#)
- [4 FAQs](#)
- [5 Technical data](#)
- [6 Safety Precautions](#)
- [7 FCC](#)
- [8 Documents / Resources](#)
  - [8.1 References](#)

**NANLITE**

**NANLITE FC-60B LED Bi Color Spot Light**



## Product Information

- **Specifications**

- **Model:** FC-60B LED Bi-color Spot Light
- **Input:** AC 100-240V 50/60Hz 72W
- **Output:** DC15V Max. 6A
- **Color Temperature:** 2700-6500K
- **CRI:** 96
- **TLCI:** 98

## Product Usage Instructions

- **Remote Control**

- The FC-60B LED Spot Light can be remotely controlled using a 2.4G remote controller or the NANLINK APP via the transmitter box or Bluetooth.
- **Note:** The 2.4G remote controller and transmitter box are sold separately.
- **Wireless Protocol:** The fixture supports the 2.4G wireless protocols V1.0 and V2.0. Set the fixture to

V2.0 when using WS-RC-C1 or WS-RC-C2 remote controllers. For other remote controllers, set the fixture to V1.0.

#### • **Safety Precautions**

- The device complies with part 15 of the FCC Rules. Please follow these safety precautions:
- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.
- **Radiation Exposure:** Maintain a minimum distance of 20cm between the radiator and your body during installation and operation.

### **FAQs**

#### • **Can I control the FC-60B LED Spot Light remotely?**

- Yes, you can control the light remotely using a 2.4G remote controller or the NANLINK APP via Bluetooth or the transmitter box.

#### • **What are the color temperature and CRI of the FC-60B?**

- The colour temperature ranges from 2700K to 6500K, and the CRI (Color Rendering Index) is 96.

### **Model and Product name:**

- FC-60B LED Bi-color Spot Light

### **Technical data**

- **Input:** AC 100-240V 50/60Hz 72W
- **Output:** DC15V Max. 6A
- **Colour Temperature:** 2700-6500K
- **CRI:** 96
- **TLCI:** 98

### **2.4G Bluetooth Remote Control**

- FC-60B can be remotely controlled by a 2.4G remote controller, or by NANLINK APP via the transmitter box or Bluetooth directly.

### **Note:**

1. 2.4G remote controller and transmitter box are sold separately.
2. The fixture supports the 2.4G wireless protocol V1.0 and V2.0. Please set the fixture to V2.0 while using the WS-RC-C1 or WS-RC-C2 remote controller. Please set the fixture to V1.0 while using other remote controllers.

### **Safety Precautions**

1. Please open the package to check for damage caused in transit, if damaged please do not use it and contact the place of purchase or manufacturer as soon as possible.
2. Please do not use a power cord with damaged insulation, do not unplug too hard or drag the power cord directly.
3. Make sure that the power supply voltage used matches the voltage designated by the light before installation.
4. Please turn the light off when it is not in use or before cleaning.
5. Please keep the light safely stored and away from children.

## **Notice**

1. Please take off the COB protective cap before using it.
2. Please do not look directly at the emitter when the light is on.
3. Please wait 10 seconds to turn off the light fixture after any parameter setting to save it for future use.
4. Please do not place any objects on the light emitter or allow liquid to flow inside the fixture or the emitter.
5. Please do not place the light fixture near flammable substances like alcohol or gasoline.
6. Please wipe off debris or dirt by using a cloth with clean water or a neutral cleanser when cleaning the light.
7. The fixture should be used in a dry and ventilated place and avoid being used in the damp, dusty or overheated environment, also make sure the fan and the vents are not blocked or obstructed.
8. Any attempt to repair the fixture by yourself will void the warranty, disassembly and repair can only be allowed when trained professionals are involved under strict protocol regulated in this manual.
9. For optimal cooling of the fixture, the vents should not be covered when using or might result in damaging the equipment.

## **FCC**

### **FCC Statement**

This device complies with part 15 of the FCC Rules.

### **Operation is subject to the following two conditions:**

1. This device may not cause harmful interference, and
2. this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

**Note:** This equipment has been tested and found to comply with the limits for a Class B digital device, under part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used per the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.

- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body

---

## Documents / Resources

	<p><a href="#">NANLITE FC-60B LED Bi Color Spot Light</a> [pdf] User Manual</p> <p>FC-60B, FC-60B LED Bi Color Spot Light, LED Bi Color Spot Light, Bi Color Spot Light, Spot Light, Light</p>
---	--

## References

- [User Manual](#)

[Manuals+](#). [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.