



NETGEAR WAG302 ProSafe Wireless Access Point Specifications And Datasheet

[Home](#) » [NETGEAR](#) » NETGEAR WAG302 ProSafe Wireless Access Point Specifications And Datasheet 

Contents

- [1 NETGEAR WAG302 ProSafe Wireless Access Point](#)
- [2 Introduction](#)
- [3 Secure and Extensible](#)
- [4 Efficient](#)
- [5 Simple](#)
- [6 Connection](#)
- [7 Package Contents](#)
- [8 System Requirements](#)
- [9 NETGEAR Related Products](#)
- [10 Technical Specifications](#)
- [11 AutoCell RF Management and Control](#)
- [12 Support](#)
- [13 FAQ's](#)
- [14 Related Posts](#)

NETGEAR

NETGEAR WAG302 ProSafe Wireless Access Point



Introduction

Protect and Expand Your Intelligent Wireless Network

It's easy to be impressed by NETGEAR®'s business-class WAG302. The WAG302 Access Point supports both 5 GHz and 2.4 GHz 54 Mbps radio transmission with up to 108 Mbps in both 802.11g and 802.11a in turbo mode to support up to 128 simultaneous wireless clients and client types within the same coverage area. With AutoCell™ cognitive radio software, the WAG302 offers optimum WLAN performance in high-density, high-interference deployments.

Built-in security and manageability features make it ideal for any organization or institution facing increasing mobile computing needs. To protect sensitive communications and data on the wireless LAN, the WAG302 Access Point offers the most advanced and comprehensive set of authentication and encryption security capabilities on the market today. Web-based network management tools make configuration and remote management of the network painless, while SNMP and ProSafe Network Management System NMS100 integrate the wireless LAN with your wired infrastructure. Wi-Fi certification ensures interoperability with Wi-Fi-certified products from other vendors.

Secure and Extensible

NETGEAR access points support the highest available security standard, WPA2 Enterprise.** With 40/64-, and 128/152-bit WEP shared key encryption and advanced AES 256-bit encryption ensures the privacy of all wireless transmissions. 802.1x RADIUS server authentication controls wireless network access and centralizes user authorization across the network. TKIP dynamic key assignment improves security and simplifies deployment. MAC addresses access control lists control access to network resources. Other security measures include blocking SSID broadcast, rogue access point detection and notification**, secure management interfaces: SSL and SSH, and intra-cell blocking to prevent client-to-client snooping – also supports VPN pass-through.

Efficient


With radio frequency (RF) management technology, the wireless network self-optimizes. The WAG302 with AutoCell intelligently chooses channels and dynamically adjusts the power levels to ensure coverage and avoid interference. The embedded IEEE 802.3af power over ethernet (PoE) port expands installation options by eliminating the need to locate the WAG302 near a power outlet. Supports Simple Network Management Protocol (SNMP) MIB I, MIB II, and 802.11MIB. The console port facilitates local configuration and

monitoring. Users can remotely configure, update, and monitor multiple WAG302 via FTP. Supports Wireless Distribution System (WDS) for bridging and repeater modes – even able to be configured as a bridge and access point simultaneously.

Simple

Cost-effective and simple to install and use. Plenum rated – appropriate for placement above drop-down ceilings and under raised floors. Equipped with the convenient Smart Wizard™ browser-based interface for quick installation. Fitted with two powerful detachable 5 dBi antennas -expand wireless capacity and range with NETGEAR ProSafe antennas for the 2.4 GHz frequency band. IEEE 802.11e** Quality of Service (QoS) support makes it easy to handle Voice over IP (VoIP) and multimedia applications. Protected with a NETGEAR 3-year warranty.

Connection



Help

Help is there when you need it! NETGEAR provides 24×7 technical support* in English, with selected local language support during office hours.

Package Contents

- ProSafe Dual Band Wireless Access Point WAG302
- Two (2) 5 dBi Detachable Antennas
- Resource CD
- Power adapter
- Ethernet cable
- Wall Mounting Kit
- Installation guide
- Warranty/support information card

System Requirements

- PC or laptop, configured for an Internet connection, with Windows® 98, Me, 2000 or XP and 802.11b, 802.11g and/or 802.11a Wi-Fi adapter card

NETGEAR Related Products

- WAG511 ProSafe Dual Band PC Card with AutoCell
- FS108P ProSafe 8 Port Fast Ethernet Switch with PoE
- FVS318 ProSafe VPN Firewall 8
- FVS338 ProSafe VPN Firewall 50
- FVX538 ProSafe VPN Firewall 200
- WG102 ProSafe 802.11g Access Point
- WG302 ProSafe 802.11g Access Point
- FSM7326P 24 Port Layer 3 Managed Switch with PoE
- NMS100 ProSafe Network Management Software

Technical Specifications

Wireless

- **Standards:** IEEE 802.11a, IEEE 802.11g, IEEE 802.11i, IEEE 802.11e
 - **Antennas:** Two (2) 5 dBi detachable
 - **Typical maximum power output:** 802.11a (15 dBm), 802.11g (20 dBm)
 - **Typical maximum receive sensitivity:** 802.11a (89 dB), 802.11b/g (87 dBm)
- Note:** Maximum Tx varies based on country and/or region selection to ensure local regulatory compliance.

Physical Interfaces

- **LAN Port:** One (1) 10/100BASE-T Ethernet (RJ-45) port with Auto Uplink™ and IEEE 802.3af Power over Ethernet (PoE) support
- **Power adapter:** Output 12 VDC, 1.2 A; plug is localized to the country of sale
- **Five (5) LEDs:** Power, Test, 100 Mbps, Link/ACT, and WLAN 802.11g, WLAN 802.11a
- **Console Port:** One (1) with a standard RS-232C interface with DB-9 male connector
- **Antenna Connectors:** Two (2) 5 dBi reverse SMA

Network Management

- Remote configuration and management through a Web browser, SNMP, or Telnet with a command-line interface (CLI)
- SNMP management supports SNMP MIB I, MIB II, and 802.11 MIB

Advanced Wireless Features

- Bridging and repeater mode
- Simultaneous wireless bridge and access point mode
- Adjustable transmit power control 100 mW down to 0 mW

Receive Sensitivity

- 802.11b

1 Mbps	-93 dBm	-87dBm
2 Mbps	-92 dBm	-84dBm
5.5 Mbps	-92 dBm	-83dBm
11 Mbps	-89 dBm	-80dBm

- 802.11g

6 Mbps	-93 dBm	-82dBm
9 Mbps	-90 dBm	-81dBm
12 Mbps	-90 dBm	-79dBm
18 Mbps	-88 dBm	-77dBm
24 Mbps	-84 dBm	-74dBm
36 Mbps	-80 dBm	-70dBm
48 Mbps	-76 dBm	-66dBm
54 Mbps	-75 dBm	-65dBm

- 802.11a

6 Mbps	-89 dBm
9 Mbps	-88 dBm
12 Mbps	-87 dBm
18 Mbps	-86 dBm
24 Mbps	-82 dBm
36 Mbps	-79 dBm
48 Mbps	-73 dBm
54 Mbps	-69 dBm

Security

- IEEE 802.11i Wi-Fi Protected Access (WPA-2)
- Block SSID Broadcast
- VPN pass-through support
- MAC address filtering with access control lists, up to 255 users
- 802.1x RADIUS support with EAP TLS, TTLS, PEAP
- Secure SSH Telnet
- Secure Socket Layer (SSL) remote management login
- Wireless isolation enables peer-to-peer blocking so users may not access another user's PC

Standards, Safety, and Electromagnetic Conformance

- IEEE 802.3af Power over Ethernet (PoE)
- FCC Part 15 Subpart B and Subpart C
- CE EN60950, EN 300328-2 v1.1.1 (2000-07), EMC EN301489-1 v1.2.1 (2000-08), and EN301489-17 v1.1.1 (2000-09), EN55022(B), CISPR22(B), AS/NZS 3548(B)

Physical Specifications

- **Dimensions:** 25.4 x 17.8 x 3.18 cm (10 x 7 x 1.25 in.)
- **Weight:** 996.15 g (2 lbs. 13 oz.)
- **Processor:** 266 MHz Intel XScale IXP 422B

- **Memory:** 16MB Flash, 32MB DRAM
- **Power over Ethernet required:** 10 W

Environmental Specifications

- **Operating temperature:** 0 to 40° C (32 to 104° F)
- **Operating humidity:** 90% maximum relative humidity, non-condensing

Warranty

- NETGEAR 3-year warranty

Antennas and Accessories

- ANT24O5 5 dBi Omni-directional antenna
- ANT24O9 9 dBi Indoor/Outdoor Omni-directional Antenna
- ANT24D18 18 dBi Indoor/Outdoor Directional Antenna
- **Four (4) antenna cable lengths:** 1.5, 3, 5, and 10 m

AutoCell RF Management and Control

AutoCell RF Management technology is sophisticated cognitive radio software embedded in the WAG302 firmware that is accessed via the user interface. The AutoCell-enabled WAG302 monitors radio frequency (RF) patterns and automatically tunes the access point signal strength and channel selection to avoid interference to achieve optimum performance. An evaluation copy of the separately sold AutoCell View monitoring software is available on the Resource CD.

Support

- **Address:** 4500 Great America Parkway Santa Clara, CA 95054 USA
- **Phone:** 1-888-NETGEAR (638-4327)
- **E-mail:** info@NETGEAR.com
- **Website:** www.NETGEAR.com

Trademarks

©2005 NETGEAR, Inc. NETGEAR®, Everybody's connecting®, the Netgear logo, Auto Uplink, ProSafe, Smart Wizard and RangeMax are trademarks or registered trademarks of NETGEAR, Inc. in the United States and/or other countries. Microsoft, Windows, and the Windows logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. All rights reserved.

* Free basic installation support is provided for 90 days from the date of purchase. Advanced product features and configurations are not included in free basic installation support; optional premium support available.

FAQ's

What is the NETGEAR WAG302 ProSafe Wireless Access Point?

The NETGEAR WAG302 is a ProSafe Wireless Access Point designed to provide wireless connectivity and network access in various settings.

What are the key features of the NETGEAR WAG302 access point?

The NETGEAR WAG302 typically features 802.11g wireless technology, multiple security options, Power over Ethernet (PoE) support, and easy setup.

What wireless standards does this access point support?

The NETGEAR WAG302 often supports the 802.11g wireless standard, offering wireless data transfer speeds of up to 54 Mbps.

Is Power over Ethernet (PoE) supported, and what are the benefits?

Yes, the NETGEAR WAG302 typically supports PoE, which allows you to power the access point via the Ethernet cable, simplifying installation and reducing cable clutter.

What security features are integrated into this access point?

This access point often includes security features such as WEP, WPA, and WPA2 encryption, as well as MAC address filtering to secure your wireless network.

Can multiple WAG302 access points be managed from a central location?

Yes, the NETGEAR WAG302 access points can often be managed centrally using NETGEAR's wireless management solutions, making it easier to oversee multiple access points.

What is the typical range of the NETGEAR WAG302 access point?

The range of this access point can vary, but it typically provides coverage for a medium-sized office or home environment, depending on obstacles and interference.

Does this access point support multiple SSIDs (Service Set Identifiers)?

Yes, the NETGEAR WAG302 often supports multiple SSIDs, allowing you to create separate wireless networks with different security settings.

Is there a web-based interface for configuring and managing the access point?

Yes, this access point typically provides a user-friendly web-based interface for configuration and monitoring.

What types of antennas are included with the NETGEAR WAG302?

The access point often includes external detachable antennas, which can be replaced or upgraded for improved coverage.

Can the NETGEAR WAG302 be used in outdoor environments?

The NETGEAR WAG302 is typically designed for indoor use and may not be suitable for outdoor deployments.

Is there a warranty provided with the NETGEAR WAG302 access point?

The NETGEAR WAG302 access point often comes with a limited warranty. The duration and terms of the warranty may vary, so check the documentation for details.

Is the NETGEAR WAG302 access point suitable for small businesses or home offices?

Yes, the NETGEAR WAG302 is often used in small business or home office environments to provide wireless network access and connectivity.

References: [NETGEAR WAG302 ProSafe Wireless Access Point – Device.report](#)