

NEXTORCH UT30 Smart Sensing Multi Function Safety or Warning Light User Manual

Home » NEXTORCH » NEXTORCH UT30 Smart Sensing Multi Function Safety or Warning Light User Manual





Learn more at www.nextorch.com

Contents

- 1 SPECIFICATIONS
- **2 FEATURES**
- **3 INSTRUCTION**
- **4 MAINTENANCE**
- **5 WARRANTY**
- 6 Documents /

Resources

- **6.1 References**
- 7 Related Posts

SPECIFICATIONS

ANSI / PLATO-FL1	Spotlight	Floodlight	Spotlight + Floodligh t	Red Light
Light Output	220 lm	140 lm	320 lm	4 lm
Run Time	7 h	7 h 30 min	3 h 45 min	21 h
Beam Distance	53 m	15 m	55 m	_
Impact Resistance	1 m			
Water Resistant	IPX4			
Weight and Dimensions	Weight: 41 g / 1.44oz (Without Accessories) Size: 61 mm (Length) × 47 mm (Width) × 19 mm (Height)			
Material	Light Source: White/Red Light LED			
	ABS			
Battery	Built-in 640 mAh Rechargeable Battery			

The above-tested specifications are strictly based on the standard of ANSI / PLATO-FL1. We tested UT30 with a built-in 640 mAh rechargeable battery at 22 °C ± 3 °C. The specifications might be different when using a different battery or testing in a different environment.

FEATURES

- LED infrared induction for hands-free operation.
- Type-C Rechargeable design, economical and convenient.
- Equipped with an LED battery indicator, easy to check the battery level.
- Compatible with headlamp strip, cap clip, bicycle mount, and helmet mount.

INSTRUCTION

• ON / OFF


Press the hold the Normal Switch for 1 second.



• Inductive Operation

Press the Inductive Switch and the blue LED indicator will be on.


Waving your hand twice at the motion detector will turn the light on / off.



Mode Switch


Press to switch modes when the light is on.

Press the hold for 3 seconds for S.O.S. mode.



Charge

Charging time is about 2 hours.



MAINTENANCE

- 1. Being infected with seawater or any corrosive chemicals, please rinse immediately with clean water.
- 2. Please use high-quality batteries; Remove batteries when not working for a long time, and then store them in a cool dry place.
- 3. Replace the waterproof O-ring immediately when considering the damage with use.

WARRANTY

- NEXTORCH warrants our products to be free from any defects in workmanship and/or materials for a period of 15-day from the date of purchase. We will replace it. NEXTORCH reserves the right to replace an obsolete product with current production, like a model.
- 2. NEXTORCH warrants our products to be free of defects for 5-year of use. We will repair it.
- 3. The warranty excludes other accessories, but rechargeable batteries are warranted for 1 year from the date of purchase.
- 4. In the event that any issue with a NEXTORCH product is not covered under this warranty, NEXTORCH can arrange to have the product repaired for a reasonable fee.
- 5. You could access to NEXTORCH website (www.nextorch.com) to gain warranty service information by scanning the following QR code. You could also:

Email us at service@nextorch.com

Call us: 0086-400-8300-799

OR contact your local dealer/distributor.



http://www.nextorch.com/en/index.php/aftersales

CONTACT WITH NEXTORCH DESIGNER

In order to improve NEXTORCH, we appreciate you could offer our designers your after-use feedback and creative suggestions by scanning the following QR code. Thank you!



https://u.wechat.com/EF0M2xYOkDZ2Z8VXBY7Gb7l



https://www.facebook.com/nextorchlight

Documents / Resources



NEXTORCH UT30 Smart Sensing Multi Function Safety or Warning Light [pdf] User Manual

UT30, Smart Sensing Multi Function Safety or Warning Light, UT30 Smart Sensing Multi Function Safety or Warning Light, Sensing Multi Function Safety or Warning Light, Safe

References

- MINEXTORCH, Professional's Edge
- MINEXTORCH Deutschland

Manuals+,