

NIGHTSTICK XPP-5452G Intrinsically Safe Dual Function Headlamp Instruction Manual

<u>Home</u> » <u>NIGHTSTICK</u> » NIGHTSTICK XPP-5452G Intrinsically Safe Dual Function Headlamp Instruction Manual

NIGHTSTICK XPP-5452G Intrinsically Safe Dual Function Headlamp Instruction Manual



Instruction Manual XPP-5452G

THE XPP-5452G IS APPROVED FOR USE

Bayco Products, Inc. XPP-5452G 640 S. Sanden Blvd. Wylie, TX 75098



Intertek

ID 4003544
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T4
CLASS II & III GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T4 Ga
CLASS I ZONE 0 Ex ia IIC T4 Ga

© II 1 G Ex ia op is IIC T4 Ga

C € 2575 CA 0359





Ex ia op is IIC T4 Ga
Intertek ITS 13 ATEX27854X
ITS21UKEX0247X
IECEx ITS 17.0002X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline

WARNINGS - INTRINSICALLY SAFE

- Warning: Use only the approved non-rechargeable batteries listed below.
- Warning: Do NOT attempt to use rechargeable AAA batteries with this light.
- Warning: To prevent ignition of a hazardous atmosphere, do not open the battery compartment in the hazardous environment. This task must ONLY be performed in an area known to be non-hazardous.
- Warning: When exchanging batteries, use only ENERGIZER E92 or EN92 BATTERIES.
- Warning: To prevent ignition of a hazardous atmosphere, the AAA batteries must only be exchanged in an area known to be non-hazardous.
- Warning: To reduce the risk of explosion, do not mix new non-rechargeable batteries

with used non-rechargeable batteries, or mix non-rechargeable batteries from different manufacturers.

• Warning: Substitution of components may impair intrinsic safety.

SPECIAL INSTRUCTIONS FOR INTRINSIC SAFETY

For personal safety, always confirm the rating of any known hazardous or potentially hazardous location where the light is to be used.

BATTERY INSTALLATION

WARNING: In order to maintain the XPP-5452G's Intrinsically Safe rating, the only AAA batteries certified for use with this light are the ENERGIZER E92 or EN92 BATTERIES.

- Do not attempt to use any other brand or model of AAA batteries with this light.
- Do not attempt to use any type of rechargeable AAA batteries with this light.

Warning: To prevent ignition of a hazardous atmosphere, do not open the battery compartment door in the hazardous environment. This task must ONLY be done in an area known to be non-hazardous.

- Loosen the locking screw located on the back of the battery compartment door. NOTE: Do NOT attempt to
 completely remove the locking screw. Doing so is not necessary and may damage the threads. The screw
 simply needs to be loosened enough to allow the battery compartment door to open.
- Using 3 AAA ENERGIZER E92 or EN92 BATTERIES (make sure that all 3 batteries are of the same model), install the batteries in the back of the light paying close attention to the markings inside the battery compartment for proper battery terminal polarity alignment.
- Close the battery compartment door.
- Tighten locking screw. CAUTION: Do NOT over-tighten. Doing so may damage the threads and impact the light's Intrinsic Safety.

OPERATION

THE XPP-5452G HAS TWO SEPARATE LIGHTING MODES:

HIGH-BRIGHTNESS SPOTLIGHT MODE Press the button on top of the light one time. LOW-BRIGHTNESS SPOTLIGHT MODE Press the button on top of the light two times. Pressing the button a third time will turn the light off.



THE XPP-5452G HAS A TILT ADJUSTMENT FEATURE:

Simply adjust the tilt angle of the light to illuminate the desired area.

THE XPP-5452G COMES WITH TWO DIFFERENT HEADBANDS:

ELASTIC NON-SLIP HEADBAND

Use this headband for wearing the headlamp directly on your head or while wearing a soft hat such as a ball cap. The non-slip feature will keep the light positioned on the head even during vigorous movement.

HEAVY-DUTY RUBBER HEADBAND

Use the heavy-duty rubber headband on any hardhat. The tacky nature of the strap will keep the light attached even if the hat is dropped or used in wet conditions.

WARRANTY

LIMITED LIFETIME WARRANTY

Bayco Products, Inc. warrants this product to be free from defects in workmanship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are excluded.

We will repair or replace this product should we determine it to be defective. This is the only warranty, expressed or implied, including any warranty of merchantability or fitness for a particular purpose.

For a complete copy of the warranty, go to www.baycoproducts.com/bayco-product-support/warranties. Retain your receipt for proof of purchase.

EU / UK Declaration of Conformity

Model(s):	XPP-5450G	Declaration Number:	20140516-G		
,	XPP-5452G				
Product Type:	Portable LED Intrinsically Safe Headlamp				
Company Name:		Bayco Products Inc.	Bayco Products Inc.		
Address:		640 S. Sanden Blvd.	640 S. Sanden Blvd.		
City, State, Postcode:		Wylie, Texas 75098 USA	Wylie, Texas 75098 USA		
Phone / Website:		001-469-326-9400 / www.r	001-469-326-9400 / www.nightstick.com		
		70			
EU Authorized representative:		Clever Rep AB	Clever Rep AB		
Address:		Box 1898 11674 Stockholr	Box 1898 11674 Stockholm, Sweden		
Email:		ar-contact@cleverrepreser	ar-contact@cleverrepresentative.eu		

ar-contact@cleverrepresentative.eu

This declaration is issued under the sole responsibility of the manufacturer. The objective of the declaration described is in conformity with the relevant union harmonization legislation:

ATEX Directive (2014/34/EU)	EMC Directive (2014/30/EU)	RoHS Directive (2011/65/EU +2015/863)		LVD (2014/35/EU)
EN IEC 60079-0:2018	N/A	IEC 62321-3-1:2013	IEC 62321-7-1:2015	N/A
EN 60079-11:2012		IEC 62321-4:2013+A1:2017	IEC 62321-7-2:2017	
EN 60079-28:2015		IEC 62321-5:2013	IEC 62321-8:2017	
		IEC 62321-6:2015		

The relevant standards and technical specifications have been applied and evaluated by:

Directives:	ATEX Directive 2014/34/EU	UKSI 2016 No. 1107	Article 34 of the Industrial Safety and Health Act and Article 58-4, Paragraph 4 of the Enforcement Rule of the same Act.
Notified Body:	Via Guido Miglioli, 2/A 20063 Cernusco sul Naviglio (MI) Italy	INTERTEK TESTING & CERTIFICATION LTD Academy Place, 1-9 Brook Street Brentwood, Essex, CM14 5NQ United Kingdom	Korea Occupational Safety and Health Agency
Notified Body Number:	2575	0359	N/A
Certificate Number:	ITS13ATEX27854X	UKEX: ITS21UKEX0247X	22-AV4BO-0216X 22-AV4BO-0217X
Type Approval:	⑤ II 1 G Ex ia op is IIC T4 Ga -20°C ≤ Ta ≤ 40°C	C € 2575 UK 0359	216X 22-AV4BO-0217X

Name: Mark Situ Title: Quality Director Date: 15th July 2024



Contents

- 1 Documents / Resources
 - 1.1 References

Documents / Resources



NIGHTSTICK XPP-5452G Intrinsically Safe Dual Function Headlamp [pdf] Instruction Manual

XPP-5452G Intrinsically Safe Dual Function Headlamp, XPP-5452G, Intrinsically Safe Dual Function Headlamp, Safe Dual Function Headlamp, Dual Function Headlamp

References

- Bayco Products, Inc. (BPI)
- User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.