



nVent CADDY TRC212 Swift Clip Threaded Rod Attachment Owner's Manual

[Home](#) » [nVent Caddy](#) » nVent CADDY TRC212 Swift Clip Threaded Rod Attachment Owner's Manual 

Contents

- 1 nVent CADDY TRC212 Swift Clip Threaded Rod Attachment
- 2 Product Information
- 3 Product Usage
- 4 FEATURES
- 5 PRODUCT ATTRIBUTES
- 6 ADDITIONAL PRODUCT DETAILS
- 7 Documents / Resources
 - 7.1 References
- 8 Related Posts



nVent CADDY TRC212 Swift Clip Threaded Rod Attachment



Product Information

Specifications

- Catalog Number: TRC212
- Product Name: nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT
- Outer Diameter: 2 1/8 inches
- Copper Tube Size: 2 inches
- Rod Size: 3/8 inches

Features

The nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT offers the following features:

- Easy and secure attachment of threaded rods
- Durable construction for long-lasting performance
- Designed to support copper tubes with a size of 2 inches
- Compatible with rods with a diameter of 3/8 inches

Product Usage

Installation

1. Ensure that you have read and understood the product instruction sheets available at www.nvent.com.
2. Select a suitable location for the attachment based on your specific application requirements.
3. Prepare the surface by cleaning it and removing any debris or obstructions.
4. Position the nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT on the surface and align it accordingly.
5. Securely fasten the attachment using appropriate screws or bolts. Refer to the product instruction sheets for recommended hardware.
6. Verify that the attachment is firmly installed and can support the intended load.

Usage Tips

Here are some tips to ensure optimal usage of the nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT:

- Regularly inspect the attachment for any signs of damage or wear. Replace if necessary.
- Ensure that the threaded rod is securely attached to the nVent CADDY SWIFT CLIP for stability.
- Do not exceed the recommended load capacity of the attachment.
- Follow all safety precautions and guidelines provided by nVent during installation and usage.

Warning

It is important to note that improper installation, misuse, misapplication, or failure to follow nVent's instructions and warnings may result in:

- Product malfunction
- Property damage
- Serious bodily injury or death

- Voiding of warranty

Please ensure that you thoroughly read and understand the product instruction sheets and training materials provided by nVent before installing and using this product.

Contact Information

If you have any questions or need further assistance, please contact nVent customer service representatives in your respective region:

- Europe Netherlands: +31 800-0200135
- France: +33 800 901 793
- Germany: 800 1890272
- Other Countries: +31 13 5835404
- APAC Shanghai: + 86 21 2412 1618/19
- Sydney: +61 2 9751 8500

Disclaimer

Product specifications are subject to change without notice. Please refer to the latest product documentation for the most up-to-date information.

FAQ

1. Can I use this attachment for threaded rods with a larger diameter?

No, this attachment is specifically designed for rods with a diameter of 3/8 inches. Using it with larger rods may compromise its performance and stability.

2. What is the maximum load capacity of this attachment?

The maximum load capacity of the nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT depends on various factors such as installation method and surface strength. It is recommended to refer to the product instruction sheets or consult nVent customer service for specific load capacity information.

3. Can I install this attachment on different types of surfaces?

The nVent CADDY SWIFT CLIP THREADED ROD ATTACHMENT is designed for versatile installation and can be used on various surfaces. However, it is important to ensure that the surface is suitable and capable of supporting the intended load. Consult the product instruction sheets for more information on surface compatibility.

FEATURES

- Snap-on and twist installation requires no tools
- Easily adjusts by rotating up or down on the threaded rod
- For support and positioning of refrigeration, A/C tubing, PEX piping, conduit and cabling
- Secures pipe and insulation without any breaks
- Compliant with UL® 2043 and suitable for use in air handling (plenum) spaces

PRODUCT ATTRIBUTES

- **Material:** Polyamide
- **Working Temperature:** -40 to 284 °F
- **Outer Diameter:** 2 1/8"
- **Copper Tube Size:** 2"
- **Rod Size:** 3/8"

ADDITIONAL PRODUCT DETAILS

Clip must be installed with temperature at or above 14 °F (-10 °C).

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe

- **Netherlands:**
+31 800-0200135
- **France:**
+33 800 901 793

Europe


- **Germany:**
800 1890272
- **Other Countries:**
+31 13 5835404

APAC

- **Shanghai:**
+ 86 21 2412 1618/19
- **Sydney:**
+61 2 9751 8500

nVent.com

Documents / Resources

	<p>nVent CADDY TRC212 Swift Clip Threaded Rod Attachment [pdf] Owner's Manual TRC212 Swift Clip Threaded Rod Attachment, TRC212, Swift Clip Threaded Rod Attachment, Clip Threaded Rod Attachment, Threaded Rod Attachment, Rod Attachment, Attachment</p>
---	--

References

- [🌟 Building a more Sustainable and Electrified World | nVent](#)
- [🌟 Building a more Sustainable and Electrified World | nVent](#)
- [User Manual](#)