

nVent 16P CADDY Push In Conduit Clamp User Guide

Home » nVent » nVent 16P CADDY Push In Conduit Clamp User Guide 🖺

nVent 16P CADDY Push In Conduit Clamp User Guide



Contents

- **1 FEATURES**
- **2 PRODUCT**
- **ATTRIBUTES**
- **3 DIAGRAMS**
- 4 Documents / Resources
 - 4.1 References

FEATURES

- · Push-in installation of conduit
- Eliminates need for offset bending conduit
- May be used for either vertical or horizontal installations

PRODUCT ATTRIBUTES


• Material: Spring Steel


Finish: nVent CADDY Armour
Outer Diameter: 30 – 35 mm

Hole Size: 7 mmHole Type: Plain

Ultimate Static Load 1: 110 N
Ultimate Static Load 2: 65 N

DIAGRAMS





WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

> Europe Netherlands: +31 800-0200135 France:

Europe Germany: 800 1890272 Other Countries: +31 13 5835404

APAC Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500

2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

their respective owners. nVent reserves the right to change specifications without notice.



Documents / Resources



nVent 16P CADDY Push In Conduit Clamp [pdf] User Guide

16P CADDY Push In Conduit Clamp, 16P, CADDY Push In Conduit Clamp, Push In Conduit Clamp, Conduit Clamp, Clamp

References

- <u>** Building a more Sustainable and Electrified World | nVent</u>
- * Building a more Sustainable and Electrified World | nVent
- User Manual

Manuals+, Privacy Policy