

nVent A366012WFLP Continuous Hinge 2 Door With Handle



nVent A366012WFLP Continuous Hinge 2 Door With Handle Owner's Manual

[Home](#) » [nVent](#) » nVent A366012WFLP Continuous Hinge 2 Door With Handle Owner's Manual 

Contents

- [1 nVent A366012WFLP Continuous Hinge 2 Door With Handle](#)
- [2 Product Usage Instructions](#)
- [3 Frequently Asked Questions](#)
- [4 FEATURES](#)
- [5 PRODUCT ATTRIBUTES](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)
- [7 Related Posts](#)



nVent A366012WFLP Continuous Hinge 2 Door With Handle



Features

Ideal for larger wall-mount applications requiring ease of installation and access to full-width internal panel. The overlapping door design allows easy access in areas with minimal aisle space.

Additional Product Details

Purchase panels separately. Optional stainless steel, conductive, composite, and aluminum panels are available for most sizes. A484812WFLP back is 10 gauge.

Warning

- nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials.
- Improper installation, misuse, misapplication, or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury, and death and/or void your warranty.
- **nVent Brands:** [nVent.com](https://www.nvent.com), CADDY, ERICO, HOFFMAN, RAYCHEM, SCHROFF, TRACER
- © All trademarks are owned by their respective owners. nVent reserves the right to change specifications without notice.

Product Usage Instructions

Installation

1. Ensure the mounting surface is suitable to hold the weight of the enclosure.
2. Mount the enclosure securely using the appropriate hardware.
3. Follow the provided instruction sheets for detailed installation steps.

Accessing Internal Panel

1. Open the overlapping doors by turning the handle.
2. Safely secure the doors in the open position to prevent accidental closure.

3. You can now easily reach and work on the internal panel.

Maintenance

- Regularly inspect the enclosure for any signs of damage or wear.
- Clean the exterior using a mild detergent and a soft cloth.
- Avoid using abrasive cleaners that may damage the powder-coated finish.

Optional Panels

- If you wish to customize the internal panel, optional stainless steel, conductive, composite, or aluminum panels are available for purchase.
- Ensure compatibility with your specific enclosure model before installation.

Frequently Asked Questions

Q: Can I install the enclosure without purchasing additional panels?

A: Yes, the enclosure comes ready for use without additional panels. However, you can purchase optional panels for customization.

Q: How can I ensure proper installation to avoid product malfunction?

A: Follow the provided instruction sheets carefully and securely mount the enclosure using appropriate hardware on a suitable surface.

- Ideal for larger wall-mount applications requiring ease of installation and access to full-width internal panel.
- The overlapping door design allows easy access in areas with minimal aisle space.

FEATURES

- Seams continuously welded and ground smooth
- External welded-on mounting brackets for easy installation
- External formed body flange channels away liquids
- Gasketed overlapping doors eliminate the need for a center post
- Removable door with continuous hinge
- Oil-tight key-locking handle with 3-point latch
- Removable heavy gauge continuous hinge pin
- Data pocket is a high-impact thermoplastic
- Collar studs for mounting optional panels
- Bonding provision on both doors
- The body is white inside with an ANSI 61 grey finish outside
- The door is ANSI 61 grey inside and outside

PRODUCT ATTRIBUTES

- **Article Number:** 27180
- **Height:** 36 in
- **Width:** 60 in
- **Depth:** 12 in
- **Material:** Mild Steel
- **Finish:** Powder Coated
- **Exterior Color:** Gray
- **Exterior Color Code:** ANSI 61
- **Interior Color:** White
- **Thickness:** 16 ga
- **Panel Size:** 57.00 x 33.00 in
- **Conductive Panel:** A60P36G
- **Panel:** A60P36
- **Panel Gauge:** 12
- **Stiffener Body:**
- **Weight:** 164 lb

ADDITIONAL PRODUCT DETAILS

- Purchase panels separately. Optional stainless steel, conductive, composite, and aluminum panels are available for most sizes.
- A484812WFLP back is 10 gauge.

WARNING

- nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials.
- Instruction sheets are available at www.nvent.com and from your nVent customer service representative.
- Improper installation, misuse, misapplication, or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury, and death and/or void your warranty.

Our powerful portfolio of brands:

- nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER
- © 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates.
- All other trademarks are the property of their respective owners.
- nVent reserves the right to change specifications without notice.

Documents / Resources



[nVent A366012WFLP Continuous Hinge 2 Door With Handle](#) [pdf] Owner's Manual
A366012WFLP Continuous Hinge 2 Door With Handle, A366012WFLP, Continuous Hinge 2 Door With Handle, Hinge 2 Door With Handle, With Handle, Handle

References

- [🌟 Building a more Sustainable and Electrified World | nVent](#)
- [🌟 Building a more Sustainable and Electrified World | nVent](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.