nVIDIA P3766 Jetson Orin Nano Developer Kit





nVIDIA P3766 Jetson Orin Nano Developer Kit Instructions

Home » Nvidia » nVIDIA P3766 Jetson Orin Nano Developer Kit Instructions

Contents

- 1 nVIDIA P3766 Jetson Orin Nano Developer Kit
- 2 Transform Visionary Al Concepts Into Reality
- 3 Key Features
- **4 NVIDIA Jetson Orin Nano Developer Kit**
- 5 Documents / Resources
 - **5.1 References**



nVIDIA P3766 Jetson Orin Nano Developer Kit



Transform Visionary AI Concepts Into Reality

The NVIDIA Jetson Orin Nano Developer Kit sets a new standard for creating entry-level AI-powered robots, smart drones, and intelligent cameras. It also simplifies the process of starting with Jetson Orin Nano series modules. Compact design, lots of connectors and up to 40 TOPS of AI performance make this the perfect developer kit to bring your AI concepts to life. With up to 80X the performance of Jetson Nano™, it can run all modern AI models, including transformer and advanced robotics models.

The developer kit comprises a Jetson Orin Nano 8GB module and a reference carrier board that can accommodate all Orin Nano and Orin NX modules. This provides the ideal platform for prototyping your next-gen edge-AI product. The Jetson Orin Nano 8GB module features an Ampere architecture GPU and a 6-core ARM CPU, enabling multiple concurrent AI application pipelines and high-performance inference. The carrier board boasts a wide array of connectors, including two camera connectors that can handle 2-lane and 4-lane cameras.

The NVIDIA Jetson™ platform runs the NVIDIA AI software stack, with a variety of available use-case-specific application frameworks, These include NVIDIA Isaac™ for robotics, DeepStream for vision AI, and Riva for conversational AI. You can save significant time with NVIDIA Omniverse™ Replicator for synthetic data generation (SDG) and NVIDIA TAO Toolkit for fine-tuning pre-trained AI models from the NGC™ catalogue. Ecosystem partners offer additional AI and system software, developer tools, and custom software development. They can also help with cameras and other sensors, as well as carrier boards and design services for your product. Jetson Orin™ modules are unmatched in performance and efficiency for robots and other autonomous machines. You now have the flexibility to create the next generation of AI solutions with the latest NVIDIA technology. Together with the world-standard NVIDIA AI software stack and an ecosystem of services and products, your road to market has never been faster.

Key Features

- Developer Kit Content (P3766)
- Jetson Orin Nano™ 8GB module with heat sink and reference carrier board
- DC Power Supply
- 802.11ac/abgn wireless network interface controller
- Quick Start Guide

Jetson Orin Nano 8GB Module

- NVIDIA Ampere architecture with 1024 NVIDIA® CUDA® cores with 32 tensor cores
- 6-core Arm® Cortex-A78AE v8.264-bit CPU
- 8GB 128-bit LPDDR5 68 GB/s
- · Supports for external NVMe

Reference carrier board

- 2x MIPI CSI-2 22-pin camera connectors
- 2x M.2 Key M, M.2 Key E
- 4x USB 3.2 Gen2 Type-A
- USB Type-C for UFP
- · Gigabit Ethernet
- DisplayPort
- · microSD slot

- 40-pin expansion header
- DC power jack

NVIDIA Jetson Orin Nano Developer Kit

Technical Specifications	
Jetson Orin Nano 8GB Module	
GPU	NVIDIA Ampere architecture with 1024 CUDA cores and 32 tensor cores
CPU	6-core Arm® Cortex®-A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3
Memory	8GB 128-bit LPDDR5
	68GB/s
Storage	Supports SD card slot and external NVMe
Video Encode	1080p30 supported by 1-2 CPU cores
Video Decode	1x 4K60 (H.265)
	2x 4K30 (H.265)
	5x 1080p60 (H.265)
	11x 1080p30 (H.265)
Power	7W-15W

Refer to the Software Features section of the latest NVIDIA Jetson Linux Developer Guide for a list of supported features.

Reference Carrier Board

Camera	2x MIPI CSI-2 22-pin camera connectors
PCle	M.2 Key M slot with x4 PCIe Gen3
	M.2 Key M slot with x2 PCIe Gen3
	M.2 Key E slot
USB	USB Type-A connector: 4x USB 3.2 Gen2
	USB Type-C connector for UFP
Networking	1xGbE connector
Display	1x DP 1.2 (+MST) connector
Other I/O	40-pin expansion header (UART, SPI, I2S, I2C, GPIO)
	12-pin button header
	4-pin fan header
	microSD slot
	DC power jack
Mechanical	100mm x 79mm x 21mm
	(Height includes feet, carrier board, module, and thermal solution

Documents / Resources



nVIDIA P3766 Jetson Orin Nano Developer Kit [pdf] Instructions
P3766 Jetson Orin Nano Developer Kit, P3766, Jetson Orin Nano Developer Kit, Orin Nano
Developer Kit, Nano Developer Kit, Developer Kit, Kit

References

- Jetson Orin for Next-Gen Robotics | NVIDIA
- O Robotic arm, mobile robot, autonomous robots, ROS robot
- O Robotic arm, mobile robot, autonomous robots, ROS robot
- Jetson Orin for Next-Gen Robotics | NVIDIA
- User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.