


NXP i.MX 91 Applications Processor User Guide

[Home](#) » [NXP](#) » NXP i.MX 91 Applications Processor User Guide 



Quick Start Guide
IMX91LP4EVK-11CM
i.MX 91 Applications Processor



Contents

- [1 About the i.MX 91 EVK](#)
- [2 Specifications](#)
- [3 Get to know the i.MX 91 EVK](#)
- [4 Getting started](#)
- [5 Additional information](#)
- [6 Documents / Resources](#)
 - [6.1 References](#)

About the i.MX 91 EVK

The i.MX 91 family of applications processors enables the rapid creation of new Linux-based edge devices. It excels in advanced multimedia and industrial IoT applications etc. Elevating edge intelligence, i.MX 91 processors provide a solid foundation for devices in smart factory, smart home, smart office, medical device, metering, and cost-optimized system-on-module platforms.

Specifications

Compute card:

- i.MX 91 applications processor with: – 1x Arm® Cortex®-A55
- LPDDR4 16-bit 2GB
- eMMC 5.1, 32GB
- Power Management IC (PMIC)
- Power Measurement ADC

Base board:

- MicroSD 3.0 card slot
- Two USB 2.0 C connector
- One USB 2.0 C for Debug
- One USB C PD only
- M.2 Key-E for Wi-Fi/BT/802.15.4
- One CAN port
- Four channels for ADC
- 6-axis IMU w/ I3C support
- Two 1 Gbps Ethernet
 - Port1 supports TSN
 - Port2 supports ETER
- I2C Expansion connector
- Audio Codec Support
- PDM MIC array support
- External RTC w/ coin cell
- 2×20 Pin Expansion I/O

Get to know the i.MX 91 EVK




Figure 1: Top view of the i.MX 91 EVK




Figure 2: Back view of the i.MX 91 EVK

Getting started

Unpack the kit

The i.MX 91 EVK is shipped with the items listed in Table 1.

Table 1 — Kit contents

Item	Description
IMX91LP4EVK-11CM	IMX91LP4EVK-11CM board
Power Supply	USB C PD 45W, 5V/3A; 9V/3A; 15V/3A; 20V/2.25A supported
USB Type-C Cable	USB 2.0 C Male to USB 2.0 A Male
M.2 Module	PN: EAR00409; Wi-Fi 6 / BT 5.2 / 802.15.4 support, basing on NXP IW612
Software	Linux BSP image programmed in eMMC
Documentation	Quick Start Guide

Prepare Accessories

The following items in Table 2 are recommended to run the i.MX 91 EVK.

Table 2 — Customer supplied accessories

Item	Description
T050RDH03-HC	Parallel LCD DISPLAY MODULE 5" TFT 800X480 RGB
M2-NAND-FLASH	M.2 NAND flash daughter card
M2-NOR-FLASH	M.2 NOR flash daughter card
Audio HAT	Audio expansion board with most of audio features
8MIC-RPI-MX8	8-microphone array proto board for voice enablement

Download software and tools

Installation software and documentation are available at www.nxp.com/imx91evkcm. The following are available on the website:

Table 3 — Software and Tools

Item	Description
Documentation	<ul style="list-style-type: none">• Schematics, layout and Gerber files• Quick Start Guide• Hardware Design Guide• i.MX 91 EVK Board User Manual• Power Consumption Measurement
Software Development	<ul style="list-style-type: none">• Linux BSPs
Demo Images	<ul style="list-style-type: none">• Copy of the latest Linux images that are available to program on to the eMMC.• IMX91LP4EVK-11CM software can be found at nxp.com/imxsw

Setting up the system

The following will describe how to run the pre-loaded Linux image on the MCIMX91-EVK (i.MX 91).

1. Confirm boot switches

The boot switches should be set to boot from “eMMC”, SW1301[4-1] (Figure 1) are used for boot, See table below:

BOOT Device	SW1301[1-4]
eMMC/uSDHC1	0000

Note: 1 = ON 0 = OFF


2. Connect USB debug cable

Connect the UART cable into the port JP1401 (Figure 1). Connect the other end of the cable to a PC acting as a host terminal.

UART connections will appear on the PC, The third port will be used as A55 core system debugging.

Open the terminal window (i.e., Hyper Terminal or Tera Term), choose the right COM port number and apply the following configuration.

- Baud rate: 115200bps
 - Data bits: 8
 - Parity: None
 - Stop bits: 1
3. Connect parallel panel display
Plug the parallel LCD panel (T050RDH03-HC) into J1001 2×20 PIN header.
 4. Connect mouse
Connect the mouse to the USB2 C port connector J302 through USB C OTG cable.
 5. Connect power supply
Connect the USB C PD power supply to J301, then power up the board by SW301 switch.



6. Board boot up
As the board boots up, you will see 4 penguins appear in the upper left-hand corner of the monitor, and then you will see the Linux terminal icon on the top left and timer on right top corner . Congratulations, you are up and running.
Run “Go Point for i.MX Applications Processors” application to explore the preinstalled demos. The NXP Logo is displayed on the top left-hand corner of screen, start the demo launcher by clicking this logo. Refer to user guide for details: <https://www.nxp.com/webapp/Download?colCode=GPNTUG.vz>



Additional information

Boot Switches



SW1301[1-4] is the boot configuration switch, the default boot device is eMMC/uSDHC1, as shown in Table 4. If you want to try other boot devices, you need to change the boot switches to corresponding values as listed in Table 4.

Note: 1 = ON 0 = OFF

Table 4 — Boot device settings

BOOT MODE	SW1301-4	SW1301-3	SW1301-2	SW1301-1
From internal fuses	0	0	0	1
Serial Downloader	0	0	1	1
USDHC1 8-bit eMMC 5.1	0	0	0	0
USDHC2 4-bit SD3.0	0	0	1	0
FlexSPI Serial NOR	0	1	0	1
FlexSPI Serial NAND 2K page	0	1	1	1
Reserved	0	1	0	0
Reserved	0	1	1	0

Do more with Accessory Boards

<p>Parallel LCD: T050RDH03-HC LCD DISPLAY MODULE 5" TFT 800X480, RGB, 120.7 mm x 75.8 mm</p>	<p>M2-NAND-FLASH QSPI NAND flash daughter card with M.2 interface. Winbond 256MB W25N02KWZEIR (WS0N8X6) + GigaDevice 256MB GD5F2GM7REBIG (BGA24)</p>
	
<p>M2-NOR-FLASH QSPI NOR flash daughter card with M.2 interface. Micron 64MB MT25QU512ABB8E12-0AAT (BGA24)</p>	<p>WiFi/BT/IEEE802.15.4 M.2 Module (LBES5PL2E L) Wi-Fi 6, IEEE 802.11a/b/g/n/ac + Bluetooth 5.2 BR/EDR/LE + IEEE802.15.4, NXP IW612 chipset</p>



Audio Board: MX93AUD-HAT

Audio expansion board with most of audio features



Microphone Board: 8MIC-RPI-MX8

8-microphone array proto board for voice enablement.



Support

Visit www.nxp.com/support for a list of phone numbers within your region.

Warranty

Visit www.nxp.com/warranty for complete warranty information.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
 - (2) This device must accept any interference received, including interference that may cause undesired operation.
- Attention that changes or modification not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This product has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This product generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this product does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This equipment should be installed and operated with a minimum distance 20cm between the radiator and your body.

www.nxp.com/iMX91EVKCM

**NXP and the NXP logo are trademarks of NXP B.V.
All other product or service names are the property of
their respective owners. © 2024 NXP B.V.
Document Number: 91EVKCMQSG REV 0
MPN : IMX91LP4EVK-11CM
Aras ID : 91450**

Documents / Resources

	<p>NXP i.MX 91 Applications Processor [pdf] User Guide IMX91LP4EVK-11CM, i.MX 91 Applications Processor, i.MX 91, Applications Processor, Proces sor</p>
---	---

References

- [i.MX Software and Development Tools | NXP Semiconductors](#)
- [Sign in to NXP.com | NXP Semiconductors](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.