



OCOM OCPP-80K 80MM Three Interfaces Thermal Receipt Printer User Guide

[Home](#) » [ocom](#) » OCOM OCPP-80K 80MM Three Interfaces Thermal Receipt Printer User Guide 

Contents

- [1 OCOM OCPP-80K 80MM Three Interfaces Thermal Receipt Printer](#)
- [2 Features](#)
- [3 Technical parameters](#)
- [4 Relevant documents](#)
- [5 Documents / Resources](#)
 - [5.1 References](#)
- [6 Related Posts](#)



OCOM OCPP-80K 80MM Three Interfaces Thermal Receipt Printer



cutter thermal parking ticket printer bluetooth Wi-Fi 80mm posy printer thermal receipt

Model NO.: OCPP-80K

Features

- Support 8 kinds abundant interface combination
Supports multi 1D barcode and QR code printing
Support printer status monitoring function
- Support printing queuing ticket function
- 100M Ethernet port, ultra high speed data transmission; 256KB NV Logo storage and 256kb big buffer
- memory; 48mm to 80mm adjustable Paper separator for optional
- ; Compatible with OPOS/JPOS driver
- 150KM long life printer head.

Technical parameters

General	
Model	OCPP-80K
Name	80mm desktop thermal printer with auto cutter
Color	Black
Interface	USB/ USB+Lan/ USB+BT/ USB +WiFi/ URL+ WiFi/ URL+BT/ USB+RS232
Power supply	Input:AC 100V-240V, 50-60Hz, Output:DC 24V/ 2.5A
Cash drawer	DC 24V/1A
Graphics printing	Supports bitmap download and print (each bitmap size Max.20K)
Printer head lifespan	150KM
Cutter	Auto cutter
Sensors	Paper out, cover open, cutter jam, paper jam and black mark detection(Optional)
Buffer	Input buffer256K, NV Flash 256K
Accessories	Data cable, power adaptor, power cord, paper roller, CD, manual, Paper separator (optional)
OS supporting	Compatible with iOS/ Android/ Windows
Safety standards	CE, FCC, Rohs etc
Printing capability	
Printing method	Direct thermal line
Resolution	576 Dots / Line or 512 Dots/ Line(8dots /mm, 203dpi)
Printing speed	200mm/s (U/ UR) 260mm/s (UL/ U+BT/ U+ WiFi) 300mm/s (URL/ URL+ BT/ URL+WiFi)
Print width	72mm
Graphics printing	Supports bitmap download and print
Printing Command	Compatible with ESC/POS
Barcode and character	
Barcode	1D barcode: UPC-A/ UPC-E/ JAN13/ EAN13/ JAN8/ EAN8/ CODE39/ ITF/ CODABAR/ CODE93/ CODE128 2D barcode: QR CODE (Single USB or UR solution no QR code function)
Character	Standard GB18030 simplified / traditional Chinese Fonts
Character size	384dots/ line, ANK character, Font: A: 12 * 24dots, 1.5(W) * 3.0(H) mm FontB: 9*17dots, 1.1(W) * 2.1 (H)mm Simplified/ Traditional: 24*24dots, 3.0(W) * 3.0(H)mm
Japanese/ Korea	optional
User-defined language	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 / WestEurope / Greek / Hebrew / EastEurope / Iran / WPC1252 / PC866 / PC852 / PC858 / IranII / Latvian / Arabic / PT151, 1251 / PC737 / WPC / 1257 / Thai/Vietnam / PC864 / PC1001 / (Latvian) / (PC1001) / (PT151, 1251) / (WPC1257) / (PC864) / (Vietnam) / (Thai)
Media	

- Paper type Thermal roll paper
- Paper width 48mm/ 52mm/ 56mm/ 64mm/ 68mm/ 76mm/ 80mm
- Paper Thickness 0.06~0.08mm
- Paper roll diameter 83mm Max
- Paper separator Optional
- Physical
- Dimension 196*145*135mm
- Weight 1.65kg

- Package box 300*190*180 mm
- 12 in 1 carton 615*370*535mm/21.5kg
- Environment
- Working temperature& humidity 0 to 45 degrees centigrade, 10%~80% No condensation
- Storage temperature& humidity -20 to 60 degrees centigrade , 10%~90% No condensation











Relevant documents

- OCPP-80K SPEC
- OCPP-80K CD

Documents / Resources

[OCOM OCPP-80K 80MM Three Interfaces Thermal Receipt Printer](#) [pdf] User Guide
OCPP-80K 80MM Three Interfaces Thermal Receipt Printer, OCPP-80K, 80MM Three Interface
s Thermal Receipt Printer, Three Interfaces Thermal Receipt Printer, Interfaces Thermal Receip
t Printer, Thermal Receipt Printer, Receipt Printer, Printer

References

- [User Manual](#)