

ONE DIRECT SENSOR Sensor with Clamp In Valves Instruction Manual

Home » ONE DIRECT SENSOR » ONE DIRECT SENSOR Sensor with Clamp In Valves Instruction Manual





Sensor with clamp-in valves Installation instructions



Contents

- 1 Sensor with Clamp In **Valves**
- 2 Installation
- 3 FCC Caution:
- 4 Documents / Resources
 - 4.1 References
- **5 Related Posts**

- 1. Screw
- 2. Sensor
- 3. Valve Stem
- 4. Nut
- 5. Valve Cap

A Caution:

- 1. Please make sure to use Siming's valves and accessories to guarantee optimal function.
- 2. Please follow the instruction of car manufacturer for the safety and correct operation.







Installation

- 1. Put down the screw nut;
- 2. Slide the valve stem through the valve hole of the rim. Tighten the screw-nut with 4.0 Nm with the help of the Torque tool.
- 3. Assemble the tire, be sure that sensor would not touched with the rim and tire.

Note: Use different way to re-lean according to the different vehicle.

FCC Caution:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on , the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body: Use only the supplied antenna.

Europe: Siming Europe GMBH Nordring 6B , 42579 Heiligenhaus Tel: +49 160 / 75 50 544

Email: d.bettchen@siming-group.eu
Web: www.siming-china.com

China: Ningbo Siming Automotive Co.,Ltd 360# Qiushi Road, Wangchun Industry park, Ningbo, China

Tel: +86 574-87103699 E-mail: <u>info@siming-china.com</u> Web: <u>www.siming-china.com</u>

Documents / Resources



ONE DIRECT SENSOR Sensor with Clamp In Valves [pdf] Instruction Manual SMONE, 2A82G-SMONE, 2A82GSMONE, Sensor with Clamp In Valves, Sensor, Clamp In Valves Sensor

References

- China
- 🕓
- ③

Manuals+,