

Outwell Fallcrest Side Panel Set Instruction Manual

Home » Outwell » Outwell Fallcrest Side Panel Set Instruction Manual



Contents

- 1 Outwell Fallcrest Side Panel Set
- **2 Product Information**
- **3 Product Usage Instructions**
- **4 PITCHING**
- 5 Cleaning and maintenance tips
- 6 Documents / Resources
 - **6.1 References**



Outwell Fallcrest Side Panel Set



Product Information


The Fallcrest Side Panel Set is an essential accessory for your camping tent. It is designed to provide additional protection and privacy to your outdoor living space. The side panels are made of durable and waterproof material, ensuring that you stay dry and comfortable during your camping adventures. The set includes multiple panels that can be easily attached to your tent, creating a versatile and customizable camping experience. The panels are designed to fit perfectly with the Fallcrest tent model, providing a seamless integration and enhancing the overall functionality of your camping setup. With the Fallcrest Side Panel Set, you can create a cozy and sheltered outdoor space, perfect for relaxing, dining, or storing your camping gear. The panels are easy to install and remove, allowing for quick and hassle-free setup.

Product Usage Instructions


- 1. Before pitching your tent, carefully unpack the Fallcrest Side Panel Set from the carry bag, taking note of how the panels havebeen packed. This will help you when it's time to pack them back up.
- 2. Choose a suitable campsite that is level and free from rocks, branches, and other sharp objects. This will ensure a stable and comfortable setup.
- 3. Spread out the side panels and position them according to your desired configuration. Make sure the door is facing the directionyou prefer. Avoid placing the panels directly under trees and consider the wind direction.
- 4. Practice pitching your tent with the side panels before your camping trip to familiarize yourself with the setup process.
- 5. During wet weather conditions, make sure to prevent the interior or any other objects from coming into contact with the inner side of the side panels. This will help avoid leaks as the flysheet is made of waterproof material.
- 6. Do not fully tighten the guy ropes. Leave some leeway to allow the side panels to adapt to wind and weather conditions.
- 7. If strong winds are expected, replace the pegs with special storm pegs for added stability. Avoid pulling the pegs out of the ground using the guy ropes. For stony or hard soil, stronger u-shaped pegs are recommended.
- 8. Avoid spraying insecticide inside or on the side panels.
- 9. When packing up the side panels, ensure that they are completely dry to prevent moisture damage. Wipe down all metal poles with acid-free oil after use.
- 10. Clean the side panels using a soft sponge and clean water. Do not wash them in a washing machine or use chemical cleaners. Store them in a dry place.
- 11. If the tape at the seams comes loose after repeated use, repair it by removing the loose tape and using a seam sealer and waterproofing spray to re-seal the seams. Detailed instructions are available at www.outwell.com/FAQ.
- 12. Please note that the Fallcrest Side Panel Set is designed for camping use and is not intended for permanent installation. It is recommended for 2-5 weeks of usage per year. Camping near the sea or lake may increase the effect of UV radiation on the panels and metal parts.
- 13. Never pull on the mud valance of the side panels to straighten them. The mud valance is designed to keep out wind and water and should not be subjected to excessive force.

PITCHING

PITCHING VERSION 1+2













PITCHING VERSION 3+4









Cleaning and maintenance tips

Congratulations on your innovative new Outwell® vehicle awning, designed and developed to accompany you out into the great outdoors.

Open the carrybag, and note how the awning has been packed as you take it out. This will help you when it is time to pack up the awning. When selecting your campsite, the ideal place is an area which is as level and as free of rocks, branches and other sharp objects as possible. Spread out the awning and position it with the door facing the desired direction. Avoid placing the awning directly under trees and consider the wind direction. We

recommend that you practice pitching your awning before travelling, to familiarise yourself with it. Under certain weather conditions, condensation can form on the inside of your vehicle awning. To prevent this as far as possible, it is important that wet clothes etc. are removed from the awning. Also make sure to air out the awning, or pitch the awning on an Outwell® groundsheet.

Condensation is not the same as a leak in the awning.

The flysheet is made of waterproof material. You should therefore avoid the interior or anything else coming into contact with the inner side of the flysheet in wet weather, to avoid leaks. Never fully tighten the guy ropes, as this leaves the awning with no leeway to adapt to wind and weather. If strong winds are expected, replace the pegs with special storm pegs. Do not pull the pegs out of the ground using the guy ropes. For stony or hard soil, we recommend stronger u-shaped pegs.

Insecticide should not be sprayed inside or on the awning.

When taking down and packing away the awning, please note that it must be completely dry to avoid moisture damage. We recommend that you wipe down all metal poles using acid-free oil after use.

Remove dirt on the awning using a soft sponge and clean water. Never wash the vehicle awning in a washing machine and never use chemical cleaners. Store the awning in a dry place.

Please note that the tape at the seams may come loose after repeated use. If this happens, repair the awning by removing the loose tape and using a seam sealer and waterproofing spray to re-seal the seams. Instructions are available at www.outwell.com/FAQ

If a minor water leak is found from taping this can easily be re-sealed using a seam sealer – the leak can happen from single thread uncovered by tape a simple fold in the covering tape or similar by human made workflows. We recommend using Outwell Waterguard on regular intervals on the flysheet material to increase the life span. Note that the sun's ultraviolet rays may cause damage to the awning flysheet if it is exposed to direct sunlight for an extended period. The Outtex® material used for Outwell vehicle awnings extends the awning's lifetime. Outwell Product are made for camping use which is normally 2-5 weeks usage a year. They are not designed for permanent usage and should only be used as camping products. Camping near the sea or lake can further enhance the effect of UV radiation. The same applies to poles and metal parts. If your awning has a mud valance, you must never pull on this to straighten the awning. The mud valance on the vehicle awning is only designed to keep out wind and water, and cannot handle being pulled on.

Taking down your tent

When detachable take out the groundsheet and clean it if necessary with a sponge and water. Clean dirty floors the same way. (Allow it to dry before packing the tent). If the inner tent is wet or dirty, take it out and clean it, the tent can be packed down with or without the inner tent inside. Then start to unpeg the tent and the guylines. Gently remove the poles from the pins and then gently push the poles through the sleeves. Do not pull the poles through! You are now ready to fold the tent. Try to fold it so you have all metal pins/rings at one side (to prevent them from making holes in the flysheet). When you have folded the tent, measure it with the carrybag to make sure it is not too wide. You should now be able to roll the tent round the poles in their pole bag and fit it into the Outwell carrybag.

Best regards, THE OUTWELL TEAM

Outwell Wind Stabilizer System

• Testing and determination of Outwell Wind Stabilizer System (OWS System) performance and matching Beaufort ratings is based on the knowledge and technique available to Outwell at the time of testing. Outwell is not responsible if a subsequent development may show that Outwell's knowledge and technique is flawed or incorrect. The ratings to this tent are obtained by erecting and testing similar tents at the facilities of Oase Outdoors ApS. The ratings are therefore no guarantee for the properties of this tent. Factors such as varying ground conditions, inadequate pegs, sun, rain, temperature, other weather conditions, defective or incorrect erection of the tent and normal wear and tear can lead to a performance of the tent that differs from the specified ratings.

• For more info on tips and maintenance please visit outwell.com.

Please direct product claims and problems to your supplying Outwell dealer.

FIND OUT! See our videos

HOW TO PITCH YOUR TENT?

- www.outwell.com/pitching
- HOW TO CLEAN AND MAINTAIN YOUR TENT?
- www.outwell.com/maintenance

Documents / Resources



Outwell Fallcrest Side Panel Set [pdf] Instruction Manual Fallcrest Side Panel Set, Side Panel Set, Panel Set, Set

References

- Outwell Innovative Family Camping buy online here
- <u>O Auto-Vorzelte hier bei Outwell online kaufen</u>
- O Three to four season sleeping bags buy online direct from Outwell here
- Outwell Innovative Family Camping acheter en ligne
- Three to four season sleeping bags buy online direct from Outwell here
- S Maintenance and repair guides | Outwell
- Pitching films How to pitch your tent | Outwell

Manuals+