



# Panasonic WL23C WLAN Plus BT Module Adapter User Manual

[Home](#) » [Panasonic](#) » Panasonic WL23C WLAN Plus BT Module Adapter User Manual 

## Panasonic WL23C WLAN Plus BT Module Adapter



## Contents

- 1 General
- 2 Integration to the end product
- 3 Technical Specification
- 4 Regulatory Information
- 5 Manual Information To the End User
- 6 Innovation, Science and Economic Development Canada (ISED)
- 7 Manual Information To the End User
- 8 Innovation, Science and Economic Development Canada (ISED)
- 9 Documents / Resources
  - 9.1 References
- 10 Related Posts

## General

This device is a 2x2 Wi-Fi + Bluetooth® adapter.

## Integration to the end product

1. WL23C module is mounted on the main board.
2. Insert Antenna Unit into Antenna Connectors of WL23C module.

## Technical Specification

- a) **Dimensions (W x L x H):** 16mm x 12mm x 1.7mm
- b) **Weight:** Approx. 0.67g
- c) **IEEE WLAN Standard:** IEEE 802.11a/b/g/n/ac/ax
- d) **Bluetooth:** BDR, EDR, Low energy
- e) **Host interface:** M.2: CNVio2

## Regulatory Information

### Federal Communications Commission Radio Frequency Interference Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

- Consult the dealer or an experienced radio/TV technician for help.

**FCC Caution:** Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

This device meets all the other requirements specified in Part 15E, Section 15.407 of the FCC Rules.

#### **FOR MOBILE DEVICE USAGE (>20cm/low power) Radiation Exposure Statement:**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.

#### **For U-NII 6 GHz**

Operation of transmitters in the 5.925-7.125 GHz band is prohibited for control of or communications with unmanned aircraft systems.

**This module is intended for OEM integrators only. Per FCC KDB 996369 D03 OEM Manual, the following conditions must be strictly followed when using this certified module:**

**KDB 996369 D03 OEM Manual rule sections:**

#### **List of applicable FCC rules**

This module has been tested for compliance to FCC Part 15

#### **Summarize the specific operational use conditions**

The module is tested for standalone mobile RF exposure use condition. Any other usage conditions such as co-location with other transmitter(s) or being used in a portable condition will need a separate reassessment through a class II permissive change application or new certification.

#### **Limited module procedures**

Not applicable.

#### **Trace antenna designs**

Not applicable.

#### **RF exposure considerations**

This equipment complies with FCC mobile radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator & your body. If the module is installed in a portable host, a separate SAR evaluation is required to confirm compliance with relevant FCC portable RF exposure rules.

#### **Antennas**

The following antennas have been certified for use with this module; antennas of the same type with equal or lower gain may also be used with this module. The antenna must be installed such that 20 cm can be maintained between the antenna and users.

Antenna Type		PIFA
Antenna Gain	2400-2483MHz	3.24 dBi
	5150-5250MHz	3.64 dBi
	5250-5350MHz	3.73 dBi
	5470-5725MHz	4.77 dBi
	5725-5850MHz	4.97 dBi
	5925-6425MH	4.83 dBi
	6425-6525MHz	4.30 dBi
	6525-6875MHz	5.37 dBi
	6875-7125MHz	5.59 dBi
Antenna connector	MHF4L	

### Label and compliance information

The final end product must be labeled in a visible area with the following: “Contains FCC ID: ACJ9TGWL23C”. The grantee’s FCC ID can be used only when all FCC compliance requirements are met.

### Information on test modes and additional testing requirements

This transmitter is tested in a standalone mobile RF exposure condition and any co-located or simultaneous transmission with other transmitter(s) or portable use will require a separate class II permissive change re-evaluation or new certification.

### Additional testing, Part 15 Subpart B disclaimer

This transmitter module is tested as a subsystem and its certification does not cover the FCC Part 15 Subpart B (unintentional radiator) rule requirement applicable to the final host. The final host will still need to be reassessed for compliance to this portion of rule requirements if applicable.

As long as all conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed.

**IMPORTANT NOTE:** In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

### Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user’s manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

### OEM/Host manufacturer responsibilities

We recommend to use “best practice” RF design engineering testing and evaluation in case non-linear interactions

generate additional non-compliant limits due to module placement to host components or properties. OEM/Host manufacturers are ultimately responsible for the compliance of the Host and Module. The final product must be reassessed against all the essential requirements of the FCC rule such as FCC Part 15 Subpart B before it can be placed on the US market. This includes reassessing the transmitter module for compliance with the Radio and EMF essential requirements of the FCC rules. This module must not be incorporated into any other device or system without retesting for compliance as multi-radio and combined equipment.

## **Innovation, Science and Economic Development Canada (ISED)**

This product complies with ISED's licence-exempt RSSs. Operation is subject to the following two conditions;

1. this device may not cause interference, and
2. this device must accept any interference, including interference that may cause undesired operation of the device.

### **Wireless LAN use**

This product (local network devices) for the band 5150-5250 MHz is only indoor usage to reduce potential for harmful interference to co-channel Mobile Satellite systems.

High power radars are allocated as primary users (meaning they have priority) of 5250-5350 MHz and 5650- 5850 MHz and these radars could cause interference and/or damage to LELAN devices.

Devices shall not be used for control of or communications with unmanned aircraft systems.

### **Antennas**

The following antennas have been certified for use with this module; antennas of the same type with equal or lower gain may also be used with this module. The antenna must be installed such that 20 cm can be maintained between the antenna and users.

<b>Antenna Type</b>		<b>PIFA</b>
Antenna Gain	2400-2483MHz	3.24 dBi
	5150-5250MHz	3.64 dBi
	5250-5350MHz	3.73 dBi
	5470-5725MHz	4.77 dBi
	5725-5850MHz	4.97 dBi
	5925-6425MH	4.83 dBi
	6425-6525MHz	4.30 dBi
	6525-6875MHz	5.37 dBi
	6875-7125MHz	5.59 dBi
Antenna connector	MHF4L	

### **Label and compliance information**

The final end product must be labeled in a visible area with the following: “Contains FCC ID: ACJ9TGWL23C”. The grantee’s FCC ID can be used only when all FCC compliance requirements are met.

### **Information on test modes and additional testing requirements**

This transmitter is tested in a standalone mobile RF exposure condition and any co-located or simultaneous transmission with other transmitter(s) or portable use will require a separate class II permissive change re-evaluation or new certification.

### **Additional testing, Part 15 Subpart B disclaimer**

This transmitter module is tested as a subsystem and its certification does not cover the FCC Part 15 Subpart B (unintentional radiator) rule requirement applicable to the final host. The final host will still need to be reassessed for compliance to this portion of rule requirements if applicable.

As long as all conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed.

**IMPORTANT NOTE:** In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

### **Manual Information To the End User**

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user’s manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

### **OEM/Host manufacturer responsibilities**

We recommend to use “best practice” RF design engineering testing and evaluation in case nonlinear interactions generate additional non-compliant limits due to module placement to host components or properties.

OEM/Host manufacturers are ultimately responsible for the compliance of the Host and Module. The final product must be reassesses against all the essential requirements of the FCC rule such as FCC Part 15 Subpart B before it can be placed on the US market. This includes reassessing the transmitter module for compliance with the Radio and EMF essential requirements of the FCC rules. This module must not be incorporated into any other device or system without retesting for compliance as multi-radio and combined equipment.

### **Innovation, Science and Economic Development Canada (ISED)**

This product complies with ISED’s licence-exempt RSSs. Operation is subject to the following two conditions;

1. this device may not cause interference, and
2. this device must accept any interference, including interference that may cause undesired operation of the device.

### **Wireless LAN use**

This product (local network devices) for the band 5150-5250 MHz is only indoor usage to reduce potential for harmful interference to co-channel Mobile Satellite systems.

High power radars are allocated as primary users (meaning they have priority) of 5250-5350 MHz and 5650- 5850 MHz and these radars could cause interference and/or damage to LELAN devices.

Devices shall not be used for control of or communications with unmanned aircraft systems.

### **Antennas**

The following antennas have been certified for use with this module; antennas of the same type with equal or lower gain may also be used with this module. The antenna must be installed such that 20 cm can be maintained between the antenna and users

Antenna Type		PIFA
Antenna Gain	2400-2483MHz	3.24 dBi
	5150-5250MHz	3.64 dBi
	5250-5350MHz	3.73 dBi
	5470-5725MHz	4.77 dBi
	5725-5850MHz	4.97 dBi
	5925-6425MH	4.83 dBi
	6425-6525MHz	4.30 dBi
	6525-6875MHz	5.37 dBi
	6875-7125MHz	5.59 dBi
Antenna connector	MHF4L	

### **RF exposure considerations**

This equipment complies with ISED mobile radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and the body of the user/or bystander. If the module is installed in a portable host, a separate SAR evaluation is required to confirm compliance with relevant ISED portable RF exposure rules.


### **Instructions to OEM Integrators**

A User manual provided to the end user must indicate the operating requirements and conditions that must be observed to ensure compliance with the above-mentioned ISED RF Exposure guideline. If this module is intended for use in a portable device, integrators are responsible for separate evaluation and/or approval to satisfy ISED RF Exposure requirements. If other radio devices are to be integrated with this module, an additional evaluation and ISED submission may be required. Integrators are responsible for such additional evaluation and ISED submission.

The following information must be indicated on the host device of this module; Contains/Continent IC : 216H-CFWL23C



Documents / Resources

	<p><a href="#">Panasonic WL23C WLAN Plus BT Module Adapter</a> [pdf] User Manual</p> <p>WL23C, WL23C WLAN Plus BT Module Adapter, WLAN Plus BT Module Adapter, BT Module Adapter, Module Adapter, Adapter</p>
---	---

References

- [User Manual](#)

Manuals+ Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.