



# PD-USB-DP60 PoE to USB-C Power and Data Adapter User Guide

[Home](#) » [PD-USB-DP60 PoE to USB-C Power and Data Adapter](#) » PD-USB-DP60 PoE to USB-C Power and Data Adapter User Guide 



## Contents

- [1 PD-USB-DP60 Quick Start Guide](#)
- [2 Ethernet-to-USB-C Data Dongle](#)
- [3 LED Indicators](#)
- [4 Specifications](#)
- [5 Environmental Information:](#)
- [6 Notes](#)
- [7 Technical Support](#)
- [8 LAN7800 Driver](#)
- [9 Documents / Resources](#)
- [10 Related Posts](#)

## PD-USB-DP60 Quick Start Guide

1. Connect an IEEE @ 802.3af/at/bt-compliant PSE to the PD-USB-DP60's "PoE IN" RJ45 socket using a standard Cat 5/5e/6 Ethernet cable. (Note: The maximum allowed length of the Ethernet cable is 100 meters).



2. Check that the “Power” LED is yellow to verify that the PD-USB-DP60 is powered on.
3. Connect one side of the supplied USB Type-C ® cable to the PD-USB-DP60’s USB-C socket. (Note: Any USB-C connection polarity is allowed.)
- 4.



Connect the other side of the USB Type-C cable to the USB-C powered device.

5. Verify that the USB-C powered device is getting power from the PD-USB-DP60.

### **Ethernet-to-USB-C Data Dongle**

If PoE power isn’t available, and wired Ethernet is required, the PD-USB-DP60 can be powered from a USB Host:

1. Connect one side of the supplied USB Type-C cable to the USB-C host.
2. Connect the other side of the USB Type-C cable to the PD-USB-DP60’s USB-C socket.
3. Connect a standard Cat 5/5e/6 Ethernet cable to the PD-USB-DP60’s “PoE IN” RJ45 socket to connect to an IEEE 802.3 10/100/1000 Mbps network.

### **LED Indicators**

LED	Appearance	Status
Power	No Light	PD-USB-DP60 is: powered off or powered on as a dongle
	Yellow On	PD-USB-DP60 is powered on
Link/ Act	No Light	No data link
	Green On	Data link on
	Green Blinking	Data activity on

## Specifications

### Data

- PoE IN
- 10/100/1000 Mbps
- USB Type-C
- USB 2.0
- USB 3.1 Gen 1

### Power

- PoE IN
- Input Voltage: 42-57 VDC
- Input Current: 1.75A max
- USB Type-C
- 5 VDC/3A
- 9 VDC/3A
- 15 VDC/3A
- 20 VDC/3A

### Environmental Information:

- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Operating Humidity: 90% Max (non-condensing)
- Storage Temperature: -20°C to +70°C (-4°F to +158°F)
- Storage Humidity: 95% Max (non-condensing)
- Dimensions: 22.4 mm (H) x 66.8 mm (W) x 105.2 mm (L)
- Weight: 150g

### Notes

- If the USB host is running the Windows ® operating system, the device driver should be automatically installed (plug and play) after the PD-USB-DP60 is connected. Linux ® may require driver installation in case the

LAN7800 Ethernet controller is missing. Apple ® requires driver installation.

- If the USB host doesn't recognize the PD-USB-DP60 as a USB device, please go to the LAN7800 product page to download and install the appropriate device driver.
- Powering multiple PD-USB-DP60 from the same PoE multiport midspan may affect data/power performance to connected USB-C devices (i.e. laptop) if they are sharing common peripheral equipment such as monitors, projectors, etc.

## Technical Support

For technical support please visit the Microchip Technical Support Portal [www.microchip.com/support](http://www.microchip.com/support)

## LAN7800 Driver




To download device drivers for the LAN7800 please visit the LAN7800 WEB page: LAN7800 USA/Canada: +1 877 480 2323

The Microchip name and logo and the Microchip logo are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. All other trademarks mentioned herein are property of their respective companies.

© 2021, Microchip Technology Incorporated. All Rights Reserved. 7/21  
**DS00003800B**

## Documents / Resources

	<a href="#">PD-USB-DP60 PoE to USB-C Power and Data Adapter PD-USB-DP60 PoE to USB-C Power and Data Adapter [pdf] User Guide</a> PD-USB-DP60, PoE to USB-C Power and Data Adapter
---	--